

**RADIO FREQUENCY EXPOSURE****LIMIT**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

**Conducted Power Results**

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)
GFSK	00	2406	<b>10.40</b>
	15	2440	<b>10.70</b>
	30	2475	<b>10.22</b>

**Manufacturing tolerance**

GFSK (Peak)			
Channel	Channel 00	Channel 15	Channel 30
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



## Compliance Certification(Shenzhen) Services Inc.

Report No: C150720Z01-RP1 FCC ID: 2AB3MDH1300-001T Date of Issue: August 24, 2014

### EUT Specification

<b>EUT</b>	2.4GHz Digital Wireless Headphone Transmitter
<b>Frequency band (Operating)</b>	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Bluetooth: 2.402GHz~ 2.480GHz <input checked="" type="checkbox"/> FHSS: 2.406GHz~ 2.472GHz <input type="checkbox"/> Others _____
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5mW/cm^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1mW/cm^2$ )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input checked="" type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	11dBm (12.59mW)
<b>Antenna gain (Max)</b>	-2dBi (Numeric gain:1.58)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

#### Note:

1. The maximum output power(including turn tolerance) is 11dBm (15.59mW) and maximum antenna gain is -2dBi
2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.



## **TEST RESULT**

*No non-compliance noted.*

### **Calculation**

Given 
$$S = \frac{P \times G}{4\pi d^2} \quad \text{Equation 1}$$

Where  $d$  = distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power Density in  $\text{mW/cm}^2$

### **Maximum Permissible Exposure**

EUT Output Power=12.59mW

Numeric antenna gain=1.58

Substituting the MPE safe distance using  $d=20$  cm into **Equation 1** :

Fields

The power density  $S = 12.59 \times 1 / (4\pi \times 400) \text{ cm}^2 = 25.04 \times 10^{-4} \text{ mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is  $1.0 \text{ mW/cm}^2$  even if the calculation indicates that the power density would be larger.)