


## 6.6. Conducted Band Edge and Spurious Emission Measurement

### 6.6.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (d)
<b>Test Method:</b>	ANSI C63.10:2013 and KDB558074
<b>Limit:</b>	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
<b>Test Setup:</b>	
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).</li> <li>5. Measure and record the results in the test report.</li> <li>6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</li> </ol>
<b>Test Result:</b>	PASS


### 6.6.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Dec. 21, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.6.3. Test Data


#### Antenna 1: 802.11b Modulation




## 100kHz PSD reference Level



## Band Edge




## Spurious emission



## Highest Channel


## 802.11g Modulation




## 100kHz PSD reference Level



## Band Edge





## Spurious emission




## Highest Channel


## 802.11n (HT20) Modulation





## 802.11n (HT40) Modulation






## Antenna 2: 802.11b Modulation


### 100kHz PSD reference Level



### Band Edge



### Spurious emission




### Lowest Channel


### 100kHz PSD reference Level




### Spurious emission



### Middle Channel




## 802.11g Modulation




## 100kHz PSD reference Level



## Band Edge





## Spurious emission




## Highest Channel

## 802.11n (HT20) Modulation






## 802.11n (HT40) Modulation




## 100kHz PSD reference Level



## Band Edge




## Spurious emission




## Highest Channel


## 6.7. Radiated Spurious Emission Measurement

### 6.7.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.209																																															
<b>Test Method:</b>	ANSI C63.4: 2014 and ANSI C63.10: 2013																																															
<b>Frequency Range:</b>	9 kHz to 25 GHz																																															
<b>Measurement Distance:</b>	3 m																																															
<b>Antenna Polarization:</b>	Horizontal & Vertical																																															
<b>Operation mode:</b>	Transmitting mode with modulation																																															
<b>Receiver Setup:</b>	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>9kHz- 150kHz</td> <td>Quasi-peak</td> <td>200Hz</td> <td>1kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>150kHz- 30MHz</td> <td>Quasi-peak</td> <td>9kHz</td> <td>30kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>100KHz</td> <td>300KHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td><td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value														
Frequency	Detector	RBW	VBW	Remark																																												
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value																																												
150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value																																												
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																																												
Above 1GHz	Peak	1MHz	3MHz	Peak Value																																												
	Peak	1MHz	10Hz	Average Value																																												
<b>Limit:</b>	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>0.009-0.490</td> <td>2400/F(KHz)</td> <td>300</td> <td></td> </tr> <tr> <td>0.490-1.705</td> <td>24000/F(KHz)</td> <td>30</td> <td></td> </tr> <tr> <td>1.705-30</td> <td>30</td> <td>30</td> <td></td> </tr> <tr> <td>30-88</td> <td>100</td> <td>3</td> <td></td> </tr> <tr> <td>88-216</td> <td>150</td> <td>3</td> <td></td> </tr> <tr> <td>216-960</td> <td>200</td> <td>3</td> <td></td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>3</td> <td></td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Above 1GHz</td><td>500</td> <td>3</td> <td>Average</td> </tr> <tr> <td>5000</td> <td>3</td> <td>Peak</td> </tr> </tbody> </table>					Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	0.009-0.490	2400/F(KHz)	300		0.490-1.705	24000/F(KHz)	30		1.705-30	30	30		30-88	100	3		88-216	150	3		216-960	200	3		Above 960	500	3		Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	Above 1GHz	500	3	Average	5000	3	Peak
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector																																													
0.009-0.490	2400/F(KHz)	300																																														
0.490-1.705	24000/F(KHz)	30																																														
1.705-30	30	30																																														
30-88	100	3																																														
88-216	150	3																																														
216-960	200	3																																														
Above 960	500	3																																														
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector																																													
Above 1GHz	500	3	Average																																													
	5000	3	Peak																																													
<b>Test setup:</b>	<p>For radiated emissions below 30MHz</p>  <p>Distance = 3m</p> <p>EUT</p> <p>Turn table</p> <p>Ground Plane</p> <p>Computer</p> <p>Pre -Amplifier</p> <p>Receiver</p> <p>30MHz to 1GHz</p>																																															



Above 1GHz



### Test Procedure:

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 1.5 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.  
For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT,

	<p>depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"><li>(1) Span shall wide enough to fully capture the emission being measured;</li><li>(2) Set RBW=100 kHz for <math>f &lt; 1</math> GHz; VBW <math>\geq</math> RBW; Sweep = auto; Detector function = peak; Trace = max hold;</li><li>(3) Set RBW = 1 MHz, VBW= 3MHz for <math>f \geq 1</math> GHz for peak measurement.</li></ul> <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW <math>\geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
<b>Test results:</b>	PASS

### 6.7.2. Test Instruments


Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
ESPI Test Receiver	ROHDE&SCHW ARZ	ESVD	100008	Nov.16 , 2015
Spectrum Analyzer	ROHDE&SCHW ARZ	FSEM	848597/001	Nov.16 , 2015
Spectrum Analyzer	Agilent	N9020A	MY49100060	Dec. 21, 2015
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Nov.16 , 2015
Pre-amplifier	HP	8447D	2727A05017	Nov.16 , 2015
Loop antenna	ZHINAN	ZN30900A	12024	Dec.14 , 2015
Broadband Antenna	Schwarzbeck	VULB9163	340	Nov.16 , 2015
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Nov.16 , 2015
Horn Antenna	Schwarzbeck	BBHA 9170	373	Nov.16 , 2015
Coax cable	TCT	RE-low-01	N/A	Nov.15 , 2015
Coax cable	TCT	RE-high-02	N/A	Nov.15 , 2015
Coax cable	TCT	RE-low-03	N/A	Nov.15 , 2015
Coax cable	TCT	RE-High-04	N/A	Nov.15 , 2015
Antenna Mast	CCS	CC-A-4M	N/A	Nov.15 , 2015
EMI Test Software	Shurples Technology	EZ-EMC	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.7.3. Test Data

Please refer to following diagram for individual  
Below 1GHz

Horizontal:



Site

Polarization: **Horizontal**

Temperature: 27


Limit: FCC Part 15B Class B RE\_3 m

Power: AC 120V/60Hz

Humidity: 50 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm		Table Degree	
								Detector	degree	Comment	
1		31.2920	33.06	-13.56	19.50	40.00	-20.50	peak	0		
2		37.5648	36.23	-12.78	23.45	40.00	-16.55	peak	0		
3		200.0432	42.08	-11.67	30.41	43.50	-13.09	peak	0		
4		266.8395	43.89	-9.38	34.51	46.00	-11.49	peak	0		
5		602.9287	39.72	-1.87	37.85	46.00	-8.15	peak	0		
6	*	833.0126	39.28	1.86	41.14	46.00	-4.86	peak	0		

Vertical:



Site

 Polarization: **Vertical**

Temperature: 27

Limit: FCC Part 15B Class B RE\_3 m

Power: AC 120V/60Hz

Humidity: 50 %

No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height cm	Table Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	Detector		
1		49.0627	40.33	-12.08	28.25	40.00	-11.75	peak	0	
2		166.6385	43.26	-14.00	29.26	43.50	-14.24	peak	0	
3		266.8395	41.51	-9.38	32.13	46.00	-13.87	peak	0	
4		535.0377	40.46	-2.60	37.86	46.00	-8.14	peak	0	
5	*	602.9287	44.80	-1.87	42.93	46.00	-3.07	peak	0	
6	!	669.9523	42.72	-0.49	42.23	46.00	-3.77	peak	0	

**Note:** 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode (Highest channel and 802.11b)

**Test Result of Radiated Spurious at Band edges**

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2310	H	46.35	-4.20	42.15	74.00	54.00
2388.98	H	48.54	-4.10	44.44	74.00	54.00
2390	H	52.76	-3.94	48.82	74.00	54.00
2310	V	45.12	-4.20	40.92	74.00	54.00
2388.98	V	54.35	-4.10	50.25	74.00	54.00
2390	V	52.72	-3.94	48.78	74.00	54.00

Modulation Type: 802.11b

Low channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2483.5	H	46.45	-3.60	42.85	74.00	54.00
2485.78	H	47.47	-3.50	43.97	74.00	54.00
2500	H	46.17	-3.34	42.83	74.00	54.00
2483.5	V	50.09	-3.60	46.49	74.00	54.00
2485.78	V	47.87	-3.50	44.37	74.00	54.00
2500	V	42.45	-3.34	39.11	74.00	54.00

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2310	H	44.84	-4.20	40.64	74.00	54.00
2387.82	H	51.32	-4.12	47.20	74.00	54.00
2390	H	53.58	-3.94	49.64	74.00	54.00
2310	V	45.35	-4.20	41.15	74.00	54.00
2387.82	V	48.95	-4.12	44.83	74.00	54.00
2390	V	53.20	-3.94	49.26	74.00	54.00

Modulation Type: 802.11g

Low channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2483.5	H	51.95	-3.60	48.35	74.00	54.00
2489.65	H	52.65	-3.52	49.13	74.00	54.00
2500	H	48.96	-3.34	45.62	74.00	54.00
2483.5	V	50.85	-3.60	47.25	74.00	54.00
2489.65	V	49.92	-3.52	46.4	74.00	54.00
2500	V	48.50	-3.34	45.16	74.00	54.00

Modulation Type: 802.11n(20MHz)

Low channel: 2412 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2310	H	48.65	-4.20	44.45	74.00	54.00
2388.01	H	52.25	-4.10	48.15	74.00	54.00
2390	H	53.20	-3.94	49.26	74.00	54.00
2310	V	48.28	-4.20	44.08	74.00	54.00
2388.01	V	53.18	-4.10	49.08	74.00	54.00
2390	V	52.21	-3.94	48.27	74.00	54.00

Modulation Type: 802.11n(20MHz)

Low channel: 2462 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2483.5	H	53.60	-3.60	50.00	74.00	54.00
2392.55	H	53.79	-3.50	50.29	74.00	54.00
2500	H	48.92	-3.34	45.58	74.00	54.00
2483.5	V	54.52	-3.60	50.92	74.00	54.00
2392.55	V	53.25	-3.50	49.75	74.00	54.00
2500	V	48.59	-3.34	45.25	74.00	54.00

Modulation Type: 802.11n(40MHz)

Low channel: 2422 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2310	H	49.84	-4.20	45.64	74.00	54.00
2387.85	H	54.58	-4.10	50.48	74.00	54.00
2390	H	53.68	-3.94	49.74	74.00	54.00
2310	V	51.65	-4.20	47.45	74.00	54.00
2389.98	V	53.95	-4.10	49.85	74.00	54.00
2390	V	54.26	-3.94	50.32	74.00	54.00

Modulation Type: 802.11n(40MHz)

Low channel: 2452 MHz						
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2483.5	H	50.62	-3.60	47.02	74.00	54.00
2493.51	H	52.62	-3.50	49.12	74.00	54.00
2500	H	51.95	-3.34	48.61	74.00	54.00
2493.51	V	52.32	-3.60	48.72	74.00	54.00
2489.36	V	54.66	-3.46	51.20	74.00	54.00
2500	V	51.69	-3.34	48.35	74.00	54.00

**Note:**

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor=Antenna Factor + Cable loss – Pre-amplifier

**Above 1GHz**

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	42.98	---	0.75	43.73	---	74	54	-10.27
7236	H	32.68	---	9.87	42.55	---	74	54	-11.45
---	H	---	---	---	---	---	---	---	---
4824	V	44.54	---	0.75	45.29	---	74	54	-8.71
7236	V	32.56	---	9.87	42.43	---	74	54	-11.57
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	40.16	---	0.97	41.13	---	74	54	-12.87
7320	H	34.9	---	9.83	44.73	---	74	54	-9.27
---	H	---	---	---	---	---	---	---	---
4874	V	40.25	---	0.97	41.22	---	74	54	-12.78
7311	V	32.18	---	9.83	42.01	---	74	54	-11.99
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	40.32	---	1.18	41.5	---	74	54	-12.5
7386	H	34.25	---	10.07	44.32	---	74	54	-9.68
---	H	---	---	---	---	---	---	---	---
4924	V	39.47	---	1.18	40.65	---	74	54	-13.35
7386	V	31.66	---	10.07	41.73	---	74	54	-12.27
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---”in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11g

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	41.38	---	0.75	42.13	---	74	54	-11.87
7236	H	33.56	---	9.87	43.43	---	74	54	-10.57
---	H	---	---	---	---	---	---	---	---
4824	V	42.89	---	0.75	43.64	---	74	54	-10.36
7236	V	33.75	---	9.87	43.62	---	74	54	-10.38
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	42.24	---	0.97	43.21	---	74	54	-10.79
7320	H	35.35	---	9.83	45.18	---	74	54	-8.82
---	H	---	---	---	---	---	---	---	---
4874	V	42.78	---	0.97	43.75	---	74	54	-10.25
7311	V	34.31	---	9.83	44.14	---	74	54	-9.86
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	42.29	---	1.18	43.47	---	74	54	-10.53
7386	H	34.35	---	10.07	44.42	---	74	54	-9.58
---	H	---	---	---	---	---	---	---	---
4924	V	41.32	---	1.18	42.5	---	74	54	-11.5
7386	V	32.69	---	10.07	42.76	---	74	54	-11.24
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---” in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	44.56	---	0.75	45.31	---	74	54	-8.69
7236	H	35.56	---	9.87	45.43	---	74	54	-8.57
---	H	---	---	---	---	---	---	---	---
4824	V	44.75	---	0.75	45.5	---	74	54	-8.5
7236	V	34.23	---	9.87	44.1	---	74	54	-9.9
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	46.58	---	0.97	47.55	---	74	54	-6.45
7320	H	35.35	---	9.83	45.18	---	74	54	-8.82
---	H	---	---	---	---	---	---	---	---
4874	V	44.78	---	0.97	45.75	---	74	54	-8.25
7311	V	34.31	---	9.83	44.14	---	74	54	-9.86
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	43.24	---	1.18	44.42	---	74	54	-9.58
7386	H	33.85	---	10.07	43.92	---	74	54	-10.08
---	H	---	---	---	---	---	---	---	---
4924	V	42.78	---	1.18	43.96	---	74	54	-10.04
7386	V	33.86	---	10.07	43.93	---	74	54	-10.07
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---” in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11n (HT40)

Low channel: 2422 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4844	H	42.31	---	0.75	43.06	---	74	54	-10.94
7266	H	33.76	---	9.87	43.63	---	74	54	-10.37
---	H	---	---	---	---	---	---	---	---
4824	V	42.32	---	0.75	43.07	---	74	54	-10.93
7236	V	32.01	---	9.87	41.88	---	74	54	-12.12
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	43.25	---	0.97	44.22	---	74	54	-9.78
7311	H	33.21	---	9.83	43.04	---	74	54	-10.96
---	H	---	---	---	---	---	---	---	---
4874	V	42.62	---	0.97	43.59	---	74	54	-10.41
7311	V	32.81	---	9.83	42.64	---	74	54	-11.36
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4904	H	43.15	---	1.18	44.33	---	74	54	-9.67
7356	H	33.54	---	10.07	43.61	---	74	54	-10.39
---	H	---	---	---	---	---	---	---	---
4904	V	42.74	---	1.18	43.92	---	74	54	-10.08
7356	V	34.09	---	10.07	44.16	---	74	54	-9.84
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---” in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

\*\*\*\*\*END OF REPORT\*\*\*\*\*