

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : LUMI LEGEND ELECTRICAL CO., LTD.
NO.18 LANE 239, BEIHAI ROAD, JIANGBEI,
NINGBO 315032 CHINA

Manufacturer : LUMI LEGEND ELECTRICAL CO., LTD.
NO.18 LANE 239, BEIHAI ROAD, JIANGBEI,
NINGBO 315032 CHINA

Product Name : REC Wall Switch/US

Type/Model : AW51011

TEST RESULT : PASS

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Date of issue: December 07, 2016

Prepared by:



Nemo Li (Project engineer)

Approved by:



Daniel Zhao (Reviewer)

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^3)$$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

As we can see from the test report 160801917SHA-001:

Frequency band (MHz)	Power dBm	Antenna Gain dBi	R (cm)	S (mW/cm2)	Limits (mW/cm2)
2400 -2483.5	18.57	2.18	20	0.0237	1

Note: 1 mW/cm² from 1.310 Table 1

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.