FCC TEST REPORT

For

Jinan Huamao Technology Co., Ltd.

Bluetooth Module

Test Model: HM-10

Additional Model No.: HM-11

Prepared for : Jinan Huamao Technology Co., Ltd.

Address : C-4020, South area, Huanbao park, Hi-Tech zone, Jinan, Shandong,

China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,

Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330 Fax : (+86)755-82591332 Web : www.LCS-cert.com

Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 13, 2015

Number of tested samples : 1

Sample Number : 201504102312

Date of Test : May 13, 2015 - May 26, 2015

Date of Report : May 26, 2015

FCC TEST REPORT
FCC CFR 47 PART 15 C(15.247): 2015

Report Reference No.: LCS1505130764E

Date of Issue: May 26, 2015

Testing Laboratory Name......: Shenzhen LCS Compliance Testing Laboratory Ltd.

Address: 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,

Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure......: Full application of Harmonised standards

Partial application of Harmonised standards \Box

Other standard testing method \Box

Applicant's Name.....: Jinan Huamao Technology Co., Ltd.

Address: C-4020, South area, Huanbao park, Hi-Tech zone, Jinan,

Shandong, China

Test Specification

Standard: FCC CFR 47 PART 15 C(15.247): 2015 / ANSI C63.10: 2009

Test Report Form No.....: LCSEMC-1.0

TRF Originator: Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF.....: Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description.: : Bluetooth Module

Trade Mark: N/A

Test Model: HM-10

Ratings: DC 3.3V

Result: Positive

Compiled by:

Supervised by:

Approved by:

Leo Lee/ File administrators

Glin Lu/ Technique principal

Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No.: LCS1505130764E

May 26, 2015 Date of issue

Test Model..... : HM-10 EUT.....: Bluetooth Module Applicant..... : Jinan Huamao Technology Co., Ltd. Address..... : C-4020, South area, Huanbao park, Hi-Tech zone, Jinan, Shandong, China Telephone..... Fax..... Manufacturer..... : Jinan Huamao Technology Co., Ltd. Address..... : C-4020, South area, Huanbao park, Hi-Tech zone, Jinan, Shandong, Telephone..... Fax..... Factory..... : Jinan Huamao Technology Co., Ltd. Address..... : C-4020, South area, Huanbao park, Hi-Tech zone, Jinan, Shandong, China Telephone..... Fax.....

> **Test Result Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. DESCRIPTION OF DEVICE (EUT) 1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS 1.3. EXTERNAL I/O 1.4. DESCRIPTION OF TEST FACILITY 1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY 1.6. MEASUREMENT UNCERTAINTY	
1.7. DESCRIPTION OF TEST MODES	7
2. TEST METHODOLOGY	8
2.1. EUT CONFIGURATION	
3. SYSTEM TEST CONFIGURATION	9
3.1. JUSTIFICATION	
4. SUMMARY OF TEST RESULTS	10
5. TEST RESULT	
6. LIST OF MEASURING EQUIPMENTS	32

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Bluetooth Module

Test Model : HM-10

Hardware Version : 10201503

Software Version : V540

Power Supply : DC 3.3V

Frequency Range : 2402.00-2480.00MHz

Channel Number : 40

Channel Spacing : 2MHz

Modulation Type : GFSK

Bluetooth Version : V4.0(BLE Only)

Antenna Description: PCB Antenna, 2.0dBi(Max.)

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
Lenovo	Notebook	B470	WB05067151	DOC
Lenovo	AC/DC ADAPTER	ADP-90DD B	36001941	VOC
Huamao	CC Debugger	V1.00	/	VOC
Huamao	USB To TTL Board	D-SUN	/	VOC

1.3. External I/O

	I/O Port Description	Quantity	Cable
١	- 1/65	163-	39 - (35

1.4. Description of Test Facility

CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

VCCI Registration Number. is C-4260 and R-3804.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

1.5. Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
7,75		9KHz~30MHz	3.10dB	(1)
		30MHz~200MHz	2.96dB	(1)
Radiation Uncertainty	:	200MHz~1000MHz	3.10dB	(1)
		1GHz~26.5GHz	3.80dB	(1)
	ŀ	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	1.63dB	(1)
Power disturbance	:	30MHz~300MHz	1.60dB	(1)

^{(1).} This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description Of Test Modes


Bluetooth operates in the unlicensed ISM Band at 2.4GHz. The EUT was set to transmit at 100% duty cycle. The following operating modes were applied for the related test items. For radiated measurement, the test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position. All test modes were tested, only the result of the worst case was recorded in the report.

Frequency Range	Data Rate
(MHz)	(Mbps)
2402	(4)
2440	125
2480	1,23
For Conducted Emission	
5 6	TX Mode
For Radiated Emission	
1,50	TX Mode
	(MHz) 2402 2440 2480 For Conducted Emission

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be TX-High Channel(2480MHz, GFSK).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX-High Channel(2480MHz, GFSK).

***Note: Using a temporary antenna connector for the EUT when the conducted measurements are performed.



2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10: 2009, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd..

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 D01 DTS Meas. Guidance v03r02 is required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

According to the requirements in Section 6.2 of ANSI C63.10: 2009, AC power-line conducted emissions shall be measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table and the turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10: 2009

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmit condition.

3.2. EUT Exercise Software

N/A

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C					
FCC Rules Description of Test Re					
§15.247(b)(3)	Maximum Conducted Output Power	Compliant			
§15.247(e)	Power Spectral Density	Compliant			
§15.247(a)(2)	6dB Bandwidth	Compliant			
§15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant			
§15.205	Emissions at Restricted Band	Compliant			
§15.207(a)	Line Conducted Emissions	Compliant			
§15.203	Antenna Requirements	Compliant			

5. TEST RESULT

5.1. Maximum Conducted Output Power Measurement


5.1.1. Standard Applicable

According to §15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt.

5.1.2. Test Procedures

The transmitter output (antenna port) was connected to the power meter.

5.1.3. Test Setup Layout



5.1.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.5. Test Result of Maximum Conducted Output Power(Peak)

Modulation	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Limit (mW)	Result
71.05	2402	-0.51	0.89	1000	Pass
GFSK	2440	-0.52	0.89	1000	Pass
0.6	2480	-0.37	0.92	1000	Pass

5.2. Power Spectral Density Measurement


5.2.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2.2. Test Procedures

- 1) The transmitter was connected directly to a Spectrum Analyzer through a directional couple.
- 2) The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
- 3) Set the RBW = 3 kHz.
- 4) Set the VBW \geq 3*RBW.
- 5) Set the span to 1.5 times the DTS channel bandwidth.
- 6) Detector = peak.
- 7) Sweep time = auto couple.
- 8) Trace mode = max hold.
- 9) Allow trace to fully stabilize.
- 10) Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

5.2.3. Test Setup Layout



5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.5. Test Result of Power Spectral Density

Modulation	Frequency (MHz)	Reading Level (dBm/3KHz)	Max. Limit (dBm/3KHz)	Result
Barrie .	2402	-19.621	8	Pass
GFSK	2440	-19.665	8	Pass
23	2480	-19.197	8	Pass

The test data refer to the following page.

Low Channel, 2402MHz



Middle Channel, 2440MHz



High Channel, 2480MHz



5.3. 6 dB Spectrum Bandwidth Measurement

5.3.1. Standard Applicable

According to §15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.3.2. Instruments Setting


The following table is the setting of the Spectrum Analyzer.

Setting		
Auto	(35	0.85
3MHz	28	28
100kHz/300kHz	0.03	300
Peak	Rose	Post
Max Hold	Book	200
	Auto 3MHz 100kHz/300kHz Peak	Auto 3MHz 100kHz/300kHz Peak

5.3.3. Test Procedures

- 1) The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- 2) The resolution bandwidth and the video bandwidth were set according to KDB558074 D01 DTS Meas. Guidance v03r02.
- 3) Measured the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.
- 4) Record the 99% occupied bandwidth and the minimum 6dB bandwidth.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.6. Test Result of Spectrum Bandwidth

Modulation	Frequency (MHz)	99% Bandwidth (MHz)	6dB Bandwidth (KHz)	Min. Limit (KHz)	Result
3	2402	1.0289	690.6	500	Complies
GFSK	2440	1.0309	690.9	500	Complies
	2480	1.0316	694.6	500	Complies

The test data refer to the following page.

Low Channel, 2402MHz



Middle Channel, 2440MHz



High Channel, 2480MHz



5.4. Radiated Emissions Measurement

5.4.1. Standard Applicable

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies(MHz)	Field Strength(microvolts/meter)	Measurement Distance(meters 300	
0.009~0.490	2400/F(KHz)		
0.490~1.705	24000/F(KHz)	30	
1.705~30.0	30	30	
30~88	100	3	
88~216	150	3	
216~960	200	3	
Above 960	500	3	

5.4.2. Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	TIMEZ/TIMEZIOI Peak, TIMEZ/TOEZIOI AVE


Spectrum Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

5.4.3. Test Procedures


- 1) Configure the EUT according to ANSI C63.10: 2009. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2) Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3) The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.

- 4) For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading
- 5) Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6) For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7) When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 8) If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9) For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emission sat the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10) In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.


5.4.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.6. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	60%
Test Engineer	Leo	Configurations	BLE V4.0

Freq.	Level	Over Limit	Over Limit	Remark
(MHz)	(dBuV)	(dB)	(dBuV)	
33	OB T	333	135	See Note

Note:

The radiated emissions from 9kHz to 30MHz are at least 20dB below the official limit and no need to report.


Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.4.7. Results of Radiated Emissions (30MHz~1GHz)

PASS.

The test data please refer to following page:



Env./Ins: EUT: M/N: Power Rating: 24°C/56% Bluetooth Module

HM-10 DC 3.3V TX-2480MHz Leo


Test Mode: Operator: Memo:

VERTICAL pol:

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dВ	dB/m	dBuV/m	dBuV/m	dВ	
1	99.84	5.59	0.60	13.15	19.34	43.50	-24.16	QP
2	181.32	16.37	0.89	9.80	27.06	43.50	-16.44	QP
3	268.62	13.08	1.00	12.32	26.40	46.00	-19.60	QP
4	419.94	6.62	1.32	15.47	23.41	46.00	-22.59	QP
5	770.11	6.25	1.76	19.69	27.70	46.00	-18.30	QP
6	839.95	5.48	1.88	20.47	27.83	46.00	-18.17	QP

Note: 1. All readings are Quasi-peak values. 2. Measured= Reading + Antenna Factor + Cable

reported The emission that ate 20db blow the offficial limit are not



Env./Ins: EUT: M/N: Power Rating: Test Mode: Operator:

24°C/56% Bluetooth Module HM-10 DC 3.3V

TX-2480MHz

nol:

HORIZONTAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dВ	dB/m	dBuV/m	dBuV/m	dВ	
1	47.46	3.40	0.35	13.40	17.15	40.00	-22.85	QP
2	180.35	20.21	0.89	9.71	30.81	43.50	-12.69	QP
3	268.62	16.12	1.00	12.32	29.44	46.00	-16.56	QP
4	358.83	10.72	1.18	14.41	26.31	46.00	-19.69	QP
5	628.49	4.97	1.60	18.55	25.12	46.00	-20.88	QP
6	734.22	7.24	1.74	19.24	28.22	46.00	-17.78	QP

te: 1. All readings are Quasi-peak values. Measured= Reading + Antenna Factor + Cable Loss The emission that ate 20db blow the offficial limit

***Note:

Pre-scan all mode and recorded the worst case results in this report (TX-High Channel(2480MHz, GFSK)).

Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Measured Level.

5.4.8. Results for Radiated Emissions (Above 1GHz)

Channel 1

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4804.16	50.64	33.06	35.04	3.94	52.60	74	-21.40	Peak	Horizontal
4804.19	41.27	33.06	35.04	3.94	43.23	54	-10.77	Average	Horizontal
4804.16	52.79	33.06	35.04	3.94	54.75	74	-19.25	Peak	Vertical
4804.19	43.61	33.06	35.04	3.94	45.57	54	-8.43	Average	Vertical

Channel 20

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4880.10	51.17	33.16	35.15	3.96	53.14	74	-20.86	Peak	Horizontal
4880.13	42.01	33.16	35.15	3.96	43.98	54	-10.02	Average	Horizontal
4880.10	53.37	33.16	35.15	3.96	55.34	74	-18.66	Peak	Vertical
4880.13	43.88	33.16	35.15	3.96	45.85	54	-8.15	Average	Vertical

Channel 40

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4960.17	52.93	33.26	35.14	3.98	55.03	74	-18.97	Peak	Horizontal
4960.20	43.81	33.26	35.14	3.98	45.91	54	-8.09	Average	Horizontal
4960.17	55.67	33.26	35.14	3.98	57.77	74	-16.23	Peak	Vertical
4960.20	45.84	33.26	35.14	3.98	47.94	54	-6.06	Average	Vertical

Notes:

- 1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz.
- 2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

5.4.9. Results for Band edge Testing (Radiated)

Tx-2402

									C
Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2377.41	43.71	32.89	35.16	3.51	44.95	74	-29.05	Peak	Horizontal
2377.43	34.56	32.90	35.16	3.51	35.81	54	-18.19	Average	Horizontal
2390.00	48.18	32.92	35.16	3.54	49.48	74	-24.52	Peak	Horizontal
2389.97	37.87	32.92	35.16	3.54	39.17	54	-14.83	Average	Horizontal
2377.41	44.14	32.89	35.16	3.51	45.38	74	-28.62	Peak	Vertical
2377.43	34.67	32.90	35.16	3.51	35.92	54	-18.08	Average	Vertical
2390.00	49.33	32.92	35.16	3.54	50.63	74	-23.37	Peak	Vertical
2389.97	39.42	32.92	35.16	3.54	40.72	54	-13.28	Average	Vertical

Tx-2480

1A 2 100								
Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
46.35	33.06	35.18	3.60	47.83	74	-26.17	Peak	Horizontal
37.06	33.08	35.18	3.60	38.56	54	-15.44	Average	Horizontal
43.57	33.08	35.18	3.62	45.09	74	-28.91	Peak	Horizontal
34.11	33.08	35.18	3.62	35.63	54	-18.37	Average	Horizontal
47.69	33.06	35.18	3.60	49.17	74	-24.83	Peak	Vertical
38.01	33.08	35.18	3.60	39.51	54	-14.49	Average	Vertical
44.53	33.08	35.18	3.62	46.05	74	-27.95	Peak	Vertical
34.68	33.08	35.18	3.62	36.20	54	-17.80	Average	Vertical
	Reading Level dBuV 46.35 37.06 43.57 34.11 47.69 38.01 44.53	Reading Level dBuV Ant. Fac. dB/m 46.35 33.06 37.06 33.08 43.57 33.08 34.11 33.08 47.69 33.06 38.01 33.08 44.53 33.08	Reading Level dBuV Ant. Fac. dB/m Pre. Fac. dB 46.35 33.06 35.18 37.06 33.08 35.18 43.57 33.08 35.18 34.11 33.08 35.18 47.69 33.06 35.18 38.01 33.08 35.18 44.53 33.08 35.18	Reading Level dBuV Ant. Fac. dB/m Pre. Fac. dB Cab. Loss dB 46.35 33.06 35.18 3.60 37.06 33.08 35.18 3.60 43.57 33.08 35.18 3.62 34.11 33.08 35.18 3.62 47.69 33.06 35.18 3.60 38.01 33.08 35.18 3.60 44.53 33.08 35.18 3.62	Reading Level dBuV Ant. Fac. dB/m Pre. Fac. dB Cab. Loss dB Measured dBuV/m 46.35 33.06 35.18 3.60 47.83 37.06 33.08 35.18 3.60 38.56 43.57 33.08 35.18 3.62 45.09 34.11 33.08 35.18 3.62 35.63 47.69 33.06 35.18 3.60 49.17 38.01 33.08 35.18 3.60 39.51 44.53 33.08 35.18 3.62 46.05	Reading Level dBuV Ant. Fac. dB/m Pre. Fac. dB Cab. Loss dB Measured dBuV/m Limit dBuV/m 46.35 33.06 35.18 3.60 47.83 74 37.06 33.08 35.18 3.60 38.56 54 43.57 33.08 35.18 3.62 45.09 74 34.11 33.08 35.18 3.62 35.63 54 47.69 33.06 35.18 3.60 49.17 74 38.01 33.08 35.18 3.60 39.51 54 44.53 33.08 35.18 3.62 46.05 74	Reading Level dBuV Ant. Fac. dB/m Pre. Fac. dB Cab. Loss dB Measured dBuV/m Limit dBuV/m Margin dB 46.35 33.06 35.18 3.60 47.83 74 -26.17 37.06 33.08 35.18 3.60 38.56 54 -15.44 43.57 33.08 35.18 3.62 45.09 74 -28.91 34.11 33.08 35.18 3.62 35.63 54 -18.37 47.69 33.06 35.18 3.60 49.17 74 -24.83 38.01 33.08 35.18 3.60 39.51 54 -14.49 44.53 33.08 35.18 3.62 46.05 74 -27.95	Reading Level dBuV Ant. Fac. dB/m Pre. Fac. dB dB Cab. Loss dB Measured dBuV/m Limit dBuV/m Margin dB Remark 46.35 33.06 35.18 3.60 47.83 74 -26.17 Peak 37.06 33.08 35.18 3.60 38.56 54 -15.44 Average 43.57 33.08 35.18 3.62 45.09 74 -28.91 Peak 34.11 33.08 35.18 3.62 35.63 54 -18.37 Average 47.69 33.06 35.18 3.60 49.17 74 -24.83 Peak 38.01 33.08 35.18 3.60 39.51 54 -14.49 Average 44.53 33.08 35.18 3.62 46.05 74 -27.95 Peak

5.5. Conducted Spurious Emissions And Band Edges Test

5.5.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.5.2. Instruments Setting

The following table is the setting of the spectrum analyzer.


Spectrum Parameter	Setting					
Detector	Peak					
Attenuation	Auto					
RB / VB (Emission in restricted band)	100KHz/300KHz					
RB / VB (Emission in non-restricted band)	100KHz/300KHz					

5.5.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

5.5.4. Test Setup Layout




5.5.5. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

5.5.6. Test Results of Conducted Spurious Emissions


Test Result of Low Channel:



Test Result of Middle Channel:



Test Result of High Channel:



5.5.7. Test Results of Band Edges Test






5.6. Power line conducted emissions

5.6.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range	Limits (dBµV)				
(MHz)	Quasi-peak	Average			
0.15 to 0.50	66 to 56	56 to 46			
0.50 to 5	56	46			
5 to 30	60	50			


5.6.2 Block Diagram of Test Setup



5.6.3 Test Results

PASS.

The test data please refer to following page.




Env. Ins: EUT: M/N: Power Rating: Test Mode: Operator: Memo: Pol: 24*/56% Bluetooth Module HM-10 AC 120V/60Hz TX-2480MHz

LINE

	Freq	Reading	LisnFac	CabLos	Atten_Fac	Measured	Limit	0ver	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.15080	24.36	9.57	0.02	10.00	43.95	65.96	-22.01	QP
2	0.15081	14.63	9.57	0.02	10.00	34.22	55.96	-21.74	Average
3	0.16241	23.64	9.59	0.02	10.00	43.25	65.34	-22.09	QP
4	0.16242	19.38	9.59	0.02	10.00	38.99	55.34	-16.35	Average
5	0.50469	16.41	9.62	0.04	10.00	36.07	56.00	-19.93	QP
6	0.50470	5.11	9.62	0.04	10.00	24.77	46.00	-21.23	Average
7	1.53548	12.68	9.64	0.05	10.00	32.37	56.00	-23.63	QP
8	1.53648	6.80	9.64	0.05	10.00	26.49	46.00	-19.51	Average
9	8.96368	12.35	9.69	0.08	10.00	32.12	60.00	-27.88	QP
10	8.96468	6.56	9.69	0.08	10.00	26.33	50.00	-23.67	Average
111	17.75494	13.48	9.74	0.11	10.00	33.33	60.00	-26.67	QP
121	17.75564	6.85	9.74	0.11	10.00	26.70	50.00	-23.30	Average

Measured = Reading + Lisn Factor +Cable The emission levels that are 20dB below limit are not reported. Loss+Atten_Fac. the official



24*/56*
Bluetooth Module
HM-10
AC 120V/60Hz
TX-2480MHz Env. Ins: EUT: M/N: Power Rating: Test Mode: Operator: Leo Memo: Pol: NEUTRAL

	Freq	Reading	LisnFac	CabLos	Atten_Fac	Measured	Limit	0ver	Remark
	MHz	dBu∀	dB	dB	dB	dBu∀	dBu∀	dB	
1	0.16155	31.72	9.67	0.02	10.00	51.41	65.38	-13.97	QP
2	0.16156	19.21	9.67	0.02	10.00	38.90	55.38	-16.48	Average
3	0.18152	19.51	9.63	0.02	10.00	39.16	64.42	-25.26	QP
4	0.18153	7.44	9.63	0.02	10.00	27.09	54.42	-27.33	Average
- 5	0.48632	12.45	9.62	0.04	10.00	32.11	56.23	-24.12	QP
6	0.48633	7.50	9.62	0.04	10.00	27.16	46.23	-19.07	Average
7	2.60823	13.83	9.64	0.05	10.00	33.52	56.00	-22.48	QP
8	2.60853	4.27	9.64	0.05	10.00	23.96	46.00	-22.04	Average
9	5.53468	12.29	9.67	0.06	10.00	32.02	60.00	-27.98	QP
10	5.53568	2.86	9.67	0.06	10.00	22.59	50.00	-27.41	Average
111	10.28758	14.39	9.72	0.08	10.00	34.19	60.00	-25.81	QP
121	10.28858	3.91	9.72	0.08	10.00	23.71	50.00	-26.29	Average

Remarks: Measured = Reading + Lisn Factor +Cable Loss+Atten_Fac. The emission levels that are 20dB below the official

***Note: Pre-scan all mode and recorded the worst case results in this report.

5.7. Antenna Requirements

5.7.1. Standard Applicable

According to §15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

5.7.2. Antenna Connector Construction

The antenna used for transmitting is permanently attached and no consideration of replacement. Please see EUT photo for details.

5.7.3. Antenna Gain

Pa	Parameter Setting					
Detector:	Peak					
Sweep Time:	Auto					
Resolution bandwidth:	3MHz					
Video bandwidth:	3MHz					
Span:	5MHz					
Trace-Mode:	Max hold					

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For Bluetooth devices, the GFSK mode is used.

Test Result						
T _{nom}	V_{nom}	Lowest Channel 2402 MHz	Middle Channel 2440 MHz	Highest Channel 2480 MHz		
Measu	power [dBm] red with nodulation	-0.51	-0.52	-0.37		
Radiated power [dBm] Measured with GFSK modulation		1.44	1.48	1.60		
Gain [dBi] Calculated		1.95	2.00	1.97		
Measurement uncertainty			± 1.6 dB (cond.) / ± 3.8 dB (rad.)			

5.7.4. Results: Compliance.

6. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal Date	Due Date
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	June 18,2014	June 17,2015
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	July 16,2014	July 15,2015
LISN	SCHWARZBECK	NLSK 8127	N/A	9KHz~30MHz	June 18,2014	June 17,2015
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	June 18,2014	June 17,2015
LISN (Support Unit)	EMCO	3819/2NM	9703-1839	9KHz-30MHz	June 18,2014	June 17,2015
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	June 18,2014	June 17,2015
ISN	SCHAFFNER	ISN ST08	21653	9KHz-30MHz	June 18,2014	June 17,2015
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03СН03-НҮ	30M-1GHz 3m	June 18,2014	June 17,2015
Amplifier	SCHAFFNER	COA9231A	18667	9kHz-2GHzz	June 18,2014	June 17,2015
Amplifier	Agilent	8449B	3008A02120	1GHz-26.5GHz	July 16,2014	July 15,2015
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz-40GHz	July 16,2014	July 15,2015
Spectrum Analyzer	Agilent	E4407B	MY41440292	9k-26.5GHz	July 16,2014	July 15,2015
Loop Antenna	R&S	HFH2-Z2	860004/001	9k-30MHz	June 18,2014	June 17,2015
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	30MHz-1GHz	June 10,2014	June 09,2015
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	June 10,2014	June 09,2015
Horn Antenna	SCHWARZBECK	ВВНА9170	BBHA9170154	15GHz-40GHz	June 10,2014	June 09,2015
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	June 18,2014	June 17,2015
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz-40GHz	June 18,2014	June 17,2015
Power Meter	R&S	NRVS	100444	DC-40GHz	June 18,2014	June 17,2015
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	June 18,2014	June 17,2015
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	June 18,2014	June 17,2015
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	June 18,2014	June 17,2015
RF CABLE-2m	JYE Bao	RG142	CB)35-2m	20MHz-1GHz	June 18,2014	June 17,2015
temporary antenna connector	LCS	LCS-RF-20150413	N/A	9KHz~40GHz Impedance: 50Ω Cable Loss: 0.5dB	N/A	N/A

Note: All equipment through GRGT EST calibration

-----THE END OF REPORT-----