



FCC PART 15, SUBPART C ISED RSS-247, ISSUE 1, MAY 2015

TEST AND MEASUREMENT REPORT

For

Intel Corporation

2200 Mission College Blvd.,

Santa Clara, CA 95054, USA

**FCC ID: 2AB8ZND18
IC: 1000X-ND18**

| | |
|--|--|
| Report Type: Original Report | Product Type: Wearable Glasses |
| Prepared By: <u>Todd Moy</u> | |
| Report Number: <u>R1604212-247</u> | |
| Report Date: <u>2016-06-07</u> | |
| Reviewed By: <u>Simon Ma</u> | |
| Reviewed By: <u>RF Lead</u> | |
| Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732-9164 | |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”

TABLE OF CONTENTS

| | |
|--|-----------|
| 1 General Description..... | 5 |
| 1.1 Product Description for Equipment Under Test (EUT) | 5 |
| 1.2 Mechanical Description of EUT | 5 |
| 1.3 Objective..... | 5 |
| 1.4 Related Submittal(s)/Grant(s) | 5 |
| 1.5 Test Methodology | 5 |
| 1.6 Measurement Uncertainty | 5 |
| 1.7 Test Facility | 6 |
| 2 System Test Configuration..... | 7 |
| 2.1 Justification..... | 7 |
| 2.2 EUT Exercise Software..... | 7 |
| 2.3 Duty Cycle Correction Factor | 7 |
| 2.4 Equipment Modifications..... | 8 |
| 2.5 Local Support Equipment | 8 |
| 2.6 EUT Internal Configuration Details..... | 8 |
| 2.7 Support Equipment | 8 |
| 2.8 Interface Ports and Cabling..... | 8 |
| 3 Summary of Test Results | 9 |
| 4 FCC §15.203 & ISED RSS-Gen §8.3 - Antenna Requirements | 10 |
| 4.1 Applicable Standards | 10 |
| 4.2 Antenna Description | 10 |
| 5 FCC §2.1093, §15.247(i) & ISED RSS-102 – RF Exposure..... | 11 |
| 5.1 Applicable Standards | 11 |
| 5.2 RF Exposure Evaluation Results..... | 13 |
| 6 FCC §15.207 & ISED RSS-Gen §8.8 - AC Line Conducted Emissions..... | 14 |
| 6.1 Applicable Standards | 14 |
| 6.2 Test Setup | 14 |
| 6.3 Test Procedure | 14 |
| 6.4 Corrected Amplitude & Margin Calculation..... | 15 |
| 6.5 Test Setup Block Diagram..... | 15 |
| 6.6 Test Equipment List and Details | 16 |
| 6.7 Test Environmental Conditions | 16 |
| 6.8 Summary of Test Results..... | 16 |
| 6.9 Conducted Emissions Test Plots and Data..... | 17 |
| 7 FCC §15.209, §15.247(d) & ISED RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions..... | 19 |
| 7.1 Applicable Standards | 19 |
| 7.2 Test Setup | 21 |
| 7.3 Test Procedure | 21 |
| 7.4 Corrected Amplitude & Margin Calculation..... | 21 |
| 7.5 Test Equipment List and Details | 22 |
| 7.6 Test Environmental Conditions | 22 |
| 7.7 Summary of Test Results..... | 22 |
| 7.8 Radiated Emissions Test Results | 23 |
| 8 FCC §15.247(a) (2) & ISED RSS-247 §5.2 -Emission Bandwidth | 26 |
| 8.1 Applicable Standards | 26 |
| 8.2 Measurement Procedure..... | 26 |
| 8.3 Test Equipment List and Details | 26 |
| 8.4 Test Environmental Conditions | 26 |
| 8.5 Test Results..... | 26 |
| 9 FCC §15.247(b) (3) & ISED RSS-247 §5.4 (4) - Output Power | 29 |

| | | |
|-----------|---|-----------|
| 9.1 | Applicable Standards | 29 |
| 9.2 | Measurement Procedure..... | 29 |
| 9.3 | Test Equipment List and Details..... | 29 |
| 9.4 | Test Environmental Conditions | 29 |
| 9.5 | Test Results..... | 29 |
| 10 | FCC §15.247(d) & ISED RSS-247 §5.5 – 100 kHz Bandwidth of Band Edges..... | 32 |
| 10.1 | Applicable Standards | 32 |
| 10.2 | Measurement Procedure..... | 32 |
| 10.3 | Test Equipment List and Details..... | 32 |
| 10.4 | Test Environmental Conditions | 32 |
| 10.5 | Test Results..... | 33 |
| 11 | FCC §15.247(e) & ISED RSS-247 §5.2(2) – Power Spectral Density | 34 |
| 11.1 | Applicable Standards | 34 |
| 11.2 | Measurement Procedure..... | 34 |
| 11.3 | Test Equipment List and Details..... | 34 |
| 11.4 | Test Environmental Conditions | 34 |
| 11.5 | Test Results..... | 34 |
| 12 | FCC §15.247(d) & ISED RSS-247 §5.5 & ISED RSS-GEN §8.9 – Spurious Emissions at Antenna Terminals.. | 37 |
| 12.1 | Applicable Standards | 37 |
| 12.2 | Test Procedure | 37 |
| 12.3 | Test Equipment List and Details..... | 37 |
| 12.4 | Test Environmental Conditions | 37 |
| 12.5 | Test Results..... | 38 |
| 13 | Exhibit A - FCC & ISED Equipment Labeling Requirements..... | 40 |
| 13.1 | FCC ID Label Requirements | 40 |
| 13.2 | ISED Label Requirements | 40 |
| 13.3 | FCC ID & IC Label Contents and Location..... | 41 |
| 14 | Exhibit B - Test Setup Photographs..... | 42 |
| 14.1 | Radiated Emission below 1 GHz Front View | 42 |
| 14.2 | Radiated Emission below 1 GHz Rear View | 42 |
| 14.3 | Radiated Emission above 1 GHz Front View | 43 |
| 14.4 | Radiated Emission above 1 GHz Rear View | 43 |
| 14.5 | AC Conducted Emissions Front View | 44 |
| 14.6 | AC Conducted Emissions Side View..... | 44 |
| 14.7 | Antenna Port Conducted Setup Photos | 45 |
| 15 | Exhibit C - EUT Photographs | 46 |
| 15.1 | EUT Front View | 46 |
| 15.2 | EUT Back View..... | 46 |
| 15.3 | EUT Bottom View | 47 |
| 15.4 | EUT Side View..... | 47 |
| 15.5 | EUT Left Side Main Board - Top View | 48 |
| 15.6 | EUT Left Side Main Board - Bottom View | 48 |
| 15.7 | EUT Right Side Main Board - Top View | 49 |
| 15.8 | EUT Right Side Main Board - Bottom View..... | 49 |
| 15.9 | EUT Battery | 50 |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number | Description of Revision | Date of Revision |
|-----------------|---------------|-------------------------|------------------|
| 0 | R1604212-247 | Original Report | 2016-06-07 |

1 General Description

1.1 Product Description for Equipment Under Test (EUT)

This test and measurement report was prepared on behalf of *Intel Corporation*, and their product model: *Radar Pace*, FCC ID: 2AB8ZND18; IC: 1000X-ND18 or the “EUT” as referred to in this report. The EUT are wearable glasses with Bluetooth, Bluetooth Low Energy and ANT+ capabilities.

1.2 Mechanical Description of EUT

The EUT measures approximately 140 mm (L) x 150 mm (W) x 53 mm (H) and weight 50 g.

The test data gathered are from typical production sample, serial number: FC5960FZ6030038-L assigned by Intel Corporation.

1.3 Objective

This report is prepared on behalf of *Intel Corporation*, in accordance with Part 2, Subpart J, and Part 15, Subparts B and C of the Federal Communication Commission’s rules and ISED RSS-247 Issue 1, MAY 2015.

The objective is to determine compliance with FCC Part 15.247 and ISED RSS-247 rules for Output Power, Antenna Requirements, 6 dB Bandwidth, Power Spectral Density, 100 kHz Bandwidth of Band Edges Measurement, Conducted and Radiated Spurious Emissions.

1.4 Related Submittal(s)/Grant(s)

FCC Part 15, Subpart C, Equipment DSS with FCC ID: 2AB8ZND18
FCC Part 15, Subpart C, Equipment DXX with FCC ID: 2AB8ZND18

1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 DTS Meas Guidance v03r05: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

1.6 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR16-4-2:2011, The Treatment of Uncertainty in EMC Measurements, the values ranging from ± 2.0 dB for Conducted Emissions tests and ± 4.0 dB for Radiated Emissions tests are the most accurate estimates pertaining to uncertainty of EMC measurements at BACL Corp.

1.7 Test Facility

Bay area compliance Laboratories Corp. (BACL) is:

1- An independent Commercial Test Laboratory accredited to ISO 17025: 2005 by A2LA, in the fields of: Electromagnetic Compatibility & Telecommunications covering Emissions, Immunity, Radio, RF Exposure, Safety and Telecom. This includes NEBS (Network Equipment Building System), Wireless RF, Telecommunications Terminal Equipment (TTE); Network Equipment; Information Technology Equipment (ITE); Medical Electrical Equipment; Industrial, Commercial, and Medical Test Equipment; Professional Audio and Video Equipment; Electronic (Digital) Products; Industrial and Scientific Instruments; Cabled Distribution Systems and Energy Efficiency Lighting.

2- An ENERGY STAR Recognized Laboratory, for the LM80 Testing, a wide variety of Luminaires and Computers.

3- A NIST Designated Phase-I and Phase-II CAB including: ACMA (Australian Communication and Media Authority), BSMI (Bureau of Standards, Metrology and Inspection of Taiwan), IDA (Infocomm Development Authority of Singapore), IC(Industry Canada), Korea (Ministry of Communications Radio Research Laboratory), NCC (Formerly DGT; Directorate General of Telecommunication of Chinese Taipei) OFTA (Office of the Telecommunications Authority of Hong Kong), Vietnam, VCCI - Voluntary Control Council for Interference of Japan and a designated EU CAB (Conformity Assessment Body) (Notified Body) for the EMC and R&TTE Directives.

4- A Product Certification Body accredited to ISO 17065: 2012 by A2LA to certify:

2. Radio Standards Specifications (RSS) in the Category I Equipment Standards List and All Broadcasting Technical Standards (BETS) in Category I Equipment Standards List for Industry Canada.

3. Radio Communication Equipment for Singapore.

4. Radio Equipment Specifications, GMDSS Marine Radio Equipment Specifications, and Fixed Network Equipment Specifications for Hong Kong.

5. Japan MIC Telecommunication Business Law (A1, A2) and Radio Law (B1, B2 and B3).

6. Audio/Video, Battery Charging Systems, Computers, Displays, Enterprise Servers, Imaging Equipment, Set-Top Boxes, Telephony, Televisions, Ceiling Fans, CFLs (Including GU24s),Decorative Light Strings, Integral LED Lamps, Luminaires, Residential Ventilating Fans.

The test site used by BACL Corp. to collect radiated and conducted emissions measurement data is located at its facility in Sunnyvale, California, USA.

The test site at BACL Corp. has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997, and Article 8 of the VCCI regulations on December 25, 1997. The test site also complies with the test methods and procedures set forth in CISPR 22:2008 §10.4 for measurements below 1 GHz and §10.6 for measurements above 1 GHz as well as ANSI C63.10-2013, ANSI C63.4-2014, TIA/EIA-603 & CISPR 24:2010.

The Federal Communications Commission and Voluntary Control Council for Interference have the reports on file and they are listed under FCC registration number: 90464 and VCCI Registration No.: A-0027. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL Corp. is an American Association for Laboratory Accreditation (A2LA) accredited laboratory (Lab Code 3297-02). The current scope of accreditations can be found at

<http://www.a2la.org/scopepdf/3297-02.pdf?CFID=1132286&CFTOKEN=e42a3240dac3f6ba-6DE17DCB-1851-9E57-477422F667031258&jsessionid=8430d44f1f47cf2996124343c704b367816b>

2 System Test Configuration

2.1 Justification

The EUT was configured for testing according to ANSI C63.10-2013 and FCC KDB 558074 D01 DTS Meas Guidance v03r04.

The EUT was tested in a testing mode to represent worst-case results during the final qualification test.

The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the average power, peak power and PPSD across all data rates bandwidths, and modulations.

2.2 EUT Exercise Software

The test utility used was Tera Term; the software was verified by *Todd Moy* to comply with the standard requirements being tested against.


2.3 Duty Cycle Correction Factor

According to KDB 558074 D01 DTS Meas Guidance v03r04 section 6.0:

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be utilized to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data is being acquired (i.e., no transmitter off-time is to be considered).

| Radio Mode | On Time (μs) | Period (μs) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) |
|------------|--------------|-------------|----------------|-----------------------------------|
| BLE | 407.3 | 625.9 | 65 | 1.87 |

Duty Cycle = On Time (ms)/ Period (ms), Duty Cycle Correction Factor (dB) = $10 \log(1/\text{Duty Cycle})$



2.4 Equipment Modifications

SMA cables were connected to the output trace of the Bluetooth and ANT+ circuits.

2.5 Local Support Equipment

| Manufacturer | Description | Model |
|--------------|-------------|---------------|
| Dell | Laptop | Latitude D630 |

2.6 EUT Internal Configuration Details

| Manufacturer | Description | Model |
|--------------|-------------|------------|
| Intel | Main Board | Radar Pace |

2.7 Support Equipment

| Manufacturer | Description | Model |
|--------------|--------------------|------------|
| Intel | USB to UART Driver | H81964-001 |

2.8 Interface Ports and Cabling

| Cable Description | Length (m) | To | From |
|-------------------|------------|--------|------|
| USB Cable | < 1 m | Laptop | EUT |
| SMA Pigtailed | < 1 m | EUT | PSA |

3 Summary of Test Results

Results reported relate only to the product tested.

| FCC & ISED Rules | Description of Test | Results |
|---|--|-----------|
| FCC §15.203 ISED RSS-Gen §8.3 | Antenna Requirement | Compliant |
| FCC §15.207 ISED RSS-Gen §8.8 | AC Line Conducted Emissions | Compliant |
| FCC §2.1093, §15.247(i) ISED RSS-102 | RF Exposure | Compliant |
| FCC §2.1051, §15.247 (d) ISED RSS-247 §5.5 | Spurious Emissions at Antenna Port | Compliant |
| FCC §2.1053, §15.205, §15.209, §15.247 (d) IC RSS-247 §5.5 ISED RSS-Gen §8.9 & §8.10 | Radiated Spurious Emissions | Compliant |
| FCC §15.247(a)(2) ISED RSS-247 §5.2 (1) | 6 dB & 99% Emission Bandwidth | Compliant |
| FCC §15.247(b)(3) ISED RSS-247 §5.4 (4) | Maximum Peak Output Power | Compliant |
| FCC §15.247(d) ISED RSS-247 §5.5 | 100 kHz Bandwidth of Frequency Band Edge | Compliant |
| FCC §15.247(e) ISED RSS-247 §5.2 (2) | Power Spectral Density | Compliant |

4 FCC §15.203 & ISED RSS-Gen §8.3 - Antenna Requirements

4.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to ISED RSS-Gen §8.3: Transmitter Antenna

The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the license-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

License-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (e.i.r.p.) limits specified in the applicable standard (RSS) for the license-exempt apparatus.

Testing shall be performed using the highest gain antenna of each combination of license-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.⁹ When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

User manuals for transmitters equipped with detachable antennas shall also contain the following notice in a conspicuous location:

This radio transmitter (identify the device by certification number) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types approved for use with the transmitter, indicating the maximum permissible antenna gain (in dBi).

4.2 Antenna Description

The antennas used by the EUT are permanently attached antennas.

| Radio | Maximum Antenna Gain (dBi) @ 2.4GHz |
|-----------|--|
| Bluetooth | -1.2 |
| ANT+ | -1.2 |

5 FCC §2.1093, §15.247(i) & ISED RSS-102 – RF Exposure

5.1 Applicable Standards

According to FCC KDB 447498 D01 General RF Exposure Guidance v05r02 Section 4.3.1, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:
 - a) $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW, at } 100 \text{ MHz to } 1500 \text{ MHz}$
 - b) $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW at } > 1500 \text{ MHz and } \leq 6 \text{ GHz}$
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion, and as illustrated in Appendix C:
 - a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm
 - b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm
 - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

According to ISED RSS-102 Issue 5 §2.5.1,

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1.

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance

| Frequency (MHz) | Exemption Limits (mW) | | | | |
|--------------------|--|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| | At separation distance of ≤ 5 mm | At separation distance of 10 mm | At separation distance of 15 mm | At separation distance of 20 mm | At separation distance of 25 mm |
| ≤ 300 | 71 | 101 | 132 | 162 | 193 |
| 450 | 52 | 70 | 88 | 106 | 123 |
| 835 | 17 | 30 | 42 | 55 | 67 |
| 1900 | 7 | 10 | 18 | 34 | 60 |
| 2450 | 4 | 7 | 15 | 30 | 52 |
| 3500 | 2 | 6 | 16 | 32 | 55 |
| 5800 | 1 | 6 | 15 | 27 | 41 |

| Frequency (MHz) | Exemption Limits (mW) | | | | |
|--------------------|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|---|
| | At separation distance of 30 mm | At separation distance of 35 mm | At separation distance of 40 mm | At separation distance of 45 mm | At separation distance of ≥ 50 mm |
| ≤ 300 | 223 | 254 | 284 | 315 | 345 |
| 450 | 141 | 159 | 177 | 195 | 213 |
| 835 | 80 | 92 | 105 | 117 | 130 |
| 1900 | 99 | 153 | 225 | 316 | 431 |
| 2450 | 83 | 123 | 173 | 235 | 309 |
| 3500 | 86 | 124 | 170 | 225 | 290 |
| 5800 | 56 | 71 | 85 | 97 | 106 |

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power. For controlled use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5. If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required. For medical implants devices, the exemption limit for routine evaluation is set at 1 mW.

The output power of a medical implants device is defined as the higher of the conducted or e.i.r.p to determine whether the device is exempt from the SAR evaluation.

5.2 RF Exposure Evaluation Results

The highest measured conducted power as reported in Section 9.5 of this report was -0.87 dBm (0.82 mW) at 2402 MHz. It is lower than both FCC and ISED SAR Exemption limit. Thus, SAR was exempted for this device.

6 FCC §15.207 & ISED RSS-Gen §8.8 - AC Line Conducted Emissions

6.1 Applicable Standards

As per FCC §15.207 and ISED RSS-Gen §8.8 Conducted limits:

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

| Frequency of Emission (MHz) | Conducted Limit (dBuV) | |
|-----------------------------|---------------------------|---------------------------|
| | Quasi-Peak | Average |
| 0.15-0.5 | 66 to 56 ^{Note1} | 56 to 46 ^{Note2} |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

Note1: Decreases with the logarithm of the frequency.

Note2: A linear average detector is required

6.2 Test Setup

The measurement was performed at shield room, using the setup per ANSI C63.10-2013 measurement procedure. The specification used were FCC §15.207 and ISED RSS-Gen §8.8 limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The AC/DC power adapter of the EUT was connected with LISN-1 which provided 120 V / 60 Hz AC power.

6.3 Test Procedure

During the conducted emissions test, the power cord of the EUT host system was connected to the mains outlet of the LISN-1 and the power cords of support equipment were connected to LISN-2.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data were recorded in the peak, quasi-peak, and average detection mode. Quasi-Peak readings are distinguished with a “QP.” Average readings are distinguished with an “Ave”.

6.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Cable Loss (CL), the Attenuator Factor (Atten) to indicated Amplitude (Ai) reading. The basic equation is as follows:


$$CA = Ai + CL + Atten$$

For example, a corrected amplitude of 46.2 dBuV = Indicated Reading (32.5 dBuV) + Cable Loss (3.7 dB) + Attenuator (10 dB)

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

6.5 Test Setup Block Diagram



6.6 Test Equipment List and Details

| Manufacturer | Description | Model No. | Serial No. | Calibration Date | Calibration Interval |
|---------------------------|--------------------------|-----------------------------|------------|------------------|----------------------|
| Rohde & Schwarz | Receiver, EMI Test | ESCI 1166.5950K03 | 100044 | 2015-07-23 | 1 year |
| Rohde & Schwarz | Impulse Limiter | ESH3-Z2 | 101963 | 2015-07-15 | 1 year |
| Keysight Technologies | RF Limiter | 11867A | MY42242931 | 2015-12-15 | 1 year |
| Solar Electronics Company | High Pass Filter | Type 7930-100 | 7930150204 | 2016-03-09 | 1 Year |
| Wireless Solutions | Conducted Emission Cable | LMR 400 | 691 | 2015-07-02 | 1 year |
| FCC | LISN | FCC-LISN-50-25-2-10-CISPR16 | 160129 | 2016-04-11 | 1 year |

Statement of Traceability: *BACL Corp.* attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.

6.7 Test Environmental Conditions

| | |
|--------------------|------------|
| Temperature: | 15° C |
| Relative Humidity: | 42 % |
| ATM Pressure: | 101.31 kPa |

The testing was performed by Leonard Gray on 2016-05-06 in 5 chamber 3.


6.8 Summary of Test Results

According to the recorded data in following table, the EUT complied with the FCC 15C and ISED RSS-Gen standard's conducted emissions limits, with the margin reading of:

| Connection: AC/DC adapter connected to 120 V/60 Hz, AC | | | |
|--|-----------------|-------------------------------|-------------|
| Margin (dB) | Frequency (MHz) | Conductor Mode (Live/Neutral) | Range (MHz) |
| 6.44 | 0.315666 | Neutral | 0.15-30 |

6.9 Conducted Emissions Test Plots and Data


120 V, 60 Hz – Line



| Frequency (MHz) | Corrected Amplitude (dBuV) | Conductor (Line/Neutral) | Limit (dBuV) | Margin (dB) | Detector (QP/Ave.) |
|-----------------|----------------------------|--------------------------|--------------|-------------|--------------------|
| 0.432897 | 42.68 | Line | 57.2 | -14.52 | QP |
| 0.627768 | 42.18 | Line | 56 | -13.82 | QP |
| 0.548379 | 43.73 | Line | 56 | -12.27 | QP |
| 0.515616 | 43.02 | Line | 56 | -12.98 | QP |
| 0.150131 | 53.34 | Line | 65.99 | -12.65 | QP |
| 0.316086 | 44.77 | Line | 59.81 | -15.04 | QP |

| Frequency (MHz) | Corrected Amplitude (dBuV) | Conductor (Line/Neutral) | Limit (dBuV) | Margin (dB) | Detector (QP/Ave.) |
|-----------------|----------------------------|--------------------------|--------------|-------------|--------------------|
| 0.432897 | 29.23 | Line | 47.2 | -17.97 | Ave. |
| 0.627768 | 37.67 | Line | 46 | -8.33 | Ave. |
| 0.548379 | 33.11 | Line | 46 | -12.89 | Ave. |
| 0.515616 | 33.09 | Line | 46 | -12.91 | Ave. |
| 0.150131 | 39.31 | Line | 55.99 | -16.68 | Ave. |
| 0.316086 | 42.2 | Line | 49.81 | -7.61 | Ave. |

120 V, 60 Hz – Neutral



| Frequency (MHz) | Corrected Amplitude (dBuV) | Conductor (Line/Neutral) | Limit (dBuV) | Margin (dB) | Detector (QP/Ave.) |
|-----------------|----------------------------|--------------------------|--------------|-------------|--------------------|
| 0.443136 | 44.84 | Neutral | 57 | -12.16 | QP |
| 0.582567 | 41.78 | Neutral | 56 | -14.22 | QP |
| 0.315666 | 45.03 | Neutral | 59.82 | -14.79 | QP |
| 0.856128 | 40.56 | Neutral | 56 | -15.44 | QP |
| 0.150127 | 51.86 | Neutral | 65.99 | -14.13 | QP |
| 0.695388 | 38.25 | Neutral | 56 | -17.75 | QP |

| Frequency (MHz) | Corrected Amplitude (dBuV) | Conductor (Line/Neutral) | Limit (dBuV) | Margin (dB) | Detector (QP/Ave.) |
|-----------------|----------------------------|--------------------------|--------------|-------------|--------------------|
| 0.443136 | 27.34 | Neutral | 47 | -19.66 | Ave. |
| 0.582567 | 33.99 | Neutral | 46 | -12.01 | Ave. |
| 0.315666 | 43.38 | Neutral | 49.82 | -6.44 | Ave. |
| 0.856128 | 24.23 | Neutral | 46 | -21.77 | Ave. |
| 0.150127 | 38.74 | Neutral | 55.99 | -17.25 | Ave. |
| 0.695388 | 23.06 | Neutral | 46 | -22.94 | Ave. |

7 FCC §15.209, §15.247(d) & ISED RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions

7.1 Applicable Standards

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As Per FCC §15.205(a) and RSS-Gen except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|---------------------|-----------------------|-----------------|---------------|
| 0.090 – 0.110 | 16.42 – 16.423 | 960 – 1240 | 4.5 – 5.15 |
| 0.495 – 0.505 | 16.69475 – 16.69525 | 1300 – 1427 | 5.35 – 5.46 |
| 2.1735 – 2.1905 | 25.5 – 25.67 | 1435 – 1626.5 | 7.25 – 7.75 |
| 4.125 – 4.128 | 37.5 – 38.25 | 1645.5 – 1646.5 | 8.025 – 8.5 |
| 4.17725 – 4.17775 | 73 – 74.6 | 1660 – 1710 | 9.0 – 9.2 |
| 4.20725 – 4.20775 | 74.8 – 75.2 | 1718.8 – 1722.2 | 9.3 – 9.5 |
| 6.215 – 6.218 | 108 – 121.94 | 2200 – 2300 | 10.6 – 12.7 |
| 6.26775 – 6.26825 | 123 – 138 | 2310 – 2390 | 13.25 – 13.4 |
| 6.31175 – 6.31225 | 149.9 – 150.05 | 2483.5 – 2500 | 14.47 – 14.5 |
| 8.291 – 8.294 | 156.52475 – 156.52525 | 2690 – 2900 | 15.35 – 16.2 |
| 8.362 – 8.366 | 156.7 – 156.9 | 3260 – 3267 | 17.7 – 21.4 |
| 8.37625 – 8.38675 | 162.0125 – 167.17 | 3.332 – 3.339 | 22.01 – 23.12 |
| 8.41425 – 8.41475 | 167.72 – 173.2 | 3 3458 – 3 358 | 23.6 – 24.0 |
| 12.29 – 12.293 | 240 – 285 | 3.600 – 4.400 | 31.2 – 31.8 |
| 12.51975 – 12.52025 | 322 – 335.4 | | 36.43 – 36.5 |
| 12.57675 – 12.57725 | 399.9 – 410 | | Above 38.6 |
| 13.36 – 13.41 | 608 – 614 | | |

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

| Frequency (MHz) | Field Strength (micro volts/meter) | Measurement Distance (meters) |
|-----------------|------------------------------------|-------------------------------|
| 0.009 - 0.490 | 2400/F(kHz) | 300 |
| 0.490 - 1.705 | 24000/F(kHz) | 30 |
| 1.705 - 30.0 | 30 | 30 |
| 30 - 88 | 100** | 3 |
| 88 - 216 | 150** | 3 |
| 216 - 960 | 200** | 3 |
| Above 960 | 500 | 3 |

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per ISED RSS-Gen 8.9,

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 4 or Table 5 below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

Table 4 – General Field Strength Limits for Licence-Exempt Transmitters at Frequencies Above 30 MHz

| Frequency (MHz) | Field Strength (μV/m at 3 metres) |
|-----------------|-----------------------------------|
| 30-88 | 100 |
| 88-216 | 150 |
| 216-960 | 200 |
| Above 960* | 500 |

* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for license-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

As per ISED RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

7.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.10-2013. The specification used was the FCC 15 Subpart C and ISED RSS-247 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

7.3 Test Procedure

For the radiated emissions test, the EUT host, and all support equipment power cords were connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT was set 3 meter away from the testing antenna, which was varied from 1-4 meter, and the EUT was placed on a turntable, which was 0.8 meter and 1.5 meter above the ground plane for below and above 1000 MHz measurements, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna's polarity should be changed between horizontal and vertical.

The spectrum analyzer or receiver was set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak: $\text{RBW} = 1\text{MHz} / \text{VBW} = 1\text{MHz} / \text{Sweep} = \text{Auto}$
- (2) Average: $\text{RBW} = 1\text{MHz} / \text{VBW} = 10\text{Hz} / \text{Sweep} = \text{Auto}$

7.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$\text{CA} = \text{Ai} + \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

7.5 Test Equipment List and Details

| Manufacturer | Description | Model No. | Serial No. | Calibration Date | Calibration Interval |
|--------------------|----------------------------|-------------------|------------------|------------------------|----------------------|
| Rohde & Schwarz | Receiver, EMI Test | ESCI 1166.5950K03 | 100044 | 2015-07-23 | 1 year |
| Agilent | Analyzer, Spectrum | E4440A | MY44303352 | 2015-06-22 | 1 year |
| Sunol Science Corp | System Controller | SC99V | 011003-1 | N/R | N/R |
| Sunol Sciences | Antenna, Biconi-Log | JB3 | A020106-2 | 2015-07-11 | 2 years |
| Sunol Sciences | Antenna, Horn | DRH-118 | A052704 | 2015-03-09 | 2 years |
| Agilent | Amplifier, Pre | 8447D | 2944A10187 | 2016-03-23 | 1 year |
| Wireless Solutions | Conducted Emission Cable | LMR 400 | 691 | 2015-07-02 | 1 year |
| - | SMA cable | - | 606 | Each time ¹ | N/A |
| IW | High Frequency Co AX Cable | DC 1531 | KPS-1501A3960KPS | 2015-08-10 | 1 year |
| Agilent | Pre-Amplifier | 8449B | 3008A01978 | 2015-09-02 | 1 year |
| Wisewave | Amplifier, Low Noise | ALN-22093530-01 | 12263-01 | 2015-04-28 | 1 year |
| Wisewave | Antenna, Horn | ARH-4223-02 | 10555-02 | 2013-09-20 | 3 year |

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL attests that all calibrations have been performed per the A2LA requirements, traceable to NIST.*

7.6 Test Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 20-22 °C |
| Relative Humidity: | 42-50 % |
| ATM Pressure: | 102.7 kPa |

The testing was performed by Todd Moy from 2016-04-25 to 2016-05-11 in 5m chamber 3.

7.7 Summary of Test Results


According to the data hereinafter, the EUT complied with FCC Title 47, Part 15C and ISED RSS-247 standard's radiated emissions limits, and had the worst margin of:

| Mode: Transmitting | | | |
|---------------------------|------------------------|---|----------------|
| Margin (dB) | Frequency (MHz) | Polarization (Horizontal/Vertical) | Channel |
| 3.18 | 9920 | Vertical | High Channel |

Please refer to the following table and plots for specific test result details

7.8 Radiated Emissions Test Results

1) 30 MHz – 1 GHz Worst Case, Measured at 3 meters



| Frequency (MHz) | Corrected Amplitude (dB μ V/m) | Antenna Height (cm) | Antenna Polarity (H/V) | Turntable Azimuth (degrees) | Limit (dB μ V/m) | Margin (dB) | Comment |
|-----------------|------------------------------------|---------------------|------------------------|-----------------------------|----------------------|-------------|---------|
| 949.2943 | 25.5 | 238 | V | 296 | 46 | -20.5 | QP |
| 200.65 | 36.68 | 153 | H | 97 | 43.5 | -6.82 | QP |
| 66.4135 | 29.92 | 298 | V | 250 | 40 | -10.08 | QP |
| 249.9848 | 38.93 | 106 | H | 159 | 46 | -7.07 | QP |
| 335.9988 | 39 | 100 | H | 15 | 46 | -7 | QP |
| 32.51475 | 26.43 | 100 | V | 105 | 40 | -13.57 | QP |

2) 1-25 GHz Measured at 3 meters

| Frequency (MHz) | S.A. Reading (dB μ V) | Turntable Azimuth (degrees) | Test Antenna | | | Cable Loss (dB) | Pre-Amp. (dB) | Cord. Reading (dB μ V/m) | FCC/IC | | Comments |
|-------------------------|---------------------------|-----------------------------|--------------|----------------|---------------|-----------------|---------------|------------------------------|----------------------|-------------|----------|
| | | | Height (cm) | Polarity (H/V) | Factor (dB/m) | | | | Limit (dB μ V/m) | Margin (dB) | |
| Low Channel 2402 MHz | | | | | | | | | | | |
| 2402 | 54.86 | 341 | 331 | V | 29.04 | 3.43 | 0.00 | 87.33 | - | - | Peak |
| 2402 | 61.74 | 73 | 291 | H | 29.04 | 3.43 | 0.00 | 94.21 | - | - | Peak |
| 2402 | 44.27 | 355 | 330 | V | 29.04 | 3.43 | 0.00 | 76.74 | - | - | Ave |
| 2402 | 48.25 | 72 | 293 | H | 29.04 | 3.43 | 0.00 | 80.72 | - | - | Ave |
| 2390 | 26.57 | 341 | 331 | V | 29.04 | 3.43 | 0.00 | 59.04 | 74 | -14.96 | Peak |
| 2390 | 25.79 | 73 | 291 | H | 29.04 | 3.43 | 0.00 | 58.26 | 74 | -15.74 | Peak |
| 2390 | 16.08 | 335 | 330 | V | 29.04 | 3.43 | 0.00 | 48.55 | 54 | -5.45 | Ave |
| 2390 | 16.10 | 72 | 293 | H | 29.04 | 3.43 | 0.00 | 48.57 | 54 | -5.43 | Ave |
| 4804 | 50.10 | 18 | 320 | V | 32.47 | 6.06 | 33.72 | 54.91 | 74 | -19.09 | Peak |
| 4804 | 50.83 | 79 | 281 | H | 32.47 | 6.06 | 33.72 | 55.64 | 74 | -18.36 | Peak |
| 4804 | 40.69 | 16 | 351 | V | 32.47 | 6.06 | 33.72 | 45.50 | 54 | -8.50 | Ave |
| 4804 | 40.45 | 33 | 331 | H | 32.47 | 6.06 | 33.72 | 45.26 | 54 | -8.74 | Ave |
| 7206 | 48.79 | 0 | 100 | V | 36.69 | 6.92 | 33.93 | 58.47 | 67.33 | -8.86 | Peak |
| 7206 | 49.24 | 0 | 100 | H | 36.69 | 6.92 | 33.93 | 58.92 | 74.21 | -15.29 | Peak |
| 7206 | 36.50 | 104 | 297 | V | 36.69 | 6.92 | 33.93 | 46.18 | 56.74 | -10.56 | Ave |
| 7206 | 37.45 | 188 | 189 | H | 36.69 | 6.92 | 33.93 | 47.13 | 60.72 | -13.59 | Ave |
| 9608 | 46.87 | 0 | 100 | V | 37.84 | 9.84 | 34.31 | 60.23 | 67.33 | -7.10 | Peak |
| 9608 | 48.82 | 0 | 100 | H | 37.84 | 9.84 | 34.31 | 62.18 | 74.21 | -12.03 | Peak |
| 9608 | 35.29 | 0 | 100 | V | 37.84 | 9.84 | 34.31 | 48.65 | 56.74 | -8.09 | Ave |
| 9608 | 35.30 | 0 | 100 | H | 37.84 | 9.84 | 34.31 | 48.66 | 60.72 | -12.06 | Ave |
| Middle Channel 2440 MHz | | | | | | | | | | | |
| 2440 | 54.01 | 357 | 321 | V | 29.41 | 3.43 | 0.00 | 86.85 | - | - | Peak |
| 2440 | 60.83 | 53 | 247 | H | 29.41 | 3.43 | 0.00 | 93.67 | - | - | Peak |
| 2440 | 43.11 | 342 | 351 | V | 29.41 | 3.43 | 0.00 | 75.95 | - | - | Ave |
| 2440 | 47.82 | 56 | 246 | H | 29.41 | 3.43 | 0.00 | 80.66 | - | - | Ave |
| 4880 | 50.50 | 33 | 331 | V | 32.64 | 6.06 | 33.75 | 55.45 | 74 | -18.55 | Peak |
| 4880 | 51.98 | 74 | 266 | H | 32.64 | 6.06 | 33.75 | 56.93 | 74 | -17.07 | Peak |
| 4880 | 41.25 | 12 | 307 | V | 32.64 | 6.06 | 33.75 | 46.20 | 54 | -7.80 | Ave |
| 4880 | 42.63 | 54 | 394 | H | 32.64 | 6.06 | 33.75 | 47.58 | 54 | -6.42 | Ave |
| 7320 | 48.78 | 0 | 100 | V | 37.15 | 7.39 | 33.99 | 59.34 | 74 | -14.66 | Peak |
| 7320 | 49.25 | 0 | 100 | H | 37.15 | 7.39 | 33.99 | 59.81 | 74 | -14.19 | Peak |
| 7320 | 36.11 | 0 | 100 | V | 37.15 | 7.39 | 33.99 | 46.67 | 54 | -7.33 | Ave |
| 7320 | 37.12 | 192 | 268 | H | 37.15 | 7.39 | 33.99 | 47.68 | 54 | -6.32 | Ave |
| 9760 | 49.28 | 0 | 100 | V | 37.92 | 8.72 | 34.31 | 61.60 | 66.85 | -5.25 | Peak |
| 9760 | 48.90 | 0 | 100 | H | 37.92 | 8.72 | 34.31 | 61.22 | 73.67 | -12.45 | Peak |
| 9760 | 35.97 | 0 | 100 | V | 37.92 | 8.72 | 34.31 | 48.30 | 55.95 | -7.65 | Ave |
| 9760 | 35.90 | 0 | 100 | H | 37.92 | 8.72 | 34.31 | 48.23 | 60.66 | -12.43 | Ave |

| Frequency (MHz) | S.A. Reading (dB μ V) | Turntable Azimuth (degrees) | Test Antenna | | | Cable Loss (dB) | Pre- Amp. (dB) | Cord. Reading (dB μ V/m) | FCC/IC | | Comments |
|-----------------------|---------------------------------|-----------------------------------|----------------|-------------------|------------------|-----------------------|----------------------|------------------------------------|-------------------------|----------------|----------|
| | | | Height (cm) | Polarity (H/V) | Factor (dB/m) | | | | Limit (dB μ V/m) | Margin (dB) | |
| High Channel 2480 MHz | | | | | | | | | | | |
| 2480 | 52.72 | 22 | 341 | V | 29.41 | 3.43 | 0.00 | 85.56 | - | - | Peak |
| 2480 | 60.08 | 58 | 334 | H | 29.41 | 3.43 | 0.00 | 92.92 | - | - | Peak |
| 2480 | 43.24 | 347 | 348 | V | 29.41 | 3.43 | 0.00 | 76.08 | - | - | Ave |
| 2480 | 47.19 | 58 | 336 | H | 29.41 | 3.43 | 0.00 | 80.03 | - | - | Ave |
| 2483.5 | 26.74 | 22 | 341 | V | 29.41 | 3.43 | 0.00 | 59.58 | 74 | -14.42 | Peak |
| 2483.5 | 25.87 | 58 | 334 | H | 29.41 | 3.43 | 0.00 | 58.71 | 74 | -15.29 | Peak |
| 2483.5 | 16.35 | 347 | 348 | V | 29.41 | 3.43 | 0.00 | 49.19 | 54 | -4.81 | Ave |
| 2483.5 | 16.36 | 58 | 336 | H | 29.41 | 3.43 | 0.00 | 49.20 | 54 | -4.80 | Ave |
| 4960 | 50.94 | 32 | 350 | V | 32.91 | 5.31 | 34.62 | 54.55 | 74 | -19.45 | Peak |
| 4960 | 51.78 | 67 | 301 | H | 32.99 | 5.31 | 34.62 | 55.46 | 74 | -18.54 | Peak |
| 4960 | 40.41 | 30 | 298 | V | 32.91 | 5.31 | 34.62 | 44.02 | 54 | -9.98 | Ave |
| 4960 | 42.92 | 67 | 300 | H | 32.99 | 5.31 | 34.62 | 46.60 | 54 | -7.40 | Ave |
| 7440 | 48.24 | 0 | 100 | V | 37.14 | 7.46 | 33.99 | 58.86 | 74 | -15.14 | Peak |
| 7440 | 49.83 | 0 | 100 | H | 37.14 | 7.46 | 33.99 | 60.45 | 74 | -13.55 | Peak |
| 7440 | 36.89 | 348 | 100 | V | 37.14 | 7.46 | 33.99 | 47.50 | 54 | -6.50 | Ave |
| 7440 | 37.37 | 0 | 266 | H | 37.14 | 7.46 | 33.99 | 47.98 | 54 | -6.02 | Ave |
| 9920 | 49.68 | 21 | 140 | V | 37.99 | 9.11 | 34.39 | 62.38 | 65.56 | -3.18 | Peak |
| 9920 | 49.68 | 0 | 232 | H | 37.99 | 9.11 | 34.39 | 62.38 | 72.92 | -10.54 | Peak |
| 9920 | 36.95 | 0 | 100 | V | 37.99 | 9.11 | 34.39 | 49.65 | 56.08 | -6.43 | Ave |
| 9920 | 37.28 | 0 | 265 | H | 37.99 | 9.11 | 34.39 | 49.98 | 60.03 | -10.05 | Ave |

Note: Duty Cycle Correction Factor has been added to the measurements.

8 FCC §15.247(a) (2) & ISED RSS-247 §5.2 -Emission Bandwidth

8.1 Applicable Standards

According to FCC §15.247(a) (2) and ISED RSS-247 §5.2, systems using digital modulation techniques may operate in the 902~928 MHz, 2400~2483.5 MHz, and 5725~5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

8.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v03r04: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8: DTS bandwidth

8.3 Test Equipment List and Details

| Manufacturer | Description | Model No. | Serial No. | Calibration Date | Calibration Interval |
|--------------|--------------------|-----------|------------|------------------------|----------------------|
| Agilent | Analyzer, Spectrum | E4440A | MY44303352 | 2015-06-22 | 1 year |
| - | SMA Pigtail | - | - | Each time ¹ | N/A |

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.

8.4 Test Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 22° C |
| Relative Humidity: | 42 % |
| ATM Pressure: | 102.7 KPa |


The testing was performed by Todd Moy on 2016-04-26 in RF site.

8.5 Test Results


| Channel | Frequency (MHz) | 99% OBW (kHz) | 6 dB OBW (kHz) | 6 dB OBW limit (kHz) |
|---------|-----------------|---------------|----------------|----------------------|
| BLE | | | | |
| Low | 2402 | 1044.6 | 665.233 | 500 |
| Middle | 2440 | 1037.3 | 660.969 | 500 |
| High | 2480 | 1056.9 | 671.872 | 500 |

Please refer to the following plots for detailed test results.

Low Channel 2402 MHz



Middle Channel 2440 MHz



High Channel 2480 MHz



9 FCC §15.247(b) (3) & ISED RSS-247 §5.4 (4) - Output Power

9.1 Applicable Standards

According to FCC §15.247(b) (3) and ISED RSS-247 §5.4 (4) for systems using digital modulation in the 902~928 MHz, 2400~2483.5 MHz, and 5725~5850 MHz bands: 1 Watt.

9.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v03r04: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 9: Fundamental emission output power

9.3 Test Equipment List and Details

| Manufacturer | Description | Model No. | Serial No. | Calibration Date | Calibration Interval |
|--------------|--------------------|-----------|------------|------------------------|----------------------|
| Agilent | Analyzer, Spectrum | E4440A | MY44303352 | 2015-06-22 | 1 year |
| - | SMA Pigtail | - | - | Each time ¹ | N/A |

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp. attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.*

9.4 Test Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 22° C |
| Relative Humidity: | 42 % |
| ATM Pressure: | 102.7 KPa |


The testing was performed by Jose Martinez on 2016-05-27 in RF site.

9.5 Test Results


| Channel | Frequency (MHz) | Conducted Power (dBm) | Limit (dBm) |
|---------|-----------------|-----------------------|-------------|
| Low | 2402 | -0.87 | 30 |
| Middle | 2440 | -2.16 | 30 |
| High | 2480 | -2.58 | 30 |

Please refer to the following plots for detailed test results.


Low Channel 2402 MHz



Middle Channel 2440 MHz



High Channel 2480 MHz



10 FCC §15.247(d) & ISED RSS-247 §5.5 – 100 kHz Bandwidth of Band Edges

10.1 Applicable Standards

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c).

According to ISED RSS-247 §5.5. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

10.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v03r04: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 13: Band-edge measurements

10.3 Test Equipment List and Details

| Manufacturer | Description | Model No. | Serial No. | Calibration Date | Calibration Interval |
|--------------|--------------------|-----------|------------|------------------------|----------------------|
| Agilent | Analyzer, Spectrum | E4440A | MY44303352 | 2015-06-22 | 1 year |
| - | SMA Pigtail | - | - | Each time ¹ | N/A |

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.


10.4 Test Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 22° C |
| Relative Humidity: | 42 % |
| ATM Pressure: | 102.7 KPa |


The testing was performed by Todd Moy on 2016-04-26 in RF site.

10.5 Test Results

Low Channel 2402 MHz



High Channel 2480 MHz



11 FCC §15.247(e) & ISED RSS-247 §5.2(2) – Power Spectral Density

11.1 Applicable Standards

According to FCC §15.247(e) and RSS-247 §5.2 (2) , for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

11.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v03r04: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10: Maximum power spectral density level in the fundamental emission.

11.3 Test Equipment List and Details

| Manufacturer | Description | Model No. | Serial No. | Calibration Date | Calibration Interval |
|--------------|--------------------|-----------|------------|------------------------|----------------------|
| Agilent | Analyzer, Spectrum | E4440A | MY44303352 | 2015-06-22 | 1 year |
| - | SMA Pigtail | - | - | Each time ¹ | N/A |

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.

11.4 Test Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 22° C |
| Relative Humidity: | 42 % |
| ATM Pressure: | 102.7 KPa |


The testing was performed by Todd Moy on 2016-04-26 in RF site.

11.5 Test Results


| Channel | Frequency (MHz) | PSD (dBm/3kHz) | Limit (dBm/3kHz) |
|---------|-----------------|----------------|------------------|
| Low | 2402 | -16.33 | 8 |
| Middle | 2440 | -17.51 | 8 |
| High | 2480 | -17.97 | 8 |

Please refer to the following plots for detailed test results


Low Channel 2402 MHz



Middle Channel 2440 MHz



High Channel 2480 MHz



12 FCC §15.247(d) & ISED RSS-247 §5.5 & ISED RSS-GEN §8.9 – Spurious Emissions at Antenna Terminals

12.1 Applicable Standards

For FCC §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per ISED RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

12.2 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

12.3 Test Equipment List and Details

| Manufacturer | Description | Model No. | Serial No. | Calibration Date | Calibration Interval |
|--------------|--------------------|-----------|------------|------------------------|----------------------|
| Agilent | Analyzer, Spectrum | E4440A | MY44303352 | 2015-06-22 | 1 year |
| - | SMA Pigtail | - | - | Each time ¹ | N/A |

Note¹: cable and attenuator included in the test set-up will be checked each time before testing.

Statement of Traceability: *BACL Corp.* attests that all calibrations have been performed per the A2LA requirements, traceable to the NIST.

12.4 Test Environmental Conditions


| | |
|--------------------|-----------|
| Temperature: | 22° C |
| Relative Humidity: | 42 % |
| ATM Pressure: | 102.7 KPa |

The testing was performed by Todd Moy on 2016-04-26 in RF site.


12.5 Test Results

Please refer to following plots.


Low Channel 30 MHz – 3 GHz




Low Channel 3 GHz – 25 GHz




Middle Channel 30 MHz – 3 GHz



Middle Channel 3 GHz – 25 GHz



High Channel 30 MHz – 3 GHz



High Channel 3 GHz – 25 GHz

