

FCC Part 15B TEST REPORT FCC ID: 2AB9N-T5T3

Product: GSM mobile phone

Trade Name: N/A

Model Number: T5

Serial Model: T3

Report No.: STS1409009E01

Prepared for

TUC INDUSTIRAL CO.,LTD

Room 2106 Block A, Huaqiangbei, Electronic Technology Building, Futian District, Shenzhen

Prepared by

Shenzhen STS Test Services Co., Ltd.

1/F, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong,
Baoan District, Shenzhen, China

TEL: +86-755 6119 6328

FAX: +86-755 6119 6328

E-mail:sts@stsapp.com

TEST RESULT CERTIFICATION

Applicant's name TUC INDUSTIRAL CO.,LTD

Building, Futian, District, Shenzhen

Manufacture's Name TUC INDUSTIRAL CO.,LTD

Building, Futian, District, Shenzhen

Product description

Product name...... GSM mobile phone

Brand name N/A

Model and/or type reference .. : T5

Serial Model T3

Ratings...... DC 5V/0.50A

Standards FCC 47 CFR Part 15 Subpart B

Test procedure...... ANSI C63.4-2009

This device described above has been tested by BZT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BZT, this document may be altered or revised by BZT, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.. 11 Sep, 2014 ~18 Sep, 2014

Test Result Pass

Testing Engineer :

(Iony Liu

Technical Manager:

(Vita Li

Authorized Signatory:

(Bovey Yang)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS 1.1 TEST FACILITY 1.2 MEASUREMENT UNCERTAINTY	4 5 5
2. GENERAL INFORMATION 2.1 GENERAL DESCRIPTION OF EUT 2.2 DESCRIPTION OF TEST MODES 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	6 6 7 7 8 9
3. EMC EMISSION TEST 3.1 CONDUCTED EMISSION MEASUREMENT 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 3.1.2 TEST PROCEDURE 3.1.3 DEVIATION FROM TEST STANDARD 3.1.4 TEST SETUP 3.1.5 EUT OPERATING CONDITIONS 3.1.6 TEST RESULTS	10 10 10 11 11 11 11
3.2 RADIATED EMISSION MEASUREMENT 3.2.1 RADIATED EMISSION LIMITS 3.2.2 TEST PROCEDURE 3.2.3 DEVIATION FROM TEST STANDARD 3.2.4 TEST SETUP 3.2.5 EUT OPERATING CONDITIONS 3.2.6 TEST RESULTS (BELOW 30 MHZ) 3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)	14 14 15 15 16 17 18
4. EUT TEST PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	22

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B (10-1-05 Edition)	Conducted Emission	PASS	Meet Class B limit
	Radiated Emission	PASS	Meet Class B limit

N		Τ.	$\overline{}$	
n	"	1	_	•

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen STS Test Services Co., Ltd. 1/F, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong, Baoan District, Shenzhen, China

FCC Registration No.: 842334

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	GSM mobile phone
Trade Name	N/A
Model Name	T5
Serial Model	Т3
Model Difference	Only difference in model name
Channel List	Please refer to the Note 2.
Adoptor	Input:AC 100-240V,50/60Hz,0.10A
Adapter	Output:DC 5V,500mA
	Rated Voltage: 3.7V
Battery	Charge Limit: 4.2V
	capacity :1800mAh
Hardware version number	
Software versioning number	
Connecting I/O Port(s)	Please refer to the User's Manual
CPU processor speed	1.2GHz

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Mode Description		
Mode 1	USB Model		
Mode 2	GSM Mode		
Mode 3	MP3/MP4 Mode		
Mode 4	Idle Mode		

For Conducted Emission		
Final Test Mode	Description	
Mode1	USB Model	

For Radiated Emission			
Final Test Mode Description			
Mode 1	USB Model		

Note:

(1) Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse modeis reported by this report.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	GSM mobile phone	N/A	T5	N/A	EUT
E-2	Notebook	Lenovo	B460	WB03928113	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.5m	
C-2	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- For detachable type I/O cable should be specified the length in cm in <code>『Length』</code> column. "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core". (2)
- (3)

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Due
1	Spectrum Analyzer	Agilent	E4407B	160400005	Jul. 06. 2015
2	Test Receiver	R&S	ESPI	101318	Jul. 06. 2015
3	Bilog Antenna	TESEQ	CBL6111D	31216	Nov.23. 2014
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	Jul. 06. 2015
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	Jul. 06. 2015
6	Horn Antenna	EM	EM-AH-10180	2011071402	Nov.23. 2014
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	Jul. 06. 2015
8	Amplifier	EM	EM-30180	060538	Jul. 06. 2015
9	Loop Antenna	ARA	PLA-1030/B	1029	Jul. 06. 2015
10	Power Meter	R&S	NRVS	100696	Jul. 06. 2015
11	Power Sensor (Peak)	R&S	NRV-Z31	0396.0101.1 9	Jul. 06. 2015

Conduction Test equipment

.00	nauction rest equipi	ICIIC			
Ite	m Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Test Receiver	R&S	ESCI	101160	Jul. 06. 2015
2	LISN	R&S	ENV216	101313	Jul. 06. 2015
3	LISN	EMCO	3816/2	00042990	Jul. 06. 2015
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	Jul. 06. 2015
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	Jul. 06. 2015
6	Absorbing clamp	R&S	MOS-21	100423	Jul. 06. 2015

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A	(dBuV)	Class B	Standard	
FREQUENCT (MITZ)	Quasi-peak	Average	Quasi-peak	Average	Statiualu
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS

EUT:	GSM mobile phone	Model Name. :	T5
Temperature :	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage : DC 5V from Adapter with AC 120V/60Hz		Test Mode:	1

Frequency	QuasiPeak	Average	Correction	QuasiPeak	Average	QuasiPeak	Average	QuasiPeak	Average	Remark
	reading	reading	factor	result	result	limit	limit	margin	margin	
(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
0.8821	19.56	8.43	19.89	39.45	28.32	56	46	-16.55	-17.68	Pass
1.478	18.24	7.25	19.92	38.16	27.17	56	46	-17.84	-18.83	Pass
2.0443	17.43	6.43	19.92	37.35	26.35	56	46	-18.65	-19.65	Pass
2.587	17.43	5.24	20	37.43	25.24	56	46	-18.57	-20.76	Pass
3.3521	12.23	0.21	20.2	32.43	20.41	56	46	-23.57	-25.59	Pass
7.1642	16.21	5.57	20.4	36.61	25.97	60	50	-23.39	-24.03	Pass


Remark:



EUT:	GSM mobile phone	Model Name. :	T5
Temperature :	26 ℃	Relative Humidity:	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter with AC 120V/60Hz	Test Mode:	1

Frequency	QuasiPeak	Average	Correction	QuasiPeak	Average	QuasiPeak	Average	QuasiPeak	Average	Remark
	reading	reading	factor	result	result	limit	limit	margin	margin	
(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
0.3967	25.35	15.86	19.72	45.07	35.58	57.88	47.88	-12.81	-12.3	Pass
0.8256	25.25	14.58	19.81	45.06	34.39	56	46	-10.94	-11.61	Pass
1.3824	23.42	14.07	19.85	43.27	33.92	56	46	-12.73	-12.08	Pass
2.0012	23.12	14.25	19.92	43.04	34.17	56	46	-12.96	-11.83	Pass
3.0765	22.43	13.13	20.14	42.57	33.27	56	46	-13.43	-12.73	Pass
4.7965	21.92	12.23	20.25	42.17	32.48	56	46	-13.83	-13.52	Pass

Remark:



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBu	V/m) (at 3M)	Class B (dBuV/m) (at 3M)		
PREQUENCY (MIDZ)	PEAK	AVERAGE	PEAK	AVERAGE	
Above 1000	80	60	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted	1 MHz / 1 MHz for Dook, 1 MHz / 10Hz for Average
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT:	GSM mobile phone	Model Name. :	T5			
Temperature:	20 ℃	Relative Humidity:	48%			
Pressure:	1010 hPa	Polarization :				
Test Voltage :	DC 5V from Adapter AC 120V/60Hz					
Test Mode :	Mode 1					

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB); Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30M - 1000 MHZ)

EUT:	GSM mobile phone	Model Name. :	T5			
Temperature :	20 ℃	Relative Humidity:	48%			
Pressure:	1010 hPa	Polarization :	Horizontal			
Test Voltage :	DC 5V from Adapter AC 120V/6	er AC 120V/60Hz				
Test Mode :	Mode 1					

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
120.24	16.21	14.03	30.24	43.5	-13.26	150	88	QP
758.35	14.35	22.85	37.2	46	-8.8	100	243	QP
795.21	13.47	23.36	36.83	46	-9.17	100	360	QP
845.87	13.12	23.34	36.46	46	-9.54	100	224	QP
891.24	14.32	24.07	38.39	46	-7.61	150	232	QP
933.12	13.14	24.81	37.95	46	-8.05	150	197	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT:	GSM mobile phone	Model Name. :	T5				
Temperature :	20 ℃	Relative Humidity:	48%				
Pressure:	1010 hPa	Polarization :	Vertical				
Test Voltage :	DC 5V from Adapter AC 120V/60Hz						
Test Mode :	Mode 1						

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
64.89	24.45	8.13	32.58	40	-7.42	150	265	QP
767.23	13.13	22.24	35.37	46	-10.63	100	167	QP
799.24	14.45	23.14	37.59	46	-8.41	100	282	QP
864.13	14.43	23.32	37.75	46	-8.25	100	33	QP
929.12	15.32	24.65	39.97	46	-6.03	100	152	QP
946.63	16.32	25.12	41.44	46	-4.56	100	164	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



The worst test data above 1 GHz was showed as thefollow:							
EUT:	SSM mobile phone Model Name. : T5						
Temperature :	20 ℃	Relative Humidity:	48%				
Pressure:	1010 hPa	Polarization :	Vertical				
Test Voltage :	DC 5V from Adapter AC 120V/60Hz						
Test Mode :	Mode 1						


Freq.	Ant. Pol	Peak	AV	Ant./CL	A	Actual Fs Peak AV		AV	Peak	AV
(MHz)	H/V	Reading	Reading	CF	Actu			Limit	margin	margin
		(dBuV)	(dBuV)	(dB)	Peak			(dBuV/m)	(dBuV/m)	(dBuV/m)
					(dBuV/m)	(dBuV/m)				
1023.12	Н	59.45	41.31	4.87	64.32	46.18	74	54	-9.68	-7.82
2645.14	Н	53.34	38.22	9.23	62.57	47.45	74	54	-11.43	-6.55
N/A										
1023.12	V	55.23	36.21	4.87	60.1	41.08	74	54	-13.9	-12.92
2645.14	V	50.22	31.45	9.23	59.45	40.68	74	54	-14.55	-13.32
N/A										

Notes:

- 1. Measuring frequencies from 1 GHz to 6GHz.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
- 3. The frequency that above 3GHz is mainly from the environment noise.

4. EUT TEST PHOTO

Radiated Measurement Photos Blow 1GHz



Above 1GHz

