


Maximum Permissible Exposure Report


FCC ID: 2AB9W-PP120XP


Report No. : BTL-FCCP-3-1911T047
Equipment : 3D Printer
Model Name : PartPro120 xP
Brand Name : XYZprinting
Applicant : XYZprinting, Inc.
Address : 10F., No.99, Sec. 5, Nanjing E. Rd., Songshan Dist., Taipei City 10571, Taiwan (R.O.C.)
Manufacturer : Cal-Comp Electronics (Thailand) Public Company Limited
Address : 138, Moo 4, Phechkasem Road, Sapang, Koawoyoi, Petchaburi 76140, Thailand.
Factory : Cal-Comp Electronics (Thailand) Public Company Limited
Address : 138, Moo 4, Phechkasem Road, Sapang, Koawoyoi, Petchaburi 76140, Thailand.
FCC Rule Part(s) : FCC Guidelines for Human Exposure IEEE C95.1
Date of Receipt : 2019/11/27
Date of Test : 2019/11/27 ~ 2019/12/30
Issued Date : 2020/1/8

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by


Peter Chen, Engineer

**Approved by**


Scott Hsu, Manager

BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299

Fax: +886-2-2657-3331

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	2020/1/8

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PCB	N/A	-8.65

TEST RESULTS

For WLAN:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-8.65	0.1365	13	19.9526	0.0005	1	Complies

Note: The calculated distance is 20 cm.

For NFC:

Limits to Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 to 3.0	614	1.63	100 (Note 2)	6
3.0 to 30	1842/f	4.89/f	900/f ² (Note 2)	6
30 to 300	61.4	0.163	1.0	6
300 to 1500	-	-	f/300	6
1500 to 100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 to 1.34	614	1.63	100 (Note 2)	30
1.34 to 30	824/f	2.19/f	180/f ² (Note 2)	30
30 to 300	27.5	0.073	0.2	30
300 to 1500	-	-	f/1500	30
1500 to 100,000	-	-	1.0	30

Notes:

- f = frequency in MHz
- Power density is plane wave equivalent power density.

Max H-field strength (dBuV/m)	E-field strength (V/m)	Limit
38.46	0.00008	60.77

COLLOCATED POWER DENSITY CALCULATIONS

So for NFC+2.4G simultaneous transmission $0.00008/60.77+0.0005/1=0.0005<1$

End of Test Report