



# **FCC** Radio Test Report

**FCC ID: 2ABAMPLLB** 

This report concerns (check one): ⊠Original Grant □Class II Change

Project No. : 1608247
Equipment : Pill
Test Model : PB15226
Series Model : N/A

Series Mode : N/A Applicant : Hello Inc.

Address: 438 Shotwell St, San Francisco, CA 94110, USA

Date of Receipt: Aug. 31, 2016

**Date of Test** : Aug. 31, 2016 ~ Oct. 13, 2016

Issued Date : Oct. 14, 2016
Tested by : BTL Inc.

Testing Engineer : Kao

(Rush Kao)

Technical Manager :

^

**Authorized Signatory** 

BTL INC.

B1, No. 37, Lane 365, Yang-Guang St., Nei-Hu District, Taipei City 114, Taiwan.

TEL: +886-2-2657-3299 FAX: +886-2-2657-3331

Report No.: BTL-FCCP-1-1608247 Page 1 of 64





#### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL**'s reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL**'s report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the ISO Guide 17025 requirements, and accredited by the conformity assessment authorities listed in this test report.

#### Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: BTL-FCCP-1-1608247 Page 2 of 64





Table of Contents	Page
1. CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	8
3. GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	10
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST	_
3.5 DESCRIPTION OF SUPPORT UNITS	11
4 . EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
4.1.2 TEST PROCEDURE 4.1.3 DEVIATION FROM TEST STANDARD	12 12
4.1.3 DEVIATION FROM TEST STANDARD  4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 EUT TEST CONDITIONS	13
4.1.7 TEST RESULTS	13
4.2 RADIATED EMISSION MEASUREMENT 4.2.1 RADIATED EMISSION LIMITS	14 14
4.2.2 TEST PROCEDURE	15
4.2.3 DEVIATION FROM TEST STANDARD	15
4.2.4 TEST SETUP	16
4.2.5 EUT OPERATING CONDITIONS 4.2.6 EUT TEST CONDITIONS	17 17
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	17 17
4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)	18
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	18
5 . BANDWIDTH TEST	19
5.1 APPLIED PROCEDURES / LIMIT	19
5.1.1 TEST PROCEDURE 5.1.2 DEVIATION FROM STANDARD	19 19
5.1.2 DEVIATION FROM STANDARD  5.1.3 TEST SETUP	19
5.1.4 EUT OPERATION CONDITIONS	19
5.1.5 EUT TEST CONDITIONS	19
5.1.6 TEST RESULTS	19

Report No.: BTL-FCCP-1-1608247





Page 4 of 64

Table of Contents	Page
6 . MAXIMUM OUTPUT POWER TEST	20
6.1 APPLIED PROCEDURES / LIMIT	20
6.1.1 TEST PROCEDURE	20
6.1.2 DEVIATION FROM STANDARD	20
6.1.3 TEST SETUP	20
6.1.4 EUT OPERATION CONDITIONS 6.1.5 EUT TEST CONDITIONS	20 20
6.1.6 TEST RESULTS	20
7. ANTENNA CONDUCTED SPURIOUS EMISSION	21
7.1 APPLIED PROCEDURES / LIMIT	21
7.1.1 TEST PROCEDURE	21
7.1.2 DEVIATION FROM STANDARD	21
7.1.3 TEST SETUP 7.1.4 EUT OPERATION CONDITIONS	21 21
7.1.5 EUT OPERATION CONDITIONS	21
7.1.6 TEST RESULTS	21
8 . POWER SPECTRAL DENSITY TEST	22
8.1 APPLIED PROCEDURES / LIMIT	22
8.1.1 TEST PROCEDURE 8.1.2 DEVIATION FROM STANDARD	22 22
8.1.3 TEST SETUP	22
8.1.4 EUT OPERATION CONDITIONS	22
8.1.5 EUT TEST CONDITIONS	22
8.1.6 TEST RESULTS	22
9 . MEASUREMENT INSTRUMENTS LIST	23
10 . EUT TEST PHOTO	25
ATTACHMENT A - CONDUCTED EMISSION	28
ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)	29
ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)	34
ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)	37
ATTACHMENT E - BANDWIDTH	50
ATTACHMENT F - MAXIMUM OUTPUT POWER TEST	53
ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION	54
ATTACHMENT H - POWER SPECTRAL DENSITY TEST	62

Report No.: BTL-FCCP-1-1608247





## **REPORT ISSUED HISTORY**

Issued No.	Description	Issued Date
BTL-FCCP-1-1608247	Original Issue.	Oct. 14, 2016

Report No.: BTL-FCCP-1-1608247 Page 5 of 64





## 1. CERTIFICATION

Equipment : Pill
Brand Name : Hello
Test Model : PB15226
Series Model : N/A
Applicant : Hello Inc.
Manufacturer : Jabil Circuit

Address : 10560 Dr. Martin Luther King Jr. St. N., St. Petersburg, FL 33716, United

States

Factory : Jabil Circuit (GuangZhou) LTD.

Address : 128, JunCheng Road, Eastern Zone, Guangzhou Economic and

Technological Development District, 510530 Guangdong Province, PRC

Date of Test : Aug. 31, 2016 ~ Oct. 13, 2016

Test Sample : Engineering Sample

Standard(s) : FCC Part15, Subpart C (15.247) / ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1608247) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: BTL-FCCP-1-1608247 Page 6 of 64





## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C				
Standard(s) Section	Test Item	Judgment	Remark	
15.207	Conducted Emission	N/A	NOTE(1)	
15.247(d)	Antenna conducted Spurious Emission	PASS		
15.247(a)(2)	6dB Bandwidth	PASS		
15.247(b)(3)	Peak Output Power	PASS		
15.247(e)	Power Spectral Density	PASS		
15.203	Antenna Requirement	PASS		
15.209/15.205	Transmitter Radiated Emissions	PASS		

### NOTE:

- (1)" N/A" denotes test is not applicable to this device.
- (2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r05 (Measurement Guidelines of DTS)

#### 2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

### Radiated emission Test (Below 1GHz):

**CB15:** (FCC RN:674415; FCC DN:TW0659)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

## Radiated emission Test (Above 1GHz):

**CB15:** (FCC RN:674415; FCC DN:TW0659)

No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

Report No.: BTL-FCCP-1-1608247 Page 7 of 64





#### 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

The BTL measurement uncertainty is less than the CISPR 16-4-2 U<sub>cispr</sub> requirement.

The reported uncertainty of measurement  $\mathbf{y} \pm \mathbf{U}$ , where expanded uncertainty  $\mathbf{U}$  is based on a standard uncertainty multiplied by a coverage factor of  $\mathbf{k=2}$ , providing a level of confidence of approximately 95 %.

#### A. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	U,(dB)
CB15	CISPR	9kHz ~ 150kHz	2.96
(3m)	CIOPK	150kHz ~ 30MHz	2.74

Test Site	Method	d Measurement Frequency Range		U,(dB)
		30MHz ~ 200MHz	V	4.76
CB15	CISPR	30MHz ~ 200MHz	Н	4.28
(3m)	CIOPK	200MHz ~ 1,000MHz	V	5.08
		200MHz ~ 1,000MHz	Н	4.50

Test Site	Method	Measurement Frequency Range	Ant.	U,(dB)
		1GHz ~ 6GHz	V	4.48
CB15	CISPR	1GHz ~ 6GHz	Н	4.50
(3m)	CIOPR	6GHz ~ 18GHz	V	4.30
		6GHz ~ 18GHz	Н	4.14

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our  $U_{\text{lab}}$  values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called  $U_{\text{CISPR}}$ , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz : 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz : 5.2 dB

It can be seen that our  $U_{\text{lab}}$  values are smaller than  $U_{\text{CISPR}}$ .

Report No.: BTL-FCCP-1-1608247 Page 8 of 64





## 3. GENERAL INFORMATION

## 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Pill		
Brand Name	Hello		
Test Model	PB15226		
Model Difference	N/A		
Power Source	Battery supplied.		
Power Rating	I/P: DC 3V (1 * CR 2430)		
	Operation Frequency	2402 MHz ~ 2480 MHz	
Draduat Description	Modulation Technology	CECK/4Mbps)	
Product Description	Bit Rate of Transmitter	GFSK(1Mbps)	
	Output Power (Max.)	3.91 dBm	

## Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

## 2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

## 3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Hello	N/A	PCB_Meander- IFA type	N/A	1.4

Report No.: BTL-FCCP-1-1608247 Page 9 of 64





#### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode <b>NOTE (1)</b>

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Radiated Test		
Final Test Mode	Description	
Mode 1	TX Mode <b>NOTE (1)</b>	

#### Note:

(1) The measurements are performed at the high, middle, low available channels.

## 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of bluetooth LE.


Test Software Version	cmd		
Frequency (MHz)	2402	2440	2480
BT LE	DEF	DEF	DEF

Report No.: BTL-FCCP-1-1608247 Page 10 of 64





## 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



## 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
	Notabook DC	ACED	ACER	NI/A	NXMPFTA00143
A	Notebook PC	ACER	V3-371-67HZ	N/A	80598B6600

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	0.8m	USB Cable
2	NO	NO	1.0m	Power Cable
3	NO	NO	1.0m	Power Cable

Report No.: BTL-FCCP-1-1608247 Page 11 of 64





#### 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

## 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Fraguency of Emission (MHz)	Conducted Limit (dBµV)		
Frequency of Emission (MHz)	Quasi-peak	Average	
0.15 -0.5	66 to 56*	56 to 46*	
0 50 -5.0	56	46	
5.0 -30.0	60	50	

#### Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following: Measurement Value = Reading Level + Correct Factor Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use) Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

## **4.1.2 TEST PROCEDURE**

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD


No deviation

Report No.: BTL-FCCP-1-1608247 Page 12 of 64





#### 4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

## 4.1.6 EUT TEST CONDITIONS

Temperature: N/A Relative Humidity: N/A Test Voltage: N/A

#### 4.1.7 TEST RESULTS

Please refer to the Attachment A.

#### Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of <code>『Note』</code>. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a " \* " marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) "N/A" denotes test is not applicable to this device.

Report No.: BTL-FCCP-1-1608247 Page 13 of 64





#### 4.2 RADIATED EMISSION MEASUREMENT

#### 4.2.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on 15.205(a) then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

## LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)		
r requericy (Wiriz)	PEAK	AVERAGE	
Above 1000	74	54	

## Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following: Measurement Value = Reading Level + Correct Factor Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use) Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW	RBW 1MHz VBW 3MHz peak detector for Pk value
(Emission in restricted band)	RMS detector for AV value

Report No.: BTL-FCCP-1-1608247 Page 14 of 64





Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### **4.2.2 TEST PROCEDURE**

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5 m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

## 4.2.3 DEVIATION FROM TEST STANDARD

No deviation


Report No.: BTL-FCCP-1-1608247 Page 15 of 64






## 4.2.4 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz




Report No.: BTL-FCCP-1-1608247 Page 16 of 64





## (C) For radiated emissions below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **4.1.5** unless otherwise a special operating condition is specified in the follows during the testing.

## 4.2.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 65% Test Voltage: AC 120V/60Hz

## 4.2.7TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

## Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

Report No.: BTL-FCCP-1-1608247 Page 17 of 64





## **4.2.8TEST RESULTS (30MHZ TO 1000 MHZ)**

Please refer to the Attachment C.

#### Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz.
- (3) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

## 4.2.9TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

#### Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (3) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (4) EUT Orthogonal Axis:
  - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (5) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (6) No limit: This is fundamental signal, the judgment is not applicable. For fundamental signal judgment was referred to Peak output test.

Report No.: BTL-FCCP-1-1608247 Page 18 of 64





## 5. BANDWIDTH TEST

## 5.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

## **5.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

#### **5.1.2 DEVIATION FROM STANDARD**

No deviation.

## **5.1.3 TEST SETUP**

EUT	SPECTRUM
	ANALYZER

#### **5.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

## **5.1.5 EUT TEST CONDITIONS**

Temperature: 25°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

#### **5.1.6 TEST RESULTS**

Please refer to the Attachment E.

Report No.: BTL-FCCP-1-1608247 Page 19 of 64





#### 6. MAXIMUM OUTPUT POWER TEST

6.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 watt or 30dBm	2400-2483.5	PASS

#### **6.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. The maximum peak conducted output power was performed in accordance with method 9.1.2 of FCC KDB 558074 D01 DTS Meas Guidance v03r05.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP

EUT	Power Meter
	1 over meter

## **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

Transmit output power was measured while the host equipment supply voltage was varied from 85 % to 115 % of the nominal rated supply voltage. No change in transmit output power was observed.

#### **6.1.5 EUT TEST CONDITIONS**

Temperature: 25°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

#### 6.1.6 TEST RESULTS

Please refer to the Attachment F.

Report No.: BTL-FCCP-1-1608247 Page 20 of 64





#### 7. ANTENNA CONDUCTED SPURIOUS EMISSION

## 7.1 Applied procedures / limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that transmitter demonstrates compliance with the peak conducted power limits.

#### 7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 10 ms.
- c. Offset=antenna gain+ cable loss

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

#### 7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

## 7.1.5 EUT OPERATION CONDITIONS

Temperature: 25°C Relative Humidity: 60%

Test Voltage: AC 120V/60Hz

#### 7.1.6 TEST RESULTS

Please refer to the Attachment G.

Report No.: BTL-FCCP-1-1608247 Page 21 of 64





## 8. POWER SPECTRAL DENSITY TEST

8.1 Applied procedures / limit

FCC Part15 (15.247) , Subpart C					
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS	

## **8.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=10 KHz, Sweep time = auto.

## **8.1.2 DEVIATION FROM STANDARD**

No deviation.

## 8.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

## **8.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

## **8.1.5 EUT TEST CONDITIONS**

Temperature: 25°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

## 8.1.6 TEST RESULTS

Please refer to the Attachment H.

Report No.: BTL-FCCP-1-1608247 Page 22 of 64





## 9. MEASUREMENT INSTRUMENTS LIST

	Radiated Emission Measurement						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until		
1	Trilog-Broadband Antenna	Schwarzbeck	VULB9168-35 2	9168-352	Feb. 04, 2017		
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-546	Nov. 05, 2017		
3	Pre-Amplifier	HP	8447D	2944A08891	Mar. 09 2017		
4	Pre-Amplifier	Agilent	8449B	3008A02331	Jan. 24, 2017		
5	Test Cable	EMCI	EMC8D-NM-N M-8000	150301	Mar. 09, 2017		
6	Test Cable	EMCI	EMC104-SM-S M-2500	150303	Mar. 09, 2017		
7	Test Cable	EMCI	EMC104-NM-S M-1000	150304	Mar. 09, 2017		
8	Test Cable	EMCI	EMC104-SM-S M-5000	150302	Mar. 29, 2017		
9	Test Cable	EMCI	EMC104-SM-S M-800	150305	Mar. 29, 2017		
10	EXA Spectrum Analyzer	Agilent	N9010A	MY52220990	Feb. 24, 2017		
11	EMI Test Receiver	Agilent	N9038A	MY51210215	Jan. 08, 2017		
12	Loop Antenna	EMCO	6502	00042960	Nov. 06. 2016		

Report No.: BTL-FCCP-1-1608247 Page 23 of 64





	6dB Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until	
1	Spectrum Analyzer	R&S	FSP-40	100129	Jan. 18, 2017	

	Peak Output Power Measurement							
Item	Item Kind of Equipment Manufacturer Type No. Serial No. Calibrated unt							
1	Power Meter	Anritsu	ML2487A	6K00004714	May 18, 2017			
2	Power Meter Sensor	Anritsu	MA2491A	034138	May 17, 2017			

	Antenna Conducted Spurious Emission Measurement						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until		
1	Spectrum Analyzer	R&S	FSP-40	100129	Jan. 18, 2017		

	Power Spectral Density Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until	
1	Spectrum Analyzer	R&S	FSP-40	100129	Jan. 18, 2017	

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

Report No.: BTL-FCCP-1-1608247 Page 24 of 64





## **ATTACHMENT A - CONDUCTED EMISSION**

		_	
Tact	Mode.	N/A	

Note: "N/A" denotes test is not applicable to this device.

Report No.: BTL-FCCP-1-1608247 Page 28 of 64






ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)

Report No.: BTL-FCCP-1-1608247 Page 29 of 64







No. Mk.	Freq.	Reading Level		Measure- ment		Margin		
	MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	0.1135	36.70	12.08	48.78	120.98	-72.20	peak	

Report No.: BTL-FCCP-1-1608247 Page 30 of 64





Test Mode: TX Mode




	No. I	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
-			MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1		0.1500	47.93	12.03	59.96	118.34	-58.38	peak	
	2		0.4187	38.46	11.80	50.26	98.95	-48.69	peak	
	3	*	0.9261	30.79	11.97	42.76	69.91	-27.15	peak	
	4		3.3140	18.93	11.15	30.08	69.54	-39.46	peak	
_	5		6.6871	14.74	11.37	26.11	69.54	-43.43	peak	
	6		13.2840	10.42	11.20	21.62	69.54	-47.92	peak	
_			,				,	,	,	·

Report No.: BTL-FCCP-1-1608247 Page 31 of 64







MHz dBuV dB dBuV/m dB Detector Comment  1 * 0.0434 41.02 13.66 54.68 126.04 -71.36 peak	No. Mk.	Freq.	_		Measure- ment		Margin			
1 * 0.0434 41.02 13.66 54.68 126.04 -71.36 peak		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
	1 *	0.0434	41.02	13.66	54.68	126.04	-71.36	peak		

Report No.: BTL-FCCP-1-1608247 Page 32 of 64







Report No.: BTL-FCCP-1-1608247 Page 33 of 64






ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Report No.: BTL-FCCP-1-1608247 Page 34 of 64








Report No.: BTL-FCCP-1-1608247 Page 35 of 64







Report No.: BTL-FCCP-1-1608247 Page 36 of 64






ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Report No.: BTL-FCCP-1-1608247 Page 37 of 64





Orthogonal Axis: X
Test Mode: TX 2402MHz\_CH00\_1Mbps



1	No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1	2	2378.400	31.83	30.92	62.75	74.00	-11.25	peak	
	2	2	2378.400	19.58	30.92	50.50	54.00	-3.50	AVG	
	3	X 2	2402.000	68.37	31.01	99.38	74.00	25.38	peak	No Limit
	4	* 2	2402.000	67.93	31.01	98.94	54.00	44.94	AVG	No Limit


Report No.: BTL-FCCP-1-1608247 Page 38 of 64





Orthogonal Axis: X TX 2402MHz\_CH00\_1Mbps Test Mode:

# Vertical



	No.	Mk.	Freq.	Reading Level		Measure- ment	Limit	Margin		
			MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1		4804.000	62.85	-11.50	51.35	74.00	-22.65	peak	
	2	*	4804.000	54.83	-11.50	43.33	54.00	-10.67	AVG	
_	3		7206.000	54.74	-5.47	49.27	74.00	-24.73	peak	
	4		7206.000	46.80	-5.47	41.33	54.00	-12.67	AVG	

Report No.: BTL-FCCP-1-1608247 Page 39 of 64



2377.000 2382.00

2387.00

2392.00

2397.00



Orthogonal Axis: X
Test Mode: TX 2402MHz\_CH00\_1Mbps

# 

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2	2378.200	34.64	30.92	65.56	74.00	-8.44	peak	
2	2	2378.200	22.06	30.92	52.98	54.00	-1.02	AVG	
3	X 2	2402.000	73.75	31.01	104.76	74.00	30.76	peak	No Limit
4	*	2402.000	73.25	31.01	104.26	54.00	50.26	AVG	No Limit

2417.00

2427.00 MHz

Report No.: BTL-FCCP-1-1608247 Page 40 of 64





Orthogonal Axis: X
Test Mode: TX 2402MHz\_CH00\_1Mbps

### Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4	4804.000	63.43	-11.50	51.93	74.00	-22.07	peak	
2	4	4804.000	52.84	-11.50	41.34	54.00	-12.66	AVG	
3		7206.000	55.95	-5.47	50.48	74.00	-23.52	peak	
4	*	7206.000	49.44	-5.47	43.97	54.00	-10.03	AVG	

Report No.: BTL-FCCP-1-1608247 Page 41 of 64





Orthogonal Axis: X
Test Mode: TX 2440MHz\_CH19\_1Mbps



	No.	Mk	. Freq.			Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1	Χ	2440.000	65.73	31.15	96.88	74.00	22.88	peak	No Limit
_	2	*	2440.000	65.24	31.15	96.39	54.00	42.39	AVG	No Limit

Report No.: BTL-FCCP-1-1608247 Page 42 of 64



20 10

1000.000 3550.00

6100.00

8650.00

11200.00



26500.00 MHz

Orthogonal Axis: X
Test Mode: TX 2440MHz\_CH19\_1Mbps

## 

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4880.000	63.64	-11.38	52.26	74.00	-21.74	peak	
2	*	4880.000	56.06	-11.38	44.68	54.00	-9.32	AVG	
3		7320.000	55.37	-5.04	50.33	74.00	-23.67	peak	
4		7320.000	48.79	-5.04	43.75	54.00	-10.25	AVG	

13750.00

16300.00 18850.00


Report No.: BTL-FCCP-1-1608247 Page 43 of 64





Orthogonal Axis: X
Test Mode: TX 2440MHz\_CH19\_1Mbps

### Horizontal



	No.	Mk	c. Freq.		Correct Factor	Measure- ment		Margin		
_			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
_	1	X	2440.000	70.19	31.15	101.34	74.00	27.34	peak	No Limit
_	2	*	2440.000	69.77	31.15	100.92	54.00	46.92	AVG	No Limit


Report No.: BTL-FCCP-1-1608247 Page 44 of 64





Orthogonal Axis: X
Test Mode: TX 2440MHz\_CH19\_1Mbps

### Horizontal




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4880.000	68.19	-11.38	56.81	74.00	-17.19	peak	
2	*	4880.000	61.50	-11.38	50.12	54.00	-3.88	AVG	
3		7320.000	56.43	-5.04	51.39	74.00	-22.61	peak	
4		7320.000	50.05	-5.04	45.01	54.00	-8.99	AVG	

Report No.: BTL-FCCP-1-1608247 Page 45 of 64





Orthogonal Axis: X
Test Mode: TX 2480MHz\_CH39\_1Mbps



No.	Mk	c. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	Χ	2480.000	66.98	31.29	98.27	74.00	24.27	peak	No Limit
2	*	2480.000	66.46	31.29	97.75	54.00	43.75	AVG	No Limit
3		2497.400	30.66	31.36	62.02	74.00	-11.98	peak	
4		2497.400	19.38	31.36	50.74	54.00	-3.26	AVG	


Report No.: BTL-FCCP-1-1608247 Page 46 of 64





Orthogonal Axis: X Test Mode: TX 2480MHz\_CH39\_1Mbps

# Vertical



No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	69.82	-11.25	58.57	74.00	-15.43	peak	
2	*	4960.000	62.25	-11.25	51.00	54.00	-3.00	AVG	
3		7440.000	57.58	-4.60	52.98	74.00	-21.02	peak	
4		7440.000	52.65	-4.60	48.05	54.00	-5.95	AVG	

Report No.: BTL-FCCP-1-1608247 Page 47 of 64



10

2455.000 2460.00

2465.00

2470.00

2475.00



2505.00 MHz

Orthogonal Axis: X
Test Mode: TX 2480MHz\_CH39\_1Mbps

# Horizontal 120.0 dBuV/m 110 90 80 70 60 41 30 20

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	Χ	2480.000	69.66	31.29	100.95	74.00	26.95	peak	No Limit
2	*	2480.000	69.21	31.29	100.50	54.00	46.50	AVG	No Limit
3		2497.400	31.13	31.36	62.49	74.00	-11.51	peak	
4		2497.400	21.01	31.36	52.37	54.00	-1.63	AVG	

Report No.: BTL-FCCP-1-1608247 Page 48 of 64





Orthogonal Axis: X
Test Mode: TX 2480MHz\_CH39\_1Mbps

### Horizontal



No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	67.97	-11.25	56.72	74.00	-17.28	peak	
2		4960.000	60.63	-11.25	49.38	54.00	-4.62	AVG	
3		7440.000	60.16	-4.60	55.56	74.00	-18.44	peak	
4	*	7440.000	56.31	-4.60	51.71	54.00	-2.29	AVG	

Report No.: BTL-FCCP-1-1608247 Page 49 of 64





ATTACHMENT E - BANDWIDTH	


Report No.: BTL-FCCP-1-1608247 Page 50 of 64





Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2402	0.558	1.048	500	Complies
2440	0.504	1.044	500	Complies
2480	0.576	1.044	500	Complies

### TX CH00




Date: 14.0CT.2016 20:34:15


Report No.: BTL-FCCP-1-1608247 Page 51 of 64







Date: 14.0CT.2016 20:35:42



Date: 14.0CT.2016 20:38:24





# **ATTACHMENT F - MAXIMUM OUTPUT POWER TEST**

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watt)	Max. Limit (dBm)	Max. Limit (Watt)	Test Result
2402	3.75	0.0024	30.00	1.00	Complies
2440	3.88	0.0024	30.00	1.00	Complies
2480	3.91	0.0025	30.00	1.00	Complies

Report No.: BTL-FCCP-1-1608247 Page 53 of 64






# ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION

Report No.: BTL-FCCP-1-1608247 Page 54 of 64








Report No.: BTL-FCCP-1-1608247 Page 55 of 64






### CH00 (10 Harmonic of the frequency)




Date: 28.JUL.2016 13:02:04



Date: 28.JUL.2016 13:02:11








Date: 28.JUL.2016 13:02:18

Report No.: BTL-FCCP-1-1608247 Page 57 of 64






### CH19 (10 Harmonic of the frequency)




Date: 28.JUL.2016 13:04:07



Date: 28.JUL.2016 13:04:13








Date: 28.JUL.2016 13:04:20

Report No.: BTL-FCCP-1-1608247 Page 59 of 64











Date: 28.JUL.2016 13:05:32



Date: 28.JUL.2016 13:05:38







Date: 28.JUL.2016 13:05:45

Report No.: BTL-FCCP-1-1608247 Page 61 of 64





ATTACHMENT H - POWER SPECTRAL DENSITY TEST						


Report No.: BTL-FCCP-1-1608247 Page 62 of 64





Frequency (MHz)	Power Density (dBm)	Max. Limit (dBm)	Result
2402	-8.72	8	Complies
2440	-9.01	8	Complies
2480	-9.38	8	Complies

### TX CH00




Date: 25.JUL.2016 14:15:25

Report No.: BTL-FCCP-1-1608247 Page 63 of 64







Date: 25.JUL.2016 14:18:01



Date: 25.JUL.2016 14:22:14