

### CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com

# RF EXPOSURE EVALUATION

Applicant : Dekist Co.,Ltd

Applicant Address : #303 465-1 Gimryangjang-dong Cheoin-

gu, Yongin-si, Gyeonggi-do, Korea

Kind of Product : Wireless Temperature Humidity Sensor

Equipment model name : RN300

Antenna type : Chip antenna Gain : 2.5 dBi

Frequency Range : 2405 – 2475 MHz

Number of channels : 15



## CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com

# \*\* MPE Calculations \*\*

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where,
EIRP = 0.69 + 2.5 = 0.87 dBm	P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)
= 0.07 dBIII	

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

 $G = Log^{-1}$  (dB antenna gain / 10)

 $G = Log^{-1} (2.5 / 10)$ 

G = 1.778

### Power density at the specific separation:

$S = PG/(4R^2\pi)$	Where,
$S = (0.69 * 1.778)/(4 * 20^2 * \pi)$	S = Maximum power density (mW/cm²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the
S =0.0002 mW/cm <sup>2</sup>	antenna (20cm = limit for MPE)

The Maximum permissible exposure (MPE) for the general population is 1  $\rm mW/cm^2$  . The power density at 20cm does not exceed the 1  $\rm mW/cm^2$  limit.

### **Estimated safe separation:**

$R = \sqrt{(PG / 4\pi)}$	Where,
$R = \sqrt{(0.69 * 1.778 / 4\pi)}$	P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the
R = 0.31 cm	antenna (20cm = limit for MPE)