

RF EXPOSURE EVALUATION

Applicant : DEKIST Co., Ltd

Applicant Address : #A1403, 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, Korea

Kind of Product : Wireless Data Logger

Equipment model name : RN400 H2-EX

FCC ID : 2ABC3-RN400

Antenna type : Chip Antenna

Antenna Gain : 1.9 dBi

** MPE Calculations **

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user. The MPE calculation for this exposure is shown below.

The peak radiated output power (EIRP) is calculated as follows:

EIRP = P + G	Where, P = Power input to the antenna (mW) G = Power gain of the antenna (dBi)
--------------	--

The numeric gain(G) of the antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain} / 10)$$

Power density at the specific separation:

$S = PG/(4R^2\pi)$	Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
--------------------	---

The Maximum permissible exposure (MPE) for the general population is 1 mW/cm². The power density at 20cm does not exceed the 1 mW/cm² limit.

Estimated safe separation:

$R = \sqrt{(PG / 4\pi)}$	Where, P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)
--------------------------	--



CTK Co., Ltd.
The Prime Leader of Global Regulatory Certification

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970 Fax: +82-31-624-9501
www.e-ctk.com

Mode	P (dBm)	P (mW)	G (dBi)	S (mW/cm ²)	R (cm)
802.11b	14.14	25.94	1.9	0.0275	20
802.11g	14.64	29.11		0.0080	
802.11n	14.20	26.30		0.0090	