



TEST REPORT

Report No. SST240408002EF04

Applicant: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Address of Applicant: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

Product Name: Android Tablet

Trade Mark: /

Standard(s): FCC CFR Title 47 Part 15 Subpart E Section 15.407

FCC ID: 2ABC5-E0055

Test Report Form No: SST-RD-7.5-02-E01(A/0)

Date of sample receipt: 2024/4/8

Date of Test: 2024/4/8 - 2024/4/24

Date of report issued: 2024/4/25

*The equipment complies with the requirements according to the standard(s) or Specification above, it is applicable only to the tested sample identified in the report.

Prepared by:

Bo Li

Reviewed by:

Seven Chan

Approved by:

Tiger Lee



*The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Version	Description	Date of Issue
V1.0	Original	2024/4/25



2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	3
3 TEST SUMMARY	4
4 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE(S)	6
5.4 TEST FACILITY	7
5.5 DESCRIPTION OF SUPPORT UNITS	7
5.6 ADDITIONAL INSTRUCTIONS	7
5.7 ANTENNA INFORMATION	7
5.8 OTHERS	7
6 TECHNICAL REQUIREMENT AND MEASUREMENT DATA	8
6.1 GENERALLY REQUIREMENT	8
6.2 DUTY CYCLE	9
6.3 CONDUCTED PEAK OUTPUT POWER	10
6.4 EMISSION BANDWIDTH	11
6.5 POWER SPECTRAL DENSITY	12
6.6 FREQUENCY STABILITY	13
6.7 RADIATED SPURIOUS EMISSION	14
6.8 CONDUCTED EMISSIONS	23
7 TEST SETUP PHOTO	26
8 EUT CONSTRUCTIONAL DETAILS	26
ANNEX A --TEST INSTRUMENTS LIST	27

3 Test Summary

Test items	Basics standards	Result
Antenna requirement	FCC part 15.203	PASS
Automatically discontinue transmission	FCC part 15.407(c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	PASS
99% Bandwidth	Report only	PASS
Emission Bandwidth	FCC part 15.407(a)	PASS
Peak Transmit Power	FCC part 15.407(a)(1)(2)	PASS
Power Spectral Density	FCC part 15.407(a) (1)(2)	PASS
Undesirable Emission	FCC part 15.407(b), 15.205/15.209	PASS
Radiated Emission	FCC part 15.205/15.209	PASS
Frequency Stability	FCC part 15.407(g)	PASS

Notes:

1: NA =Not Applicable

2: Determining compliance based on the results of the compliance measurement, not taking into account measurement uncertainty. If necessary, the applicant shall inform test lab in advance

3: Additions, Deviations and Exclusions from Standards: None.

4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Item	Uncertainty ($\pm$) ($k=2$, 95%)	
Output Power, Conducted	0.54	
Power Spectral Density, Conducted	1.28	
Spurious Emissions, Conducted	1.28	
Radiated Emissions(<1GHz)	9kHz~30MHz	2.6
	30MHz~1GHz	5.08
Radiated Emissions(>1GHz)	1GHz~6GHz	4.02
	6GHz~18GHz	4.62
	18GHz~40GHz	4.7
Occupied Bandwidth	1.14	
Conducted Emissions—AC mains	9kHz~150KHz	1.76
	150kHz~30MHz	2.52
Conducted Emissions—Telecom	2.64	

5 General Information

5.1 Client Information

Applicant: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.
Address of applicant: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.
Manufacturer: Same as applicant
Address of Manufacturer: Same as applicant
Factory: Same as applicant
Address of Factory: Same as applicant

5.2 General Description of EUT

Product Name:	Android Tablet
Model No.:	SW3295T, NW3295T
Test Model:	SW3295T
Test sample(s) ID:	24040800202
Sample(s) Status:	Continuously transmitter
S/N:	/
Hardware version:	R136 V1.0
Software version:	/
Operation Frequency:	5180MHz~5240MHz
Technical specific:	802.11a, 802.11n, 802.11ac, 802.11ax
Supported bandwidth:	20MHz, 40MHz, 80MHz
Modulation technology:	OFDM(A)
Antenna gain:	Refer to section 5.7 for details
Power supply:	SW3295T: SWITCH MODE POWER SUPPLY Model No.: E096-1A180500B3 INPUT: AC 100-240V, 50/60Hz, 1.5A OUTPUT: DC 18V, 5.0A, 90.0W Or 6800mAh, 14.6V, 99.28Wh Lithium-ion Rechargeable Battery NW3295T: SWITCH ADAPTER Model No.: FJ-SW20171205000 INPUT: AC 100-240V, 50/60Hz, 1.5A MAX OUTPUT: DC 12V, 5.0A, 60.0W

Channel list for 802.11							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	54	5270MHz	104	5520MHz	122	5610MHz
38	5190MHz	56	5280MHz	106	5530MHz	124	5620MHz
40	5200MHz	58	5290MHz	108	5540MHz	126	5630MHz
42	5210MHz	60	5300MHz	110	5550MHz	128	5640MHz
44	5220MHz	62	5310MHz	112	5560MHz	132	5660MHz
46	5230MHz	64	5320MHz	116	5580MHz	134	5670MHz
48	5240MHz	100	5500MHz	118	5590MHz	136	5680MHz
52	5260MHz	102	5510MHz	120	5600MHz	140	5700MHz

5.3 Test mode(s)

Mode 1:	continuously transmitting, with its lowest data rate which emit the max power level
Mode 2:	
Mode 3:	

5.4 Test Facility

The test facility is recognized, certified, or accredited by these organizations:	FCC Accredited Lab Test Firm Registration Number: 638130 Designation Number: CN1359
	IC Registration Lab CAB Identifier No.CN0154
	A2LA Accreditation Lab Certificate No.:7057.01

Test Performed at:	Name GuangDong Set Sail Testing Co., Ltd.
	Address 101, No.19, Tianxin Hudie 1st Road, Huangjiang Town, Dongguan, Guangdong, China

5.5 Description of Support Units

Device Type	Brand	Model	Series No.	Note
Notebook PC	HP	ZHAN 66P	---	---

5.6 Additional Instructions

Test Software	Special test command used
Power level setup	Default

5.7 Antenna Information

Ant	Manufacturer	Model	Antenna Type	Antenna Gain (dBi)
1	Shenzhen Yishengbang Technology Co., Ltd	/	/	2.09
2		/	/	1.56

All above information provided by the applicant which is fully responsible for those information.

5.8 Others


The laboratory responsible for all the information provided in the report, except those information provided by the applicant. The applicant shall fully responsible for the information they provided. The report would be invalid without a stamp of test laboratory and the signatures of compiler and approver. The laboratory has not been responsible for the sampling stage; the test report merely corresponds to the test sample received. Any objection to the test report shall submitted to the test laboratory within 15 days from the date of receipt of the report. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

6 Technical Requirement and Measurement Data

6.1 Generally requirement


15.203 requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.407 requirement:
If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:
Reference to the appendix II for details
15.407(c) requirement:
The applicant declares that the device (FCC Part 15 Subpart E Section 15.407) shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure.

6.2 Duty Cycle

Limit
Report for use
Block diagram of Test Setup
 The diagram shows a Spectrum Analyzer and an E.U.T (Equipment Under Test) connected by a red cable. They are both resting on a table labeled 'Non-Conducted Table'. This table is supported by a 'Ground Reference Plane'.
Test Instrument
Refer to Annex A for details
Test Procedures
The transmitter output connected to the Spectrum Analyzer. Test according to Procedure B.2 in KDB 789033 D02 v02r01. 1.RBW=8 MHz(the largest available value) 2.VBW=8 MHz(>RBW) 3.SPAN = 0 Hz 4.Detector = Peak 5.Number of points in sweep: 30001 6.Trace mode: Clear write 7.Measure T_{total} and T_{on} 8.Calculate Duty Cycle = T_{on}/T_{total} and Duty Cycle Factor = $10\log(1/\text{Duty Cycle})$
Verdict
Pass


Measurement Data: The detailed test data see Appendix

6.3 Conducted Peak Output Power

Limit	
Frequency band(MHz)	Maximum conducted power
5150-5250	≤1W(30dBm) for master device
	≤250Mw(23.98dBm) for client device
5250-5350	≤250Mw(23.98dBm) for client device or 11dBm+10logB*
5470-5725	≤250Mw(23.98dBm) for client device or 11dBm+10logB*
Remark: *Where B is the 26dB emission bandwidth in MHz. The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.	
Block diagram of Test Setup	
	
Test Instrument	
Refer to Annex A for details	
Test Procedures	
Test applies to ANSI C63.10:2013 & KDB 789033 D02 v02r01	
Verdict	
Pass	


Measurement Data: The detailed test data see Appendix

6.4 Emission Bandwidth

Limit
Report only
Block diagram of Test Setup
 The diagram shows a Spectrum Analyzer and an E.U.T. (Equipment Under Test) connected by a red cable. They are positioned on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.
Test Instrument
Refer to Annex A for details
Test Procedures
Test applies to ANSI C63.10:2013 & KDB 789033 D02 v02r01
Verdict
Pass


Measurement Data: The detailed test data see Appendix

6.5 Power Spectral Density

Limit	
Frequency band (MHz)	Maximum power spectral density
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
Block diagram of Test Setup	
	
Test Instrument	
Refer to Annex A for details	
Test Procedures	
Test applies to ANSI C63.10:2013 & KDB 789033 D02 v02r01	
Verdict	
Pass	

Measurement Data: The detailed test data see Appendix

6.6 Frequency Stability

Limit
Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Block diagram of Test Setup
 Note : Measurement setup for testing on Antenna connector
Test Instrument
Refer to Annex A for details
Test Procedures
Test applies to ANSI C63.10:2013, FCC Part 2.1055.
Verdict
Pass

Measurement Data: The detailed test data see Appendix

6.7 Radiated Spurious Emission

Limit

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Undesirable emission limits: the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:



- (1) For transmitters operating in the 5.15–5.25 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.
- (2) For transmitters operating in the 5.25–5.35 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.
- (3) For transmitters operating in the 5.47–5.725 GHz band: All emissions outside of the 5.47–5.725 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.

Block diagram of Test Setup



☐ For table-top equipment

☒ For floor standing equipment



For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Test Instrument

Refer to Annex A for details

Test Procedures

Test applies to ANSI C63.10:2013 & KDB 789033 D02 v02r01

Verdict


Pass


Note:

1. The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.
2. For those undesirable emission (in the Restricted Bands and out-of-band spurious) above 1GHz, According to KDB 789033 D02 v02r01 section II.G, as an alternative, antenna-port conducted measurements in conjunction with cabinet emissions tests will be permitted to demonstrate compliance.
3. The undesirable spurious emission range from 26GHz to 40GHz is as low as the cabinet noise, so there is no report, refer to appendix for details.
4. According to KDB 789033 D02 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:

$$E[dBuV/m] = EIRP[dBm] + 95.2;$$
For example, if $EIRP = -27dBm$

$$E[dBuV/m] = -27 + 95.2 = 68.2dBuV/m.$$





Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.		25 °C/60%		
Test voltage	AC 120V/60Hz			Test channel		802.11ac20, 5180MHz		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	52.95	39.34	11.73	53.2	50.82	68.2	-17.38	Vertical
15540	52.99	38.92	14.71	52.85	53.77	68.2	-14.43	Vertical
10360	52.96	39.34	11.73	53.2	50.83	68.2	-17.37	Horizontal
15540	51.53	38.92	14.71	52.85	52.31	68.2	-15.89	Horizontal
10360	44.36	39.34	11.73	53.2	42.23	54	-11.77	Vertical
15540	41.58	38.92	14.71	52.85	42.36	54	-11.64	Vertical
10360	40.82	39.34	11.73	53.2	38.69	54	-15.31	Horizontal
15540	39.45	38.92	14.71	52.85	40.23	54	-13.77	Horizontal

Note: Final Level =Receiver Read level + Factor
Factor= Antenna Factor + Cable Loss – Preamplifier Factor
Only the worst case report(ANT 2)
The level of emissions from 18GHz to 40GHz is same as the ambient noise, so no data report here.

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.		25 °C/60%		
Test voltage	AC 120V/60Hz			Test channel		802.11ac20, 5200MHz		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	51.09	39.36	11.76	53.2	49.01	68.2	-19.19	Vertical
15600	50	38.96	14.73	52.78	50.91	68.2	-17.29	Vertical
10400	52.64	39.36	11.76	53.2	50.56	68.2	-17.64	Horizontal
15600	51.03	38.96	14.73	52.78	51.94	68.2	-16.26	Horizontal
10400	43.92	39.36	11.76	53.2	41.84	54	-12.16	Vertical
15600	41.68	38.96	14.73	52.78	42.59	54	-11.41	Vertical
10400	39.38	39.36	11.76	53.2	37.3	54	-16.7	Horizontal
15600	45.6	38.96	14.73	52.78	46.51	54	-7.49	Horizontal

Note: Final Level =Receiver Read level + Factor
Factor= Antenna Factor + Cable Loss – Preamplifier Factor
Only the worst case report(ANT 2)
The level of emissions from 18GHz to 40GHz is same as the ambient noise, so no data report here.

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.		25 °C/60%		
Test voltage	AC 120V/60Hz			Test channel		802.11ac20, 5240MHz		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	50.15	39.39	11.82	53.2	48.16	68.2	-20.04	Vertical
15720	51.38	39.03	14.78	52.64	52.55	68.2	-15.65	Vertical
10480	49.82	39.39	11.82	53.2	47.83	68.2	-20.37	Horizontal
15720	52.17	39.03	14.78	52.64	53.34	68.2	-14.86	Horizontal
10480	43.8	39.39	11.82	53.2	41.81	54	-12.19	Vertical
15720	42.56	39.03	14.78	52.64	43.73	54	-10.27	Vertical
10480	41.78	39.39	11.82	53.2	39.79	54	-14.21	Horizontal
15720	39.29	39.03	14.78	52.64	40.46	54	-13.54	Horizontal
Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor Only the worst case report(ANT 2) The level of emissions from 18GHz to 40GHz is same as the ambient noise, so no data report here.								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.		25 °C/60%		
Test voltage	AC 120V/60Hz			Test channel		802.11ac40, 5190MHz		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10380	51.13	39.35	11.75	53.2	49.03	68.2	-19.17	Vertical
15570	52.91	38.94	14.72	52.82	53.75	68.2	-14.45	Vertical
10380	52.69	39.35	11.75	53.2	50.59	68.2	-17.61	Horizontal
15570	49.43	38.94	14.72	52.82	50.27	68.2	-17.93	Horizontal
10380	42.19	39.35	11.75	53.2	40.09	54	-13.91	Vertical
15570	40.49	38.94	14.72	52.82	41.33	54	-12.67	Vertical
10380	45	39.35	11.75	53.2	42.9	54	-11.1	Horizontal
15570	45.12	38.94	14.72	52.82	45.96	54	-8.04	Horizontal
Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor Only the worst case report(ANT 2) The level of emissions from 18GHz to 40GHz is same as the ambient noise, so no data report here.								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.		25 °C/60%		
Test voltage	AC 120V/60Hz			Test channel		802.11ac40, 5230MHz		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10460	51.45	39.38	11.8	53.2	49.43	68.2	-18.77	Vertical
15690	52.35	39.01	14.77	52.67	53.46	68.2	-14.74	Vertical
10460	49.92	39.38	11.8	53.2	47.9	68.2	-20.3	Horizontal
15690	52.59	39.01	14.77	52.67	53.7	68.2	-14.5	Horizontal
10460	40.34	39.38	11.8	53.2	38.32	54	-15.68	Vertical
15690	39.39	39.01	14.77	52.67	40.5	54	-13.5	Vertical
10460	40.37	39.38	11.8	53.2	38.35	54	-15.65	Horizontal
15690	40	39.01	14.77	52.67	41.11	54	-12.89	Horizontal
Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor Only the worst case report(ANT 2) The level of emissions from 18GHz to 40GHz is same as the ambient noise, so no data report here.								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.		25 °C/60%		
Test voltage	AC 120V/60Hz			Test channel		802.11ac80, 5210MHz		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10420	49.84	39.37	11.77	53.2	47.78	68.2	-20.42	Vertical
15630	50.4	38.98	14.74	52.74	51.38	68.2	-16.82	Vertical
10420	50.18	39.37	11.77	53.2	48.12	68.2	-20.08	Horizontal
15630	52.03	38.98	14.74	52.74	53.01	68.2	-15.19	Horizontal
10420	39.75	39.37	11.77	53.2	37.69	54	-16.31	Vertical
15630	45.68	38.98	14.74	52.74	46.66	54	-7.34	Vertical
10420	42.09	39.37	11.77	53.2	40.03	54	-13.97	Horizontal
15630	45.2	38.98	14.74	52.74	46.18	54	-7.82	Horizontal
Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor Only the worst case report(ANT 2) The level of emissions from 18GHz to 40GHz is same as the ambient noise, so no data report here.								

Test Result(Emissions in Restricted band)								
Test mode		Mode 1		Temp. /Hum.		25 °C/60%		
Test voltage		AC 120V/60Hz		Test channel		802.11ac20		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5150	52.64	33.87	8.01	53.64	40.88	68.2	-27.32	Horizontal
5350	49.75	33.83	8.17	53.56	38.19	68.2	-30.01	Horizontal
5150	51.94	33.87	8.01	53.64	40.18	68.2	-28.02	Vertical
5350	50.98	33.83	8.17	53.56	39.42	68.2	-28.78	Vertical
5150	39.19	33.87	8.01	53.64	27.43	54	-26.57	Horizontal
5350	40.92	33.83	8.17	53.56	29.36	54	-24.64	Horizontal
5150	41.7	33.87	8.01	53.64	29.94	54	-24.06	Vertical
5350	40.89	33.83	8.17	53.56	29.33	54	-24.67	Vertical

Note:

1. Final Level =Receiver Read level + Factor
2. Factor= Antenna Factor + Cable Loss – Preamplifier Factor
3. Only the worst case report(ANT 2)

Test Result(Emissions in Restricted band)								
Test mode		Mode 1		Temp. /Hum.		25 °C/60%		
Test voltage		AC 120V/60Hz		Test channel		802.11ac40		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5150	49.27	33.87	8.01	53.64	37.51	68.2	-30.69	Horizontal
5350	51.55	33.83	8.17	53.56	39.99	68.2	-28.21	Horizontal
5150	51.92	33.87	8.01	53.64	40.16	68.2	-28.04	Vertical
5350	50	33.83	8.17	53.56	38.44	68.2	-29.76	Vertical
5150	45	33.87	8.01	53.64	33.24	54	-20.76	Horizontal
5350	40.57	33.83	8.17	53.56	29.01	54	-24.99	Horizontal
5150	39.7	33.87	8.01	53.64	27.94	54	-26.06	Vertical
5350	42.3	33.83	8.17	53.56	30.74	54	-23.26	Vertical

Note:

1. Final Level =Receiver Read level + Factor
2. Factor= Antenna Factor + Cable Loss – Preamplifier Factor
3. Only the worst case report(ANT 2)

Test Result(Emissions in Restricted band)								
Test mode		Mode 1		Temp. /Hum.		25 °C/60%		
Test voltage		AC 120V/60Hz		Test channel		802.11ac80		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
5150	51.26	33.87	8.01	53.64	39.5	68.2	-28.7	Horizontal
5350	52.91	33.83	8.17	53.56	41.35	68.2	-26.85	Horizontal
5150	50.19	33.87	8.01	53.64	38.43	68.2	-29.77	Vertical
5350	52.33	33.83	8.17	53.56	40.77	68.2	-27.43	Vertical
5150	44.85	33.87	8.01	53.64	33.09	54	-20.91	Horizontal
5350	45.88	33.83	8.17	53.56	34.32	54	-19.68	Horizontal
5150	40.57	33.87	8.01	53.64	28.81	54	-25.19	Vertical
5350	39.17	33.83	8.17	53.56	27.61	54	-26.39	Vertical

Note:

1. Final Level =Receiver Read level + Factor
2. Factor= Antenna Factor + Cable Loss – Preamplifier Factor
3. Only the worst case report(ANT 2)

6.8 Conducted Emissions



Limit

Frequency (MHz)	Quasi-peak	Average
0.15~0.50	66 to 56*	56 to 46*
0.50~5.0	56	46
5.0~30	60	50

*Decreases with the logarithm of the frequency.

If the limit for the measurement with the average detector is met when using a receiver with a quasi-peak detector, the equipment under test shall be deemed to meet both limits and the measurement using the receiver with an average detector need not be carried out

Block diagram of Test Setup

☐ For table-top equipment

☒ For floor standing equipment


Test Instrument

Refer to Annex A for details

Test Procedures

The measurement was performed in a shield room.


Measured levels of ac power-line conducted emission shall be the radio-noise voltage from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), as terminated into a 50 Ω EMI receiver or spectrum analyzer. All radio-noise voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord or calibrated extension cord by the use of mating plugs and receptacles on the EUT and LISN, if used. The manufacturer shall test equipment with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended. For measurements using a LISN, the 50 Ω measuring port is terminated into a 50 Ω EMI receiver or spectrum analyzer. All other ports are terminated into 50 Ω loads.


Table top devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

Verdict

Pass





7 Test Setup Photo

Reference to the **appendix I** for details.

8 EUT Constructional Details

Reference to the **appendix II** for details.



Annex A --Test Instruments list

Radiated Emission:						
Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. cycle	Cal.Date
SST-E-SAC001	3m Semi- Anechoic Chamber	BOST	966	/	3 years	2023.01.07
SST-E-SCC001	Control Room	BOST	333	/	3 years	2023.01.07
SST-E-SAC002	Breiband TRILOG Messantenne	Schwarzbeck	VULB 9162	00556	1 year	2024.04.20
SST-E-SAC004	Broad-band Horn Antenna	Schwarzbeck	BBHA 9120 D	02783	1 year	2024.04.16
SST-E-SCC003	EMI Test Receiver	R&S	ESU 8	100372	1 year	2024.04.16
SST-E-SCC004	Amplifier	Schwarzbeck	BBV 9744	00327	1 year	2024.04.16
SST-E-SCC015	Amplifier (1-18GHz)	TSTPASS	LNA10180G45	TSAM2303003	1 year	2024.04.16
SST-E-SCC016	Amplifier (40G)	RFsystem	TRLA-180400G45B	23060801	1 year	2024.04.16
SST-E-SAC006	Broadband Horn Antenna (40G)	Schwarzbeck	BBHA9170	01306	1 year	2024.04.17
SST-E-RSC010	Spectrum analyzer	R&S	FSV40-N	/	1 year	2024.04.16
SST-E-SAC007	Loop Antenna	Schwarzbeck	FMZB 1513-60B	1513-60B 044	1 year	2024.04.17
SST-E-SAC005	5W 6dB attenuator	/	DC-6GHz	/	Internal calibration	/
SST-E-EMC006	Thermohygrometer	KTJ	TA218A	879030	1 year	2024.04.18
/	EMI Test Software	Tonscend	TS+	/	/	/

Conducted Emission						
Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. cycle	Cal.Date
SST-E-CSC001	Shielding Room	BOST	854	/	3 year	2023.01.07
SST-E-CSC002	EMI Test Receiver	R&S	ESR3	103057	1 year	2024.04.16
SST-E-CSC003	LISN	R&S	ENV 216	102832	1 year	2024.04.16
SST-E-CSC004	ISN	R&S	NTFM 8158	00347	1 year	2024.04.16
SST-E-CSC007	Antenna port test assembly	/	DC-3GHz	/	Internal calibration	/
SST-E-EMC011	Thermohygrometer	KTJ	TA218A	879036	1 year	2024.04.18
/	EMI Test Software	Tonscend	TS+	V4.0	/	/

RF conducted						
Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. cycle	Cal.Date
SST-E-RSC001	Shielding Room	BOST	543	/	3 year	2023.01.07
SST-E-RSC007	Spectrum analyzer	keysight	N9020A	MY51280659	1 year	2024.04.16
SST-E-RSC008	Analog signal source	Agilent	N5181A	MY48180054	1 year	2024.04.16
SST-E-RSC009	Vector signal source	keysight	N5172B	MY57281610	1 year	2024.04.16
SST-E-EMC007	Thermohygrometer	KTJ	TA218A	879032	1 year	2024.04.18
SST-E-RSC010	Spectrum analyzer	R&S	FSV40-N	/	1 year	2024.04.16
SST-E-RSC015-1	Power meter 1	TST	TST V2	/	1 year	2024.04.16
/	Test Software	TST PASS	TST PASS	V2.0	/	/

▶▶▶ END OF REPORT ◀◀◀

