

# **FCC Test Report**

Report No.: RF131118E02B

FCC ID: 2ABC8-PP300850SE

Test Model: DT8050A

Series Model: DT8050M

Received Date: Dec. 26, 2018

Test Date: Jan. 02 to 11, 2019

**Issued Date:** Mar. 27, 2019

Applicant: Honeywell Security Sensor CoE

Address: 2 Corporate Center Dr.Melville New York 11747 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

FCC Registration / **Designation Number:** 

723255 / TW2022





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: RF131118E02B Page No. 1 / 33 Report Format Version: 6.1.1 Reference No.: 181226E03



# **Table of Contents**

R	Release Control Record3					
1		ertificate of Conformity				
2 Summary of Test Results		Summary of Test Results	5			
	2.1 2.2	Measurement Uncertainty				
3	(	General Information	6			
	3.1 3.2 3.2.1 3.3 3.4 3.4.1 3.5	General Description of Applied Standards	7 8 10 .11 12 13			
4	7	Test Types and Results	14			
	4.1.2	Radiated Emission and Bandedge Measurement  Limits of Radiated Emission and Bandedge Measurement  Test Instruments  Test Procedures	14 16			
	4.1.5	Deviation from Test Standard  Test Setup  EUT Operating Conditions	20			
	4.2 4.2.1	Test Results  Conducted Emission Measurement  Limits of Conducted Emission Measurement	26 26			
	4.2.3 4.2.4	Test Instruments Test Procedures Deviation from Test Standard	27 27			
	4.2.6	Test Setup  EUT Operating Conditions  Test Results  20dB bandwidth Measurement	27 28			
	4.3.2 4.3.3		30 30			
	4.3.5 4.3.6	Deviation from Test Standard  Test Setup  EUT Operating Conditions  Test Results	30 30			
5		Pictures of Test Arrangements				
		dix – Information of the Testing Laboratories				



# **Release Control Record**

Issue No.	Description	Date Issued
RF131118E02B	Original release.	Mar. 27, 2019

Page No. 3 / 33 Report Format Version: 6.1.1

Report No.: RF131118E02B Reference No.: 181226E03



## 1 Certificate of Conformity

Product: DUAL TEC Motion Sensor

Brand: Honeywell

Test Model: DT8050A

Series Model: DT8050M

Sample Status: ENGINEERING SAMPLE

Applicant: Honeywell Security Sensor CoE

Test Date: Jan. 02 to 11, 2019

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.245)

ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by: , Date: Mar. 27, 2019

Cindy Hsin / Specialis

**Approved by :** , **Date:** Mar. 27, 2019

May Chen / Manager



# 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.245)					
FCC Clause	Test Item	Result	Remarks		
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.  Minimum passing margin is -34.68dB at 19.80078MHz.		
15.245 Radiated Emission Test		PASS	Meet the requirement of limit Minimum passing margin is -5.5dB at 10550.00MHz		
15.215 (c)	20dB Bandwidth	PASS	Meet the requirement of limit		
15.203	Antenna Requirement	PASS	No antenna connector is used.		

# 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
	30MHz ~ 1GHz	5.33 dB
Radiated Emissions	1GHz ~ 6GHz	5.10 dB
Radiated Emissions	6GHz ~ 18GHz	4.85 dB
	18GHz ~ 40GHz	5.24 dB

## 2.2 Modification Record

There were no modifications required for compliance.



#### 3 General Information

#### 3.1 General Description of EUT

Product	DUAL TEC Motion Sensor
Product	DOAL TEC MOTION Sensor
Brand	Honeywell
Test Model	DT8050A
Series Model	DT8050M
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	DC 9~15V, 15mA
Modulation Type	GFSK
Carrier Frequency	10.525GHz
Number of Channel	1
Antenna Type	Integral PCB antenna with 7dBi gain
Antenna Connector	NA
Accessory Device	NA
Data Cable Supplied	NA

#### Note:

- 1. This report is prepared for FCC class II permissive change. The difference compared with the Report No.: RF131118E02 design is as the following information:
  - Upgraded standard to ANSI C63.10: 2013.
  - ◆ The FET electrical characteristics are quite closed, yet there are some difference in component shape and dimension.
  - Detail change list as refer as below, Confirmed RF circuit and performance are no changed:
    - 1. Replace NE4210S01(300-06289) with CE3512K2(300-09313)
    - 2. Replace DR(300-06688) with DR(300-08959)
    - 3. Replace Resistor 21ohm(5-108-2212-00) with 33ohm(RJ6-3301)
    - 4. PCB minor changed (replace PCB footprint of NE4210S01 with CE3512K2')
  - More detailed information, please refer to CI2PC request form.
- 2. According to above condition, all test items need to be performed. And all data were verified to meet the requirements.
- 3. From the power supply, the worse case was found in voltage: **DC 9V**. Therefore only the test data of the mode was recorded in this report.
- 4. The EUT have two model names, which are identical to each other in all aspects except for the following table:

Brand	Model No. Difference	
Honovavoll	DT8050A	-
Honeywell	DT8050M	Remove AM feature base on DT8050A

From the above models, model: **DT8050A** was selected as representative model for the test and its data was recorded in this report.

- 5. DUAL TEC Motion Sensor is applying Doppler radar phenomenon to sense motion. It transmits a low power microwave and receives energy reflected by objects.
- 6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



# 3.2 Description of Test Modes

1 channel is provided for test:

Channel	Frequency
1	10.525 GHz

Report No.: RF131118E02B Reference No.: 181226E03



## 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE	APPLICABLE TO				DESCRIPTION
MODE	RE≥1G	RE<1G	PLC	BW	DESCRIPTION
-	V	<b>V</b>	V	V	-

Where

RE≥1G: Radiated Emission above 1GHz &

Bandedge Measurement

**PLC:** Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

BW: 20dB Bandwidth Measurement

### Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

TESTED	MODULATION
CHANNEL	TYPE
1	GFSK

## Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

TESTED	MODULATION
CHANNEL	TYPE
1	GFSK

## **Power Line Conducted Emission Test:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

TESTED	MODULATION
CHANNEL	TYPE
1	GFSK

### 20dB Bandwidth Measurement:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

TESTED	MODULATION
CHANNEL	TYPE
1	GFSK

 Report No.: RF131118E02B
 Page No. 8 / 33
 Report Format Version: 6.1.1



# **Test Condition:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	24deg. C, 71%RH	DC 9V	Robert Cheng
RE<1G	25deg. C, 70%RH	DC 9V	Robert Cheng
PLC	24deg. C, 74%RH	120Vac, 60Hz (system)	Andy Ho
BW	25deg. C, 60%RH	DC 9V	Anderson Chen


Page No. 9 / 33 Report Format Version: 6.1.1

Report No.: RF131118E02B Reference No.: 181226E03



# 3.3 Duty Cycle of Test Signal

Duty cycle = 0.018 ms/0.338 ms = 0.053





# 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
Α	DC Power Supply	GOOD WILL INSTRUMENT CO., LTD.	GPC-3030D	7700087	NA	Provided by Lab

#### Note:

1. All power cords of the above support units are non-shielded (1.8m).


ID	Descriptions	Qtv.	Length (m)	Shielding (Yes/No)	Cores (Qtv.)	Remarks	1
1	DC Cable	1	2	No	0	Provided by Lab	

Report No.: RF131118E02B Page No. 11 / 33 Report Format Version: 6.1.1




# 3.4.1 Configuration of System under Test

# For conducted emission test:



# For other Test:





3.5 General Description of Applied Standards
The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:
FCC Part 15, Subpart C (15.245) ANSI C63.10-2013
All test items have been performed and recorded as per the above standards.

Page No. 13 / 33 Report Format Version: 6.1.1

Report No.: RF131118E02B Reference No.: 181226E03



## 4 Test Types and Results

# 4.1 Radiated Emission and Bandedge Measurement

# 4.1.1 Limits of Radiated Emission and Bandedge Measurement

According to 15.245 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fund	damental (dBuV/m)
()	Peak	Average
	147.9	127.9
10500 ~10550	Field Strength of Har	rmonics (dBuV/m)
	107.9	87.9

Harmonic emissions in the restricted bands at and above 17.7 GHz shall not exceed the following field strength limits:

Application	Field Strength of Harmonics (dBuV/m)
Field disturbance sensors operating in the 24075-24175 MHz band and for Other field disturbance sensors designed for use only within a building or to open building doors.	87.9
All other field disturbance sensors	77.5

Note: Field disturbance sensors designed to be used in motor vehicles or aircraft must include features to prevent continuous operation unless their emissions in the restricted bands, other than the second and third harmonics from devices operating in the 24075-24175 MHz band, fully comply with the limits given in Section15.209.

- (1) Field strength limits are specified at a distance of 3 meters.
- (2) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Report No.: RF131118E02B Page No. 14 / 33 Report Format Version: 6.1.1



Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

## NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level  $(dBuV/m) = 20 \log Emission level (uV/m)$ .
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.1.2 Test Instruments

## Below 40GHz test:

DESCRIPTION &	MODEL NO	SERIAL NO.	CALIBRATED	CALIBRATED	
MANUFACTURER	MODEL NO.	SERIAL NO.	DATE	UNTIL	
Test Receiver Keysight	N9038A	MY54450088	July 05, 2018	July 04, 2019	
Pre-Amplifier EMCI	EMC001340	980142	Feb. 09, 2018	Feb. 08, 2019	
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019	
RF Cable	NA	LOOPCAB-001	Jan. 15, 2018	Jan. 14, 2019	
RF Cable	NA	LOOPCAB-002	Jan. 15, 2018	Jan. 14, 2019	
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Oct. 30, 2018	Oct. 29, 2019	
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 22, 2018	Nov. 21, 2019	
RF Cable	8D	966-4-1	Mar. 21, 2018	Mar. 20, 2019	
RF Cable	8D	966-4-2	Mar. 21, 2018	Mar. 20, 2019	
RF Cable	8D	966-4-3	Mar. 21, 2018	Mar. 20, 2019	
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Sep. 27, 2018	Sep. 26, 2019	
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Nov. 25, 2018	Nov. 24, 2019	
Pre-Amplifier Mini-Circuits	ZVA-183-S+	AMP-ZVA-03	May 10, 2018	May 09, 2019	
RF Cable	EMC104-SM-SM-1200	160923	Jan. 29, 2018	Jan. 28, 2019	
RF Cable	EMC104-SM-SM-2000	150318	Jan. 29, 2018	Jan. 28, 2019	
RF Cable	EMC104-SM-SM-5000	150321	Jan. 29, 2018	Jan. 28, 2019	
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 29, 2018	Jan. 28, 2019	
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Nov. 25, 2018	Nov. 24, 2019	
RF Cable	EMC102-KM-KM-1200	160925	Jan. 29, 2018	Jan. 28, 2019	
Software	ADT_Radiated_V8.7.08	NA	NA	NA	
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA	

# Note:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2. The test was performed in 966 Chamber No. 4.
- 3. The CANADA Site Registration No. is 20331-2
- 4. Loop antenna was used for all emissions below 30 MHz.
- 5. Tested Date: Jan. 02 to 04, 2019



## Above 40GHz test:

DESCRIPTION &	MODEL NO	SEDIAL NO	CALIBRATED	CALIBRATED
MANUFACTURER	MODEL NO.	SERIAL NO.	DATE	UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250254	Nov. 14, 2018	Nov. 13, 2019
*Harmonic Mixer (33~55GHz) OML	M22HWD	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Horn Antenna (33~55GHz) OML	M22RH	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Harmonic Mixer (50~75GHz) OML	M15RH	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Horn Antenna (50~75GHz) OML	M15HWD	110215-1	Oct. 17, 2017	Oct. 16, 2019
*Diplexer EMCI	DPL26	DPL26_01	Oct. 17, 2017	Oct. 16, 2019
*Diplexer EMCI	DPL26	DPL26_02	Oct. 17, 2017	Oct. 16, 2019
*Precision 30dB Attenuator Keysight	11708A	MY55260015	Oct. 17, 2017	Oct. 16, 2019
*Zero-Bias Detector (50~75GHz) Vdi	WR15ZBD	WR15R5 1-30	Oct. 17, 2017	Oct. 16, 2019
*WR15CH Conical Horn Keysight	WR15CH	WR15CH-01	Oct. 17, 2017	Oct. 16, 2019
*WR10CH Conical Horn Keysight	WR10CH	WR10CH-01	Oct. 17, 2017	Oct. 16, 2019
*Millimeter-Wave Signal Generator Frequency Extension Module (50~75 GHz) Keysight	E8257DV15	US54250106	Oct. 17, 2017	Oct. 16, 2019
PSG analog signal generator Keysight	E8257D	MY53401987	June 26, 2018	June 25, 2019
Antenna Tower & Turn Table CT	NA	NA	NA	NA

#### Note:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2. \*The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 3. The test was performed in 966 Chamber No. 4.
- 4. The FCC Site Registration No. is 966073.
- 5. The VCCI Site Registration No. is G-137.
- 6. The CANADA Site Registration No. is IC 7450H-2.
- 7. Tested Date: Jan. 04, 2019



#### 4.1.3 Test Procedures

#### For Radiated emission: Below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

#### For Radiated emission: 30MHz ~ 18GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

### Note:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection (PK) at frequency from 1GHz to 18GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency from 1GHz to 18GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

Report No.: RF131118E02B Page No. 18 / 33 Report Format Version: 6.1.1



#### For Radiated emission: Above 18GHz

External harmonic mixers are utilized.

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The distance at which limits are typically specified is 3 meter; however, closer measurement distances may be utilized.
- c. Begin handheld measurements with the test antenna (horn) at a distance of 1 meter from the EUT, in a horizontally polarized position. Slowly adjust its position, entirely covering the plane 1 meter from the EUT.
- d. Repeat (b) with the horn in a vertically polarized position.
- e. If the emission cannot be detected at 1 meter, reduce the RBW in order to increase system sensitivity. Note the value. If the emission still cannot be detected, move the horn closer to the EUT, noting the distance at which a measurement is made.
- f. Note the maximum level indicated on the Spectrum Analyzer.
- g. Based on the distance at which the measurement was made and the calculated distance to the edge of the far field, determine the appropriate distance attenuation factor. Apply this factor to the calculated field strength in order to determine the equivalent field strength at the distance at which the regulatory limit is specified. Compare to the appropriate limits
- h. Repeat (a) (f) for every emission that must be measured, up through the required frequency range of investigation

#### NOTE:

- The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection (PK).
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10Hz (Duty cycle ≥ 98%) for Average detection (AV).

4.1.4	Deviation	from	Toct	Standar	٨
4.1.4	Deviation	HOH	rest	Stanuar	u


No deviation.

Report No.: RF131118E02B Page No. 19 / 33 Report Format Version: 6.1.1




## 4.1.5 Test Setup

## For Radiated emission below 30MHz




# For Radiated emission 30MHz to 1GHz





# For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

# 4.1.6 EUT Operating Conditions

Set the EUT under transmission / receiver condition continuously at specific channel frequency.

Report No.: RF131118E02B Reference No.: 181226E03



## 4.1.7 Test Results

#### Above 1GHz Data:

CHANNEL	TX Channel 1	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 18GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	10500.00	59.2 PK	74.0	-14.8	1.57 H	248	45.5	13.7
2	10500.00	48.1 AV	54.0	-5.9	1.57 H	248	34.4	13.7
3	*10525.30	112.6 PK	147.9	-35.3	1.57 H	248	98.8	13.8
4	*10525.30	110.4 AV	127.9	-17.5	1.57 H	248	96.6	13.8
5	10550.00	58.8 PK	74.0	-15.2	1.57 H	248	45.0	13.8
6	10550.00	48.5 AV	54.0	-5.5	1.57 H	248	34.7	13.8
		ANTENNA	POLARITY	& TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
<b>NO.</b>	-	LEVEL			HEIGHT	ANGLE	VALUE	FACTOR
	(MHz)	LEVEL (dBuV/m)	(dBuV/m)	(dB)	HEIGHT (m)	ANGLE (Degree)	VALUE (dBuV)	FACTOR (dB/m)
1	(MHz) 10500.00	LEVEL (dBuV/m) 59.9 PK	(dBuV/m) 74.0	(dB) -14.1	HEIGHT (m)	ANGLE (Degree)	<b>VALUE</b> (dBuV) 46.2	FACTOR (dB/m) 13.7
1 2	(MHz) 10500.00 10500.00	LEVEL (dBuV/m) 59.9 PK 48.2 AV	(dBuV/m) 74.0 54.0	(dB) -14.1 -5.8	HEIGHT (m) 1.79 V 1.79 V	ANGLE (Degree) 116 116	VALUE (dBuV) 46.2 34.5	FACTOR (dB/m) 13.7 13.7
1 2 3	(MHz) 10500.00 10500.00 *10525.30	LEVEL (dBuV/m) 59.9 PK 48.2 AV 98.0 PK	74.0 54.0 147.9	-14.1 -5.8 -49.9	HEIGHT (m) 1.79 V 1.79 V 1.79 V	ANGLE (Degree) 116 116 116	VALUE (dBuV) 46.2 34.5 84.2	FACTOR (dB/m)  13.7  13.7  13.8

## **REMARKS:**

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 1	DETECTOR	Peak (PK)
FREQUENCY RANGE	18GHz ~53GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY: HORIZONTAL										
NO.	FREQ. (MHz)	i LEVEL I		LIMIT (dBuV/m) MARGIN (dB) ANTENNA TABLE ANGLE (m) (Degree)		ANGLE	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	21050.60	49.6 PK	97.5	-47.9	1.53 H	77	60.2	-10.6			
2	21050.60	46.8 AV	77.5	-30.7	1.53 H	77	57.4	-10.6			
3	31575.90	47.2 PK	97.5	-50.3	1.60 H	177	55.8	-8.6			
4	31575.90	46.0 AV	77.5	-31.5	1.60 H	177	54.6	-8.6			
			ANTEN	NA POLARI	TY: VERTIC	AL					
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	21050.60	48.6 PK	97.5	-48.9	1.44 V	99	59.2	-10.6			
2	21050.60	46.0 AV	77.5	-31.5	1.44 V	99	56.6	-10.6			
3	31575.90	47.0 PK	97.5	-50.5	1.45 V	88	55.6	-8.6			
4	31575.90	45.9 AV	77.5	-31.6	1.45 V	88	54.5	-8.6			

## **REMARKS:**

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. Measurements made at 1 meter distance. Test value converted to account for 3-meter measurement distance.

Report No.: RF131118E02B Page No. 23 / 33 Report Format Version: 6.1.1




## **Below 1GHz Data:**

CHANNEL	TX Channel 1	DETECTOR	Oversi Bask (OD)
FREQUENCY RANGE	9kHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
NO.	(MHz) (dBuV/m) (dBuV/m)		MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)					
1	50.16	21.6 QP	40.0	-18.4	1.42 H	113	29.7	-8.1				
2	160.21	21.6 QP	43.5	-21.9	1.42 H	144	29.4	-7.8				
3	334.85	23.6 QP	46.0	-22.4	1.32 H	165	30.3	-6.7				
4	505.90	29.6 QP	46.0	-16.4	1.42 H	77	32.2	-2.6				
5	656.88	30.1 QP	46.0	-15.9	1.21 H	100	29.7	0.4				
6	828.98	32.5 QP	46.0	-13.5	1.42 H	99	29.5	3.0				

## **REMARKS:**

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. Margin value = Emission Level Limit value
- 4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.






CHANNEL	TX Channel 1	DETECTOR	Ougai Pagis (OP)
FREQUENCY RANGE	9kHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)				
1	63.21	20.6 QP	40.0	-19.4	1.02 V	244	29.4	-8.8				
2	145.21	21.1 QP	43.5	-22.4	1.65 V	211	29.3	-8.2				
3	416.36	24.1 QP	46.0	-21.9	1.33 V	165	28.8	-4.7				
4	524.65	26.4 QP	46.0	-19.6	1.65 V	100	28.8	-2.4				
5	749.10	32.1 QP	46.0	-13.9	1.44 V	99	30.0	2.1				
6	941.11	32.1 QP	46.0	-13.9	1.65 V	244	27.5	4.6				

#### **REMARKS:**

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. Margin value = Emission Level Limit value
- 4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.





#### 4.2 Conducted Emission Measurement

#### 4.2.1 Limits of Conducted Emission Measurement

Fragues av (MILIT)	Conducted I	Limit (dBuV)
Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

## 4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2018	Oct. 23, 2019
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 22, 2018	Oct. 21, 2019
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 04, 2018	June 03, 2019
50 ohms Terminator	N/A	3	Oct. 22, 2018	Oct. 21, 2019
RF Cable	5D-FB	COCCAB-001	Sep. 28, 2018	Sep. 27, 2019
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 16, 2018	Mar. 15, 2019
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

### Note:

- 1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2. The test was performed in Conduction 1.
- 3. Tested Date: Jan. 05, 2019

<sup>2.</sup> The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.



#### 4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 4.2.6 EUT Operating Conditions

Same as 4.1.6.

Report No.: RF131118E02B Reference No.: 181226E03




## 4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) /
riiase	Line (L)	Detector Function	Average (AV)

	Phase Of Power : Line (L)										
No	Frequency	Correction Factor	Reading Value (dBuV)		Emission Level (dBuV)			Limit (dBuV)		Margin (dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.15000	10.02	2.91	-3.93	12.93	6.09	66.00	56.00	-53.07	-49.91	
2	0.18906	10.04	10.32	1.25	20.36	11.29	64.08	54.08	-43.72	-42.79	
3	0.31016	10.06	-2.30	-8.69	7.76	1.37	59.97	49.97	-52.21	-48.60	
4	0.92734	10.11	-6.44	-11.91	3.67	-1.80	56.00	46.00	-52.33	-47.80	
5	7.92188	10.43	-7.99	-12.02	2.44	-1.59	60.00	50.00	-57.56	-51.59	
6	19.80078	11.06	11.79	4.26	22.85	15.32	60.00	50.00	-37.15	-34.68	

### Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) /
Filase	inediai (in)	Detector i unction	Average (AV)

	Phase Of Power : Neutral (N)									
No	Frequency	Correction Factor	Reading Value (dBuV)				Limit (dBuV)		Margin (dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.93	3.15	-3.63	13.08	6.30	66.00	56.00	-52.92	-49.70
2	0.18906	9.94	10.18	1.17	20.12	11.11	64.08	54.08	-43.96	-42.97
3	0.24766	9.94	5.86	-10.14	15.80	-0.20	61.84	51.84	-46.04	-52.04
4	0.91172	9.99	0.52	-10.24	10.51	-0.25	56.00	46.00	-45.49	-46.25
5	7.87891	10.29	7.98	-11.95	18.27	-1.66	60.00	50.00	-41.73	-51.66
6	19.57813	10.85	8.73	1.78	19.58	12.63	60.00	50.00	-40.42	-37.37

#### Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value





#### 4.3 20dB bandwidth Measurement

#### 4.3.1 Limits of 20dB bandwidth Measurement

According to 15.215(c), the requirement is to ensure the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified, is contained within the frequency band designated in the rule section under which the equipment is operated.

#### 4.3.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019

#### Note:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2. Tested date: Jan. 11, 2019

#### 4.3.3 Test Procedures


The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span from band edge. The bandedge was measured and recorded.

#### 4.3.4 Deviation from Test Standard

No deviation

### 4.3.5 Test Setup



#### 4.3.6 EUT Operating Conditions


Set the EUT under transmission / receiver condition continuously.

Report No.: RF131118E02B Page No. 30 / 33 Report Format Version: 6.1.1




#### 4.3.7 Test Results

### For 20dB Bandwidth



# For Bandedge





5 Pictures of Test Arrangements				
Please refer to the attached file (Test Setup Photo).				



## Appendix - Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a>
Web Site: <a href="mailto:www.bureauveritas-adt.com">www.bureauveritas-adt.com</a>

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: RF131118E02B Page No. 33 / 33 Report Format Version: 6.1.1