

**Test Report for the
FCC and ISED Testing of a
Raspberry Pi Pico 2 W
to FCC Rule 47CFR 15.247
and ISED RSS-247 for
Raspberry Pi Ltd**

Report number: C15655TR3

Project number: C8779

Author: 

L Trickett
Radio Test Engineer

Checked: 

J Beevers MPhys (Hons), PhD
Radio Testing Team Lead

Approved: 

J Beevers MPhys (Hons), PhD
Radio Testing Team Lead

Issue	Description						Issue by	Date
3	Copy 1		Copy 2		PDF	✓	JB	14 th October 2024

**This report shall not be reproduced, except in full without the prior written approval of Eurofins E&E UK Ltd
The results contained in this report are only applicable to the apparatus tested.**

CONTENTS

Test Report Change History	5
Section 1 Test Location.....	6
1.1 UKAS Accreditation.....	6
Section 2 Customer Information	7
Section 3 Equipment Details.....	8
3.1 Equipment Under Test (EUT).....	8
3.2 EUT Photographs.....	9
3.3 Configuration of EUT	9
3.4 EUT Monitoring/Auxiliary Equipment	10
3.5 Monitoring Software	10
Section 4 Test Specifications	11
4.1 Knowledge Database References.....	13
4.1.1 Radiated Emissions (30MHz to 1000MHz)	13
4.1.2 Radiated Emissions (1GHz to 40GHz)	13
4.2 Compliance Statement.....	13
Section 5 Spurious Emission Results – Radiated and Conducted.....	14
5.1 Test Specification	14
5.2 Procedure and Test Software Version	14
5.3 Radiated Emissions (30MHz to 1GHz)	15
5.3.1 Limits at 3m	15
5.3.2 Emissions measurements	15
5.3.3 Date of Test.....	15
5.3.4 Test Area.....	15
5.3.5 Tested by.....	15
5.3.6 Test Setup	16
5.3.7 Electric field emissions, 30MHz to 1GHz	17
5.4 Radiated Emissions (1GHz to 18GHz).....	19
5.4.1 Limits	19
5.4.2 Receiver Settings	19
5.4.3 Emissions measurements	19
5.4.4 Date of Test	19
5.4.5 Test Area.....	19
5.4.6 Tested by.....	19
5.4.7 Test Setup	20
5.4.8 Exploratory Radiated Emission Maximization	21
5.4.9 Electric field emissions, 1GHz to 18GHz	23
5.4.10 Example field strength calculation	25
5.4.11 Sample Data.....	25
5.5 Radiated Emissions (18GHz to 25GHz)	26
5.5.1 Limits	26
5.5.2 Receiver Settings	26
5.5.3 Emissions measurements	26
5.5.4 Date of Test	26
5.5.5 Test Area.....	26
5.5.6 Tested by.....	26
5.5.7 Test Setup	26
5.5.8 Exploratory Radiated Emission Maximization	27
5.6 Conducted Spurious Emissions 30MHz to 25GHz	29
5.6.1 Limits	29
5.6.2 Emissions measurements	29
5.6.3 Date of Test	29
5.6.4 Test Area.....	29
5.6.5 Tested by.....	29
5.6.6 Test Setup	30
5.6.7 Test Results	30

5.6.8	Antenna port conducted emissions, 30MHz to 25GHz	31
Section 6	6dB Bandwidth and 99% Occupied Bandwidth	33
6.1	Test Specification	33
6.2	Procedure and Test Software Version	33
6.2.1	Emissions measurements	34
6.2.2	Date of Test	34
6.2.3	Test Area	34
6.2.4	Tested by	34
6.2.5	Test Setup	34
6.2.6	Test Results	34
Section 7	Peak Output Power	38
7.1	Test Specification	38
7.2	Procedure and Test Software Version	38
7.2.1	Emissions measurements	39
7.2.2	Date of Test	39
7.2.3	Test Area	39
7.2.4	Tested by	39
7.2.5	Test Setup	39
7.2.6	Test Result	40
Section 8	Power Spectral Density	43
8.1	Test Specification	43
8.2	Procedure and Test Software Version	43
8.2.1	Emissions measurements	44
8.2.2	Date of Test	44
8.2.3	Test Area	44
8.2.4	Tested by	44
8.2.5	Test Setup	44
8.2.6	Test Results	45
Section 9	Band Edge Compliance	48
9.1	Test Specification	48
9.2	Procedure and Test Software Version	48
9.2.1	Emissions measurements	49
9.2.2	Date of Test	49
9.2.3	Test Area	49
9.2.4	Tested by	49
9.2.5	Test Setup	49
9.2.6	Test Results	49
Appendix A	EUT Test Photos	53
Appendix B	Test Equipment List	54

List of Figures

Figure 1 Test Setup for E-Field Measurements from 30MHz to 1GHz	16
Figure 2 Electric field emissions Plot, 30MHz to 1GHz, Operation on 2480MHz.....	17
Figure 3 Electric field emissions Plot, 30MHz to 1GHz, Operation on 2402MHz - Peak detector scan	18
Figure 4 Electric field emissions Plot, 30MHz to 1GHz, Operation on 2440MHz - Peak detector scan	18
Figure 5 – Manual investigation – Operating on BLE channel 2480MHz.....	22
Figure 6 Electric field emissions Plot, 1GHz to 8GHz. Operation on 2402MHz.....	23
Figure 7 Electric field emissions Plot, 1GHz to 8GHz, Operation on 2440MHz - Peak detector scan.....	24
Figure 7 Electric field emissions Plot, 1GHz to 8GHz, Operation on 2480MHz – Peak detector scan.....	24
Figure 9 – Manual investigation – Operating on BLE channel 2402MHz.....	27
Figure 10 – Manual investigation – Operating on BLE channel 2440MHz.....	28
Figure 11 – Manual investigation – Operating on BLE channel 2480MHz.....	28
Figure 12 Conducted emissions 30MHz to 25GHz. Operation on channel 2402MHz	31
Figure 13 Conducted emissions 30MHz to 25GHz. Operation on channel 2440MHz	31
Figure 14 Conducted emissions 30MHz to 25GHz. Operation on channel 2480MHz	32
Figure 15 Bandwidth at 6dB Point. Operation on channel 2402MHz	35
Figure 16 Bandwidth at 6dB Point. Operation on channel 2440MHz	35
Figure 17 Bandwidth at 6dB Point. Operation on channel 2480MHz	36
Figure 18 99% Occupied Bandwidth. Operation on channel 2402MHz	36
Figure 19 99% Occupied Bandwidth. Operation on channel 2440MHz	37
Figure 20 99% Occupied Bandwidth. Operation on channel 2480MHz	37
Figure 21 Peak output power, Operation on channel 2402MHz	41
Figure 22 Peak output power, Operation on channel 2440MHz	41
Figure 23 Peak output power, Operation on channel 2480MHz	42
Figure 24 Power spectral density, Operation on channel 2402MHz	46
Figure 25 Power spectral density, Operation on channel 2440MHz	46
Figure 26 Power spectral density, Operation on channel 2480MHz	47
Figure 27 Band Edge Measurement – upper band edge - horizontal polarity.....	51
Figure 28 Band Edge Measurement – upper band edge - vertical polarity.....	51
Figure 29 Band Edge Measurement – lower band edge - horizontal polarity	52
Figure 30 Band Edge Measurement – lower band edge - vertical polarity	52

List of Tables

Table 1 Electric Field Emissions Peaks, 30MHz to 1GHz. Operation on 2480MHz	17
Table 2 Frequencies identified during Exploratory Radiated Emission maximization.....	21
Table 3 Electric Field Emissions Peaks, 1GHz to 8GHz – Operation on 2402MHz.....	23
Table 4 Frequencies identified during Exploratory Radiated Emission maximization	27
Table 5 Bandwidth Measurements	34
Table 6 Peak Output Power Measurements.....	40
Table 7 Peak Spectral Density Measurements	45
Table 8 Operation on 2480MHz Channel, Peak detector measurements.....	50
Table 9 Operation on Channel 2480MHz, average detector measurements	50
Table 10 Operation on channel 2402MHz Peak detector measurements	50
Table 11 Operation on channel 2402MHz average detector measurements.....	50

Test Report Change History

Issue	Date	Modification Details
1	27 th September 2024	First Issue
2	7 th October 2024	Customer email amended
3	14 th October 2024	Exploratory graph added
4		
5		
6		
7		
8		
9		
10		

Section 1 Test Location

All testing was performed at:

Eurofins E&E UK	Unit 5
	Speedwell Road
	Castleford
	WF10 5PY
Tel:	01977 731173
Website	http://www.yorkemc.co.uk
UKAS Testing No.	1574

1.1 UKAS Accreditation

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

Eurofins E&E UK latest accreditation schedule can be found at:

http://www.ukas.org/testing/lab_detail.asp?lab_id=989&location_id=&vMenuOption=3

Eurofins E&E UK Castleford Laboratory, is an Accredited facility recognised by the Federal Communications Commission (FCC) for certification testing. The appropriate FCC Designation Number is UK2013, dated 1st March 2021.

Eurofins E&E UK Castleford Laboratory is recognised by ISED for certification testing.

ISED Assigned Code: 22959

CAB Identifier: UK0004

Section 2 Customer Information

Company name	Raspberry Pi Ltd
Address	194 Cambridge Science Park
	Milton Road
	Cambridge
	CB4 0AB
	United Kingdom
Contact	Tom Westcott
Email	compliance@raspberrypi.com

Section 3 Equipment Details

3.1 Equipment Under Test (EUT)

Date received:	9 th September 2024
EUT name:	Raspberry Pi Pico 2 W
PMN:	Raspberry Pi Pico 2 W
HVIN:	Raspberry Pi Pico 2 W
FCC ID:	2ABCB-PICO2W
IC:	20953-PICO2W
EUT description:	The Raspberry Pi Pico 2 W is a mini-PC with an on board radio module and antenna. The module has 2.4GHz Wi-Fi, Bluetooth classic and Bluetooth Low Energy functionality, which allows the user to connect to a 2.4GHz Wi-Fi network, BT Classic 5 compliant devices and BLE devices.
Antenna	Integral Antenna
Transmission	Digital Transmission System (DTS) Bluetooth Low Energy (BLE)
Modulation schemes	PRBS9
Operating frequency band	2400MHz to 2483.5MHz
No of units tested:	Unit 1: radiated tests Unit 2: conducted tests
EUT power:	3.3V via USB port
Highest internal frequency:	2.480GHz
Mode/s of operation:	Continuous transmit of packetised data at top, middle and bottom channels. Channels used: 2402MHz, 2440MHz and 2480MHz
Test software:	EUT was programmed with bt_mfg_test.uf2 Test Firmware installed. The EUT test modes were controlled via USB connection to a Raspberry Pi 400 device. The output power was set to the default value in the test software.
Modifications incorporated during testing:	N/A

Ports and Cables	Cable Length	Screened/unscreened	Connected to
USB cable	1m	unscreened	Raspberry Pi 400

EUT Monitoring/Auxiliary Equipment

Equipment name	Type no.	Serial no
Raspberry Pi 400	RPI-400	80000214328

3.2 EUT Photographs

Photographs are supplied separately.

3.3 Configuration of EUT

The apparatus was supplied in one single possible configuration.

BLE Channel Number	Frequency	BLE Channel Number	Frequency
0	2404 MHz	20	2446 MHz
1	2406 MHz	21	2448 MHz
2	2408 MHz	22	2450 MHz
3	2410 MHz	23	2452 MHz
4	2412 MHz	24	2454 MHz
5	2414 MHz	25	2456 MHz
6	2416 MHz	26	2458 MHz
7	2418 MHz	27	2460 MHz
8	2420 MHz	28	2462 MHz
9	2422 MHz	29	2464 MHz
10	2424 MHz	30	2466 MHz
11	2428 MHz	31	2468 MHz
12	2430 MHz	32	2470 MHz
13	2432 MHz	33	2472 MHz
14	2434 MHz	34	2474 MHz
15	2436 MHz	35	2476 MHz
16	2438 MHz	36	2478 MHz
17	2440 MHz	37*	2402 MHz
18	2442 MHz	38*	2426 MHz
19	2444 MHz	39*	2480 MHz

*Advertising channels.

BLE Channelization

Lowest channel	Default
Middle channel	Default
Highest channel	Default

Power settings table

Note: Modulation type PRBS9 Pattern. Packet type 3-DH1. Packet length 65535 used for all tests.

3.4 EUT Monitoring/Auxiliary Equipment

None.

3.5 Monitoring Software

None. The channel required was selected via software prior to the testing.

Section 4 Test Specifications

For USA:

Regulation / Test Standard	<p>Regulation:</p> <p>Title 47 of the Code of Federal Regulations (CFR) Part 15 (47CFR15) Subpart C – Intentional Radiators</p> <p>Measurement standard:</p> <p>ANSI C63.10-2013 American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices</p>
-----------------------------------	---

Requirement	FCC Rule Part	Comments	Result Summary
6 dB Bandwidth	FCC § 15.247(a)(2)	Applies	Pass
Maximum peak conducted power	FCC § 15.247(b)(3)	Applies	Pass
Power spectral density	FCC § 15.247(e)	Applies	Pass
Band edge compliance	FCC § 15.247(d)	Applies	Pass
Conducted spurious emissions	FCC § 15.247(d)	Applies	Pass
Transmitter radiated spurious emissions – restricted bands	FCC § 15.247(d) FCC § 15.209	Applies	Pass

For Canada:

Regulation / Test Standard	RSS-247 Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices Issue 3 August 2023 And, RSS-Gen — General Requirements for Compliance of Radio Apparatus Issue 5 April 2018 +A1 March 2019 +A2 February 2021
-----------------------------------	--

Requirement	ISED Regulation	Comments	Results Summary
99% Occupied Bandwidth	RSS-Gen 6.6	Applies	Pass
6 dB Bandwidth	ISED RSS-247 § 5.2	Applies	Pass
Maximum peak conducted power	ISED RSS-247 § 5.4	Applies	Pass
Power spectral density	ISED RSS-247 § 5.2	Applies	Pass
Band edge compliance	ISED RSS-247 § 3.3 and 5.5 RSS-GEN Issue 5 Section 8.10	Applies	Pass
Conducted spurious emissions	ISED RSS-247 § 5.5	Applies	Pass
Transmitter radiated spurious emissions	ISED RSS-GEN § 8.9	Applies	Pass

4.1 Knowledge Database References

The following KDBs were referenced during the testing.

The latest knowledge database references are available via the FCC KDB website at:

<https://apps.fcc.gov/kdb>

4.1.1 Radiated Emissions (30MHz to 1000MHz)

Publication Number	Keyword	Publication Date
913591	Measurement of radiated emissions at the band-edge for a Part 15 RF Device	04/05/2017

4.1.2 Radiated Emissions (1GHz to 40GHz)

Publication Number	Keyword	Publication Date
414788	Test Site Validation Requirements above 1 GHz.	07/12/2018
414788	Comparison Noise Emitter (CNE), reference noise source, .pdf	07/12/2018
913591	Measurement of radiated emissions at the band-edge for a Part 15 RF Device	04/05/2017
414788	Comparison Noise Emitters (CNE), test equipment, Broadband.pdf	07/12/2018

4.2 Compliance Statement

The Raspberry Pi Pico 2 W, as tested, was shown to meet requirements of the standards listed in Section 4 of this report.

Note: Only the Bluetooth Low Energy (BLE) functionality has been testing in this report.

Section 5 Spurious Emission Results – Radiated and Conducted

5.1 Test Specification

FCC Rule Part	47CFR 15.247 (d)
Standard	ANSI C63.10:2013
Measurement Uncertainty Radiated tests	<p>The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95% is</p> <p>+/- 5.01dB for the frequency range from 9kHz to 30MHz +/- 6.26dB for the frequency range 30MHz to 1GHz +/- 5.14dB for the frequency range from 1GHz to 6GHz +/- 5.45dB for the frequency range from 6GHz to 18GHz</p>
Measurement Uncertainty Conducted Power tests	+/- 1.4dB

5.2 Procedure and Test Software Version

Radiated tests:- 47CFR15.205 and 47CFR15.209

Eurofins E&E UK test procedure (30MHz to 1GHz)	CEP23 Issue 10
Eurofins E&E UK test procedure (1GHz to 40GHz)	CEP64 Issue 11
Test software	RadiMation Version 2023.1.6

Conducted Tests 47CFR 15.247(d)

ANSI C63.10-2013 Clause reference:	11.11.2 and 11.11.3
Test software	N/A

5.3 Radiated Emissions (30MHz to 1GHz)

Radiated electric field emission measurements are applied as defined in 47CFR15.205 and 47CFR15.209.

5.3.1 Limits at 3m

Frequency (MHz)	Electric Field Strength Limit (dB μ V/m) at 3m measurement distance
Quasi Peak	
30 - 88	40.0
88 -216	43.5
216 - 960	46.0
960- 1000	54.0

Note: FCC 47 CFR Part 15 Section 15.209 and 15.205 specifies test limits at 3m

Receiver Settings

Receiver Parameters	Setting
Detector Function	Quasi Peak
Start Frequency	30MHz
Stop Frequency	1000MHz
Resolution Bandwidth	120kHz
Video Bandwidth	Auto

5.3.2 Emissions measurements**5.3.3 Date of Test**

16th September 2024

5.3.4 Test Area

LAB 1 (SAC)

5.3.5 Tested by

L Trickett

5.3.6 Test Setup

The EUT was configured in the SAC on an 80cm high polystyrene table.

The measurement was performed with an antenna to EUT separation distance of 3m. The results were maximised in orientation 0-360 degrees and height 1-4m.




Figure 1 Test Setup for E-Field Measurements from 30MHz to 1GHz

Note 1 : With the EUT de-energized the ambient radio noise and signals met the 6dB peak detection requirement of ANSI C63.10-2013.

Note 2 : There were no significant environmental temperature changes during the test duration and hence it was not considered necessary to consider any variation in cable loss.

Operating Mode During testing

During spurious emission testing the equipment under test was set to transmit at the same frequency on the following channels: 2402MHz, 2440MHz and 2480MHz.

The equipment under test was pre-scanned using peak detection when operating on all three channels. Final measurements were performed with the equipment under test operating on 2480MHz.

5.3.7 Electric field emissions, 30MHz to 1GHz




Figure 2 Electric field emissions Plot, 30MHz to 1GHz, Operation on 2480MHz

Frequency MHz	Quasi-Peak dB μ V/m	Quasi Peak Limit dB μ V/m	Quasi-Peak Difference dB	Quasi-Peak Status	Angle degrees	Height m	Polarization
44.94	24.30	40.00	-15.70	Pass	125	1.0	Vertical
48.00	31.70	40.00	-8.30	Pass	135	1.0	Vertical
51.18	27.10	40.00	-12.90	Pass	270	1.0	Vertical
53.40	25.20	40.00	-14.80	Pass	35	1.0	Vertical
69.12	22.80	40.00	-17.20	Pass	25	1.4	Vertical
72.00	33.50	40.00	-6.50	Pass	90	1.2	Vertical
75.66	20.60	40.00	-19.40	Pass	105	1.3	Vertical
84.06	22.10	40.00	-17.90	Pass	45	1.1	Vertical
92.64	28.50	43.50	-15.00	Pass	10	1.1	Vertical
96.00	32.00	43.50	-11.50	Pass	30	1.1	Vertical
99.36	22.60	43.50	-20.90	Pass	40	1.0	Vertical
480.06	34.30	46.00	-11.70	Pass	360	2.2	Vertical

Table 1 Electric Field Emissions Peaks, 30MHz to 1GHz. Operation on 2480MHz




Figure 3 Electric field emissions Plot, 30MHz to 1GHz, Operation on 2402MHz - Peak detector scan




Figure 4 Electric field emissions Plot, 30MHz to 1GHz, Operation on 2440MHz - Peak detector scan

5.4 Radiated Emissions (1GHz to 18GHz)**5.4.1 Limits**

Frequency (GHz)	Limit (dB μ V/m)	Limit (dB μ V/m)
	Peak	Average
1-18	74.0	54.0

5.4.2 Receiver Settings

Receiver Parameters	Setting
Detector Function	Average and Peak
Start Frequency	1GHz
Stop Frequency	8GHz
Resolution Bandwidth	1MHz
Video Bandwidth	Auto

5.4.3 Emissions measurements**5.4.4 Date of Test**17th September 2024**5.4.5 Test Area**

LAB 1 (SAC)

5.4.6 Tested by

L Trickett

5.4.7 Test Setup

The EUT was configured in the SAC on a 1.5m high table. Exploratory measurements on the EUT were carried out to identify suspect frequencies and worst case orientations, see Section 5.4.8.

The measurement was then performed with an antenna to EUT separation distance of 3m.

The antenna was kept in the “cone of radiation” from the EUT and pointed at the area both in azimuth and elevation using the tilt mechanism on the antenna mast.

The results were maximised in orientation 0-360 degrees and height 1-4m.




Figure 5.4.7.1: Test Setup for Final E-Field Measurements from 1GHz to 18GHz

Note 1: With the EUT de-energized the ambient radio noise and signals met the 6dB peak detection requirement of ANSI C63.4-2010.

Note 2: There were no significant environmental temperature changes during the test duration and hence it was not considered necessary to consider any variation in cable loss.

Note 3: On all swept and final measurements made between 1GHz and 18GHz a 2.4GHz Microtronics BRM50702 notch filter was placed in the measurement chain between the antenna and pre-amplifier in order to prevent the artificial generation of harmonics within the pre-amplifier.

5.4.8 Exploratory Radiated Emission Maximization

During exploratory testing, suspect emissions from the EUT were identified both in terms of the frequency and directionality. This was achieved by manually positioning the antenna close to the EUT and also by scanning it over all sides of the EUT whilst observing a spectral display. The typical distance between the surface of the EUT and the scanning antenna was circa 30cm.

Frequency (GHz)	Mode of operation	EUT face *	Emissions Angle (w.r.t. turntable)	Height	Polarization
1.025	Transmitting on channel 2402MHz	Front	0	1.5	V
1.331	Transmitting on channel 2440MHz & 2480MHz	Front	0	1.5	V
1.348	Transmitting on channel 2402MHz	Front	0	1.5	V
1.433	Transmitting on channel 2480MHz	Front	0	1.5	V
3.845	Transmitting on channel 2402MHz	Front	0	1.5	V
4.796	Transmitting on channel 2402MHz	Front	0	1.5	V
4.881	Transmitting on channel 2440MHz	Front	0	1.5	V
4.966	Transmitting on channel 2480MHz	Front	0	1.5	V

Table 2 Frequencies identified during Exploratory Radiated Emission maximization

Note 1: The front face of the EUT is deemed to be 0°, which is then turned in a clockwise direction through 360°.

Note 2: With no emissions observed above 5GHz during the exploratory investigation, final measurements were performed up to 8GHz only.




Figure 5 – Manual investigation – Operating on BLE channel 2480MHz

5.4.9 Electric field emissions, 1GHz to 18GHz

The equipment under test was pre-scanned using peak detection when operating on all three channels. Final measurements were performed with the equipment under test operating on 2402MHz




Figure 6 Electric field emissions Plot, 1GHz to 8GHz. Operation on 2402MHz

Frequency GHz	Average dB μ V/m	Average Limit dB μ V/m	Average Difference dB	Average Status	Angle degrees	Height m	Polarization
2.07	24.47	54.00	-29.53	Pass	65	3.5	Vertical
2.93	26.86	54.00	-27.14	Pass	100	2.6	Vertical
3.84	34.35	54.00	-19.65	Pass	235	1.7	Vertical
4.81	33.03	54.00	-20.97	Pass	300	2.1	Vertical
5.78	35.37	54.00	-18.63	Pass	135	1.8	Vertical
7.07	37.30	54.00	-16.70	Pass	100	1.5	Vertical
7.80	35.76	54.00	-18.24	Pass	255	4.0	Horizontal

Table 3 Electric Field Emissions Peaks, 1GHz to 8GHz – Operation on 2402MHz




Figure 7 Electric field emissions Plot, 1GHz to 8GHz, Operation on 2440MHz - Peak detector scan




Figure 8 Electric field emissions Plot, 1GHz to 8GHz, Operation on 2480MHz – Peak detector scan

5.4.10 Example field strength calculation

The total average corrections are shown in the above table. This correction figure consists of Preamplifier gain (PG), Antenna factor (AF); and Cable loss (CL), and where necessary distance extrapolation factor (dB).

Field strength (FS) is calculated as follows:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Indicated Signal Level (dB}\mu\text{V)} - PG \text{ (dB)} + AF \text{ (dB)} + CL \text{ (dB)}$$

5.4.11 Sample Data

From Figure 6 and table 3. The Average level at 7.80GHz is calculated as follows:

$$FS \text{ (dB}\mu\text{V/m)} = 45.12(\text{dB}\mu\text{V}) - 54.47(\text{dB}) + 38.91(\text{dB/m}) + 6.20(\text{dB}) = 35.76 \text{ dB}\mu\text{V/m}$$

5.5 Radiated Emissions (18GHz to 25GHz)**5.5.1 Limits**

Frequency (GHz)	Limit (dB μ V/m)	Limit (dB μ V/m)
	Peak	Average
18-25	74.0	54.0

5.5.2 Receiver Settings

Receiver Parameters	Setting
Detector Function	Average and Peak
Start Frequency	18GHz
Stop Frequency	25GHz
Resolution Bandwidth	1MHz
Video Bandwidth	Auto

5.5.3 Emissions measurements**5.5.4 Date of Test**17th September 2024**5.5.5 Test Area**

LAB 1 (SAC)

5.5.6 Tested by

L Trickett

5.5.7 Test Setup

This is the same as for the 1-18GHz range for final measurements, except with a measurement distance of 1m.

5.5.8 Exploratory Radiated Emission Maximization

During exploratory testing, suspect emissions from the EUT were identified both in terms of the frequency and directionality. This was achieved by manually positioning the antenna close to the EUT and also by scanning it over all sides of the EUT whilst observing a spectral display. The typical distance between the surface of the EUT and the scanning antenna was circa 30cm.

Frequency (GHz)	Mode of operation	EUT face *	Emissions Angle (w.r.t. turntable)	Height	Polarization
-	Tx on channels 2402MHz, 2440MHz and 2480MHz.	-	-	-	-

Table 4 Frequencies identified during Exploratory Radiated Emission maximization

Note 1: The front face of the EUT is deemed to be 0°, which is then turned in a clockwise direction through 360°.

Note 2: No emissions were identified for further investigation above 18GHz.




Figure 9 – Manual investigation – Operating on BLE channel 2402MHz




Figure 10 – Manual investigation – Operating on BLE channel 2440MHz



Figure 11 – Manual investigation – Operating on BLE channel 2480MHz

5.6 Conducted Spurious Emissions 30MHz to 25GHz**5.6.1 Limits**

Frequency (MHz)	Limit, 47CFR 15.247(d)
Peak	
30 – 25000	-20dBc

Spectrum analyser settings as specified by ANSI C63.10-2013 Clause 11.11.2

Receiver Parameters	Setting
Detector Function	Peak
Start Frequency	30MHz
Stop Frequency	25000MHz
Resolution Bandwidth	100kHz
Video Bandwidth	300kHz
Sweep rate	Auto couple
Trace mode	Max hold

5.6.2 Emissions measurements**5.6.3 Date of Test**

16th September 2024

5.6.4 Test Area


LAB 8

5.6.5 Tested by

L Trickett

5.6.6 Test Setup

The antenna port was connected directly to the signal analyser.



5.6.7 Test Results

The results of the conducted spurious emissions are stated below and by the signal analyser images.

All disturbances detected were > 20dB below the carrier.

5.6.8 Antenna port conducted emissions, 30MHz to 25GHz




Figure 12 Conducted emissions 30MHz to 25GHz. Operation on channel 2402MHz.




Figure 13 Conducted emissions 30MHz to 25GHz. Operation on channel 2440MHz.




Figure 14 Conducted emissions 30MHz to 25GHz. Operation on channel 2480MHz.

Section 6 6dB Bandwidth and 99% Occupied Bandwidth

6.1 Test Specification

FCC Rule Part	46CFR 15.247 (b)(2)
Standard	ANSI C63.10:2013
Measurement Uncertainty Frequency tests	$\pm 9 \times 10^{-8}$

6.2 Procedure and Test Software Version

Conducted Tests

ANSI C63.10-2013 Clause reference:	11.9.1.1 (RBW>DTS bandwidth)
Test software	N/A

Frequency (MHz)	Limit, 47CFR 15.247(a)(2) 6dB bandwidth
	Peak
2400MHz to 2483.5MHz	At least 500kHz

Spectrum analyser settings as specified by ANSI C63.10-2013 Clause 11.8.1

Receiver Parameters	Setting
Detector Function	Peak
Span	3MHz
Resolution Bandwidth	100kHz
Video Bandwidth	300kHz
Sweep rate	Auto couple
Trace mode	Max hold

6.2.1 Emissions measurements**6.2.2 Date of Test**16th September 2024**6.2.3 Test Area**


LAB 8

6.2.4 Tested by

L Trickett

6.2.5 Test Setup

The antenna port was connected directly to the signal analyser.

**6.2.6 Test Results**

The results of the 6dB bandwidth measurements are stated in the table below and by the signal analyser images.

Channel (MHz)	99% Occupied Bandwidth (MHz)	Measured 6dB bandwidth (kHz)	Minimum requirement (kHz)	Figure	Result
2402.0	1.19	1120	500.0	15 & 18	Pass
2440.0	1.19	1100	500.0	16 & 19	Pass
2480.0	1.18	1009	500.0	17 & 20	Pass

Table 5 Bandwidth Measurements



Figure 15 Bandwidth at 6dB Point. Operation on channel 2402MHz




Figure 16 Bandwidth at 6dB Point. Operation on channel 2440MHz



Figure 17 Bandwidth at 6dB Point. Operation on channel 2480MHz



Figure 18 99% Occupied Bandwidth. Operation on channel 2402MHz




Figure 19 99% Occupied Bandwidth. Operation on channel 2440MHz




Figure 20 99% Occupied Bandwidth. Operation on channel 2480MHz

Section 7 Peak Output Power

7.1 Test Specification

FCC Rule Part	46CFR 15.247 (b)(3)
Standard	ANSI C63.10:2013
Measurement Uncertainty Conducted Power tests	±1.4dB

7.2 Procedure and Test Software Version

Conducted Tests

ANSI C63.10-2013 Clause reference:	11.9.1.1 (RBS>DTS bandwidth)
Test software	N/A

Frequency (MHz)	Limit, 47CFR 15.247(b)(2)
	Peak
2400MHz to 2483.5MHz	1 watt

Spectrum analyser settings as specified by ANSI C63.10-2013 Clause 11.11.2

Receiver Parameters	Setting
Detector Function	Peak
Span	10MHz
Resolution Bandwidth	2MHz
Video Bandwidth	10MHz
Sweep rate	Auto couple
Trace mode	Max hold

7.2.1 Emissions measurements

7.2.2 Date of Test

16th September 2024

7.2.3 Test Area


LAB 8

7.2.4 Tested by

L Trickett

7.2.5 Test Setup

The antenna port was connected directly to the signal analyser.



7.2.6 Test Result

The results of the peak output power measurements are stated in the table below and by the signal analyser images.

Channel (MHz)	Peak Power (dBm)	Peak Power (Watts)	Limit (Watts)	Figure
2402	4.58	0.0029	1	21
2440	5.23	0.0033	1	22
2480	5.30	0.0034	1	23

Table 6 Peak Output Power Measurements

The MAX antenna gain is 2.0 dBi, MAX EIRP=MAX peak power *MAX antenna gain = $5.30 + 2.0 = 7.30$ dBm,

The Max EIRP is 7.30 dBm (0.0054W) and does not exceed 4W, which meets the EIRP requirement of RSS-247 section 5.4.




Figure 21 Peak output power, Operation on channel 2402MHz




Figure 22 Peak output power, Operation on channel 2440MHz




Figure 23 Peak output power, Operation on channel 2480MHz

Section 8 Power Spectral Density

8.1 Test Specification

FCC Rule Part	46CFR 15.247 (e)
Standard	ANSI C63.10:2013
Measurement Uncertainty Conducted Power tests	±1.4dB

8.2 Procedure and Test Software Version

Conducted Tests

ANSI C63.10-2013 Clause reference:	Clause 11.10.2
Test software	N/A

Frequency (MHz)	Limit, 47CFR 15.247(e)
	Peak
2400MHz to 2483.5MHz	<8dBm in any 3kHz band during any time interval of complete transmission

Spectrum analyser settings as specified by ANSI C63.10-2013 Clause 11.10.2

Receiver Parameters	Setting
Detector Function	Peak
Span	1.5 x DTS bandwidth
Resolution Bandwidth	3kHz ≤RBW ≤100kHz
Video Bandwidth	3 x RBW
Sweep rate	Auto couple
Trace mode	Max hold

8.2.1 Emissions measurements

8.2.2 Date of Test

16th September 2024

8.2.3 Test Area


LAB 8

8.2.4 Tested by

L Trickett

8.2.5 Test Setup

The antenna port was connected directly to the signal analyser.



8.2.6 Test Results

Channel (MHz)	Power in 3kHz RBW (dBm)	Limit (dBm)	Figure	Result
2402	-11.34	8.0	24	Pass
2440	-10.30	8.0	25	Pass
2480	-10.28	8.0	26	Pass

Table 7 Peak Spectral Density Measurements




Figure 24 Power spectral density, Operation on channel 2402MHz




Figure 25 Power spectral density, Operation on channel 2440MHz




Figure 26 Power spectral density, Operation on channel 2480MHz

Section 9 Band Edge Compliance

9.1 Test Specification

FCC Rule Part	46CFR 15.205 and 47CFR15.209
Standard	ANSI C63.10:2013
Measurement Uncertainty Radiated tests	The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95% is $\pm 5.14\text{dB}$ for the frequency range from 1GHz to 6GHz

9.2 Procedure and Test Software Version

Conducted Tests

ANSI C63.10-2013 Clause reference:	Clause 6.10.4 Authorised band-edge measurements
Test software	N/A

Frequency (MHz)	Limit, 47CFR 15.247(e)
	Peak
2400MHz to 2483.5MHz	Measured signal at the band edge must be below the radiated emission limits of 47CFR15.209

Spectrum analyser settings as specified by ANSI C63.10-2013 Clause 6.10.5 “Restricted band-edge measurements”

Receiver Parameters	Setting
Detector Function	Peak
Span	As necessary
Resolution Bandwidth	1MHz
Video Bandwidth	3 x RBW
Sweep rate	Auto couple
Trace mode	Max hold

9.2.1 Emissions measurements

9.2.2 Date of Test

20th September

9.2.3 Test Area

LAB 1

9.2.4 Tested by

L Trickett

9.2.5 Test Setup

The test setup was identical to radiated emissions testing 1-18GHz.

9.2.6 Test Results

Results are presented in two formats:

Tabular results of measurements at the band edges. Manual measurements were performed to measure the maximum value of signal at the band edge. The tabular data includes the following:

1. Polarity of the measurement antenna
2. Frequency at the band edge
3. Amplitude of signal at the input of the test receiver
4. Pre-amplifier gain
5. Cable loss
6. Antenna factor
7. Resultant Electric field strength = 3-4+5+6

Spectrum analyser screen displays are also included. Please note that the screen displays do not include losses or antenna factor.

Tabular Data

The following radiated measurements were made at the band edges:

Upper band edge

Polarity	Frequency (MHz)	Amplitude (dBuV)	Preamp (dB)	Cable loss (dB)	AF(dB/m)	E (dBuV/m)	Limit (dBuV/m)	Margin (dB)
H	2483.5	63.4	54.3	4.1	30.6	43.8	74.0	30.2
V	2483.5	64.8	54.3	4.1	30.6	45.2	74.0	28.8

Table 8 Operation on 2480MHz Channel, Peak detector measurements

Polarity	frequency (MHz)	Amplitude (dBuV)	Preamp (dB)	Cable loss (dB)	AF(dB/m)	E (dBuV/m)	Limit (dBuV/m)	Margin (dB)
H	2483.5	45.2	54.3	4.1	30.6	25.6	54.0	28.4
V	2483.5	46.0	54.3	4.1	30.6	26.4	54.0	27.6

Table 9 Operation on Channel 2480MHz, average detector measurements

Lower band edge

Polarity	frequency (MHz)	Amplitude (dBuV)	Preamp (dB)	Cable loss (dB)	AF(dB/m)	E (dBuV/m)	Limit (dBuV/m)	Margin (dB)
H	2400.0	75.3	54.2	4.0	30.0	55.1	74.0	18.9
V	2400.0	75.3	54.2	4.0	30.0	55.1	74.0	18.9

Table 10 Operation on channel 2402MHz Peak detector measurements

Polarity	frequency (MHz)	Amplitude (dBuV)	Preamp (dB)	Cable loss (dB)	AF(dB/m)	E (dBuV/m)	Limit (dBuV/m)	Margin (dB)
H	2400.0	51.3	54.2	4.0	30.0	31.1	54.0	22.9
V	2400.0	59.2	54.2	4.0	30.0	39.0	54.0	15.0

Table 11 Operation on channel 2402MHz average detector measurements

Spectrum analyser displays




Figure 27 Band Edge Measurement – upper band edge - horizontal polarity




Figure 28 Band Edge Measurement – upper band edge - vertical polarity




Figure 29 Band Edge Measurement – lower band edge - horizontal polarity




Figure 30 Band Edge Measurement – lower band edge - vertical polarity

Appendix A EUT Test Photos

Test set up photographs are supplied separately.

Appendix B Test Equipment List

Conducted Emissions from Antenna Port

Item	Serial No.	Last Calibration Date	Calibration Interval
R&S ESW44 EMI Receiver	C0658	30 th October 2023	12 Months
Kikusui PCR200M	C0198	-	-

Radiated Emissions Equipment

Item	Serial No.	Last Calibration Date	Calibration Interval
Laboratory 1 Semi-Anechoic Chamber	C0471	6 th December 2022	36 Months
ETS Lindgren 2017B Mast (1 – 4m) with tilting mechanism	--	N/A	N/A
R&S ESW44 EMI Receiver	C0751	5 th August 2024	12 Months
Kikusui PCR200M	C0198	-	-
Teseq CBL6112D Bilog Antenna	C0506	22 nd August 2024	36 Months
HF27 Cable	19149.03.13.004	13 th December 2023	12 Months
HF29 Cable	20147.01.09.001	13 th December 2023	12 Months
HF32 Cable	19149.01.09.003	13 th December 2023	12 Months
HF35 Cable	19149.02.13.003	13 th December 2023	12 Months
HF47 Cable	E44808	7 th March 2024	12 Months
Schwarzbeck STLP 9148 Antenna 1-18GHz	C0626	26 th March 2024	24 Months
2.4GHz Microtronics BRM50702 notch filter	79178	7 th December 2023	12 Months
BONN BLMA 0118-M Preamplifier	C0702	1 st August 2024	12 Months
ETS Lingren 3116C-PA Horn Antenna 18-40GHz	C0433	29 th September 2022	36 Months

-----END OF REPORT-----