

## Rear View Mirror GPS

### 1) How does this device operate?

The device automatically run when ACC is power on . Press the power key to enter sleep or awake.

### 2) Provide information on the device and its antenna.

The FM Antenna is connected to the 5th pin of USB slot, it is the GND line in the RM050A, this is permanently attached antenna and meets the requirements of the section.

### 3) How is it installed?

It is a professional Rear View Mirror Device, which has the vehicle specific mounts for replacing with original mirror.. And power by 12Vdc Car Power.

### 4) What test procedure was used?

Operating condition is according to ANSI C63.4-2009

### 5) If tested in a car, how was it configured/tested?

N/A

### 6) Was the tuning range properly verified?

The test lab should indicate in the report that the tuning controls were manually adjusted to verify maximum tuning range. EUT was adjusted to work at the selected channels: 88.1 MHz, 98.1 MHz, and 107.9 MHz. The EUT will not allow operation below 88.1 MHz and will not allow operation above 107.9 MHz.

### 7) Was the bandwidth properly tested with maximum audio input?

Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operation frequency. The 200 kHz band shall lie wholly within the frequency range of 88 – 108 MHz. Setup the EUT and simulators as shown in the report. Enable RF signal and confirm EUT active. Modulate output capacity of EUT up to specifications.

### 8) Provide the test report.

Test Report Submitted.

signature



name Chen WanLu

Title: Project manager

Telephone: +86-755-29111731

Email: cz@roadtom.com

Date: 2013-12-2