





The Nest Network S.L.

For

eNest

Model Name:

NE101SA

Trade Name:

eNest

Brand Name:

Nestwork

FCC ID:

2ABF8-NE101SA

Standard:

47 CFR Part 15 Subpart B

Test date:

October 23, 2013 - November 6, 2013

Issue date:

February 11, 2014

By

Shenzhen Morlab Communications Technology Co., Ltd.

FL.3, Building A, FeiYang Science Park, No.8 Long Chang Road, Block 67, BaoAn District, ShenZhen, Guang Brovince P. R. China 518101

Tested by XiAD XiONQ Xiao Xiong

(Test Engineer)

Date 2014, 2, 11

Approved by Zene Deron

Certific ptich

(Chief Engineer)

Review by Wuzhom

Wu Zhangli

(EMC Manager)

Date

2014.2.11

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate



TABLE OF CONTENTS

<u>1.</u> <u>G</u>	SENERAL INFORMATION	<u> 3</u>
1.1	EUT DESCRIPTION	3
1.2	TEST STANDARDS AND RESULTS	4
1.3	FACILITIES AND ACCREDITATIONS	5
1.3.1	FACILITIES	5
1.3.2	FACILITIES	5
1.3.3	MEASUREMENT UNCERTAINTY	5
2 T	EST CONDITIONS SETTING	6
<u> </u>	LOT GONDITIONG OLT TING	<u> U</u>
2.1 ·	Test Mode	6
	TEST SETUP AND EQUIPMENTS LIST	
2.2.1	CONDUCTED EMISSION	7
2.2.2	RADIATED EMISSION	8
3. 4 ⁻	7 CFR PART 15B REQUIREMENTS	10
3.1	CONDUCTED EMISSION	10
3.1.1	REQUIREMENT	10
3.1.2	TEST DESCRIPTION	10
3.1.3	TEST RESULT	10
3.2	RADIATED EMISSION	13
3.2.1	REQUIREMENT	13
3.2.2	TEST DESCRIPTION	13
	FREQUENCY RANGE OF MEASUREMENT	
3.2.4	TEST RESULT	14

Change History					
Issue	Date	Reason for change			
1.0 February 11, 2014		First edition			
2.0 March 4, 2014		Second edition			

Email: info sz@morlab.cn



1. GENERAL INFORMATION

1.1 EUT Description

EUT Type:	eNest	
Serial No:	(n.a., marked #1 by test site)	
Hardware Version:	V4.0	
Software Version:	V1.5.2	
Applicant:	The Nest Network S.L.	
	Plaza Republica Argentina 3 Madrid Spain	
Manufacturer:	The Nest Network S.L.	
	Plaza Republica Argentina 3 Madrid Spain	

Power supply:	Battery		
	Brand Name:	Nestwork	
	Model No.:	453738A	
	Serial No.:	(n.a. marked #1 by test site)	
	Capacitance:	700mAh	
	Rated Voltage:	3.7V	
	Charge Limit:	5V	
Ancillary Equipment:	AC Adapter (Charger for Battery)		
	Brand Name:	Nestwork	
	Model No.:	S01A22	
	Serial No.:	(n.a. marked #1 by test site)	
	Rated Input:	~ 100-240V, 200mA, 50/60Hz	
	Rated Output:	= 5V, 1000mA	

NOTE:

Web site: http://www.morlab.cn/

- 1. The EUT is a eNest. It is an advanced personal mobile emergency device that combines GSM, GPRS, GPS and WiFi technologies to offer the most comprehensive alert and location features. By just pressing an alarm button, the users can call for assistance and get the help they need efficiently.
- 2. The EUT supports GSM850MHz, 900MHz, 1800MHz, 1900MHz, GPRS, GPS, ISM 2.4GHz WIFI and another 2.4GHz transmit. The EUT is equipped with a Micro-B USB port which can be connected to the ancillary equipments supplied by the manufacturer e.g. the USB Cable.
- 3. Please refer to Annex A for the photographs of the EUT. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Shenzhen Morlab Communications Technology Co., Ltd Phone: +86 (0) 755 36698555

Email: info sz@morlab.cn Page 3 of 15

Fax: +86 (0) 755 36698525



Web site: http://www.morlab.cn/

Report No.: SZ13090062E01

1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15(10-1-12 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2009.

Shenzhen Morlab Communications Technology Co., Ltd Phone: +86 (0) 755 36698555

Fax: +86 (0) 755 36698525

Email: info_sz@morlab.cn Page 4 of 15



1.3 Facilities and Accreditations

1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

Report No.: SZ13090062E01

Fax: +86 (0) 755 36698525

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China 518101. The test site is constructed in conformance with the requirements of ANSI C63.4-2009 and CISPR Publication 22:2008; the FCC registration number is 695796.

1.3.2 Facilities

Web site: http://www.morlab.cn/

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 -106

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	±1.8dB
Uncertainty of Radiated Emission:	±3.1dB

Shenzhen Morlab Communications Technology Co., Ltd Phone: +86 (0) 755 36698555

Email: info_sz@morlab.cn Page 5 of 15



2. **TEST CONDITIONS SETTING**

2.1 **Test Mode**

1 The test mode (Data Transmission)					
The EUT configuration of the emission tests is EUT + Battery + PC.					
	During the measurement, the EUT was connected with a PC via the Micro-B USB port,				
	the data is transmitting between the PC and the EUT.				
2	The second test mode (Standby)				
	The EUT configuration of the emission tests is EUT + Battery + Charger.				
	During the measurement, the EUT was charged by its adapter and turned on.				
Note:	Note: All test modes are performed, only the worst case(Data Transmission) is recorded in this				

report.

Shenzhen Morlab Communications Technology Co., Ltd

Web site: http://www.morlab.cn/ Fax: +86 (0) 755 36698525 Email: info sz@morlab.cn Page 6 of 15

Phone: +86 (0) 755 36698555






Test Setup and Equipments List 2.2

2.2.1 **Conducted Emission**

A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu H$ of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
Receiver	Narda	PMM 9010	595WX11007	12/11/2013	11/11/2014
EMC Analyzer	Agilent	E7405A	US44210471	12/05/2013	11/05/2014
LISN	Schwarzbeck	NSLK 8127	812744	12/05/2013	11/05/2014
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)
System Simulator	Agilent	E5515C	GB43130131	12/05/2013	11/05/2014
PC	Lenovo	ThinkPadT61	ZZF3077	(n.a.)	(n.a.)

Shenzhen Morlab Communications Technology Co., Ltd

Web site: http://www.morlab.cn/ Email: info sz@morlab.cn

Phone: +86 (0) 755 36698555 Fax: +86 (0) 755 36698525







2.2.2 Radiated Emission

A. Test Setup:

1) For radiated emissions from 30MHz to1GHz



2) For radiated emissions above 1GHz



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table,

Shenzhen Morlab Communications Technology Co., Ltd

Web site: http://www.morlab.cn/

Email: info sz@morlab.cn

Phone: +86 (0) 755 36698555

Fax: +86 (0) 755 36698525

Page 8 of 15



For the test Antenna:

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
EMC Analyzer	Agilent	E7405A	US44210471	12/05/2013	11/05/2014
Semi-Anechoic	Albatross	9m*6m*6m	(n.a.)	12/05/2012	11/05/2014
Chamber					
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	12/05/2012	11/05/2014
Test Antenna - Horn	Schwarzbeck	BBHA 9120D	9120D-963	12/05/2012	11/05/2014
PC	Lenovo	ThinkPadT61	ZZF3077	(n.a.)	(n.a.)

Shenzhen Morlab Communications Technology Co., Ltd Phone: +86 (0) 755 36698555

Web site: http://www.morlab.cn/
Email: info_sz@morlab.cn

Fax: +86 (0) 755 36698525

Page 9 of 15



3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a $50\mu\text{H}/50\Omega$ line impedance stabilization network (LISN).

Eroguanay ranga (MU=)	Conducted Limit (dBμV)			
Frequency range (MHz)	Quasi-peak	Average		
0.15 - 0.50	66 to 56	56 to 46		
0.50 - 5	56	46		
5 - 30	60	50		

NOTE:

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 0.50MHz.

3.1.2 Test Description

See section 2.2.1 of this report.

3.1.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.


A. Test Plot and Suspicious Points:

Shenzhen Morlab Communications Technology Co., Ltd Phone: +86 (0) 755 36698555

Web site: http://www.morlab.cn/
Fax: +86 (0) 755 36698525
Email: info-sz@morlab.cn
Page 10 of 15








NO.	Fre.	Emission Level (dBµV)		Limit (d	dBµV)	Power-line	Verdict
	(MHz)	Quai-peak	Average	Quai-peak	Average		
1	7.17	37.54	25.52	60.00	50.00		PASS
2	8.145	38.03	25.91	60.00	50.00		PASS
3	9.105	36.35	21.10	60.00	50.00	Lino	PASS
4	9.53	35.83	24.32	60.00	50.00	Line	PASS
5	17.445	35.79	18.99	60.00	50.00		PASS
6	18.535	35.34	17.61	60.00	50.00		PASS

Web site: http://www.morlab.cn/
Email: info sz@morlab.cn







NO.	Fre.	Emission Level (dBµV)		Limit (dBµV)	Power-line	Verdict
	(MHz)	Quai-peak	Average	Quai-peak	Average		
1	0.15	38.89	16.25	66.00	56.00		PASS
2	0.595	37.56	25.12	56.00	46.00		PASS
3	6.94	39.48	29.18	60.00	50.00	Neutral	PASS
4	7.82	42.14	30.88	60.00	50.00	Neutrai	PASS
5	8.815	41.20	30.04	60.00	50.00		PASS
6	9.865	39.52	28.72	60.00	50.00		PASS

Test Result: PASS

Web site: http://www.morlab.cn/
Email: info-sz@morlab.cn



3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109(a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Report No.: SZ13090062E01

Phone: +86 (0) 755 36698555

Frequency	Field Stre	ngth	Field Strength Limitation at 3m Measurement Dist			
range (MHz) µV/m Dist		(μV/m)	(dBµV/m)			
30.0 - 88.0	100	3m	100	20log 100		
88.0 - 216.0	150	3m	150	20log 150		
216.0 - 960.0	200	3m	200	20log 200		
Above 960.0	500	3m	500	20log 500		

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBμV/m is calculated by 20log Emission Level(μV/m).
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of Ld1 = Ld2 * $(d2/d1)^{2}$.

Example:

F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as Ld1 = L1 = 30μ V/m * $(10)^2$ = $100 * 30\mu$ V/m

3.2.2 Test Description

See section 2.2.2 of this report.

3.2.3 Frequency range of measurement

Highest frequency generated or used in the device is the highest speed of the processor. According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:

Frequency	Frequency generated or used in the device	Frequency range of radiated measurement in the report
Highest	400MHz	2GHz

Shenzhen Morlab Communications Technology Co., Ltd

Web site: http://www.morlab.cn/
Fax: +86 (0) 755 36698525
Email: info-sz@morlab.cn
Page 13 of 15




3.2.4 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.

A. Test Plots and Suspicious Points:



NO.	Fre.	Pk	QP	AV	Limit-	Limit-	Limit-	Antenna	Verdict
	(MHz)				PK	QP	AV		
1	61.446	N.A	31.53	N.A	N.A	40.0	N.A	Vertical	Pass
2	165.461	N.A	31.13	N.A	N.A	43.5	N.A	Vertical	Pass
3	288.828	N.A	36.43	N.A	N.A	46.0	N.A	Vertical	Pass

Shenzhen Morlab Communications Technology Co., Ltd

Web site: http://www.morlab.cn/


Email: info sz@morlab.cn

Phone: +86 (0) 755 36698555 Fax: +86 (0) 755 36698525

Page 14 of 15



4	349.123	N.A	32.96	N.A	N.A	46.0	N.A	Vertical	Pass
5	390.424	N.A	30.88	N.A	N.A	46.0	N.A	Vertical	Pass
6	683.117	N.A	29.53	N.A	N.A	46.0	N.A	Vertical	Pass



NO.	Fre.	Pk	QP	AV	Limit-	Limit-	Limit-	Antenna	Verdict
	(MHz)				PK	QP	AV		
1	138.853	N.A	34.40	N.A	N.A	43.5	N.A	Horizontal	Pass
2	288.828	N.A	40.25	N.A	N.A	46.0	N.A	Horizontal	Pass
3	361.397	N.A	36.66	N.A	N.A	46.0	N.A	Horizontal	Pass
4	500.793	N.A	28.85	N.A	N.A	46.0	N.A	Horizontal	Pass
5	692.793	N.A	36.68	N.A	N.A	46.0	N.A	Horizontal	Pass
6	1000.000	N.A	38.09	N.A	N.A	54.0	N.A	Horizontal	Pass

Test Result: PASS

**END OF REPORT **

Shenzhen Morlab Communications Technology Co., Ltd

Web site: http://www.morlab.cn/
Email: info sz@morlab.cn

Phone: +86 (0) 755 36698555

Fax: +86 (0) 755 36698525

Page 15 of 15