

FCC 47 CFR PART 15 SUBPART C CERTIFICATION TEST REPORT

For

WIRELESS CAMERA

MODEL No.: 92616A

FCC ID: 2ABFE-92616A

Trade Mark: N/A

REPORT NO.: ES160928014E

ISSUE DATE: October 28, 2016

Prepared for

General Sensing Systems LLC

250 CLEARBROOK RD STE 260, ELMSFORD, New York, United States 10523

Prepared by

EMTEK (SHENZHEN) CO., LTD

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China TEL: 86-755-26954280

FAX: 86-755-26954282



Report No.: ES160928014E Ver.1.0

TABLE OF CONTENTS

1	TE	ST RESULT CERTIFICATION	3
2		T TECHNICAL DESCRIPTION	
3		MMARY OF TEST RESULT	
4		ST METHODOLOGY	
	4.1 4.2 4.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	6
5	FA	CILITIES AND ACCREDITATIONS	8
	5.1 5.2	FACILITIESLABORATORY ACCREDITATIONS AND LISTINGS	8 8
6	TE	ST SYSTEM UNCERTAINTY	9
7	SE	ΓUP OF EQUIPMENT UNDER TEST	10
	7.1 7.2 7.3 7.4 7.5	RADIO FREQUENCY TEST SETUP 1 RADIO FREQUENCY TEST SETUP 2 CONDUCTED EMISSION TEST SETUP BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM SUPPORT EQUIPMENT	
8	TE	ST REQUIREMENTS	14
	8.1 8.2 8.3 8.4 8.5	DTS (6DB) BANDWIDTH	
	8.6 8.7	CONDUCTED EMISSIONS TESTANTENNA APPLICATION	
	J.,		



1 TEST RESULT CERTIFICATION

Applicant: General Sensing Systems LLC

250 CLEARBROOK RD STE 260, ELMSFORD, New York, United States 10523

Manufacturer: General Sensing Systems LLC

250 CLEARBROOK RD STE 260, ELMSFORD, New York, United States 10523

EUT Description: WIRELESS CAMERA

Model Number: 92616A

File Number: ES160928014E

Date of Test: October 08, 2016 to October 28, 2016

Measurement Procedure Used:

APPLICABLE STANDARDS					
STANDARD	TEST RESULT				
FCC 47 CFR Part 2, Subpart J	PASS				
FCC 47 CFR Part 15, Subpart C	PASS				

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report.

Date of Test :	October 08, 2016 to October 28, 2016
Prepared by :	Hoppingchen
Prepared by : Reviewer :	Hopping Chen/Editor
Reviewer :	Foe Xia
	Joe Xia/Supervisor
Approve & Authorized Signer :	
	Lisa Wang/Manager

TRF No: FCC 15.247/A Page 3 of 51 Report No.: ES160928014E Ver.1.0



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Device Type	Wifi 2.4G Device
IEEE 802.11 WLAN Mode Supported	⊠802.11b(20MHz bandwidth) ⊠802.11g(20MHz bandwidth) ⊠802.11n(20MHz bandwidth)
Data Rate	⊠802.11 b:1,2,5.5,11Mbps ⊠802.11 g:6,9,12,18,24,36,48,54Mbps ⊠802.11n(HT20):MCS0-MCS15
MIMO Mode	Not Support
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n
Operating Frequency Range	☐2412-2462MHz for 802.11b/g ☐2412-2462MHz for 802.11n(HT20)
Number of Channels	⊠11 channels for 802.11b/g ⊠11 channels for 802.11n(HT20)
Transmit Power Max	16.46dBm for 802.11b 14.15dBm for 802.11g 12.53dBm for 802.11/n(HT20)
Antenna Type	FPC antenna
Antenna Gain	0dBi
Power supply	DC 3.7V from lithium battery or DC 5V from USB port

Note: for more details, please refer to the User's manual of the EUT.

TRF No: FCC 15.247/A Page 4 of 51 Report No.: ES160928014E Ver.1.0



3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d)	Unwanted Emission Into Restricted Frequency Bands	PASS	
15.209	(conducted)		
15.247(d)	Radiated Spurious Emission	PASS	
15.209			
15.207	Conducted Emission Test	PASS	
15.203	Antenna Application	PASS	

NOTE1: N/A (Not Applicable)

NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ABFE-92616A filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

The system is compliance with Subpart B is authorized under a DOC procedure



4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards: FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 DTS Meas Guidance v03r05

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT	MFR	MODEL	SERIAL	LAST CAL.
TYPE	IVII TX	NUMBER	NUMBER	LAOT OAL.
ITPE		NUMBER	NUMBER	
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	May 29, 2016
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	May 28, 2016
50Ω Coaxial Switch	Anritsu	MP59B	M20531	May 29, 2016
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	May 28, 2016
Voltage Probe	Rohde & Schwarz	TK9416	N/A	May 28, 2016

4.2.2 Radiated Emission Test Equipment

EQUIPMENT	MFR	MODEL	SERIAL	LAST CAL.
TYPE		NUMBER	NUMBER	
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 29, 2016
Pre-Amplifier	HP	8447D	2944A07999	May 28, 2016
Bilog Antenna	Schwarzbeck	VULB9163	142	May 28, 2016
Loop Antenna	ARA	PLA-1030/B	1029	May 28, 2016
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	May 28, 2016
Horn Antenna	Schwarzbeck	BBHA 9120	D143	May 28, 2016
Cable	Schwarzbeck	AK9513	ACRX1	May 29, 2016
Cable	Rosenberger	N/A	FP2RX2	May 29, 2016
Cable	Schwarzbeck	AK9513	CRPX1	May 29, 2016
Cable	Schwarzbeck	AK9513	CRRX2	May 29, 2016

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	May 28, 2016
Signal Analyzer	Agilent	N9010A	My53470879	May 28, 2016
Power meter	Anritsu	ML2495A	0824006	May 28, 2016
Power sensor	Anritsu	MA2411B	0738172	May 28, 2016

Remark: Each piece of equipment is scheduled for calibration once a year.



4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (\boxtimes 802.11b: 1 Mbps; \boxtimes 802.11g: 6 Mbps; \boxtimes 802.11n (HT20): MCS0; \boxtimes 802.11n (HT20): MCS15)were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

☐ Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest F	Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
1	2412	6	2437	11	2462	



5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2013.10.29

The certificate is valid until 2016.10.28

The Laboratory has been assessed and proved to be in compliance with

CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)

The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2015.4

The Laboratory has been assessed according to the requirements

ISO/IEC 17025.

Accredited by FCC, July 06, 2016

The Certificate Registration Number is 406365.

Accredited by Industry Canada, November 24, 2015 The Certificate Registration Number is 4480A.

Name of Firm : SHENZHEN EMTEK CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone,

Nanshan District, Shenzhen, Guangdong, China

TRF No: FCC 15.247/A Page 8 of 51 Report No.: ES160928014E Ver.1.0



6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

apparatus.	
Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5℃
Humidity	±3%


Measurement Uncertainty for a level of Confidence of 95%



7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:

(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz




TRF No: FCC 15.247/A Page 10 of 51 Report No.: ES160928014E Ver.1.0



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz






7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.


Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.





7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
N/A	N/A	N/A	N/A	N/A	N/A	N/A

Notes:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



8 TEST REQUIREMENTS

8.1 DTS (6DB) BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r05

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.

8.1.5 Test Results

Temperature :	28℃	Humidity:	65 %
Antenna:	A	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (MHz)	Limit (kHz)	Verdict
	1	2412	9.41	500	PASS
⊠802.11b	6	2437	10.01	500	PASS
	11	2462	8.56	500	PASS
	1	2412	16.43	500	PASS
⊠802.11g	6	2437	16.42	500	PASS
	11	2462	16.39	500	PASS
⊠802.11n (HT20)	1	2412	17.72	500	PASS
	6	2437	17.70	500	PASS
	11	2462	17.72	500	PASS




DTS (6dB) Bandwidth
Test Model 802.11b

Channel 1: 2412MHz



Test Model DTS (6dB) Bandwidth 802.11b Channel 6: 2437MHz





Test Model DTS (6dB) Bandwidth 802.11b

Channel 11: 2462MHz





DTS (6dB) Bandwidth 802.11g

Channel 1: 2412MHz



Test Model

DTS (6dB) Bandwidth 802.11g

Channel 6: 2437MHz





DTS (6dB) Bandwidth Test Model

802.11g

Channel 11: 2462MHz





DTS (6dB) Bandwidth 802.11n (HT20) Channel 1: 2412MHz




Test Model

DTS (6dB) Bandwidth 802.11n (HT20) Channel 6: 2437MHz





DTS (6dB) Bandwidth 802.11n (HT20) Channel 11: 2462MHz





8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r05

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part15.247(b)(3)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The testing follows KDB 558074 and KDB662911 Measurement Guidelines.

The RF output of EUT was connected to the power meter by RF cable and attnuator. The path loss was compensated to the results for each measurement.

Set to the maximum output power setting and enable the EUT transmit continuously.

Measure the conducted output power with cable loss and record the results in the test report.

Measure and record the results in the report.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit=30-(Gain - 6)

8.2.5 Test Results

Temperature :	28℃	Humidity:	65 %
Antenna:	A	Test By:	King Kong

Operation	Channel	Channel	Measurement	Limit	Verdict
Mode	Number	Frequency (MHz)	Level (dBm)	(dBm)	verdict
	1	2412	16.46	30	PASS
⊠802.11b	6	2437	15.03	30	PASS
	11	2462	14.88	30	PASS
	1	2412	14.15	30	PASS
⊠802.11g	6	2437	13.54	30	PASS
	11	2462	12.65	30	PASS
⊠802.11n (HT20)	1	2412	12.53	30	PASS
	6	2437	12.32	30	PASS
(11120)	11	2462	12.16	30	PASS



8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r05

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz Set the VBW to: 10 kHz. Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain - 6)

8.3.5 Test Results

Temperature :	28℃	Humidity:	65 %
Antenna:	A	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
	1	2412	-12.651	8	PASS
⊠802.11b	6	2437	-15.479	8	PASS
	11	2462	-14.015	8	PASS
	1	2412	-18.212	8	PASS
⊠802.11g	6	2437	-20.646	8	PASS
	11	2462	-20.789	8	PASS
⊠802.11n (HT20)	1	2412	-21.185	8	PASS
	6	2437	-21.658	8	PASS
	11	2462	-22.190	8	PASS



Power Spectral Density
Test Model 802.11b

Channel 1: 2412MHz



Power Spectral Density
802.11b

Channel 6: 2437MHz





Power Spectral Density
Test Model 802.11b

Channel 11: 2462MHz





Power Spectral Density 802.11g

Channel 1: 2412MHz




Test Model

Power Spectral Density

802.11g

Channel 6: 2437MHz





Power Spectral Density


802.11g

Channel 11: 2462MHz






Power Spectral Density 802.11n (HT20) Channel 1: 2412MHz




Test Model

Power Spectral Density 802.11n (HT20) Channel 6: 2437MHz





Power Spectral Density 802.11n (HT20) Channel 11: 2462MHz





8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r05

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to \geq 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW =300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.4.5 Test Results

TRF No: FCC 15.247/A Page 29 of 51 Report No.: ES160928014E Ver.1.0



All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:











PSD(Power Spectral Density) RBW=100kHz

⊠802.11b □802.11g ☐802.11n(HT20)

☐802.11n(HT40)



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands ⊠802.11b 802.11n(HT20) ☐802.11n(HT40) **■**802.11g Channel 6: 2437MHz











Band edge ⊠802.11b

□802.11g

☐802.11n(HT20) ☐802.11n(HT40) ☐Channel 9: 2452MHz

Channel 11: 2462MHz





8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 DTS 01 Meas. Guidance v03r05

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

MHz	MHz	GHz
16.42-16.423	399.9-410	4.5-5.15
16.69475-16.69525	608-614	5.35-5.46
16.80425-16.80475	960-1240	7.25-7.75
25.5-25.67	1300-1427	8.025-8.5
37.5-38.25	1435-1626.5	9.0-9.2
73-74.6	1645.5-1646.5	9.3-9.5
74.8-75.2	1660-1710	10.6-12.7
123-138	2200-2300	14.47-14.5
149.9-150.05	2310-2390	15.35-16.2
156.52475-156.52525	2483.5-2500	17.7-21.4
156.7-156.9	2690-2900	22.01-23.12
162.0125-167.17	3260-3267	23.6-24.0
167.72-173.2	3332-3339	31.2-31.8
240-285	3345.8-3358	36.43-36.5
322-335.4	3600-4400	(2)
	16.42-16.423 16.69475-16.69525 16.80425-16.80475 25.5-25.67 37.5-38.25 73-74.6 74.8-75.2 123-138 149.9-150.05 156.52475-156.52525 156.7-156.9 162.0125-167.17 167.72-173.2 240-285	16.42-16.423 399.9-410 16.69475-16.69525 608-614 16.80425-16.80475 960-1240 25.5-25.67 1300-1427 37.5-38.25 1435-1626.5 73-74.6 1645.5-1646.5 74.8-75.2 1660-1710 123-138 2200-2300 149.9-150.05 2310-2390 156.52475-156.52525 2483.5-2500 156.7-156.9 2690-2900 162.0125-167.17 3260-3267 167.72-173.2 3332-3339 240-285 3345.8-3358

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	2400/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Remark :1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.

for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz])., the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.



8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

 $\overrightarrow{RBW} = 9kHz$

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.



8.5.5 Test Results

Spurious Emission below 30MHz (9KHz to 30MHz)

24℃ October 13, 2016 Temperature: Test Date:

Humidity: 53 % Test By: King Kong

Test mode: TX Mode

Freq.	Ant.Pol.		ssion BuV/m)	Limit 3m	(dBuV/m)	Over(dB)		
(MHz)	H/V	PK	AV	PK	AV	PK	AV	
					-	-	-	

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Temperature : 28℃ Test Date : October 13, 2016

Humidity: 65 % Test By: King Kong

Test mode: 802.11b Frequency: Channel 1: 2412MHz

Freq.	Ant.Po I.	Emission Lev	vel(dBuV/m)	Limit 3m((dBuV/m)	Over(dB)		
(MHz)	H/V	PK	AV	PK	AV	PK	AV	
9401.00	V	51.70	33.95	74.00	54.00	-22.30	-20.05	
12587.00	V	54.42	37.26	74.00	54.00	-19.58	-16.74	
17036.00	V	54.33	36.43	74.00	54.00	-19.67	-17.57	
						1		
						1		
8407.00	Н	50.55	30.10	74.00	54.00	-23.45	-23.90	
11009.00	Н	51.21	30.49	74.00	54.00	-22.79	-23.51	
14354.00	Н	51.58	34.12	74.00	54.00	-22.42	-19.88	

Temperature : 28℃ Test Date : October 13, 2016

Humidity: 65 % Test By: King Kong

Test mode: 802.11b Frequency: Channel 6: 2437MHz

Freq.	Ant.Po I.	Emission Lev	vel(dBuV/m)	Limit 3m	(dBuV/m)	Over(dB)		
(MHz)	H/V	PK	AV	PK	AV	PK	AV	
9523.00	V	51.99	34.03	74.00	54.00	-22.01	-19.97	
12600.00	V	54.55	37.33	74.00	54.00	-19.45	-16.67	
17013.00	V	54.54	36.53	74.00	54.00	-19.46	-17.47	
				-		-		
				1		1	-	
				1		1	-	
8431.00	Н	51.08	30.33	74.00	54.00	-22.92	-23.67	
11062.00	Н	51.95	34.33	74.00	54.00	-22.05	-19.67	
14591.00	Н	53.44	36.33	74.00	54.00	-20.56	-17.67	

Temperature : 28°C Test Date : October 13, 2016

Humidity: 65 % Test By: King Kong

Test mode: 802.11b Frequency: Channel 11: 2462MHz

Freq.	Ant.Pol.	Emission Lev	/el(dBuV/m)	Limit 3m	(dBuV/m)	Ove	er(dB)
(MHz)	H/V	PK	AV	PK	AV	PK	AV
10347.00	V	52.76	35.13	74.00	54.00	-21.24	-18.87
13716.00	V	54.57	37.03	74.00	54.00	-19.43	-16.97
17483.00	V	55.26	36.93	74.00	54.00	-18.74	-17.07
				-		-	-
				-		-	1
9556.00	Н	51.74	34.53	74.00	54.00	-22.26	-19.47
13653.00	Н	54.38	37.13	74.00	54.00	-19.62	-16.87
17464.00	Н	54.49	37.03	74.00	54.00	-19.51	-16.97

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b mode recorded was report as below:

Temperature : 28°C Test Date : October 13, 2016

Humidity: 65 % Test By: King Kong
Test mode: 802.11b Frequency: Channel 3: 2412MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2389.60	Н	58.13	74.00	40.10	54.00
2387.28	V	57.08	74.00	41.30	54.00

Temperature : 28° C Test Date : October 13, 2016

Humidity: 65 % Test By: King Kong

Test mode: 802.11b Frequency: Channel 9: 2462MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2484.03	Н	59.75	74.00	42.60	54.00
2483.68	V	59.47	74.00	43.50	54.00

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).


(2) Emission Level= Reading Level+Probe Factor +Cable Loss.


(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.




















53 %

■ Spurious Emission below 1GHz (30MHz to 1GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:



Limit: (RE)FCC PART 15 C

Mode:TX LOW

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		181.3200	33.78	-17.08	16.70	43.50	-26.80	QP			
2		253.1000	35.93	-13.25	22.68	46.00	-23.32	QP			
3		296.7500	36.98	-11.63	25.35	46.00	-20.65	QP			
4		579.9900	27.61	-6.16	21.45	46.00	-24.55	QP			
5		644.0100	27.11	-5.12	21.99	46.00	-24.01	QP			
6	*	792.4200	32.57	-2.83	29.74	46.00	-16.26	QP			


Power: AC 120V/50Hz

*:Maximum data x:Over limit !:over margin Operator:

TRF No: FCC 15.247/A Page 42 of 51 Report No.: ES160928014E Ver.1.0



53 %



Limit: (RE)FCC PART 15 C

Mode:TX LOW

Note:


No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	30.9700	37.48	-17.71	19.77	40.00	-20.23	QP			
2		103.7200	31.98	-15.29	16.69	43.50	-26.81	QP			
3		175.5000	32.12	-17.15	14.97	43.50	-28.53	QP			
4		395.6900	34.23	-9.51	24.72	46.00	-21.28	QP			
5		622.6700	27.61	-5.48	22.13	46.00	-23.87	QP			
6		792.4200	28.16	-2.83	25.33	46.00	-20.67	QP			

Power: AC 120V/50Hz

*:Maximum data x:Over limit !:over margin Operator:



53 %



Limit: (RE)FCC PART 15 C

Mode:TX MID Note:

Reading Correct Measure-Antenna Table No. Mk. Freq. Limit Over Level Factor Height Degree ment MHz dBuV dΒ dBuV/m dBuV/m dΒ Detector cm degree Comment 252.1300 37.41 -13.29 QP 1 24.12 46.00 -21.88


Power: AC 120V/50Hz

2 296.7500 37.82 -11.63 26.19 46.00 -19.81 QP 3 395.6900 30.25 -9.51 20.74 46.00 -25.26 QP 4 533.4300 27.32 -6.89 20.43 46.00 -25.57 QΡ 5 720.6400 28.53 24.64 46.00 -21.36 QP -3.89 792.4200 6 34.00 -2.8331.17 46.00 -14.83 QP

*:Maximum data x:Over limit !:over margin Operator:



53 %



Limit: (RE)FCC PART 15 C

Mode:TX MID

Note:


No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		181.3200	33.37	-17.08	16.29	43.50	-27.21	QP			
2		395.6900	32.46	-9.51	22.95	46.00	-23.05	QP			
3		507.2400	27.83	-7.31	20.52	46.00	-25.48	QP			
4		569.3200	27.39	-6.33	21.06	46.00	-24.94	QP			
5		643.0400	28.44	-5.14	23.30	46.00	-22.70	QP			
6	*	792.4200	32.52	-2.83	29.69	46.00	-16.31	QP			

Power: AC 120V/50Hz

*:Maximum data x:Over limit !:over margin Operator:



53 %



Limit: (RE)FCC PART 15 C

Mode:TX HIGH

Note:


No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		252.1300	36.15	-13.29	22.86	46.00	-23.14	QP			
2		296.7500	38.61	-11.63	26.98	46.00	-19.02	QP			
3		395.6900	29.44	-9.51	19.93	46.00	-26.07	QP			
4		499.4800	28.09	-7.44	20.65	46.00	-25.35	QP			
5		720.6400	28.86	-3.89	24.97	46.00	-21.03	QP			
6	*	792.4200	33.63	-2.83	30.80	46.00	-15.20	QP			

Power: AC 120V/50Hz

*:Maximum data x:Over limit !:over margin Operator:



53 %



Limit: (RE)FCC PART 15 C

Mode:TX HIGH

Note:

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		30.0000	38.34	-17.68	20.66	40.00	-19.34	QP			
2		395.6900	32.39	-9.51	22.88	46.00	-23.12	QP			
3		542.1600	27.70	-6.76	20.94	46.00	-25.06	QP			
4		592.6000	28.14	-5.96	22.18	46.00	-23.82	QP			
5		660.5000	27.37	-4.84	22.53	46.00	-23.47	QP			
6	*	792.4200	32.38	-2.83	29.55	46.00	-16.45	QP			

Power: AC 120V/50Hz

*:Maximum data x:Over limit !:over margin Operator:



8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Conducted Emission Limit								
Frequency(MHz)	Quasi-peak	Average						
0.15-0.5	66-56	56-46						
0.5-5.0	56	46						
5.0-30.0	60	50						

Note: 1. The lower limit shall apply at the transition frequencies

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results


Pass

We test the EUT at all modes 2.4G 802.11b/g/n, and show the worst result as bellow.

^{2.} The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.



55 %



Power: AC 120V/60Hz

Site Conduction #1

Limit: (CE)FCC PART 15 class B_QP


Mode: TX Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1600	44.04	0.00	44.04	65.46	-21.42	QP	
2		0.1600	28.27	0.00	28.27	55.46	-27.19	AVG	
3		0.2750	40.21	0.00	40.21	60.97	-20.76	QP	
4		0.2750	26.46	0.00	26.46	50.97	-24.51	AVG	
5		0.3250	37.98	0.00	37.98	59.58	-21.60	QP	
6		0.3250	25.85	0.00	25.85	49.58	-23.73	AVG	
7		0.6400	42.24	0.00	42.24	56.00	-13.76	QP	
8	*	0.6400	33.03	0.00	33.03	46.00	-12.97	AVG	
9		1.1655	31.44	0.00	31.44	56.00	-24.56	QP	
10		1.1655	20.49	0.00	20.49	46.00	-25.51	AVG	
11		12.1750	33.84	0.00	33.84	60.00	-26.16	QP	
12		12.1750	18.08	0.00	18.08	50.00	-31.92	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: JLH



55 %



Power: AC 120V/60Hz

Limit: (CE)FCC PART 15 class B_QP

Mode: TX Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBu∀	dB	Detector	Comment
1	0.1600	44.21	0.00	44.21	65.46	-21.25	QP	
2	0.1600	28.42	0.00	28.42	55.46	-27.04	AVG	
3	0.3500	43.10	0.00	43.10	58.96	-15.86	QP	
4	0.3500	27.81	0.00	27.81	48.96	-21.15	AVG	
5 *	0.6350	46.64	0.00	46.64	56.00	-9.36	QP	
6	0.6350	33.61	0.00	33.61	46.00	-12.39	AVG	
7	1.0450	36.47	0.00	36.47	56.00	-19.53	QP	
8	1.0450	24.29	0.00	24.29	46.00	-21.71	AVG	
9	8.0500	32.76	0.00	32.76	60.00	-27.24	QP	
10	8.0500	19.90	0.00	19.90	50.00	-30.10	AVG	
11	19.6500	40.88	0.00	40.88	60.00	-19.12	QP	
12	19.6500	25.92	0.00	25.92	50.00	-24.08	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: JLH



8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement				
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.				

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 **Result**

PASS.

Т	he EU	Γ has 1 FPC Antenna for wifi 2.4G, the gain is 0 dBi;
Note:		Antenna use a permanently attached antenna which is not replaceable. Not using a standard antenna jack or electrical connector for antenna replacement The antenna has to be professionally installed (please provide method of installation)
	which	in accordance to section 15.203, please refer to the internal photos.