

FCC PART 15, CLASS B TEST REPORT

For

Conplex International Limited

Unit 902-904, 9th Floor, Tower B, Hung Hom Commercial Centre, 37, Ma Tau Wai Road. Hung Hum, Kowloon, HongKong.

FCC ID: 2ABGBJP5151

Report Type: Original Report		Product Type: 2G Feature Phone	
Test Engineer:	Simon Wang	Simon	wang
Report Number:	RSZ150114002	-00A	
Report Date:	2015-01-21		
Reviewed By:	Jimmy Xiao RF Engineer	Jimm	y xiao
Prepared By:	Bay Area Comp 6/F, the 3rd Pha	3320018 3320008	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION	4
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
External I/O Cable	
EUT	
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	7
APPLICABLE STANDARD	7
MEASUREMENT UNCERTAINTY	7
EUT SETUP	
EMI TEST RECEIVER SETUP	8
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
CORRECTED FACTOR & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	9
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	12
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP	
EMI TEST RECEIVER SETUP	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS.	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
Test Data	14

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Conplex International Limited*'s product, model number: *JP 5151 (FCC ID: 2ABGBJP5151)* or the "EUT" in this report was a *2G Feature Phone*, which was measured approximately: 12.4 cm (L) x 6.5 cm (W) x 0.85 cm (H), rated with input voltage: DC 3.7 V rechargeable Li-ion battery or DC5.0 V from adapter. The highest operating frequency is 312MHz.

Report No.: RSZ150114002-00A

Adapter Information: Model: JV X57

Input: AC100-300V, 50/60Hz, 150 mA

Output: DC 5.0V, 600mA

Note: The serial models JP 5151, JP 4242, JP 4251 share the same schematics, they are different in storage area, the details was explained in the attached product similarity declaration letter provided and guaranteed by applicant. Model JP 5151 was selected for testing.

*All measurement and test data in this report was gathered from production sample serial number: 1501193 (Assigned by Shenzhen BACL). The EUT supplied by the applicant was received on 2015-01-14.

Objective

This test report is prepared on behalf of *Conplex International Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 22H/24E PCE submissions with ID: 2ABGBJP5151

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15, Class B Page 3 of 16

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Downloading (data transfer with computer)

EUT Exercise Software

"BurnIn test v5.3" exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Mouse	MOC5UO	G1900NKD
SAST	Modem	AEM-2100	0293
Kingston	Micro SD card	4GB	N/A

Report No.: RSZ150114002-00A


FCC Part 15, Class B Page 4 of 16

External I/O Cable

Cable Description	Length (m)	From/Port	То
Shielding Detachable K/B Cable	1.5	Host PC	Keyboard
Shielding Detachable Mouse Cable	1.5	Host PC	Mouse
Shielding Detachable Serial Cable	1.5	Host PC	Modem
Shielding Detachable VGA Cable	1.5	Host PC	Monitor
Shielding Detachable RS232 Cable	1.0	Host PC	EUT
Un-shielding Detachable USB Cable	1.1	EUT	PC

Block Diagram of Test Setup

For conducted emission



FCC Part 15, Class B Page 5 of 16

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance

Report No.: RSZ150114002-00A

FCC Part 15, Class B Page 6 of 16

FCC §15.107 - AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.107

Measurement Uncertainty


Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Report No.: RSZ150114002-00A

Port	Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2009. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

The host PC was connected to a 120 VAC/60 Hz power source.

FCC Part 15, Class B Page 7 of 16

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Report No.: RSZ150114002-00A

Test Procedure

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2014-06-03	2015-06-03
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2014-06-09	2015-06-09
Rohde & Schwarz	LISN	ESH2-Z5	892107/021	2014-06-09	2015-06-09
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2014-05-14	2015-05-14
Rohde & Schwarz	CE Test software	EMC 32	V8.53		

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15, Class B Page 8 of 16

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107, with the worst margin reading of:

4.4 dB at 18.823610 MHz in the Line conducted mode

Report No.: RSZ150114002-00A

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	22 ℃
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2015-01-20


FCC Part 15, Class B Page 9 of 16

EUT Operation Mode: Downloading

AC 120V/60 Hz, Line

EMI Auto Test L

Report No.: RSZ150114002-00A




Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
5.841110	26.8	19.5	60.0	33.2	QP
5.841110	25.0	19.5	50.0	25.0	Ave.
12.724070	41.1	19.7	60.0	18.9	QP
12.724070	37.7	19.7	50.0	12.3	Ave.
12.784770	41.3	19.7	60.0	18.7	QP
12.784770	37.0	19.7	50.0	13.0	Ave.
17.684190	46.8	19.7	60.0	13.2	QP
17.684190	42.5	19.7	50.0	7.5	Ave.
18.823610	50.1	19.7	60.0	9.9	QP
18.823610	45.6	19.7	50.0	4.4	Ave.
19.406590	49.0	19.7	60.0	11.0	QP
19.406590	44.4	19.7	50.0	5.6	Ave.

FCC Part 15, Class B Page 10 of 16

AC 120V/60 Hz, Neutral

EMI Auto Test N

Report No.: RSZ150114002-00A



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
12.682150	41.8	19.7	60.0	18.2	QP
12.682150	38.1	19.7	50.0	11.9	Ave.
17.524790	45.8	19.7	60.0	14.2	QP
17.524790	41.1	19.7	50.0	8.9	Ave.
19.089610	48.4	19.7	60.0	11.6	QP
19.089610	43.7	19.7	50.0	6.3	Ave.
19.410530	49.5	19.6	60.0	10.5	QP
19.410530	45.1	19.6	50.0	4.9	Ave.
24.661070	41.3	19.7	60.0	18.7	QP
24.661070	38.0	19.7	50.0	12.0	Ave.
28.492150	40.0	19.8	60.0	20.0	QP
28.492150	35.0	19.8	50.0	15.0	Ave.

Note:

FCC Part 15, Class B Page 11 of 16

¹⁾ Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation The corrected factor has been input into the transducer of the test software.

²⁾ Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit – Corrected Amplitude

FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §15.109

Measurement Uncertainty


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Report No.: RSZ150114002-00A

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report

Frequency	Polarity	Measurement uncertainty
30 MHz~200 MHz	Horizontal	4.62 dB (k=2, 95% level of confidence)
30 MHZ~200 MHZ	Vertical	4.54 dB (k=2, 95% level of confidence)
200 MHz∼1 GHz	Horizontal	4.84 dB (k=2, 95% level of confidence)
200 MHZ~1 GHZ	Vertical	5.91 dB (k=2, 95% level of confidence)
1 GHz~6 GHz	Horizontal/Vertical	4.68 dB (k=2, 95% level of confidence)
Above 6 GHz	Horizontal/Vertical	4.92 dB (k=2, 95% level of confidence)

EUT Setup



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15.109 Class B limits.

FCC Part 15, Class B Page 12 of 16

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Report No.: RSZ150114002-00A

The spacing between the peripherals was 10 cm.

The host PC was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 2 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector	
30 MHz – 1000 MHz	Hz – 1000 MHz 100 kHz 3		120 kHz	QP	
Above 1 GHz	1MHz	3 MHz	/	PK	
	1MHz	10 Hz	/	Ave.	

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date	
HP	Amplifier	8447E	1937A01046	2014-05-06	2015-05-06	
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2014-11-03	2015-11-03	
Sunol Sciences	Broadband Antenna	ЈВ3	A111513	2014-06-18	2017-06-17	
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2015-02-10	
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-08-22	2015-08-22	
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2014-04-23	2015-04-23	
TDK	Chamber	Chamber A	2#	2012-10-15	2015-10-15	
TDK	Chamber	Chamber B	1#	2012-07-23	2015-07-22	
R&S	Auto test Software	EMC32	V9.10	-	-	

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC Part 15, Class B Page 13 of 16

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: RSZ150114002-00A

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, with the worst margin reading of:

13.73 dB at 30.495750 MHz in the Vertical polarization mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	21 ℃		
Relative Humidity:	52 %		
ATM Pressure:	101.0 kPa		

The testing was performed by Simon Wang on 2015-01-21

FCC Part 15, Class B Page 14 of 16

30 MHz - 2.0 GHz

Frequency (MHz)	Receiver			Rx Antenna		Corrected	Corrected	FCC Part 15B	
	Reading (dBµV)	Detector (PK/QP/Ave.)	Turntable Degree	Height (m)	Polar (H/V)	Factor	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.495750	32.57	QP	101	1.9	V	-6.3	26.27	40.00	13.73
59.886500	36.16	QP	67	3.9	Н	-19.8	16.36	40.00	23.64
71.960875	31.97	QP	176	1.3	V	-19.6	12.37	40.00	27.63
72.126875	30.48	QP	239	1.2	V	-19.6	10.88	40.00	29.12
168.005750	39.40	QP	135	1.1	V	-14.4	25.00	43.50	18.50
192.021750	39.20	QP	78	2.0	Н	-14.9	24.30	43.50	19.20
1178.0	56.52	PK	343	1.8	Н	-0.58	55.94	74.00	18.06
1178.0	29.96	Ave.	343	1.8	Н	-0.58	29.38	54.00	24.62
1457.2	43.27	PK	168	1.5	V	0.74	44.01	74.00	29.99
1457.2	26.01	Ave.	168	1.5	V	0.74	26.75	54.00	27.25

Report No.: RSZ150114002-00A

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit Corrected Amplitude

FCC Part 15, Class B Page 15 of 16

PRODUCT SIMILARITY DECLARATION LETTER



Sourcing the best for the future Conplex International Limited Unit902-904,9th Floor, Tower B, Hung Hom Commercial Centre, 37, Ma Tau Wai

Road Hung Hum, Kowloon, Hong Kong

Tel: 86-755-29081966

2015/01/20

Product Similarity Declaration

To Whom It May Concern,

We, Conplex International Limited, hereby declare that our 2G feature phone, Model Number: JP 5151, JP 4242, and JP 4251 are electrically identical with the model number JP 5151 that was tested by BACL. They are just different in model numbers and Appearance colors.

Report No.: RSZ150114002-00A

Please contact me if you have any question.

Signature:

Hugo Zhai

Project Manager

For and an behalf of COMPLEX INTERNATIONAL LIMITED 港 战 網 综 布 現 公 司

de de de de

***** END OF REPORT *****

FCC Part 15, Class B Page 16 of 16