# Matsunichi Digital Technology (Hong **Kong) Limited**

# **MID**

Main Model: T-101 Serial Model: N/A

**December 02, 2013 Report No.: 13070542-FCC-E1** (This report supersedes NONE)



**Modifications made to the product: None** 

This Test Report is Issued Under the Authority of: Kahn Yang

Kahn Yang Alex Liu **Compliance Engineer Technical Manager** 



This test report may be reproduced in full only. Test result presented in this test report is applicable to the representative sample only.





Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 2 of 38

vww siemic com c

# **Laboratory Introduction**

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the <u>global markets</u>.

SIEMIC (Shenzhen-China) Laboratories Accreditations for Conformity Assessment

Country/Region Scope		
USA	EMC, RF/Wireless, Telecom	
Canada	EMC, RF/Wireless, Telecom	
Taiwan	EMC, RF, Telecom, Safety	
Hong Kong	RF/Wireless ,Telecom	
Australia	EMC, RF, Telecom, Safety	
Korea	EMI, EMS, RF, Telecom, Safety	
Japan	EMI, RF/Wireless, Telecom	
Singapore	EMC, RF, Telecom	
Europe	EMC, RF, Telecom, Safety	



Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 3 of 38

This page has been left blank intentionally.

Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 4 of 38

# **CONTENTS**

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
AN.	NEX A. TEST INSTRUMENTATION & GENERAL PROCEDURES	14
AN.	NEX B. EUT AND TEST SETUP PHOTOGRAPHS	19
AN.	NEX C. TEST SETUP AND SUPPORTING EQUIPMENT	33
AN.	NEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	37
AN.	NEX E. DECLARATION OF SIMILARITY	38



Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 5 of 38

# 1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the Matsunichi Digital Technology (Hong Kong) Limited, MID and Model: T-101 against the current Stipulated Standards. The MID has demonstrated compliance with the FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009.

### **EUT Information**

**EUT** 

**Description** 

: MID

Main Model : T-101

Serial Model N/A

UMTS-FDD Band V/GPRS850: 0.9dBi

Antenna Gain : UMTS-FDD Band II/GPRS1900: 0.6dBi

Bluetooth: 1.9dBi

WIFI: 1.9dBi

**Battery:** 

Model: 3655148/7000mAh/3.7V

Spec: 3.7V 7000mAh

Input Power : Limited charger voltage: 4.2V

Adapter:

Model: CYSG10-050200-U

Input: AC 100-240V 50/60Hz 0.5A

Output: DC 5V 2A

Classification

Per Stipulated : Class B Emission Product Per

Test Standard FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009

Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 6 of 38

# 2 TECHNICAL DETAILS

	TECHNICIAE DETITIES			
Purpose	Compliance testing of MID with stipulated standards			
Applicant / Client	Matsunichi Digital Technology (Hong Kong) Limited 20/F, York House, The, Landmark 15 Queens Road Central, Hong Kong			
Manufacturer	Matsunichi Digital Technology (Hong Kong) Limited 20/F, York House, The, Landmark 15 Queens Road Central, Hong Kong			
Laboratory performing the tests	SIEMIC (Shenzhen-China) Laboratories Zone A, Floor 1, Building 2, Wan Ye Long Technology Park, South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong, China Tel: +86-0755-2601 4629 / 2601 4953 Fax: +86-0755-2601 4953-810 Email: China@siemic.com.cn			
Test report reference number	13070542-FCC-E1			
Date EUT received	November 19, 2013			
Standard applied	FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009			
Dates of test (from – to)	November 20 to November 29, 2013			
No of Units	#1			
<b>Equipment Category</b>	JBC			
Trade Name	N/A			
RF Operating Frequency (ies)	GPRS850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz GPRS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz 802.11b/g/n(20M): 2412-2462 MHz Bluetooth: 2402-2480 MHz			
Number of Channels	299CH (GPRS1900) and 124CH (GPRS850)  UMTS-FDD Band V: 102CH  UMTS-FDD Band II: 277CH  Bluetooth: 79CH  802.11b/g/n: 11CH			
Modulation	GPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS/OFDM Bluetooth: GFSK& π/4DQPSK&8DPSK			
GPRS Multi-slot class	8/10/12			
FCC ID	2ABGI-T-101			



Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 7 of 38

# **MODIFICATION**

**NONE** 

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 8 of 38

# 4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

### **Class B Emission Product**

**Test Results Summary** 

Emissions					
Test Standard	Description	Product Class	Pass / Fail		
FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009	Conducted Emissions	See Above	Pass		
FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009	Radiated Emissions	See Above	Pass		

All measurement uncertainty is not taken into consideration for all presented test result.

Issue Date: December 02, 2013
Page: 9 of 38

# 5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

# **5.1 Conducted Emissions Test Result**

#### *Note:*

- 1. All possible modes of operation were investigated. Only the several worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. <u>Conducted Emissions Measurement Uncertainty</u>

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz - 30MHz (Average & Quasi-peak) is  $\pm 3.86dB$ .

4. Environmental Conditions Temperature 23°C

Relative Humidity 50%

Atmospheric Pressure 1011mbar

5. Test date: November 22, 2013


Tested By: Kahn Yang

**Test Result: Pass** 

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 10 of 38

Test Mode: Charging & Downloading

Peak Detector Quasi Peak Limit Average Detector Average Limit



### Test Data

# Phase Line Plot at 120V AC, 60Hz

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
0.30	46.42	60.24	-13.82	29.76	50.24	-20.48	10.10
0.75	45.82	56.00	-10.18	42.45	46.00	-3.55	10.10
0.52	38.92	56.00	-17.08	26.70	46.00	-19.30	10.10
1.23	40.57	56.00	-15.43	25.85	46.00	-20.15	10.10
1.09	34.19	56.00	-21.81	24.55	46.00	-21.45	10.10
3.50	38.43	56.00	-17.57	30.90	46.00	-15.10	10.15


Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 11 of 38

Test Mode: Charging & Downloading

Peak Detector

Average Detector

Quasi Peak Limit
Average Limit



## Test Data

# Phase Natural Plot at 120V AC, 60Hz

Frequency (MHz)	Quasi Peak (dBuV)	Limit (dBuV)	Margin (dB)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Factors (dB)
0.50	38.78	56.00	-17.22	19.18	46.00	-26.82	10.10
1.15	36.08	56.00	-19.92	19.83	46.00	-26.17	10.10
0.68	36.28	56.00	-19.72	22.64	46.00	-23.36	10.10
1.09	41.11	56.00	-14.89	29.82	46.00	-16.18	10.10
1.58	37.65	56.00	-18.35	25.05	46.00	-20.95	10.10
3.98	37.63	56.00	-18.37	29.01	46.00	-16.99	10.17

# **5.2** Radiated Emissions Test Result

#### *Note:*

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.

2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.

3. <u>Radiated Emissions Measurement Uncertainty</u>

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30 MHz - 1 GHz (QP only @ 3m & 10m) is +6 dB/-6 dB (for EUTs < 0.5 m X 0.5m).

4. Environmental Conditions Temperature 23°C Relative Humidity 50%

Atmospheric Pressure 1011mbar


5. Test date: November 22, 2013 Tested By: Kahn Yang

**Test Result: Pass** 

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 13 of 38 www.siemic.com.cn

Test Mode: Charging & Downloading

## **Below 1GHz**



Test Data

Frequency (MHz)	Quasi Peak (dBuV/m)	Azimuth	Polarity(H/ V)	Height (cm)	Factors (dB)	Limit (dBuV)	Margin (dB)
827.77	29.47	221.00	Н	331.00	3.84	46.00	-16.53
232.42	33.43	86.00	Н	132.00	-7.65	46.00	-12.57
199.80	29.77	98.00	Н	141.00	-8.13	43.52	-13.75
331.89	28.04	68.00	Н	102.00	-5.51	46.00	-17.96
166.46	26.64	100.00	Н	163.00	-8.39	43.52	-16.88
276.98	20.44	44.00	Н	126.00	-7.01	46.00	-25.56

Note: The data above 1 GHz which below 20 dB to the limit was not recorded.

Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 14 of 38

# Annex A. TEST INSTRUMENTATION & GENERAL PROCEDURES

# **Annex A. i. TEST INSTRUMENTATION**


Instrument	Model	Serial #	Calibration Date	Calibration Due Date
AC Line Conducted Emissions				
EMI test receiver	ESL6	100262	11/19/2013	11/18/2014
Line Impedance Stabilization Network	LI-125A	191106	11/14/2013	11/13/2014
Line Impedance Stabilization Network	LI-125A	191107	11/14/2013	11/13/2014
Transient Limiter	LIT-153	531118	03/03/2013	03/02/2014
Radiated Emissions				
EMI test receiver	ESL6	100262	11/19/2013	11/18/2014
Positioning Controller	UC3000	MF78020828 2	11/19/2013	11/18/2014
OPT 010 AMPLIFIER(0.1- 1300MHz)	8447E	2727A02430	11/19/2013	11/18/2014
Microwave Preamplifier(0.5~ 18GHz)	PAM-118	443008	11/08/2013	11/07/2014
Bilog Antenna (30MHz~6GHz)	JB6	A110712	01/27/2013	01/26/2014
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	071283	11/20/2013	11/19/2014

### Annex A. ii. AC LINE CONDUCTED EMISSIONS TEST DESCRIPTION

#### **Test Set-up**

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
- 2. The power supply for the EUT was fed through a  $50\Omega/50\mu$ H EUT LISN, connected to filtered mains.
- 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.

4. All other supporting equipments were powered separately from another main supply.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration1

#### **Test Method**

- 1. The EUT was switched on and allowed to warm up to its normal operating condition.
- 2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
- 3. High peaks, relative to the limit line, were then selected.
- 4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
- 5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

#### **Description of Conducted Emission Program**

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the common scan range from 150 kHz to 30 MHz; the program will first start a peak and average scan on selectable measurement time and step size. After the program complete the pre-scan, this program will perform the Quasi Peak and Average measurement, based on the pre-scan peak data reduction result.

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 16 of 38

## **Sample Calculation Example**

At 20 MHz  $limit = 250 \mu V = 47.96 dB\mu V$ 

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver =  $40.00 \text{ dB}\mu\text{V}$  (Calibrated for system losses)

Therefore, Q-P margin = 47.96 - 40.00 = 7.96 i.e. **7.96 dB below limit** 

## Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION


#### **EUT Characterization**

EUT characterisation, over the frequency range from 30MHz to 10<sup>th</sup> Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8 m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred; clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) or 3m EMC chamber.

#### **Test Set-up**

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5mX1.0mX0.8m high, non-conductive table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration2

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 18 of 38

www.siemic.com.cn

#### Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

#### Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on an open test site. As the same purpose, for emission frequencies measured above 1GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1GHz, set the spectrum analyzer on a 100kHz and 1MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
- 5. Repeat step 4 until all frequencies need to be measured was complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Band (MHz) Function Resolution bandwidth		Video Bandwidth
30 to 1000	Peak	100kHz	100kHz
Above 1000	Peak	1MHz	1MHz
Above 1000	Average	1MHz	10Hz

### **Sample Calculation Example**

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any) And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz, VBW = 10Hz.

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1GHz. And the measuring instrument is set to quasi peak detector function.

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 19 of 38

# Annex B. EUT AND TEST SETUP PHOTOGRAPHS

# Annex B. i. Photograph 1: EUT External Photo



Whole Package - Top View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 20 of 38 www.siemic.com.cn



EUT - Front View



EUT - Rear View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 21 of 38 www.siemic.com.cn




EUT - Top View



EUT - Bottom View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 22 of 38 www.siemic.com.cn



EUT - Left View



EUT - Right View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 23 of 38 www.siemic.com.cn

# Annex B.ii. Photograph 2: EUT Internal Photo



Cover Off - Front View 1



Cover Off - Front View 2

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 24 of 38




Adapter - Top View



Battery - Top View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 25 of 38



Battery - Bottom View




**EUT- Uncover Front View** 

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 26 of 38



Main board With Shielding - Top View




Main board - Bottom View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 27 of 38




Main board Without Shielding - Bottom View



Connect board - Top View



Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 28 of 38 www.siemic.com.cn




 $Connect\ board-Bottom\ View$ 




LCD - Top View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 29 of 38 www.siemic.com.cn




LCD - Bottom View



Bluetooth / BLE / WIFI Antenna View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 30 of 38 www.siemic.com.cn




GSM / PCS/ UMTS Antenna View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 31 of 38

# Annex B.iii. Photograph 3: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 32 of 38 www.siemic.com.cn



Radiated Spurious Emissions Test Setup Below 1GHz - Front View



Radiated Spurious Emissions Test Setup Above 1GHz -Front View

Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 33 of 38

www.siemic.com.cn

# Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


# **EUT TEST CONDITIONS**

## Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION


The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
Lenovo Laptop	E40& 0579A52	N/A

# **Block Configuration Diagram for Conducted Emissions Mode: Charging & Downloading**



# **Block Configuration Diagram for Radiated Emissions Mode: Charging & Downloading**



Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 36 of 38

# Annex C. ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions	Charging & Downloading

Report No.: 13070542-FCC-E1 Issue Date: December 02, 2013 Page: 37 of 38

# Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment



Report No.: 13070542-FCC-E1
Issue Date: December 02, 2013
Page: 38 of 38

# **Annex E. DECLARATION OF SIMILARITY**

N/A