FCC Test Report

Report No.: AGC05322151101FE03

FCC ID : 2ABH3-DV5XXX

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: DVD Stereo

BRAND NAME: Furrion

MODEL NAME : DV5700, DV5XXX

CLIENT : Furrion Ltd.

DATE OF ISSUE : Nov.23,2015

STANDARD(S)

TEST PROCEDURE(S)

: FCC CFR Title 47 Part 15 Subpart C Section15.249:2015

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report No.: AGC05322151101FE03 Page 2 of 50

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov.23,2015	Valid	Original Report

TABLE OF CONTENTS

1.	VERIFICATION OF CONFORMITY	4
2.	GENERAL INFORMATION	5
	2.1. PRODUCT DESCRIPTION	5
	2.2. TABLE OF CARRIER FREQUENCYS	5
3.	MEASUREMENT UNCERTAINTY	6
4.	DESCRIPTION OF TEST MODES	6
5.	SYSTEM TEST CONFIGURATION	7
	5.1. CONFIGURATION OF EUT SYSTEM	7
	5.2. EQUIPMENT USED IN EUT SYSTEM	7
	5.3. SUMMARY OF TEST RESULTS	7
6.	TEST FACILITY	8
7.	ALL TEST EQUIPMENT LIST	8
8.	RADIATED EMISSION	9
	8.1TEST LIMIT	9
	8.2. MEASUREMENT PROCEDURE	10
	8.3. TEST SETUP	12
	8.4. TEST RESULT	14
9.	BAND EDGE EMISSION	27
	9.1. MEASUREMENT PROCEDURE	27
	9.2 TEST SETUP	27
	9.3 RADIATED TEST RESULT	28
10	D. 20DB BANDWIDTH	32
	10.1. MEASUREMENT PROCEDURE	32
	10.2. TEST SET-UP	32
	10.3. LIMITS AND MEASUREMENT RESULTS	32
11	1. FCC LINE CONDUCTED EMISSION TEST	39
	11.1. LIMITS OF LINE CONDUCTED EMISSION TEST	39
	11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	39
	11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	40
	11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	40
	11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	40
A	PPENDIX A: PHOTOGRAPHS OF TEST SETUP	41
ΔΙ	PPENDIX B. PHOTOGRAPHS OF FUT	42

Page 4 of 50

1. VERIFICATION OF CONFORMITY

Applicant	Furrion Ltd.		
Address	Units 1603-05, 16/F, Pacific Plaza, 410 Des Voeux Road West, Sai Wan, Hong Kong		
Manufacturer	Furrion Ltd.		
Address	Units 1603-05, 16/F, Pacific Plaza, 410 Des Voeux Road West, Sai Wan, Hong Kong		
Product Designation	DVD Stereo		
Brand Name	Furrion		
Test Model	DV5700		
Series Model	DV5XXX(where X represents 0-9 or A-Z)		
Difference description	All the same except for the outlook of panel 1. Different color of panel. 2. Different outlook of buttons. 3. Location of part buttons on the panel is slightly different.		
Date of test	Nov.19,2015 to Nov.23,2015		
Deviation	None		
Condition of Test Sample	Normal		
Report Template	AGCRT-US-BR/RF		

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested By	Time Huang	
,	Time Huang(Huang Nanhui)	Nov.23,2015
Reviewed By	Forest ce	
	Forrest Lei(Lei Yonggang)	Nov.23,2015
Approved By	Solya Hang	
	Solger Zhang(Zhang Hongyi)	Nov.23,2015

Page 5 of 50

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	1.30dBm(Max)
Bluetooth Version	V2.1+EDR
Modulation	GFSK, π /4-DQPSK, 8DPSK
Number of channels	79
Hardware Version	2.1
Software Version	2.1
Antenna Designation	Fixed Antenna (Met 15.203 Antenna requirement)
Antenna Gain	0dBi
Power Supply	DC 12V

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency	
	0	2402MHZ	
	1	2403MHZ	
	:	:	
	38	2440 MHZ	
2400~2483.5MHZ	39	2441 MHZ	
	40	2442 MHZ	
	:	:	
	77	2479 MHZ	
	78	2480 MHZ	

Report No.: AGC05322151101FE03 Page 6 of 50

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y $\pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 % \circ

No.	Item	Uncertainty
1	Conducted Emission Test	±3.18dB
2	All emissions,radiated	±3.91dB
3	Temperature	±0.5°C
4	Humidity	±2%

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel π /4-DQPSK
5	Middle channel π /4-DQPSK
6	High channel π /4-DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	BT Link

Page 7 of 50

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	DVD Stereo	Furrion	DV5700	EUT
2	Control box	N/A	N/A	A.E
3	PC	SONY	E1412AYCW	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	N/A
N/A	BANDWITH	Compliant

Note: N/A means not applicable.

Page 8 of 50

6. TEST FACILITY

Site Dongguan Precise Testing Service Co., Ltd.	
Location Building D,Baoding Technology Park,Guangming Road2,Dongcheng Distri Dongguan, Guangdong, China,	
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site						
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration	
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016	
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016	
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016	
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016	
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016	
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A	
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016	
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016	

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

	Radiat	ed Emission Tes	t Site		
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full MF-7802		MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016

Page 9 of 50

8. RADIATED EMISSION

8.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental	Field Strength of Harmonics			
	(millivolts/meter)	(microvolts/meter)			
900-928MHz	50	500			
2400-2483.5MHz	50	500			
5725-5875MHz	50	500			
24.0-24.25GHz	250	2500			

Standard FCC 15.209

Frequency	Distance	Field Strengths Limit					
(MHz)	Meters	μ V/m	dB(μV)/m				
0.009 ~ 0.490	300	2400/F(kHz)					
0.490 ~ 1.705	30	24000/F(kHz)					
1.705 ~ 30	30	30					
30 ~ 88	3	100	40.0				
88 ~ 216	3	150	43.5				
216 ~ 960	3	200	46.0				
960 ~ 1000	3	500	54.0				
Above 1000	3	Other:74.0 dB(µV)/m (Peak) 54.0 dB(µV)/m (Ave					

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Page 10 of 50

8.2. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1.5MHz VBW and RBW for peak reading. Then 1.5MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Report No.: AGC05322151101FE03 Page 11 of 50

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting					
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP					
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP					
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP					
Start ~Stop Frequency	1GHz~26.5GHz 1.5MHz/1.5MHz for Peak, 1.5MHz/10Hz for Average					

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP


Page 12 of 50

8.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz



Page 13 of 50

RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Page 14 of 50

8.4. TEST RESULT


(Worst modulation:GFSK)

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 22.7
Limit: FCC Class B 3M Radiation Power: Humidity: 53.9 %

Distance: 3m

EUT: DVD Stereo M/N: DV5700


Mode: Low Channel TX

Note:

	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
			MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
	1		122.1500	23.83	12.22	36.05	43.50	-7.45	peak			
ſ	2		298.3666	24.06	15.36	39.42	46.00	-6.58	peak			
	3	*	416.3833	20.76	19.57	40.33	46.00	-5.67	peak			
	4		490.7500	15.41	21.03	36.44	46.00	-9.56	peak			
	5		675.0498	13.62	24.52	38.14	46.00	-7.86	peak			
	6		880.3667	10.21	28.10	38.31	46.00	-7.69	peak			

Page 15 of 50

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1

M/N: DV5700

Limit: FCC Class B 3M Radiation

EUT: DVD Stereo

Mode: Low Channel TX

Note:

Polarization:	Vertical	Temperature: 22.				
Power:		Humidity:	53.9 %			

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment	
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree		
1		122.1500	19.19	7.76	26.95	43.50	-16.55	peak				
2		298.3666	15.53	15.36	30.89	46.00	-15.11	peak				
3		429.3167	13.91	19.96	33.87	46.00	-12.13	peak				
4	*	550.5665	12.61	22.48	35.09	46.00	-10.91	peak				
5		657.2667	10.76	24.04	34.80	46.00	-11.20	peak				
6		775.2833	6.79	26.98	33.77	46.00	-12.23	peak				


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 16 of 50

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 22.7
Limit: FCC Class B 3M Radiation Power: Humidity: 53.9 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		122.1500	24.33	12.22	36.55	43.50	-6.95	peak			
2	*	306.4499	24.51	15.84	40.35	46.00	-5.65	peak			
3	ļ	418.0000	20.40	19.62	40.02	46.00	-5.98	peak			
4		655.6499	14.32	24.00	38.32	46.00	-7.68	peak			
5		797.9166	9.55	27.29	36.84	46.00	-9.16	peak			
6		880.3667	8.71	28.10	36.81	46.00	-9.19	peak			

Page 17 of 50

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1 Polarization: Vertical Temperature: 22.7
Limit: FCC Class B 3M Radiation Power: Humidity: 53.9 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700

Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		122.1500	20.69	7.76	28.45	43.50	-15.05	peak			
2		298.3666	17.03	15.36	32.39	46.00	-13.61	peak			
3	*	418.0000	16.81	19.62	36.43	46.00	-9.57	peak			
4		539.2500	11.04	22.19	33.23	46.00	-12.77	peak			
5		675.0498	10.93	24.52	35.45	46.00	-10.55	peak			
6		775.2833	7.29	26.98	34.27	46.00	-11.73	peak			


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 18 of 50

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 22.7
Limit: FCC Class B 3M Radiation Power: Humidity: 53.9 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700

Mode: High Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	į	118.9167	26.63	11.79	38.42	43.50	-5.08	peak			
2	*	298.3666	27.56	15.36	42.92	46.00	-3.08	peak			
3	į	358.1831	23.77	18.79	42.56	46.00	-3.44	peak			
4	į	418.0000	21.90	19.62	41.52	46.00	-4.48	peak			
5	į	675.0498	15.62	24.52	40.14	46.00	-5.86	peak			
6		875.5167	10.77	27.97	38.74	46.00	-7.26	peak			

Humidity: 53.9 %

Page 19 of 50

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Power:

Distance: 3m

46.00 -11.77

46.00

46.00

-8.20

-11.23

Limit: FCC Class B 3M Radiation

Reading

dBuV

21.69

17.53

17.81

12.04

13.76

6.75

22.19

24.04

28.02

34.23

37.80

34.77

EUT: DVD Stereo M/N: DV5700

Mode: High Channel TX

Freq.

MHz

122.1500

298.3667

418.0000

539.2500

657.2667

877.1333

Note:

Mk Nο

1

2

3

4

5

6

Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
7.76	29.45	43.50	-14.05	peak			
15.36	32.89	46.00	-13.11	peak			
19.62	37.43	46.00	-8.57	peak		·	

peak

peak

peak

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 20 of 50

RADIATED EMISSION ABOVE 1GHZ

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	106.21	-9.68	96.53	114.00	-17.47	peak			
2		3608.333	51.44	-7.22	44.22	74.00	-29.78	peak			
3		4608.333	47.95	-2.83	45.12	74.00	-28.88	peak			
4	*	2402.000	98.30	-9.68	88.62	94.00	-5.38	AVG	100	109	

Page 21 of 50

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	106.23	-9.68	96.55	114.00	-17.45	peak			
2		3750.000	50.49	-6.35	44.14	74.00	-29.86	peak			
3		4441.667	47.59	-3.31	44.28	74.00	-29.72	peak			
4	*	2402.000	97.83	-9.68	88.15	94.00	-5.85	AVG	100	267	

Page 22 of 50

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	105.79	-9.63	96.16	114.00	-17.84	peak			
2		3416.667	52.16	-7.97	44.19	74.00	-29.81	peak			
3		5508.333	46.35	-1.81	44.54	74.00	-29.46	peak			
4	*	2441.000	97.92	-9.63	88.29	94.00	-5.71	AVG	100	262	

Page 23 of 50

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	106.23	-9.63	96.60	114.00	-17.40	peak			
2		3541.667	52.31	-7.63	44.68	74.00	-29.32	peak			
3		5125.000	46.64	-1.80	44.84	74.00	-29.16	peak			
4	*	2441.000	97.70	-9.63	88.07	94.00	-5.93	AVG	100	105	

Page 24 of 50

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	105.42	-9.59	95.83	114.00	-18.17	peak			
2		3833.333	50.40	-5.84	44.56	74.00	-29.44	peak			
3		5350.000	47.37	-1.81	45.56	74.00	-28.44	peak			
4	*	2480.000	97.21	-9.59	87.62	94.00	-6.38	AVG	100	108	

Page 25 of 50

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: DVD Stereo Distance: 3m

M/N: DV5700

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	105.37	-9.59	95.78	114.00	-18.22	peak			
2		3441.667	52.59	-7.94	44.65	74.00	-29.35	peak			
3		4341.667	48.59	-3.65	44.94	74.00	-29.06	peak			
4	*	2480.000	97.93	-9.59	88.34	94.00	-5.66	AVG	100	264	_

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Page 26 of 50

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	106.21	-9.68	96.53	114	-17.47	Horizontal
2402	106.23	-9.68	96.55	114	-17.45	Vertical
2441	105.79	-9.63	96.16	114	-17.84	Horizontal
2441	106.23	-9.63	96.60	114	-17.40	Vertical
2480	105.42	-9.59	95.83	114	-18.17	Horizontal
2480	105.37	-9.59	95.78	114	-18.22	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	98.30	-9.68	88.62	94	-5.38	Horizontal
2402	97.83	-9.68	88.15	94	-5.85	Vertical
2441	97.92	-9.63	88.29	94	-5.71	Horizontal
2441	97.70	-9.63	88.07	94	-5.93	Vertical
2480	97.21	-9.59	87.62	94	-6.38	Horizontal
2480	97.93	-9.59	88.34	94	-5.66	Vertical

Page 27 of 50

9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE


1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1.5MHz / Sweep=AUTO

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




Page 28 of 50

9.3 RADIATED TEST RESULT

(Worst modulation:GFSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: DVD Stereo Distance:

M/N: DV5700


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2267.650	29.59	10.17	39.76	74.00	-34.24	peak			
2		2390.000	29.62	10.31	39.93	74.00	-34.07	peak			
3	*	2402.000	86.41	10.32	96.73	74.00	22.73	peak			

Page 29 of 50

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: DVD Stereo Distance:

M/N: DV5700


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2296.692	30.20	10.21	40.41	74.00	-33.59	peak			
2		2390.000	29.35	10.31	39.66	74.00	-34.34	peak			
3	*	2402.000	86.26	10.32	96.58	74.00	22.58	peak			

Page 30 of 50

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: DVD Stereo Distance:

M/N: DV5700

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.46	10.41	95.87	74.00	21.87	peak			
2		2483.500	28.25	10.41	38.66	74.00	-35.34	peak			
3		2492.923	29.84	10.42	40.26	74.00	-33.74	peak			

Page 31 of 50

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: DVD Stereo Distance:

M/N: DV5700

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.40	10.41	95.81	74.00	21.81	peak			
2		2483.500	28.37	10.41	38.78	74.00	-35.22	peak			
3		2492.410	30.91	10.42	41.33	74.00	-32.67	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Page 32 of 50


10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)



10.3. LIMITS AND MEASUREMENT RESULTS


BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL				
Applicable Limits	Measurement Result			
	Test Data (MHz)		Criteria	
N/A	Low Channel	0.758	PASS	
	Middle Channel	0.757	PASS	
	High Channel	0.755	PASS	

Page 33 of 50

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Page 34 of 50

TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 35 of 50


BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESUL				
Applicable Limits	Measurement Result			
	Test Data (MHz)		Criteria	
N/A	Low Channel	1.134	PASS	
	Middle Channel	1.137	PASS	
	High Channel	1.145	PASS	

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Page 36 of 50

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 37 of 50


BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESUL				
Applicable Limits	Measurement Result			
	Test Data (MHz)		Criteria	
N/A	Low Channel	1.147	PASS	
	Middle Channel	1.147	PASS	
	High Channel	1.146	PASS	

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Page 38 of 50

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 39 of 50

11. FCC LINE CONDUCTED EMISSION TEST


11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage		
	Q.P.(dBuV)	Average(dBuV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 40 of 50

11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. All support equipments received DC 12V from a LISN, if any.
- 5. The EUT received DC charging voltage by PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.


11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Page 41 of 50

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP







Page 42 of 50

APPENDIX B: PHOTOGRAPHS OF EUT


TOTAL VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT




FRONT VIEW OF EUT



Page 44 of 50

BACK VIEW OF EUT



LEFT VIEW OF EUT



Page 45 of 50

RIGHT VIEW OF EUT



VIEW OF EUT (USB)




Report No.: AGC05322151101FE03 Page 46 of 50

VIEW OF EUT (AUX)




OPEN VIEW OF EUT




Page 47 of 50


INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4




Report No.: AGC05322151101FE03 Page 49 of 50

INTERNAL VIEW OF EUT-5




INTERNAL VIEW OF EUT-6



Report No.: AGC05322151101FE03 Page 50 of 50

INTERNAL VIEW OF EUT-7



----END OF REPORT----