

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Job No.: 190401162GZU Page: 1 of 1

FCC ID: 2ABH3-FBSM05NSU

RF Exposure Compliance Requirement

The product belongs to **standalone portable device** base the FCC rule part 2.1091&2.1093. The transmission frequencies of the device are between 100 MHz and 6 GHz. The worst case test separation distance is **5mm**.

The Max Conducted Output Power(Stated by client) and SAR Test Exclusion Threshold (mW) are listed below:

Transmit frequency (GHz)	Max Conducted Output Power	SAR Test Exclusion
	(mW)	Threshold (mW)
2.402	0.63	9.7
2.441	0.63	9.6
2.480	0.63	9.5

The SAR Test Exclusion Threshold is calculated from:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation17
- The result is rounded to one decimal place for comparison

According to SAR Exclusion Threshold in KDB 447498 (D01) General RF Exposure Guidance v05, the SAR report is not required.