

FCC RADIO TEST REPORT FCC ID:2ABH3FOC48TA-BL

Product: Digital wireless observation system

Trade Name: FURRION

Model Name: FOS48TA-BL

Serial Model: FOD43TA-BL,FOC48TA-BL

Report No.: NTEK-2015NT0114234F

Prepared for

Furrion Ltd.

Suite 3-5, 16/F Pacific Plaza, 410 Des Voeux Road West, Sai Wan, Hong Kong.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website:www.ntek.org.cn



	TEST RESULT CERTIFICATION			
Applicant's name:	Furrion Ltd.			
Address:	Suite 3-5, 16/F Pacific Plaza, 410 Des Voeux Road West, Sai Wan, Hong Kong.			
	Dongguan Protronic Electronics Ltd.			
Address:	Protronic Industrial Park, Xiangxi Village, Shipai Town, DongGuan, GuangDong, China			
Product description				
Product name:	Digital wireless observation system			
Model and/or type reference :	FOS48TA-BL			
Serial Model:	FOD43TA-BL,FOC48TA-BL			
Standards:	FCC Part15.247: 01 Oct. 2014			
Test procedure	ANSI C63.4-2003			
	is been tested by NTEK, and the test results show that the in compliance with the FCC requirements. And it is applicable only in the report.			
•	ced except in full, without the written approval of NTEK, this rised by NTEK, personal only, and shall be noted in the revision of			
Date (s) of performance of tests	: 14 Jan. 2015 ~10 Feb. 2015			
Date of Issue				
Test Result	Pass			
Testing Engine	eer: Danny Guary			
	Denny Huang			
Technical Man	pager: $\mathcal{F}_{\mathcal{W}_{\mathcal{N}}} \ell_{\mathcal{N}}$			
	(Brown Lu)			
Authorized Sig	gnatory:			

(Bill Yao)



Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	8
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 9
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.1.2 TEST PROCEDURE 3.1.3 DEVIATION FROM TEST STANDARD	13 13
3.1.4 TEST SETUP	13
3.1.5 EUT OPERATING CONDITIONS	13
3.1.6 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 RADIATED EMISSION LIMITS	15
3.2.2 TEST PROCEDURE 3.2.3 DEVIATION FROM TEST STANDARD	16 16
3.2.4 TEST SETUP	17
3.2.5 EUT OPERATING CONDITIONS	18
3.2.6 TEST RESULTS (BELOW 30 MHZ)	19
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ) 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	20 22
,	
4 . NUMBER OF HOPPING CHANNEL	23
4.1 APPLIED PROCEDURES / LIMIT	23
4.1.1 TEST PROCEDURE 4.1.2 DEVIATION FROM STANDARD	23 23
4.1.3 TEST SETUP	23
4.1.4 EUT OPERATION CONDITIONS	23
4.1.5 TEST RESULTS	24
5 . AVERAGE TIME OF OCCUPANCY	25
5.1 APPLIED PROCEDURES / LIMIT	25



Table of Contents

Table of Contents	Page
5.1.1 TEST PROCEDURE 5.1.2 DEVIATION FROM STANDARD 5.1.3 TEST SETUP 5.1.4 EUT OPERATION CONDITIONS 5.1.5 TEST RESULTS	25 25 26 26 27
6 . HOPPING CHANNEL SEPARATION MEASUREMENT	31
6.1 APPLIED PROCEDURES / LIMIT 6.1.1 TEST PROCEDURE 6.1.2 DEVIATION FROM STANDARD 6.1.3 TEST SETUP 6.1.4 EUT OPERATION CONDITIONS 6.1.5 TEST RESULTS	31 31 31 31 31 32
7 . BANDWIDTH TEST	34
7.1 APPLIED PROCEDURES / LIMIT 7.1.1 TEST PROCEDURE 7.1.2 DEVIATION FROM STANDARD 7.1.3 TEST SETUP 7.1.4 EUT OPERATION CONDITIONS 7.1.5 TEST RESULTS	34 34 34 34 34 35
8 . PEAK OUTPUT POWER TEST	37
8.1 APPLIED PROCEDURES / LIMIT 8.1.1 TEST PROCEDURE 8.1.2 DEVIATION FROM STANDARD 8.1.3 TEST SETUP 8.1.4 EUT OPERATION CONDITIONS 8.1.5 TEST RESULTS	37 37 37 37 37 38
9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 9.1 DEVIATION FROM STANDARD 9.2 TEST SETUP 9.3 EUT OPERATION CONDITIONS 9.4 TEST RESULTS	40 40 40 40 41
10 . ANTENNA REQUIREMENT	44
10.1 STANDARD REQUIREMENT	44
10.2 EUT ANTENNA	44
11 . EUT TEST PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	45



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C				
Standard Section	Test Item	Judgment	Remark	
15.207	Conducted Emission	N/A		
15.247(a)(1)	Hopping Channel Separation	PASS		
15.247(b)(1)	Peak Output Power	PASS		
15.247(c)	Radiated Spurious Emission	PASS		
15.247(a)(iii)	Number of Hopping Frequency	PASS		
15.247(a)(iii)	Dwell Time	PASS		
15.247(a)(1)	Bandwidth	PASS		
15.205	Band Edge Emission	PASS		
15.203	Antenna Requirement	PASS		

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Digital wireless observation system			
Trade Name	FURRION			
Model Name	FOS48TA-BL			
Serial Model	FOD43TA-BL,FOC48TA-BI	L		
Model Difference	All the model are the same circuit and RF module, except the model name and colour.			
Product Description	The EUT is a Digital wireless observation system Operation Frequency: 2403~2478 MHz Modulation Type: QPSK Number Of Channel 26 CH Antenna Designation: Please see Note 3.			
Channel List	Please refer to the Note 2.			
Adapter	N/A			
Battery	N/A			
Connecting I/O Port(s)	Please refer to the User's Manual			

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2403	11	2433	21	2463
02	2406	12	2436	22	2466
03	2409	13	2439	23	2469
04	2412	14	2442	24	2472
05	2415	15	2445	25	2475
06	2418	16	2448	26	2478
07	2421	17	2451		
08	2424	18	2454		
09	2427	19	2457		
10	2430	20	2460		

Table for Filed Antenna

Ar	it Barrel	Madal Nasa	A t	0	O = i = (-IDi)	NOTE
	" Brand	Model Name	Antenna Type	Connector	Gain (dBI)	NOTE
1	N/A	N/A	External Antenna	N/A	3.0	BT Antenna



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH01
Mode 2	CH14
Mode 3	CH26
Mode 4	normal link

For Conducted Emission			
Final Test Mode Description			
Mode 4	normal link		

For Radiated Emission			
Final Test Mode Description			
Mode 1	CH01		
Mode 2	CH14		
Mode 3	CH26		

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3)The data rate was set in 3Mbps for radiated emission due to the highest RF output power.


2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Broadcom			
Frequency	2403 MHz 2442 MHz 2478 MHz			
Parameters(1/2/3Mbps)	DEF	DEF	DEF	



2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED





2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Digital wireless observation system	FURRION	FOS48TA-BL	N/A	EUT
E-2	Car charger	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	120cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".





2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

	ation rest equip						
Item	Kind of	Manufacturer	Type No.	Serial No.	Last	Calibrated	Calibratio
	Equipment				calibration	until	n period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-101 80	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2014.07.06	2015.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2014.07.06	2015.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2014.07.06	2015.07.05	1 year

Conduction Test equipment

Conduction rest equipment							
Item	Kind of	Manufactu	Type No.	Serial No.	Last	Calibrated	Calibratio
	Equipment	rer			calibration	until	n period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year
7	Test Cable	N/A	C01	N/A	2014.06.08	2015.06.07	1 year
8	Test Cable	N/A	C02	N/A	2014.06.08	2015.06.07	1 year
9	Test Cable	N/A	C03	N/A	2014.06.08	2015.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2014 06 08	2015.06.07	1 year
•	, ((to)) (datio)			2.10200	2017.00.00	2010.00.01	. , -



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

	Class A	(dBuV)	Class B	(dBuV)	Ctondord
FREQUENCY (MHz)	Quasi-peak	Average	Quasi-peak	Average	Standard
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting	
Attenuation	10 dB	
Start Frequency	0.15 MHz	
Stop Frequency	30 MHz	
IF Bandwidth	9 kHz	




3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS

IEU I ·	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N/A
Test Voltage :	N/A	Test Mode:	N/A



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

EDECHENCY (MUz)	Class B (dBuV/m) (at 3M)		
FREQUENCY (MHz)	PEAK	AVERAGE	
Above 1000	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted	1 MHz / 1 MHz for Dook 1 MHz / 10Hz for Average
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter Setting	
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
	Peak	1 MHz	1 MHz
Above 1000	Peak	1 MHz	10 Hz


3.2.3 DEVIATION FROM TEST STANDARD

No deviation




3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.6 TEST RESULTS (BELOW 30 MHZ)

IEUI •	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX	Polarization :	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				Р
				Р

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =20 log (specific distance/test distance)(dB); Limit line = specific limits(dBuv) + distance extrapolation factor.




3.2.7 TEST RESULTS (BETWEEN 30M - 1000 MHZ)

IEU I •	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010hPa	Test Mode:	TX
Test Voltage :	DC 12V		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	7101110111
V	53.8817	24.81	9.58	34.39	40.00	-5.61	QP
V	150.0107	28.69	10.41	39.10	43.50	-4.40	QP
V	300.3672	27.17	14.16	41.33	46.00	-4.67	QP
V	390.7225	22.20	17.93	40.13	46.00	-5.87	QP
V	510.0436	19.77	20.50	40.27	46.00	-5.73	QP
V	752.7432	15.37	26.17	41.54	46.00	-4.46	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit






Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Roman
Н	53.8817	19.03	9.58	28.61	40.00	-11.39	QP
Н	171.3925	23.59	10.57	34.16	43.50	-9.34	QP
Н	239.9874	26.91	13.49	40.40	46.00	-5.60	QP
Н	390.7225	24.79	17.93	42.72	46.00	-3.28	QP
Н	691.9867	17.68	24.58	42.26	46.00	-3.74	QP
Н	993.0113	15.49	27.53	43.02	54.00	-10.98	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit





3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

IEUI •	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	TX
Test Mode :	DC 12V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remar	0
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	k	Comment
		Low Ch	annel (2403 MHz)-A	Above 1G			
4806.147	59.51	-3.69	55.82	74.00	-18.18	Pk	Vertical
4806.147	41.71	-3.69	38.02	54.00	-15.98	AV	Vertical
7209.246	52.66	-0.91	51.75	74.00	-22.25	Pk	Vertical
7209.246	37.66	-0.91	36.75	54.00	-17.25	AV	Vertical
4806.148	59.85	-3.69	56.16	74.00	-17.84	Pk	Horizontal
4806.148	41.63	-3.69	37.94	54.00	-16.06	AV	Horizontal
7209.206	54.31	-0.91	53.40	-0.91	54.31	Pk	Horizontal
7209.206	37.64	-0.91	36.73	-0.91	37.64	AV	Horizontal
		Mid Ch	annel (2441 MHz)-A	Above 1G			
4884.176	60.24	-3.74	56.50	74.00	-17.50	Pk	Vertical
4884.176	40.71	-3.74	36.97	54.00	-17.03	AV	Vertical
7326.234	56.71	-0.88	55.83	74.00	-18.17	Pk	Vertical
7326.234	41.64	-0.88	40.76	54.00	-13.24	AV	Vertical
4884.196	59.24	-3.74	55.50	74.00	-18.50	Pk	Horizontal
4884.196	40.43	-3.74	36.69	54.00	-17.31	AV	Horizontal
7326.142	56.61	-0.88	55.73	74.00	-18.27	Pk	Horizontal
7326.142	40.85	-0.88	39.97	54.00	-14.03	AV	Horizontal
	Γ	High Ch	annel (2480 MHz)-	Above 1G	Г	1 1	
4956.259	59.61	-3.32	56.29	74.00	-17.71	Pk	Vertical
4956.259	42.85	-3.32	39.53	54.00	-14.47	AV	Vertical
7434.077	54.15	-0.46	53.69	74.00	-20.31	Pk	Vertical
7434.077	38.34	-0.46	37.88	54.00	-16.12	AV	Vertical
4956.314	58.44	-3.32	55.12	74.00	-18.88	Pk	Horizontal
4956.314	40.61	-3.32	37.29	54.00	-16.71	AV	Horizontal
7434.172	54.02	-0.46	53.56	74.00	-20.44	Pk	Horizontal
7434.172	37.81	-0.46	37.35	54.00	-16.65	AV	Horizontal



4. NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting		
Attenuation	Auto		
Span Frequency = the frequency band of operation			
RB RBW=100kHz			
VB VBW ≥ RBW			
Detector	Peak		
Trace Max Hold			
Sweep Time	Auto		


4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100kHz, VBW=100kHz, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



4.1.5 TEST RESULTS

IF() .	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature:	25 ℃	Relative Humidity:	60%
Pressure:	1015 hPa	Test Voltage :	DC 12V
Test Mode :	Hopping Mode-QPSK		

Number of Hopping Channel	26
11 3	





5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS	

5.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer and working at hopping mode.
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- q. Change the sweep time to the observation time: 26*0.4/100s=104ms.
- h. Calculate the times of the appeard pulses in the observation time.
- i. The average time of occupancy = :
 the maximum time duration of one single pulse* times of the appeard pulses in the observation time*100

5.1.2 DEVIATION FROM STANDARD

No deviation.

NTEK	Page 26 of 45	Report No.:NTEK-2015NT0114234F
5.1.3 TEST SETUR)	
EUT		SPECTRUM
		ANALYZER
5.1.4 EUT OPERA	TION CONDITIONS	
The EUT tested sys	stem was configured as the statements of is specified in the follows during the testion	f 2.4 Unless otherwise a special ng.




5.1.5 TEST RESULTS


EUI ·	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	25 ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 12V
Test Mode :	QPSK		


Frequency	Pulse Duration	Dwell Time	Limits
	(ms)	(s)	(s)
2403 MHz	0.2167	0.39	0.4
2442 MHz	0.2167	0.39	0.4
2478 MHz	0.2167	0.39	0.4

Note: Please refer to the test methods at page 27.
























6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting	
Attenuation	Auto	
Span Frequency	> Measurement Bandwidth or Channel Separation	
RB	30 kHz (Channel Separation)	
VB	100 kHz (Channel Separation)	
Detector	Peak	
Trace	Max Hold	
Sweep Time	Auto	


6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode
- b. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.




6.1.5 TEST RESULTS


IEUI •	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	25 ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 12V
Test Mode :	CH01 / CH14 /CH26		

Frequency	Ch. Separation (MHz)	Result
2403 MHz	3.000	Complies
2442 MHz	3.000	Complies
2478 MHz	3.000	Complies

Ch. Separation Limits: > 2/3 20dB BW









7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



7.1.5 TEST RESULTS

IEU I •	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	25 ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	CH01 / CH14 /CH26		

Frequency	20dB Bandwidth (MHz)	Result
2403 MHz	4.354	PASS
2442 MHz	4.354	PASS
2478MHz	4.352	PASS









8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 20.96dBm	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

8.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




8.1.5 TEST RESULTS


IEU I •	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	25 ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	CH01/ CH14 /CH26		

Test Channel	Frequency	Peak Output Power	LIMIT
rest Chamilei	(MHz)	(dBm)	(dBm)
CH01	2403	9.75	20.96
CH14	2442	9.18	20.96
CH26	2478	9.14	20.96











Report No.:NTEK-2015NT0114234F

9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

9.1 DEVIATION FROM STANDARD

No deviation.

9.2 TEST SETUP

EUT	SPECTRUM
	ANALYZER

9.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



9.4 TEST RESULTS

IEU I •	Digital wireless observation system	Model Name :	FOS48TA-BL
Temperature :	25 ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 12V
Test Mode :	CH01/ CH26		


Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result		
Non-hopping					
2400	57.97	20	Pass		
2483.5	50.24	20	Pass		
hopping					
2400	32.68	20	Pass		
2483.5	51.06	20	Pass		


Radiated band edge:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBµV/m)	(dBμV/m)	(dB)	Туре	Comment
			Non-hopping				
2390	56.61	-13.06	43.55	74.00	-30.45	peak	Vertical
2390	57.74	-13.06	44.68	74.00	-29.32	peak	Horizontal
2483.5	56.49	-12.78	43.71	74.00	-30.29	peak	Vertical
2483.5	58.84	-12.78	46.06	74.00	-27.94	peak	Horizontal
	hopping						
2390	57.95	-13.06	44.89	74.00	-29.11	peak	Vertical
2390	59.06	-13.06	46.00	74.00	-28.00	peak	Horizontal
2483.5	56.78	-12.78	44.00	74.00	-30.00	peak	Vertical
2483.5	59.09	-12.78	46.31	74.00	-27.69	peak	Horizontal


Note: Refer to chapter 3.2 test method, When PK value is lower than the Average value limit, average didn't record.
















10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is unique connector antenna(R-SMA)	, detailed in the internal photos,
It comply with the standard requirement.	



11. EUT TEST PHOTO



