

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT  
INTENTIONAL RADIATOR CERTIFICATION TO  
FCC PART 15 SUBPART C REQUIREMENT**

OF

**Bluetooth headset**

**Model No.: 7199-83, SL133, 7199-71, CT172071**

**Trademark: N/A**

**FCC ID: 2ABHA0054**

**Report No.: ES181113010E**

**Issue Date: November 16, 2018**

*Prepared for*

**NINGBO CSTAR IMP&EXP CO., LTD.  
Floor 4, Building E, No. 655-90, Qiming Road, Yinzhou Investment  
& Innovation Center, Ningbo, China**

*Prepared by*

**EMTEK(SHENZHEN) CO., LTD.**

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,  
Guangdong, China.**

**TEL: 86-755-26954280**

**FAX: 86-755-26954282**

**This report shall not be reproduced, except in full, without the written approval of  
EMTEK(SHENZHEN) CO., LTD.**

## VERIFICATION OF COMPLIANCE

Applicant:	NINGBO CSTAR IMP&EXP CO., LTD. Floor 4, Building E, No. 655-90, Qiming Road, Yinzhou Investment & Innovation Center, Ningbo, China
Manufacturer:	NINGBO CSTAR IMP&EXP CO., LTD. Floor 4, Building E, No. 655-90, Qiming Road, Yinzhou Investment & Innovation Center, Ningbo, China
Product Description:	Bluetooth headset
Trade Mark:	N/A
Model Number:	7199-83, SL133, 7199-71, CT172071 (Note: These models are same except model number and appearance, here model: SL133 was selected for full test.)

### We hereby certify that:

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2017).

Date of Test : November 13, 2018 to November 16, 2018

Prepared by : Yaping Shen  
Yaping Shen/Editor

Reviewer : Joe Xia  
Joe Xia/Supervisor

Approved & Authorized  
Signer : Lisa Wang  
Lisa Wang/Manager

## Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	ES181113010E

## Table of Contents

<b>1. GENERAL INFORMATION.....</b>	<b>6</b>
1.1 PRODUCT DESCRIPTION.....	6
1.2 TEST METHODOLOGY.....	6
1.3 TEST FACILITY.....	7
<b>2. SYSTEM TEST CONFIGURATION.....</b>	<b>8</b>
2.1 EUT CONFIGURATION.....	8
2.2 EUT EXERCISE.....	8
2.3 TEST PROCEDURE.....	8
2.4 CONFIGURATION OF TESTED SYSTEM.....	9
<b>3. SUMMARY OF TEST RESULTS.....</b>	<b>10</b>
<b>4. DESCRIPTION OF TEST MODES.....</b>	<b>11</b>
<b>5. TEST SYSTEM UNCERTAINTY.....</b>	<b>12</b>
<b>6. RADIATED EMISSION TEST .....</b>	<b>13</b>
6.1 MEASUREMENT PROCEDURE .....	13
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	15
6.3 MEASUREMENT EQUIPMENT USED:.....	16
6.4 RADIATED EMISSION LIMIT .....	17
6.5 MEASUREMENT RESULT.....	18
6.5 RADIATED MEASUREMENT PHOTOS:.....	25
<b>7. CHANNEL SEPARATION TEST.....</b>	<b>26</b>
7.1 MEASUREMENT PROCEDURE .....	26
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	26
7.3 MEASUREMENT EQUIPMENT USED:.....	26
7.4 MEASUREMENT RESULTS:.....	26
<b>8. 20DB BANDWIDTH TEST .....</b>	<b>31</b>
8.1 MEASUREMENT PROCEDURE .....	31
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	31
8.3 MEASUREMENT EQUIPMENT USED:.....	32
8.4 MEASUREMENT RESULTS:.....	32
<b>9. QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>37</b>
9.1 MEASUREMENT PROCEDURE .....	37
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	37
9.3 MEASUREMENT EQUIPMENT USED: .....	37
9.4 MEASUREMENT RESULTS:.....	37
<b>10. TIME OF OCCUPANCY (DWELL TIME) TEST .....</b>	<b>38</b>

10.1 TEST DESCRIPTION .....	38
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	38
10.3 MEASUREMENT EQUIPMENT USED:.....	38
10.4 TEST REQUIREMENTS / LIMITS .....	39
10.5 TEST RESULT.....	39
<b>11. MAXIMUM PEAK OUTPUT POWER TEST.....</b>	<b>41</b>
11.1 MEASUREMENT PROCEDURE .....	41
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	41
11.3 MEASUREMENT EQUIPMENT USED:.....	41
11.4 MEASUREMENT RESULTS: .....	42
<b>12. BAND EDGE TEST.....</b>	<b>46</b>
12.1 MEASUREMENT PROCEDURE.....	46
12.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	47
12.3 MEASUREMENT EQUIPMENT USED:.....	47
12.4 MEASUREMENT RESULTS:.....	48
<b>13. ANTENNA APPLICATION.....</b>	<b>62</b>
13.1 ANTENNA REQUIREMENT .....	62
13.2 RESULT.....	62

## 1. GENERAL INFORMATION

### 1.1 Product Description

Characteristics	Description
<b>Product Name</b>	Bluetooth headset
<b>Model number</b>	7199-83, SL133, 7199-71, CT172071 (Note: These models are same except model number and appearance, here model: SL133 was selected for full test.)
<b>Power Supply</b>	DC 3.7V Battery
<b>Kind of Device</b>	Bluetooth Ver.4.2+EDR
<b>Modulation</b>	GFSK, $\pi/4$ -DQPSK
<b>Operating Frequency Range</b>	2402-2480MHz
<b>Number of Channels</b>	79
<b>Transmit Power Max(PK)</b>	2.01dBm(0.001589W)
<b>Antenna Type</b>	Internal Antenna
<b>Antenna Gain</b>	0dBi

### 1.2 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10-2013. Radiated testing was performed at an antenna to EUT distance 3 meters.

### 1.3 Test Facility

#### Site Description

EMC Lab. : Accredited by CNAS, 2016.10.24  
The certificate is valid until 2022.10.28  
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)  
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2016.5.19  
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

Accredited by FCC, August 03, 2017  
Designation Number: CN1204  
Test Firm Registration Number: 882943

Accredited by Industry Canada, November 24, 2015  
The Certificate Registration Number is 4480A.

Accredited by A2LA, July 31, 2017  
The Certificate Number is 4321.01.

Name of Firm : EMTEK(SHENZHEN) CO., LTD.

Site Location : Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China.

## 2. System Test Configuration

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The Tx frequency was fixed which was for the purpose of the measurements.

### 2.3 Test Procedure

#### 2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

#### 2.3.2 Radiated Emissions

Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of EUT was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

## 2.4 Configuration of Tested System

**Fig. 2-1 Configuration of Tested System**



**Table 2-1 Equipment Used in Tested System**

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	Bluetooth headset	N/A	SL133	2ABHA0054	<b>EUT</b>
2.	/	/	/	/	/

**Note:**

(1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.

### 3. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	N/A(see note 1)
§15.247(d),§15.209	Radiated Emission	Compliant
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)(iii)	Time of Occupancy(Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.203	Antenna Requirement	Compliant

Remark: The product was tested under the battery fully charged.

Note 1: During the charging proceed, the Bluetooth function of this device is inactive.

## 4. Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

The EUT has been tested under TX operating condition.

This EUT is a FHSS system, were conducted to determine the final configuration from all possible combinations. We use software control the EUT, Let EUT hopping on and transmit with highest power, all the modes GFSK,  $\Pi/4$ -DQPSK have been tested. 79 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency(MHz)
1	2402
40	2441
79	2480

## 5. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Power Density	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5 \text{ }^{\circ}\text{C}$
Humidity	$\pm 3\%$

Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%

## 6. Radiated Emission Test

### 6.1 Measurement Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
  - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
  - 2) Change the antenna polarization and repeat 1) with vertical polarization.
  - 3) Make a hardcopy of the spectrum.
  - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
  - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
  - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
  - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
  - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak+AV
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

## 6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



**6.3 Measurement Equipment Used:**

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.03	9KHz-3GHz	05/16/2018	1 Year
2.	Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	05/16/2018	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	000141	25MHz-2GHz	05/16/2018	1 Year
4.	Power Amplifier	CDS	RSU-M352	818	1MHz-1GHz	05/16/2018	1 Year
5.	Power Amplifier	HP	8447F	OPT H64	1GHz-26.5GHz	05/16/2018	1 Year
6.	Color Monitor	SUNSPO	SP-140A	N/A	--	05/16/2018	1 Year
7.	Single Line Filter	JIANLI	XL-3	N/A	--	05/16/2018	1 Year
8.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	--	05/16/2018	1 Year
9.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	--	05/16/2018	1 Year
10.	DC Power Filter	JIANLI	DL-2X50B	N/A	--	05/16/2018	1 Year
11.	Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	05/16/2018	1 Year
12.	Cable	Rosenberger	CIL02	A0783566	9KHz-3GHz	05/16/2018	1 Year
13.	Cable	Rosenberger	RG 233/U	525178	9KHz-3GHz	05/16/2018	1 Year
14.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	05/16/2018	1 Year
15.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	1GHz-18GHz	05/16/2018	1 Year
16.	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	14GHz -26.5GHz	05/16/2018	1 Year
17.	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	05/16/2018	1 Year
18.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/16/2018	1 Year
19.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/16/2018	1 Year
20.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/16/2018	1 Year

## 6.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

## 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

Remark 1. Emission level in dB<sub>B</sub>uV/m=20 log (uV/m)  
 : 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.  
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of  $\xi$  15.205, and the emissions located in restricted bands also comply with 15.209 limit.

## 6.5 Measurement Result

### Below 30MHz:

Operation Mode:	TX	Test Date :	November 13, 2018
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Lin

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--


Note: The low frequency, which started from 9KHz-30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### Below 1000MHz:

Pass.

All the modulation modes were tested the data of the worst mode (TX  $\Pi/4$ -DQPSK 2441MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m

Power: Battery 3.7V

Humidity: 55 %


Mode: TX2441

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Degree
		MHz	dBuV	dB	dBuV/m	dB	dB	Detector	cm	degree
1		655.6500	27.16	-5.07	22.09	46.00	-23.91	QP		
2		697.3600	26.79	-4.26	22.53	46.00	-23.47	QP		
3		738.1000	28.65	-3.79	24.86	46.00	-21.14	QP		
4		800.1800	27.22	-3.29	23.93	46.00	-22.07	QP		
5		858.3800	26.90	-3.71	23.19	46.00	-22.81	QP		
6	*	951.5000	27.94	-1.99	25.95	46.00	-20.05	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: Lin



Site Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m

Power: Battery 3.7V

Humidity: 55 %

Mode: TX2441

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Degree
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		697.3600	27.65	-5.85	21.80	46.00	-24.20	QP		
2		759.4400	27.74	-4.80	22.94	46.00	-23.06	QP		
3		807.9400	27.38	-4.33	23.05	46.00	-22.95	QP		
4		848.6800	28.39	-4.28	24.11	46.00	-21.89	QP		
5		911.7300	27.32	-2.91	24.41	46.00	-21.59	QP		
6	*	951.5000	26.74	-1.91	24.83	46.00	-21.17	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: Lin

**Above 1000MHz~10<sup>th</sup> Harmonics:**

Operation Mode: GFSK (CH1: 2402MHz) Test Date : November 13, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4804	V	95.5	75.56	-32.3	63.2	43.26	74	54	-10.8	-10.74
7206	V	98.32	78.78	-37.2	61.12	41.58	74	54	-12.88	-12.42
9608	V	99.16	80.16	-39.8	59.36	40.36	74	54	-14.64	-13.64
12010	V	98.8	80.08	-40.5	58.3	39.58	74	54	-15.7	-14.42
14412	V	98.03	79.11	-41.7	56.33	37.41	74	54	-17.67	-16.59
16814	V	95.55	76.58	-40	55.55	36.58	74	54	-18.45	-17.42
4804	H	94.72	75.18	-31.6	63.12	43.58	74	54	-10.88	-10.42
7206	H	96.7	77.35	-35.5	61.2	41.85	74	54	-12.8	-12.15
9608	H	97.66	79.26	-38.3	59.36	40.96	74	54	-14.64	-13.04
12010	H	97.66	78.58	-39	58.66	39.58	74	54	-15.34	-14.42
14412	H	98.36	79.58	-42	56.36	37.58	74	54	-17.64	-16.42
16814	H	94.77	75.88	-39.3	55.47	36.58	74	54	-18.53	-17.42

Operation Mode: GFSK (CH40: 2441MHz) Test Date : November 13, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4882	V	95.55	76.26	-32.3	63.25	43.96	74	54	-10.75	-10.04
7323	V	98.52	79.5	-37.2	61.32	42.3	74	54	-12.68	-11.7
9764	V	99.38	80.05	-39.8	59.58	40.25	74	54	-14.42	-13.75
12205	V	98.97	80.08	-40.5	58.47	39.58	74	54	-15.53	-14.42
14646	V	97.32	78.58	-41	56.32	37.58	74	54	-17.68	-16.42
17087	V	96.57	77.68	-41.1	55.47	36.58	74	54	-18.53	-17.42
4882	H	94.72	75.32	-31.6	63.12	43.72	74	54	-10.88	-10.28
7323	H	96.05	76.82	-35.5	60.55	41.32	74	54	-13.45	-12.68
9764	H	97.66	78.9	-38.3	59.36	40.6	74	54	-14.64	-13.4
12205	H	97.47	79.34	-39	58.47	40.34	74	54	-15.53	-13.66
14646	H	98.32	79.65	-42	56.32	37.65	74	54	-17.68	-16.35
17087	H	96.97	78.38	-41.5	55.47	36.88	74	54	-18.53	-17.12

Operation Mode: GFSK (CH79: 2480MHz) Test Date : November 13, 2018

Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4960	V	94.66	75.08	-32.3	62.36	42.78	74	54	-11.64	-11.22
7440	V	97.52	77.56	-37.2	60.32	40.36	74	54	-13.68	-13.64
9920	V	99.16	79.82	-39.8	59.36	40.02	74	54	-14.64	-13.98
12400	V	98.82	80.15	-40.5	58.32	39.65	74	54	-15.68	-14.35
14880	V	97.58	78.58	-41	56.58	37.58	74	54	-17.42	-16.42
17360	V	96.73	77.68	-41.1	55.63	36.58	74	54	-18.37	-17.42
4960	H	94.18	74.62	-31.6	62.58	43.02	74	54	-11.42	-10.98
7440	H	96.52	77.52	-35.5	61.02	42.02	74	54	-12.98	-11.98
9920	H	97.99	78.66	-38.3	59.69	40.36	74	54	-14.31	-13.64
12400	H	97.47	78.58	-39	58.47	39.58	74	54	-15.53	-14.42
14880	H	98.58	79.25	-42	56.58	37.25	74	54	-17.42	-16.75
17360	H	96.82	78.38	-41.5	55.32	36.88	74	54	-18.68	-17.12

Operation Mode: Pi/4-DQPSK (CH1: 2402MHz) Test Date : November 13, 2018

Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4804	V	95.87	75.95	-32.3	63.57	43.65	74	54	-10.43	-10.4
7206	V	98.78	79.45	-37.2	61.58	42.25	74	54	-12.42	-11.8
9608	V	100.46	81.49	-39.8	60.66	41.69	74	54	-13.34	-12.3
12010	V	100.08	80.82	-40.5	59.58	40.32	74	54	-14.42	-13.7
14412	V	100.17	80.92	-41.7	58.47	39.22	74	54	-15.53	-14.8
16814	V	96.58	77.85	-40	56.58	37.85	74	54	-17.42	-16.2
4804	H	95.02	76.03	-31.6	63.42	44.43	74	54	-10.58	-9.57
7206	H	96.53	78.08	-35.5	61.03	42.58	74	54	-12.97	-11.4
9608	H	98.3	79.99	-38.3	60	41.69	74	54	-14	-12.3
12010	H	98.36	79.32	-39	59.36	40.32	74	54	-14.64	-13.7
14412	H	100.14	80.58	-42	58.14	38.58	74	54	-15.86	-15.4
16814	H	95.62	76.88	-39.3	56.32	37.58	74	54	-17.68	-16.4

Operation Mode: Pi/4-DQPSK (CH40: 2441MHz) Test Date : November 13, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	dB	PK	AV	PK	AV	PK	AV
4882	V	95.88	76.32	-32.3	63.58	44.02	74	54	-10.42	-9.98
7323	V	97.78	78.44	-37.2	60.58	41.24	74	54	-13.42	-12.76
9764	V	98.46	79.45	-39.8	58.66	39.65	74	54	-15.34	-14.35
12205	V	97.08	78.08	-40.5	56.58	37.58	74	54	-17.42	-16.42
14646	V	96.47	78.71	-41	55.47	37.71	74	54	-18.53	-16.29
17087	V	96.74	78.68	-41.1	55.64	37.58	74	54	-18.36	-16.42
4882	H	94.92	75.06	-31.6	63.32	43.46	74	54	-10.68	-10.54
7323	H	95.97	77.3	-35.5	60.47	41.8	74	54	-13.53	-12.2
9764	H	96.99	78.62	-38.3	58.69	40.32	74	54	-15.31	-13.68
12205	H	96.52	77.69	-39	57.52	38.69	74	54	-16.48	-15.31
14646	H	98.56	79.05	-42	56.56	37.05	74	54	-17.44	-16.95
17087	H	97.64	79.06	-41.5	56.14	37.56	74	54	-17.86	-16.44

Operation Mode: Pi/4-DQPSK (CH79: 2480MHz) Test Date : November 13, 2018


Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	dB	PK	AV	PK	AV	PK	AV
4960	V	95.8	75.53	-32.3	63.5	43.23	74	54	-10.5	-10.77
7440	V	99.5	79.23	-37.2	62.3	42.03	74	54	-11.7	-11.97
9920	V	99.95	81	-39.8	60.15	41.2	74	54	-13.85	-12.8
12400	V	98.08	79.02	-40.5	57.58	38.52	74	54	-16.42	-15.48
14880	V	97.33	78.52	-41	56.33	37.52	74	54	-17.67	-16.48
17360	V	96.12	77.35	-41.1	55.02	36.25	74	54	-18.98	-17.75
4960	H	94.81	75.18	-31.6	63.21	43.58	74	54	-10.79	-10.42
7440	H	97.8	78.46	-35.5	62.3	42.96	74	54	-11.7	-11.04
9920	H	97.56	78.6	-38.3	59.26	40.3	74	54	-14.74	-13.7
12400	H	97.83	78.58	-39	58.83	39.58	74	54	-15.17	-14.42
14880	H	98.36	79.58	-42	56.36	37.58	74	54	-17.64	-16.42
17360	H	97.35	78.08	-41.5	55.85	36.58	74	54	-18.15	-17.42

Other harmonics emissions are lower than 20dB below the allowable limit.

**Note:**

- (1) All Readings are Peak Value and AV.
- (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
- (3) The average measurement was not performed when the peak measured data under the limit of average detection.
- (4) Measuring frequencies from 1GHz to 25GHz.

## 6.5 Radiated Measurement Photos:



## 7. Channel Separation test

### 7.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	3MHz
RBW	100K
VBW	300K
Detector	Peak
Trace	Max hold
Sweep Time	Auto

Limit:

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 7.2 Test SET-UP (Block Diagram of Configuration)



### 7.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



### 7.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector: PK      Test Date : November 16, 2018  
 Test By: YF      Temperature : 24°C  
 Test Result: PASS      Humidity : 53 %  
 Modulation: GFSK


Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>729
40	2441	1003	>727
79	2480	1003	>732







Spectrum Detector: PK      Test Date : November 16, 2018  
 Test By: YF      Temperature : 24°C  
 Test Result: PASS      Humidity : 53 %  
 Modulation: Π/4-DQPSK

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>912
40	2441	1003	>909
79	2480	1003	>912





## 8. 20dB Bandwidth test

### 8.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1% occupied bandwidth (100KHz).

Set the video bandwidth (VBW) =300KHz.

Set Span= approximately 2 to 3 times the occupied bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 99% down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 99% bandwidth of the emission.


If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Limit:

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHzband may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 8.2 Test SET-UP (Block Diagram of Configuration)



### 8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018



Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.


### 8.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	November 16, 2018
Test By:	YF	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK		


Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1094
40	2441	1090
79	2480	1098







Spectrum Detector: PK      Test Date : November 16, 2018  
 Test By: YF      Temperature : 24°C  
 Test Result: PASS      Humidity : 53 %  
 Modulation: Π/4-DQPSK

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1368
40	2441	1363
79	2480	1368





## 9. Quantity of Hopping Channel Test

### 9.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

### 9.2 Test SET-UP (Block Diagram of Configuration)



### 9.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018


Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

### 9.4 Measurement Results:

Refer to attached data chart.

Worst Test Mode      GFSK      Test Date :      November 16, 2018  
 Test By:      YF      Temperature :      25 °C  
 Test Result:      PASS      Humidity :      50 %

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
2402-2480	79	>15



## 10. Time of Occupancy (Dwell Time) test

### 10.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:

$$\text{Dwell time} = \text{time slot length} * \text{hop rate} / \text{number of hopping channels} * 31.6s$$

with:

- hop rate =  $1600 * 1/s$  for DH1 packets =  $1600 \text{ s}^{-1}$
- hop rate =  $1600/3 * 1/s$  for DH3 packets =  $533.33 \text{ s}^{-1}$
- number of hopping channels = 79
- $31.6 \text{ s} = 0.4 \text{ seconds multiplied by the number of hopping channels} = 0.4 \text{ s} * 79$

The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	0Hz
RBW	1M
VBW	3M
Detector	Peak
Trace	Max hold
Sweep Time	1ms for 1DH1,3ms for 1DH3,5ms for 1DH5

### 10.2 Test SET-UP (Block Diagram of Configuration)



### 10.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 10.4 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)


Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6seconds. Refer to attached data chart.

## 10.5 Test result


Mode	Number of transmission in a 31.6( 79 Hopping*0.4)	Length of transmissions time(msec)	Result (msec)	Limit (msec)
DH1	$1600/(2*79) \times 31.6 = 320$	0.384	122.88	400
DH3	$1600/(4*79) \times 31.6 = 160$	1.643	262.88	400
DH5	$1600/(6*79) \times 31.6 = 106.67$	2.899	309.24	400

Remark: The results of worst cased was recorded.


DH1:



DH3:



DH5:



## 11. MAXIMUM PEAK OUTPUT POWER TEST

### 11.1 Measurement Procedure

- a. Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	9MHz
RBW	3M
VBW	10M
Detector	Peak
Trace	Max hold
Sweep Time	Auto

Limit:

FCC Part 15, Subpart C, §15.247 (b) (1)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 11.2 Test SET-UP (Block Diagram of Configuration)



### 11.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018


Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



#### 11.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	November 16, 2018
Test By:	YF	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %
Modulation:	GFSK		


Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	0.35	1.084	125	PASS
40	2441	1.2	1.318	125	PASS
79	2480	0.91	1.233	125	PASS







Spectrum Detector: PK Test Date : November 16, 2018  
 Test By: YF Temperature : 25 °C  
 Test Result: PASS Humidity : 50 %  
 Modulation: Π/4-DQPSK

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	1.29	1.346	125	PASS
40	<b>2441</b>	<b>2.01</b>	<b>1.589</b>	125	PASS
79	2480	1.79	1.510	125	PASS





## 12. Band EDGE test

### 12.1 Measurement Procedure

#### For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

#### For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band.

Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

## 12.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



## 12.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	05/16/2018	1 Year
2	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-12 72	1GHz-18GHz	05/16/2018	1 Year
3	Power Amplifier	LUNAR EM	LNA1G18-40	J1010000 0081	1GHz-26.5GHz	05/16/2018	1 Year
4	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/16/2018	1 Year
5	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/16/2018	1 Year
6	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/16/2018	1 Year

**12.4 Measurement Results:**

Refer to attached data chart.



Spectrum Detector:	PK	Test Date :	November 16, 2018
Test By:	YF	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %

**1. Conducted Test**



For Non-Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2397.99	GFSK	0.23	42.19	>20dBc
2397.97	pi/4-DQPSK	0.17	42.54	>20dBc
2484.1	GFSK	0.83	57.8	>20dBc
2483.79	pi/4-DQPSK	0.77	58.35	>20dBc

## Test plots of GFSK




## Test plots of pi/4-DQPSK



For Hopping Mode:


Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.13	GFSK	0.23	42.34	>20dBc
2398.99	pi/4-DQPSK	0.21	42.22	>20dBc
2486.03	GFSK	0.82	53.31	>20dBc
2483.82	pi/4-DQPSK	0.67	56.73	>20dBc


### Test plots of GFSK





### Test plots of pi/4-DQPSK






## 2. Radiated emission Test

**Worst test modulation: pi/4-DQPSK**

For Non-Hopping Mode:



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m\_PEAK

Power: Battery 3.7V

Humidity: 55 %


Mode:DSS (TX2402)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2396.084	66.15	-20.95	45.20	74.00	-28.80	peak		
2		2396.084	50.25	-20.95	29.30	54.00	-24.70	AVG		
3		2400.000	87.37	-20.93	66.44	74.00	-7.56	peak		
4		2400.000	70.02	-20.93	49.09	54.00	-4.91	AVG		
5	*	2402.000	117.22	-20.93	96.29	74.00	22.29	peak		

\*:Maximum data x:Over limit !:over margin

Operator: washington



Site Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m\_PEAK

Power: Battery 3.7V

Humidity: 55 %


Mode:DSS (TX2402)

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		2385.068	56.15	-19.85	36.30	74.00	-37.70	peak		
2		2385.068	38.25	-19.85	18.40	54.00	-35.60	AVG		
3		2400.000	83.22	-19.77	63.45	74.00	-10.55	peak		
4		2400.000	67.00	-19.77	47.23	54.00	-6.77	AVG		
5	*	2402.000	115.99	-19.76	96.23	74.00	22.23	peak		

\*:Maximum data    x:Over limit    !:over margin

Operator: washington



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m\_PEAK

Power: Battery 3.7V

Humidity: 55 %


Mode:DSS (TX2480)

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment			Height	Degree	
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.080	116.72	-20.71	96.01	74.00	22.01	peak		
2		2483.500	55.55	-20.72	34.83	74.00	-39.17	peak		
3		2483.500	37.15	-20.72	16.43	54.00	-37.57	AVG		
4		2490.540	57.78	-20.69	37.09	74.00	-36.91	peak		
5		2490.540	40.15	-20.69	19.46	54.00	-34.54	AVG		

\*:Maximum data x:Over limit !:over margin

Operator: washington



Site Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m\_PEAK

Power: Battery 3.7V

Humidity: 55 %

Mode:DSS (TX2480)


Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.160	115.29	-19.28	96.01	74.00	22.01	peak			
2		2483.500	54.62	-19.27	35.35	74.00	-38.65	peak			
3		2483.500	37.15	-19.27	17.88	54.00	-36.12	AVG			
4		2488.840	56.28	-19.23	37.05	74.00	-36.95	peak			
5		2488.840	39.55	-19.23	20.32	54.00	-33.68	AVG			

\*:Maximum data x:Over limit !:over margin

Operator: washington


For Hopping Mode:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2358.752	58.51	-21.04	37.47	74.00	-36.53	peak			
2		2358.752	42.12	-21.04	21.08	54.00	-32.92	AVG			
3		2400.000	85.57	-20.93	64.64	74.00	-9.36	peak			
4		2400.000	67.15	-20.93	46.22	54.00	-7.78	AVG			
5	*	2402.000	117.05	-20.93	96.12	74.00	22.12	peak			

\*:Maximum data    x:Over limit    !:over margin

Operator: washington



Site: Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m\_PEAK

Power: Battery 3.7V

Humidity: 55 %


Mode: Hopping

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2375.888	57.78	-19.92	37.86	74.00	-36.14	peak			
2		2375.888	40.25	-19.92	20.33	54.00	-33.67	AVG			
3		2400.000	78.22	-19.77	58.45	74.00	-15.55	peak			
4		2400.000	63.58	-19.77	43.81	54.00	-10.19	AVG			
5	*	2402.000	115.91	-19.76	96.15	74.00	22.15	peak			

\*:Maximum data    x:Over limit    !:over margin

Operator: washington



Site Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m\_PEAK

Power: Battery 3.7V

Humidity: 55 %


Mode:Hopping

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Height	Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.140	116.68	-20.71	95.97	74.00	21.97	peak			
2		2483.500	54.27	-20.72	33.55	74.00	-40.45	peak			
3		2483.500	37.14	-20.72	16.42	54.00	-37.58	AVG			
4		2488.920	56.01	-20.69	35.32	74.00	-38.68	peak			
5		2488.920	38.15	-20.69	17.46	54.00	-36.54	AVG			

\*:Maximum data    x:Over limit    !:over margin

Operator: washington



Site Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 C 3m\_PEAK

Power: Battery 3.7V

Humidity: 55 %

Mode: Hopping

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment			Height	Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2480.100	115.26	-19.28	95.98	74.00	21.98	peak			
2		2483.500	53.87	-19.27	34.60	74.00	-39.40	peak			
3		2483.500	37.14	-19.27	17.87	54.00	-36.13	AVG			
4		2489.260	56.46	-19.23	37.23	74.00	-36.77	peak			
5		2489.260	40.55	-19.23	21.32	54.00	-32.68	AVG			

\*:Maximum data    x:Over limit    !:over margin

Operator: washington

## 13. Antenna Application

### 13.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 13.2 Result



The EUT's antenna, permanent attached antenna, used a PCB antenna and integrated on PCB, The antenna's gain is 0dBi and meets the requirement.

**APPENDIX  
(Photos of EUT)**









-----The end-----