## RF Exposure evaluation

Product Description:Bluetooth headphone

Model Number: BT-1525 FCC ID: 2ABL8BT-1525

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power ( $P_t$ ) formula :  $P_t$ = ( $E \times d$ )  $^2$ /( $30 \times g_t$ )  $P_t$ =transmitter output power in watts  $g_t$ =numeric gain of the transmitting antenna (unitess) E=electric field strength in V/m d=measurement distance in meters (m)

According to the above test data, Emax=104.24dBuv/m=0.163V/m,d=3m,g<sub>t</sub>=1.58  $P_t$ = ( E x d ) <sup>2</sup>/ ( 30 x g<sub>t</sub> ) =(0.163x3)<sup>2</sup>/(30x1.58)=0.005045W=5.05mW

The result is rounded to one decimal place for comparison Worse case is as below: [2480MHz -5.05mW output power] (5.05mW /5mm) .[ $\sqrt{2.480}$ (GHz)]= 1.591<3.0 for 1-g SAR Then SAR evaluation is not required

**NOTE:** For the maximum power, you can refer FCC test report.