

Report No.: AGC01619140601FE08
Page 1 of 48

FCC Test Report

Report No.: AGC01619140601FE08

FCC ID : 2ABMFNT-267

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Car Bluetooth Handsfree

BRAND NAME : iPDA

MODEL NAME : NT-267

CLIENT : Shenzhen Pinda Technologies Ltd.

DATE OF ISSUE : Jul.09, 2014

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test aboratory and shall not be quoted out of context.

Page 2 of 48

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jul.09, 2014	Valid	Original Report

Page 3 of 48

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	
2.GENERAL INFORMATION	6
2.2 RELATED SUBMITTAL(S)/GRANT(S)	
2.3TEST METHODOLOGY	
2.4 TEST FACILITY	
2.5 SPECIAL ACCESSORIES	
2.6 EQUIPMENT MODIFICATIONS	
2.7 MEASUREMENT UNCERTAINTY	
3. SYSTEM TEST CONFIGURATION	8 8
3.2 EQUIPMENT USED IN TESTED SYSTEM	8
3.3. SUMMARY OF TEST RESULTS	3
4. DESCRIPTION OF TEST MODES	
5. ANTENNA REQUIREMENT 5.1. STANDARD APPLICABLE	
5.2. TEST RESULT	
6. TEST FACILITY	
7. RADIATED EMISSION	11
7.1 MEASUREMENT PROCEDURE	
7.3 LIMITS AND MEASUREMENT RESULT	
7.4 TEST RESULT (WORST MODULATION: GFSK)	
8. BAND EDGE EMISSION	
8.2. TEST SET-UP	
8.3. TEST RESULT	27
9. 6DB BANDWIDTH	
9.1. TEST PROCEDURE	
9.2. SUMMARY OF TEST RESULTS/PLOTS	
10. CONDUCTED OUTPUT POWER	33
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	33
10.3. LIMITS AND MEASUREMENT RESULT	34
11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	
11.1 MEASUREMENT PROCEDURE	36

Page 4 of 48

	11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	36
	11.3 LIMITS AND MEASUREMENT RESULT	36
12	P. FCC LINE CONDUCTED EMISSION TEST	
	12.1 LIMITS	39
	12.2 TEST SETUP	39
	12.3 PRELIMINARY PROCEDURE	40
	12.4 FINAL TEST PROCEDURE	40
	12.5 TEST RESULT OF POWER LINE	41
ΑF	PPENDIX A: PHOTOGRAPHS OF TEST SETUP	42
	PPENDIX B: PHOTOGRAPHS OF EUT	

Page 5 of 48

1. VERIFICATION OF COMPLIANCE

Shenzhen Pinda Technologies Ltd.
2nd Floor, 9th Building, 1st Area, Huaide Cuihai Industrial Base, Fengtang Road, Fuyong, Bao'an, Shenzhen, Guangdong, China
Shenzhen Pinda Technologies Ltd.
2nd Floor, 9th Building, 1st Area, Huaide Cuihai Industrial Base, Fengtang Road, Fuyong, Bao'an, Shenzhen, Guangdong, China
Car Bluetooth Handsfree
iPDA
NT-267
Jul.04, 2014 to Jul.08, 2014
None
Normal
AGCRT-US-BLE/RF (2013-03-01)

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with requirement of FCC Part 15 Rules requirement.

Water Zuo Jul.09, 2014

Checked By

Forrest Lei Jul.09, 2014

Authorized By

Solger Zhang Jul.09, 2014

Page 6 of 48

2.GENERAL INFORMATION 2.1PRODUCT DESCRIPTION

The EUT is designed as a "Car Bluetooth Handsfree". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

2.402 GHz to 2.480GHz
V4.0
GFSK
40 Channel(37 Hopping Channel,3 advertising Channel)
PCB Antenna
0dBi
N/A
N/A
DC 12V by DC source

Note: The USB cable can not be used for communication with PC. It's only for power supply.

2.2 RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2ABMFNT-267** filing to comply with Section 15.247of the FCC Part 15, Subpart C Rules.

2.3TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

Test has been referenced to the KDB558074 D01 DTS Meas Guidance v03r02

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions. The EUT was tested in all three orthogonal planes and the worse case was showed.

2.4 TEST FACILITY

All measurement facilities used to collect the measurement data are located at Attestation of Global Compliance (Shenzhen) Co, Ltd

2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China.

FCC register No.: 259865

Page 7 of 48

2.5 SPECIAL ACCESSORIES

Refer to section 2.2.

2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7 MEASUREMENT UNCERTAINTY

Radiation Emission:+/-3.2


Conduction Emission:+/-2.5

Page 8 of 48


3. SYSTEM TEST CONFIGURATION

3.1 CONFIGURATION OF TESTED SYSTEM

Configuration: Normal Operating



Configuration: Continuous TX



3.2 EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Car Bluetooth Handsfree	iPDA	NT-267	EUT
2	PC	Dell	INSPIRON	A.E
3	Control box	N/A	N/A	A.E

3.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§ 15.203	Antenna Requirement	Compliant
§15.209 §15.247(d)	Radiated Emission	Compliant
§15.247(d)	Band Edges	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247(b)	Conducted Power	Compliant
§15.247(e)	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.207	Line Conduction Emission	N/A

Note: N/A means not applicable.

Page 9 of 48

4. DESCRIPTION OF TEST MODES

The EUT has been operated in one modulation: GFSK.

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal Operating (BT)

Note:

- 1. All the test modes can be supply by DC Source, only the result of the worst case was recorded in the report if no any records.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

5. ANTENNA REQUIREMENT

5.1. STANDARD APPLICABLE

According to FCC 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

5.2. TEST RESULT

This product has a permanent antenna, fulfill the requirement of this section.

Page 10 of 48

6. TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.

ALL TEST EQUIPMENT LIST

ALL ILSI EQUITMENT LIST					
Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power Probe	R&S	NRP-Z23	100323	07/17/2013	07/16/2014
RF attenuator	N/A	RFA20db	68	N/A	N/A
Spectrum Analyzer	Agilent	E4440A	US41421290	07/17/2013	07/16/2014
Amplifier	EM	EM30180	0607030	02/28/2014	02/27/2015
Horn Antenna	EM	EM-AH-10180	67	04/19/2014	04/18/2015
Horn Antenna	A.H. Systems Inc.	SAS-574		07/17/2013	07/16/2014
EMI Test Receiver	Rohde & Schwarz	ESCI	100694	07/17/2013	07/16/2014
Bilogical Antenna	A.H. Systems Inc.	SAS-521-4	26	06/06/2014	06/05/2015
Loop Antenna	Daze	ZN30900N	SEL0097	07/17/2013	07/16/2014
Isolation Transformer	LETEAC	LTBK		07/17/2013	07/16/2014

Page 11 of 48

7. RADIATED EMISSION

7.1 MEASUREMENT PROCEDURE


 Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.


Page 12 of 48

7.2 TEST SETUP

RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Page 13 of 48

7.3 LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,

the test records reported below are the worst result compared to other modes.

7.4 TEST RESULT (Worst Modulation: GFSK)


RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

Page 14 of 48

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT:Car Bluetooth Handsfree

M/N:NT-267

Mode:Low Channel TX

Note:


Polarization:	Horizontal	Temperature: 2	6
Power:		Humidity: 60 %	,

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		52.6333	22.49	11.22	33.71	40.00	-6.29	peak			
2		63.9500	21.92	10.80	32.72	40.00	-7.28	peak			
3		104.3667	25.68	10.78	36.46	43.50	-7.04	peak			
4	*	120.5333	27.60	11.95	39.55	43.50	-3.95	peak			
5		143.1667	15.19	15.22	30.41	43.50	-13.09	peak			
6		264.4166	14.53	14.34	28.87	46.00	-17.13	peak			

Page 15 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance: 3m

M/N:NT-267

Mode:Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	İ	62.3333	29.19	7.24	36.43	40.00	-3.57	peak			
2	*	70.4167	33.22	4.16	37.38	40.00	-2.62	peak			
3		122.1500	28.98	7.76	36.74	43.50	-6.76	peak			
4		136.7000	22.18	13.82	36.00	43.50	-7.50	peak			
5		152.8667	16.02	15.28	31.30	43.50	-12.20	peak			
6		180.3500	12.43	13.98	26.41	43.50	-17.09	peak			


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 16 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT:Car Bluetooth Handsfree

M/N:NT-267

Mode:Middle channel TX

Note:

Polarization:	Horizontal	Temperatur	e: 26
Power:		Humidity: 6	60 %

Distance: 3m


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		52.6333	22.32	11.22	33.54	40.00	-6.46	peak			
2		102.7500	24.75	10.67	35.42	43.50	-8.08	peak			
3	*	120.5333	27.36	11.95	39.31	43.50	-4.19	peak			
4		133.4667	21.20	14.11	35.31	43.50	-8.19	peak			
5		224.0000	17.37	12.91	30.28	46.00	-15.72	peak			
6		264.4166	12.72	14.34	27.06	46.00	-18.94	peak			

Temperature: 26

Humidity: 60 %

Page 17 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT:Car Bluetooth Handsfree

LOT. Car Didelocti i Hali

M/N:NT-267

Mode:Middle channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	70.4167	31.88	4.16	36.04	40.00	-3.96	peak			
2		120.5333	29.41	7.08	36.49	43.50	-7.01	peak			
3		136.7000	22.17	13.82	35.99	43.50	-7.51	peak			
4		152.8667	15.23	15.28	30.51	43.50	-12.99	peak			
5		180.3500	11.55	13.98	25.53	43.50	-17.97	peak			
6		224.0000	13.90	11.35	25.25	46.00	-20.75	peak			

Power:

Distance: 3m

Polarization: Vertical


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 18 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT:Car Bluetooth Handsfree

M/N:NT-267

Mode:High channel TX

Note:


Polarization:	Horizontal	Temperature: 26	6
Power:		Humidity: 60 %	

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		65.5667	22.53	10.65	33.18	40.00	-6.82	peak			
2	*	125.3833	26.91	12.76	39.67	43.50	-3.83	peak			
3		148.0167	17.84	15.25	33.09	43.50	-10.41	peak			
4		172.2667	15.52	12.72	28.24	43.50	-15.26	peak			
5		224.0000	16.45	12.91	29.36	46.00	-16.64	peak			
6		264.4166	9.97	14.34	24.31	46.00	-21.69	peak			

Page 19 of 48

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1 Limit: FCC Class B 3M Radiation EUT:Car Bluetooth Handsfree

M/N:NT-267

Mode:High channel TX

Note:

Polarization:	Vertical	Temperature: 26
Power:		Humidity: 60 %

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1	*	70.4167	33.05	4.16	37.21	40.00	-2.79	peak			
2		122.1500	28.07	7.76	35.83	43.50	-7.67	peak			
3		130.2332	24.09	11.13	35.22	43.50	-8.28	peak			
4		152.8667	15.97	15.28	31.25	43.50	-12.25	peak			
5		180.3500	10.66	13.98	24.64	43.50	-18.86	peak			
6		224.0000	11.86	11.35	23.21	46.00	-22.79	peak			

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 20 of 48

RADIATED EMISSION ABOVE 1GHZ

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267


Mode: Low channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1	*	2402.000	91.61	-9.68	81.93	74.00	7.93	peak			
2		3413.333	46.50	-7.97	38.53	74.00	-35.47	peak			
3		4200.000	43.05	-4.13	38.92	74.00	-35.08	peak			

Page 21 of 48

RADIATED EMISSION TEST-(ABOVE 1GHZ)-LOW CHANNEL-VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267

Mode: Low channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		1453.333	53.00	-15.40	37.60	74.00	-36.40	peak			
2	*	2402.000	91.45	-9.68	81.77	74.00	7.77	peak			
3		2786.667	48.57	-8.88	39.69	74.00	-34.31	peak			


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 22 of 48

RADIATED EMISSION TEST-(ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267


Mode: Middle channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2440.000	93.26	-9.64	83.62	74.00	9.62	peak			
2		3580.000	49.96	-7.40	42.56	74.00	-31.44	peak			
3		4646.667	44.08	-2.73	41.35	74.00	-32.65	peak			

Page 23 of 48

RADIATED EMISSION TEST-(ABOVE 1GHZ)-MIDDLE CHANNEL-VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267

Mode: Middle channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		1193.333	54.65	-15.51	39.14	74.00	-34.86	peak			
2	*	2440.000	93.17	-9.64	83.53	74.00	9.53	peak			
3		3460.000	48.71	-7.93	40.78	74.00	-33.22	peak			


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 24 of 48

RADIATED EMISSION TEST-(ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267


Mode: High channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	92.96	-9.59	83.37	74.00	9.37	peak			
2		3200.000	48.62	-8.17	40.45	74.00	-33.55	peak			
3		3933.333	46.41	-5.22	41.19	74.00	-32.81	peak			

Page 25 of 48

RADIATED EMISSION TEST-(ABOVE 1GHZ)-HIGH CHANNEL-VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267

Mode: High channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1		1733.333	49.67	-12.93	36.74	74.00	-37.26	peak			
2	*	2480.000	92.77	-9.59	83.18	74.00	9.18	peak			
3		3253.333	46.41	-8.12	38.29	74.00	-35.71	peak			

RESULT: PASS

Note: 5~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor+ Cable loss-Amplifier gain,

Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Page 26 of 48

8. BAND EDGE EMISSION

8.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the bottom operation frequency individually.
- 2. Set SPA Start or Stop Frequency=Operation Frequency , RBW>=1%span, VBW>=RBW, Center frequency =Operation frequency
- 3. The band edges was measured and recorded.


8.2. TEST SET-UP

Radiated same as 7.2

Page 27 of 48

8.3. TEST RESULT

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2264.233	53.39	-9.83	43.56	74.00	-30.44	peak			
2		2390.000	53.76	-9.69	44.07	74.00	-29.93	peak			
3	*	2402.000	91.37	-9.68	81.69	74.00	7.69	peak			

Page 28 of 48

TEST PLOT OF BAND EDGE FOR LOW CHANNEL - Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2250.567	53.59	-9.84	43.75	74.00	-30.25	peak			
2		2390.000	53.06	-9.69	43.37	74.00	-30.63	peak			
3	*	2402.000	91.37	-9.68	81.69	74.00	7.69	peak			

Page 29 of 48

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1	*	2480.000	92.54	-9.59	82.95	74.00	8.95	peak			
2		2483.500	50.60	-9.59	41.01	74.00	-32.99	peak			
3		2498.460	51.45	-9.57	41.88	74.00	-32.12	peak			

Page 30 of 48

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT:Car Bluetooth Handsfree Distance:

M/N:NT-267

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	92.81	-9.59	83.22	74.00	9.22	peak			
2		2483.500	52.08	-9.59	42.49	74.00	-31.51	peak			
3		2492.483	53.17	-9.58	43.59	74.00	-30.41	peak			

Page 31 of 48

9. 6DB BANDWIDTH

9.1. TEST PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW≥3*RBW.
- 4. Set SPA Trace 1 Max hold, then View.

9.2. SUMMARY OF TEST RESULTS/PLOTS


Channel	6dB Bandwidth (KHz)	Minimum Limit (KHz)	Pass/Fail
Low	697		Pass
Middle	678	500KHz	Pass
High	690		Pass

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Page 32 of 48

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 33 of 48

10. CONDUCTED OUTPUT POWER

10.1. MEASUREMENT PROCEDURE

For peak power test:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, middle and the bottom operation frequency individually.
- 3. Use the following spectrum analyzer settings:
 - a) Set the RBW ≥ DTS bandwidth.
- b) Set VBW ≥ 3 RBW.
- c) Set span ≥ 3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.
- 4. Allow the trace to stabilize.
- 5. Record the result form the Spectrum Analyzer.

For average power test:

- 1. Connect EUT RF output port to power probe through an RF attenuator.
- 2. Connect the power probe to the PC.
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Record the maximum power from the software.
- 5. The maximum peak power shall be less 1W (30dBm).

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements


10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



Page 34 of 48


10.3. LIMITS AND MEASUREMENT RESULT


Channel	Average Power (dBm)	Peak Power (dBm)	Applicable Limits (dBm)	Pass/Fail
Low Channel	-0.28	1.57	30	Pass
Middle Channel	1.97	3.86	30	Pass
High Channel	1.22	3.13	30	Pass



Page 35 of 48








Page 36 of 48

11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 11.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the span to 1.5times the DTS bandwidth, RBW: 3kHz<=RBW<=100KHz, VBW>=3*RBW
- 4). Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




11.3 LIMITS AND MEASUREMENT RESULT


Channel No.	PSD (dBm)	Limit (dBm)	Result
Low Channel	-14.23	8	Pass
Middle Channel	-12.07	8	Pass
High Channel	-12.57	8	Pass

Page 37 of 48

TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL








Page 38 of 48

TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL



Page 39 of 48


12. FCC LINE CONDUCTED EMISSION TEST

12.1 LIMITS

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

^{**}Note: 1. The lower limit shall apply at the transition frequency.

12.2 TEST SETUP



A: Powered through filter

^{2.} The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

Page 40 of 48

12.3 PRELIMINARY PROCEDURE

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) All support equipments received AC120V/60Hz power from a LISN, if any.
- 5) The EUT received power by adapter which received power by a LISN.
- 6) The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test. Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 FINAL TEST PROCEDURE

- 10) EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 11) 2) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 12) 3) The test data of the worst case condition(s) was reported on the Summary Data page.

Page 41 of 48


12.5 TEST RESULT OF POWER LINE


N/A

Page 42 of 48

APPENDIX A: PHOTOGRAPHS OF TEST SETUP







Page 43 of 48

APPENDIX B: PHOTOGRAPHS OF EUT

All VIEW OF EUT







Page 44 of 48








Page 45 of 48











Page 46 of 48


RIGHT VIEW OF EUT






Page 47 of 48





Page 48 of 48





----END OF REPORT----