

Shenzhen CTL Electromagnetic Technology Co., Ltd. Tel: +86-755-89486194 Fax: +86-755-26636041

## FCC PART 15 SUBPART C TEST REPORT

FCC Part 15.249

Report Reference No..... CTL1312192005-WF

Compiled by

Tackychen

Luy Ch:

Luy Ch: File administrators Jacky Chen ( position+printed name+signature)..:

Name of the organization performing

the tests

Test Engineer Tracy Qi

( position+printed name+signature)...

Approved by

( position+printed name+signature)..: Manager Tracy Qi

Date of issue....: Dec. 26, 2013

Shenzhen CTL Electromagnetic Technology Co., Ltd. Representative Laboratory Name .:

Address....: Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road,

Nanshan, Shenzhen 518055 China.

Test Firm....: **Bontek Compliance Testing Laboratory Ltd** 

Road, Nanshan, Shenzhen, China

Applicant's name..... **Jenesis Holdings Limited** 

7F, Kyodo Building Mansei, 2-2-17, Sotokanda, Chiyoda-ku, Address.....

Tokyo, Japan 101-0021

Test specification:

Standard .....: FCC Part 15.249: Operation within the bands 920-928 MHz. 2400-

2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator.....: Shenzhen CTL Electromagnetic Technology Co., Ltd.

Master TRF...... Dated 2011-01

#### Shenzhen CTL Electromagnetic Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Electromagnetic Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Electromagnetic Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....: **Bluetooth Remote Control** 

Trade Mark .....: Growthfeel

Models/Type reference....: GFRM-0002

Modulation ....: **GFSK** 

Work Frequency...... 2402 MHz~2480 MHz

Antenna Type..... internal

FCC ID ...... 2ABMPGFRM-0002

Result..... Positive

## TEST REPORT

Test Report No. :	CTL1312192005-WF	Dec. 26, 2013	
rest Report No	T NO.: C1L1312192005-WF	Date of issue	

Equipment under Test : Bluetooth Remote Control

Model /Type : GFRM-0002

Applicant : Jenesis Holdings Limited

Address : 7F, Kyodo Building Mansei, 2-2-17, Sotokanda, Chiyoda-ku,

Tokyo, Japan 101-0021

Manufacturer Shenzhen Meidi Electronic Co.,Ltd

Address Room208, 2F, Block A, Min You Industrious Center, No.168,

Baoyuan Road, Bao'an District, Shenzhen, Guangdong, China

Report No.: CTL1312192005-WF

Tool Beault	ATTEN OF TO	
Test Result according to the standards on page 4:	Positive	

Tilectromagnetic Techno

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

Page 3 of 27

1. TEST STANDARDS	<u>4</u>
2. SUMMARY	
2.1. General Remarks	E
2.2. Equipment Under Test	
2.3. Short description of the Equipment under Test (EUT)	
2.4. EUT operation mode	
2.5. EUT configuration	6
2.6. Related Submittal(s) / Grant (s)	
2.7. Modifications	
A TEAT ENVIRONMENT	_
3. TEST ENVIRONMENT	<u></u>
. 1.	
3.1. Address of the test laboratory	7
3.2. Test Facility	7
3.3. Environmental conditions	7
3.4. Configuration of Tested System	7
3.5. Statement of the measurement uncertainty	8
3.6. Equipments Used during the Test	9
CO NE THE	
A TEST CONDITIONS AND RESULTS	10
4. TEST CONDITIONS AND RESULTS	
4.1. Conducted Emissions Test	
4.1. Conducted Emissions Test	10
4.2. Radiated Emission Test4.3. Band Edge Measurement	12
5. ANTENNA REQUIREMENT	2 1
6. TEST SETUP PHOTOS OF THE EUT	22
5. ANTENNA REQUIREMENT6. TEST SETUP PHOTOS OF THE EUT	
Villagnette	
7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	<u>23</u>

## Report No.: CTL1312192005-WF

# 1. TEST STANDARDS

The tests were performed according to following standards:

**ANSI C63.4-2003** 



## 2. SUMMARY

## 2.1. General Remarks

Date of receipt of test sample : Dec. 20, 2013

Testing commenced on : Dec. 20, 2013

Testing concluded on : Dec. 26, 2013

## 2.2. Equipment Under Test

## Power supply system utilised

Power supply voltage : o 120V / 60 Hz o 115V / 60Hz

o 12 V DC o 24 V DC

Other (specified in blank below)

DC 3V(A76\*2 coin battery)

## 2.3. Short description of the Equipment under Test (EUT)

The EUT is a Bluetooth remote control work at 2402~2480 MHz. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	(31)	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

Power Range: -5dBm~0dBm

Modulation: GFSK

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

V1.0 Page 6 of 27 Report No.: CTL1312192005-WF

## 2.4. EUT operation mode

Test Mode(TM)	est Mode(TM) Description	
TM1	Bottom Channel Transmitting	/
TM2	Middle Channel Transmitting	/
TM3	Top Channel Transmitting	/

The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis).

The following data show only with the worst case setup.

The worst case of Y axis was reported.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

Remark: The worst case mode is TM1(1Mbps) reported for unwanted emission and band edge test.

### 2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- o supplied by the manufacturer
- o supplied by the lab

## 2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2ABMPGFRM-0002 filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

CITIO Technology of the Command Technology o

### 2.7. Modifications

No modifications were implemented to meet testing criteria.

## 3. TEST ENVIRONMENT

## 3.1. Address of the test laboratory

Bontek Compliance Testing Laboratory Ltd 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

## 3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

## IC Registration No.: 7631A

The 3m alternate test site of Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on March, 2011.

### FCC-Registration No.: 338263

Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March 24, 2008.

### 3.3. Environmental conditions

During the measurement the en Temperature:	nvironmental conditions were within the listed 15-35 ° C	ranges:
Humidity:	30-60 %	0.3
Atmospheric pressure:	950-1050mbar	Ó

## 3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System

EUT	
EUT	

V1.0

## 3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Bontek Compliance Testing Laboratory Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Bontek laboratory is reported:

Test Range		Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	1~26.5GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3,20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



# 3.6. Equipments Used during the Test


No.	Equipment	Manufacturer	Model No.	S/N	Calibration date	Calibration due date
1	EMI Test Receiver	R&S	ESCI	100687	2013-4-5	2014-4-4
2	EMI Test Receiver	R&S	ESPI	100097	2013-7-25	2014-7-24
3	Amplifier	HP	8447D	1937A02492	2013-4-5	2014-4-4
4	Single Power Conductor Module	FCC	FCC-LISN-5- 50-1-01- CISPR25	07101	2013-4-5	2014-4-4
5	Single Power Conductor Module	FCC	FCC-LISN-5- 50-1-01- CISPR25	07102	2013-4-5	2014-4-4
6	Positioning Controller	C&C	CC-C-1F	MF7802113	N/A	N/A
7	Signal generator	Rhode & Schwarz	SMIQ 03HD + option SM-B1, SMIQB11, SMIQB12, SMIQB14, SMIQB17, SMIQB20	1125.5555.46	2013-4-5	2014-4-4
8	GSM system simulator	Rhode & Schwarz	CMU200 + option K20, K21, K22, K23, K24, K27, K28, K29, K42, K65, B12, B41, B52, B66, B56	1100.0008.34	2013-4-5	2014-4-4
9	GSM system simulator	Agilent	8960 Series 10 E1985A + GSM_AMPS	B.01.76 GB42450443	2013-4-5	2014-4-4
10	Spectrum Analyzer	Agilent	E4404B	US41192833	2013-4-5	2014-4-4
11	6dB Attenuator	Atten	Attenuator	DC-4GHz	2013-4-5	2014-4-4
12	Digital Multimeter	Fluke	15B	91280239	2013-4-5	2014-4-4
13	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2013-4-9	2014-4-8
14	Horn Antenna	SCHWARZBECK	BBHA9120A	0499	2012-11-27	2014-11-25
15	Horn Antenna	SCHWARZBECK	BBHA9170	1562	2012-11-27	2014-11-25
16	Active Loop Antenna	DAZE	ZN30900A	1200	2013-4-5	2014-4-4
17	9kHz-2.4GHz signal generator 2024	MARCONI	10S/6625-99- 457-8730	112260/042	2013-4-5	2014-4-4
18	10dB attenuator	ELECTRO- METRICS	EM-7600	836	2013-4-5	2014-4-4
19	Spectrum Analyzer	R&S	FSP	100397	2012-11-2	2014-10-31
20	Broadband preamplifier	SCH WARZBECK	BBV9718	9718-182	2013-4-5	2014-4-4
21	Temperature & Humidity Chamber	TOPSTAT	TOS-831A	3438A05208	2013-4-5	2014-4-4

V1.0 Page 10 of 27 Report No.: CTL1312192005-WF

## 4. TEST CONDITIONS AND RESULTS

#### 4.1. Conducted Emissions Test

#### **TEST CONFIGURATION**



#### **TEST PROCEDURE**

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4.
- 2 Support equipment, if needed, was placed as per ANSI C63.4.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4 If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

The RBW/VBW for 150KHz to 30MHz: 9KHz

## CONDUCTED POWER LINE EMISSION LIMIT

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following:

F=====================================	Maximum RF Line Voltage (dBμV)			
Frequency (MHz)	CLASS A CLAS		CLASS B	
(111112)	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

<sup>\*</sup> Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

## **TEST RESULTS**

Owing the device is powered by 3V Coin Cell, not applicable to this device.




V1.0 Page 12 of 27 Report No.: CTL1312192005-WF


## 4.2. Radiated Emission Test

## **TEST CONFIGURATION**


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



V1.0 Page 13 of 27 Report No.: CTL1312192005-WF

#### FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)	
RA = Reading Amplitude	AG = Amplifier Gain	
AF = Antenna Factor		

#### RADIATION LIMIT

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (μV/m)
// -	AVIANI	70 17 1	. ,
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500
N			

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

#### **TEST PROCEDURE**

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7. Based on the Frequency Generator in the device include 16MHz. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

#### Note:


Three axes are chosen for pretest, the Y axis is the worst mode for final test. For battery operated equipment, the equipment tests shall be performed using a new battery.


V1.0 Page 14 of 27 Report No.: CTL1312192005-WF

### **TEST RESULTS**

All the test modes (TM1, TM2, and TM3) completed for test. The worst case of Radiated Emission is TM1; the test data of this mode was reported.

Below 1GHz Test Results:







### MEASUREMENT RESULT: "CTL131225031\_red"

1	2/25/2013 4	:51PM							
	Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
	30.000000	23.60	21.1	40.0	16.4		0.0	0.00	VERTICAL
	70.740000	12.50	8.4	40.0	27.5		0.0	0.00	VERTICAL
	136.700000	18.30	14.7	43.5	25.2		0.0	0.00	VERTICAL
	181.320000	17.10	13.3	43.5	26.4		0.0	0.00	VERTICAL
	551.860000	25.20	21.1	46.0	20.8		0.0	0.00	VERTICAL
	957.320000	31.40	26.7	46.0	14.6		0.0	0.00	VERTICAL

#### Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.





#### MEASUREMENT RESULT: "CTL131225030 red"

12/25/2013 4: Frequency MHz	:50PM Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	22.20	21.1	40.0	17.8		0.0	0.00	HORIZONTAL
68.800000	11.90	8.4	40.0	28.1		0.0	0.00	HORIZONTAL
134.760000	16.40	14.8	43.5	27.1		0.0	0.00	HORIZONTAL
202.660000	17.80	14.4	43.5	25.7		0.0	0.00	HORIZONTAL
546.040000	24.10	20.9	46.0	21.9		0.0	0.00	HORIZONTAL
930.160000	31.20	26.4	46.0	14.8		0.0	0.00	HORIZONTAL

#### Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.

V1.0 Page 16 of 27 Report No.: CTL1312192005-WF

#### **Above 1 GHz Test Results:**

Freq. (MHz)	Ant.Pol. H/V	DetectorMode (PK/AV)	Reading (dBuV)	Ant./CL/ Amp. CF(dB)	Actual FS (dBuV/m)	Limit3m (dBuV/m)	Safe Margin (dB)
2480	V	Peak	76.17	-3.30	72.87	113.98	-41.11
2480	Н	Peak	71.53	-3.30	68.23	113.98	-45.75
4960	V	Peak	48.20	3.90	52.10	74.00	-21.90
4960	Н	Peak	44.51	3.90	48.41	74.00	-25.59
7440	V						
7440	Н						
Others							

Freq.	Ant.Pol.	DetectorMode	Reading	Ant./CL/	Actual FS	Limit3m	Safe Margin
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB)	(dBuV/m)	(dBuV/m)	(dB)
2441	V	Peak	75.23	-3.40	71.83	113.98	-42.15
2441	Н	Peak	70.86	-3.40	67.46	113.98	-46.52
4882	V	Peak	49.18	3.70	52.88	74.00	-21.12
4882	Н	Peak	43.52	3.70	47.22	74.00	-26.78
7323	V						
7323	Н						
Others							

Freq.	Ant.Pol.	DetectorMode	Reading	Ant./CL/	Actual FS	Limit3m	Safe Margin
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB)	(dBuV/m)	(dBuV/m)	(dB)
2402	V	Peak	74.74	-3.30	71.44	113.98	-42.54
2402	Н	Peak	70.93	-3.30	67.63	113.98	-46.35
4804	V	Peak	48.91	3.50	52.41	74.00	-21.59
4804	Н	Peak	44.36	3.50	47.86	74.00	-26.14
7206	V						
7206	Н						
Others							

#### Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 72.87dBuV/m(PK Value) <93.98(AV Limit), at harmonic 52.88 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.

١

## 4.3. Band Edge Measurement

#### **TEST CONFIGURATION**

Same as Section 4.2

#### **TEST PROCEDURE**

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength.

The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBM to 300 KHz, to measure the conducted peak band edge.

#### **LIMIT**


FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

#### **TEST RESULTS**

#### **Radiated Test:**


Operation Mode: TX on Bot Channel

Polarity: Hor.



Operation Mode: TX on Bot Channel

Polarity: Ver.




### Note:

- 1. The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.
- The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: TX on Top Channel


Polarity: Hor.



Report No.: CTL1312192005-WF

Operation Mode: TX on Top Channel

Polarity: Ver.



#### Note:

- 1. The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.
- 2. The average measurement was not performed when the peak measured data under the limit of average detection.

C. T. C. Technology of the Comagnetic Technol

V1.0 Page 21 of 27 Report No.: CTL1312192005-WF

## 5. Antenna Requirement

#### **Standard Applicable**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **Antenna Connected Construction**

The antenna used in this product is a PCB Antenna, The directional gains of antenna used for transmitting is 0 dBi.



## Report No.: CTL1312192005-WF

# 6. Test Setup Photos of the EUT








V1.0 Page 23 of 27 Report No.: CTL1312192005-WF


# 7. External and Internal Photos of the EUT


## **External Photos**











## **Internal Photos**

