

Guangdong Changhong Electronics Co., Ltd.

Application For Certification

FCC ID: 2ABNOUD49YC5500UA-1

LED TV

Model: UD49YC5500UA

2.4GHz Transceiver

Report No.: 140811026SZN-002

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-13]

Prepared and Checked by: Approved by:

Sign on file

Hardy Suo Assistant Engineer Andy Yan Project Engineer

Date: September 12, 2014

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample
 may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_TX_b

LIST OF EXHIBITS

INTRODUCTION

EXHIBIT 1: General Description

EXHIBIT 2: System Test Configuration

EXHIBIT 3: Emission Results

EXHIBIT 4: Equipment Photographs

EXHIBIT 5: Product Labelling

EXHIBIT 6: Technical Specifications

EXHIBIT 7: Instruction Manual

EXHIBIT 8: Miscellaneous Information

EXHIBIT 9: Test Equipment List

TRF No.: FCC 15C_TX_b

MEASUREMENT/TECHNICAL REPORT

Guangdong Changhong Electronics Co., Ltd.

MODEL: UD49YC5500UA

FCC ID: 2ABNOUD49YC5500UA-1

This report concerns (check one:)	Original Grant <u>X</u>	Class II Change
Equipment Type: DXX - Part 15 Low Pow	er Communication Devi	<u>ce Transmitter</u>
Deferred grant requested per 47 CFR 0.4	57(d)(1)(ii)? Yes	No _X_
	If yes, defer until	: date
Company Name agrees to notify the Com	mission by:	
of the intended date of announcement of date.	the product so that the	date grant can be issued on that
Transition Rules Request per 15.37?	Yes	No <u>X</u>
If no, assumed Part 15, Subpart C for Edition] provision.	intentional radiator –	the new 47 CFR [10-1-13
Report prepared by:		
	Hardy Suo Intertek Testing Servic Kejiyuan Branch 6F, Block D, Huahan E Nanshan District, Sher Phone: (86 755) 8614 Fax: (86 755) 860	Building, Langshan Road, nzhen, P. R. China 4 0743

TRF No.: FCC 15C_TX_b

Table of Contents

1.0 General Description	2
1.1 Product Description	2
1.2 Related Submittal(s) Grants	2
1.3 Test Methodology	2
1.4 Test Facility	2
·	
2.0 System Test Configuration	4
2.1 Justification	4
2.2 EUT Exercising Software	4
2.3 Special Accessories	
2.4 Equipment Modification	
2.5 Measurement Uncertainty	5
2.6 Support Equipment List and Description	5
3.0 Emission Results	
3.1 Radiated Test Results	
3.1.1 Field Strength Calculation	
3.1.2 Radiated Emission Configuration Photograph	
3.1.3 Radiated Emissions	
3.1.4 Transmitter Spurious Emissions	
3.2 Conducted Emission at Mains Termina	
3.2.1 Conducted Emissions Configuration Photograph	
3.2.2 Conducted Emissions	15
4.0 Equipment Photographs	19
5.0 Product Labelling	21
5.0 Froduct Labelling	∠ 1
6.0 Technical Specifications	23
7.0 Instruction Manual	25
8.0 Miscellaneous Information	27
8.1 Bandedge Plot	
8.2 Emissions Test Procedures	30
0.0 Toet Equipment List	33

TRF No.: FCC 15C_TX_b

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
Test Report	Bandedge Plot	bandedge.pdf
Test Report	20dB BW Plot	bw.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

EXHIBIT 1 GENERAL DESCRIPTION

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a LED TV with 2.4GHz wireless transmission function operating in 2409-2413MHz. The EUT is powered by AC 100-240V, 50/60Hz. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is an application for certification of a transceiver for the LED TV which has 2.4GHz wireless transmission function, and other digital functions were reported in the verification report: 140811023SZN-001, and related report for PC peripheral is subjected to FCC Report No.: 140811026SZN-001, and there has a Remote Control which associated with this EUT, was already filed.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

TRF No.: FCC 15C_TX_b

EXHIBIT 2 SYSTEM TEST CONFIGURATION

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The EUT was powered by AC 120V/60Hz during the test.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during testing was designed to exercise the various system components in a manner similar to a typical use.

2.3 Special Accessories

No special accessories used.

2.4 Equipment Modification

Any modifications installed previous to testing by Guangdong Changhong Electronics Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Kejiyuan Branch.

TRF No.: FCC 15C_TX_b

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

Description	Manufacturer	Model No.		
USB Memory	TOSHIBA	UHYBS-004G-BL		
Dummy Load	N/A	N/A		
VGA Cable	HP	Unshielded, Length 180cm		
HDMI Cable*3	N/A	Unshielded, Length 110cm		
HDMI Streaming Stick	ROKU	3400X		
Component In Cable	N/A	Unshielded, Length 120cm		
PC Audio Input Cable	N/A	Unshielded, Length 150cm		
Digital Audio Out Cable	N/A	Unshielded, Length 120cm		
Audio Cable (RL)	N/A	Unshielded, Length 120cm		
Audio Output Cable	N/A	Unshielded, Length 120cm		
Tuner Resister	N/A	75ohm		
Remote controller	CHANGHONG	N/A		

TRF No.: FCC 15C_TX_b

EXHIBIT 3 EMISSION RESULTS

Emission Results 3.0

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

FS = RA + AF + CF - AG + PD

Where FS = Field Strength in $dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $RA = 62.0 dB\mu V$

AF = 7.4 dB

CF = 1.6 dB

 $AG = 29.0 \, dB$

PD = 0 dB

 $FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \, dB\mu V/m$

Level in μ V/m = Common Antilogarithm [(42 dB μ V/m)/20] = 125.9 μ V/m

TRF No.: FCC 15C_TX_b

3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

3.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission at 166.770 MHz

Judgement: Passed by 6.3 dB

TEST PERSONNEL:

Sign on file

Hardy Suo, Assistant Engineer
Typed/Printed Name

September 09, 2014
Date

TRF No.: FCC 15C_TX_b

Applicant: Guangdong Changhong Electronics Co., Ltd.

Model: UD49YC5500UA

Sample: 1/1

Worst Case Operating Mode: 2.4 GHz wireless transmission

Date of Test: September 09, 2014

Table 1

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	132.335	45.7	20.0	5.6	31.3	43.5	-12.2
Horizontal	165.315	48.3	20.0	8.4	36.7	43.5	-6.8
Horizontal	216.240	39.8	20.0	11.7	31.5	46.0	-14.5
Vertical	63.950	25.9	20.0	18.3	24.2	40.0	-15.8
Vertical	82.865	36.7	20.0	15.7	32.4	40.0	-7.6
Vertical	166.770	51.8	20.0	5.4	37.2	43.5	-6.3

NOTES: 1. Quasi-Peak detector is used except for others stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. All emissions are below the QP limit.

TRF No.: FCC 15C_TX_b

3.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission at 9636.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 6.6 dB

TEST PERSONNEL:

Sign on file

<u>Hardy Suo, Assistant Engineer</u> *Typed/Printed Name*

September 09, 2014

Date

TRF No.: FCC 15C_TX_b

Applicant: Guangdong Changhong Electronics Co., Ltd.

Model: UD49YC5500UA

Sample: 1/1

Worst Case Operating Mode: Transmitting

Date of Test: September 09, 2014

Table 2

Radiated Emissions

(2409MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,	,	Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)				
Horizontal	2409.000	108.0	36.7	28.5	99.8	114.0	-14.2
Horizontal	4818.000	66.4	36.7	28.5	58.2	74.0	-15.8
Horizontal	7227.000	65.3	36.1	33.1	62.3	74.0	-11.7
Horizontal	9636.000	63.2	36.2	37.8	64.8	74.0	-9.2

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2409.000	90.5	36.7	28.5	82.3	94.0	-11.7
Horizontal	4818.000	48.3	36.7	28.5	40.1	54.0	-13.9
Horizontal	7227.000	46.2	36.1	33.1	43.2	54.0	-10.8
Horizontal	9636.000	45.8	36.2	37.8	47.4	54.0	-6.6

- Notes: 1. Peak Detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).
 - 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 - 3. Negative value in the margin column shows emission below limit.
 - 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Hardy Suo

TRF No.: FCC 15C_TX_b

Applicant: Guangdong Changhong Electronics Co., Ltd.

Model: UD49YC5500UA

Sample: 1/1

Worst Case Operating Mode: Transmitting

Date of Test: September 09, 2014

Table 3

Radiated Emissions

(2411MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2411.000	108.3	36.7	28.5	100.1	114.0	-13.9
Horizontal	4822.000	69.3	36.7	28.5	61.1	74.0	-12.9
Horizontal	7233.000	65.2	36.1	33.1	62.2	74.0	-11.8
Horizontal	9644.000	61.5	36.2	37.8	63.1	74.0	-10.9

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2411.000	89.6	36.7	28.5	81.4	94.0	-12.6
Horizontal	4822.000	48.4	36.7	28.5	40.2	54.0	-13.8
Horizontal	7233.000	47.4	36.1	33.1	44.4	54.0	-9.6
Horizontal	9644.000	45.7	36.2	37.8	47.3	54.0	-6.7

Notes: 1. Peak Detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Hardy Suo

TRF No.: FCC 15C_TX_b

Applicant: Guangdong Changhong Electronics Co., Ltd.

Model: UD49YC5500UA

Sample: 1/1

Worst Case Operating Mode: Transmitting

Date of Test: September 09, 2014

Table 4

Radiated Emissions

(2413MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2413.000	107.0	36.7	28.5	98.8	114.0	-15.2
Horizontal	4826.000	65.6	36.7	28.5	57.4	74.0	-16.6
Horizontal	7239.000	65.8	36.1	33.1	62.8	74.0	-11.2
Horizontal	9652.000	62.1	36.2	37.8	63.7	74.0	-10.3

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dB µV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2413.000	88.9	36.7	28.5	80.7	94.0	-13.3
Horizontal	4826.000	48.3	36.7	28.5	40.1	54.0	-13.9
Horizontal	7239.000	47.3	36.1	33.1	44.3	54.0	-9.7
Horizontal	9652.000	44.9	36.2	37.8	46.5	54.0	-7.5

Notes: 1. Peak Detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Hardy Suo

TRF No.: FCC 15C_TX_b

- 3.2 Conducted Emission at Mains Terminal
- 3.2.1 Conducted Emissions Configuration Photograph

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

3.2.2 Conducted Emissions

Worst Case Neutral-Conducted Configuration At

0.298 MHz

Judgement: Passed by 9.6 dB margin

TEST PERSONNEL:

Sign on file

Hardy Suo, Assistant Engineer
Typed/Printed Name

September 09, 2014

Date

TRF No.: FCC 15C_TX_b

Date of Test: September 09, 2014

Applicant: Guangdong Changhong Electronics Co., Ltd.


Model: UD49YC5500UA

Sample: 1/1

Worst Case Operating Mode: 2.4 GHz wireless transmission

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.182	45.4	L1	9.8	19.0	64.4
0.298	40.5	L1	9.8	19.8	60.3
0.698	35.8	L1	10.0	20.2	56.0
0.922	33.7	L1	9.9	22.4	56.0
2.910	40.2	L1	9.9	15.8	56.0
10.054	34.3	L1	10.2	25.7	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.182	36.9	L1	9.8	17.5	54.4
0.298	40.5	L1	9.8	9.8	50.3
0.698	25.6	L1	10.0	20.4	46.0
0.922	25.0	L1	9.9	21.0	46.0
2.910	33.8	L1	9.9	12.2	46.0
10.054	28.5	L1	10.2	21.5	50.0

TRF No.: FCC 15C_TX_b

FCC ID: 2ABNOUD49YC5500UA-1

16

Date of Test: September 09, 2014

Applicant: Guangdong Changhong Electronics Co., Ltd.


Model: UD49YC5500UA

Sample: 1/1

Worst Case Operating Mode: 2.4 GHz wireless transmission

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.186	44.6	N	10.0	19.6	64.2
0.298	40.8	Ν	10.1	19.5	60.3
0.554	35.0	N	10.2	21.0	56.0
1.666	34.2	Ν	10.3	21.8	56.0
2.954	39.9	Ν	10.3	16.1	56.0
9.830	35.9	Ζ	10.4	24.1	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.186	36.0	N	10.0	18.2	54.2
0.298	40.7	N	10.1	9.6	50.3
0.554	26.2	N	10.2	19.8	46.0
1.666	25.9	N	10.3	20.2	46.0
2.954	35.4	N	10.3	10.6	46.0
9.830	30.5	N	10.4	19.5	50.0

TRF No.: FCC 15C_TX_b

FCC ID: 2ABNOUD49YC5500UA-1

17

EXHIBIT 4 EQUIPMENT PHOTOGRAPHS

4.0 **Equipment Photographs**

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

EXHIBIT 5

PRODUCT LABELLING

TRF No.: FCC 15C_TX_b

Product Labelling 5.0

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

EXHIBIT 6 TECHNICAL SPECIFICATIONS

TRF No.: FCC 15C_TX_b

Technical Specifications 6.0

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 7

INSTRUCTION MANUAL

Instruction Manual 7.0

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 8 MISCELLANEOUS INFORMATION

TRF No.: FCC 15C_TX_b

Miscellaneous Information 8.0

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

8.1 Bandedge Plot

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: bandedge.pdf. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

(i) Lower channel 2409MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

= $99.8dB\mu\nu/m-41.6dB$ = $58.2dB\mu\nu/m$

Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot

= 82.3dB μ v/m-41.6dB = 40.7dB μ v/m

(ii) Upper channel 2413MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

= $98.8dB\mu\nu/m-46.4dB$ = $52.4dB\mu\nu/m$

Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot

= $80.7 dB\mu\nu/m$ -46.4 dB= $34.3 dB\mu\nu/m$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB $\mu\nu$ /m (Peak Limit) and 54dB $\mu\nu$ /m (Average Limit).

TRF No.: FCC 15C_TX_b

8.1 Bandedge Plot (cont'd)

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Figure 8.1 Bandwidth

TRF No.: FCC 15C_TX_b

8.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

TRF No.: FCC 15C_TX_b

8.2 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used (RBW=3MHz is used for fundament emission measurement).

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

TRF No.: FCC 15C_TX_b

EXHIBIT9 TEST EQUIPMENT LIST

9.0 **Test Equipment List**

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	28-Jun-14	28-Jun-15
SZ185-01	EMI Receiver	R&S	ESCI	100547	10-Mar-14	10-Mar-15
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	3-Sep-14	3-Sep-15
SZ061-08	Horn Antenna	ETS	3115	00092346	26-Oct-13	26-Oct-14
SZ061-06	Active Loop Antenna	Electro- Metrics	EM-6876	217	13-May-14	13-May-15
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	10-Mar-14	10-Mar-15
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	10-Mar-14	10-Mar-15
SZ188-01	Anechoic Chamber	ETS	RFD-F/A- 100	4102	02-Mar-14	02-Mar-15
SZ062-02	RF Cable	RADIALL	RG 213U		03-Jul-14	03-Jan-15
SZ062-06	RF Cable	RADIALL	0.04- 26.5GHz		09-Nov-13	09-Nov-14
SZ062-12	RF Cable	RADIALL	0.04- 26.5GHz		17-Apr-13	17-Oct-14
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02		21-May-14	21-May-15
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	9-Nov-13	9-Nov-14
SZ187-01	Two-Line V- Network	R&S	ENV216	100072	9-Nov-13	9-Nov-14
SZ187-02	Two-Line V- Network	R&S	ENV216	100073	9-Nov-13	9-Nov-14
SZ188-03	Shielding Room	ETS	RFD-100	4100	22-Aug-14	22-Aug-15