

Guangdong Changhong Electronics Co., Ltd.

Application
For
Certification
FCC ID: 2ABNOUD55YC5500UA

Computer Peripheral

Report No.: 140513027SZN-002

Prepared and Checked by:	Approved by:	
Sign on file		
Hardy Suo Assistant Engineer	Andy Yan Project Engineer Date: June 20, 2014	

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_PC_b

LIST OF EXHIBITS

INTRODUCTION

General Description EXHIBIT 1:

System Test Configuration EXHIBIT 2:

EXHIBIT 3: **Emission Results**

EXHIBIT 4: **Equipment Photographs**

EXHIBIT 5: **Product Labeling**

EXHIBIT 6: **Technical Specifications**

EXHIBIT 7: Instruction Manual

EXHIBIT 8: Miscellaneous Information

EXHIBIT 9: Test Equipment List

MEASUREMENT / TECHNICAL REPORT

Guangdong Changhong Electronics Co., Ltd. MODEL: UD55YC5500UA FCC ID: 2ABNOUD55YC5500UA

June 20, 2014

This report concerns (check one:)	Original Grant X C	lass II Change
Equipment Type: <u>JBP-Class B Computin</u>	ng Device Peripheral	
Deferred grant requested per 47 CFR 0.4	457(d)(1)(ii)? Yes	NoX
	If yes, defer until: _	date
Company Name agrees to notify the Cor	nmission by:	
, , ,	date	
of the intended date of announcement of that date.	of the product so that the gr	ant can be issued on
T '' D D 15.070		
Transition Rules Request per 15.37?	Yes	NoX
Iransition Rules Request per 15.37? If no, assumed Part 15, Subpart B for un Edition] provision.		
If no, assumed Part 15, Subpart B for u		

Table of Contents

1.0	<u>Gen</u>	<u>leral description</u>	2
	1.1 1.2 1.3 1.4	Product Description Related Submittal(s) Grants Test Methodology Test Facility	2 3
2.0	Sys	tem Test Configuration	5
	2.1 2.2 2.3 2.4 2.5 2.6	Justification EUT Exercising Software Special Accessories Equipment Modification Measurement Uncertainty Support Equipment List and Description	5 5 6
3.0	<u>Emi</u>	ssion Results	8
	3.1 3.2 3.3 3.4 3.5	Field Strength Calculation Radiated Emission Configuration Photograph Radiated Emission Data Conducted Emission Configuration Photograph Conducted Emission Data	11 12 15
4.0	<u>Equ</u>	ipment Photographs	22
5.0	Prod	duct Labelling	24
6.0	Tec	hnical Specifications	26
7.0	<u>Inst</u>	ruction Manual	28
8.0	Misc	cellaneous Information	30
9.0	Test	t Equipment List	34

List of attached file

Exhibit Type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated photos	radiated photos.pdf
Test Setup Photo	Conducted photos	conducted photos.pdf
External Photo	External Photos	external photos.pdf
Internal Photo	Internal Photos	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
ID Label / Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidential Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

EXHIBIT 1 GENERAL DESCRIPTION

1.0 **General Description**

1.1 **Product Description**

The Equipment Under Test (EUT) is a LED TV. The device can be used to connect PC by HDMI and VGA port. The EUT is powered by AC 120V/60Hz.

1.2 Related Submittal(s) Grants

This is an application for certification of a computer peripheral. Other digital functions were reported in the verification report: 140513027SZN-001, and related report for 2.4GHz transceiver is subjected to FCC Report No.: 140513027SZN-003, and there has a Remote Control which associated with this EUT, is filed at the same time.

1.3 **Test Methodology**

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semianechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

1.4 **Test Facility**

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

EXHIBIT 2 SYSTEM TEST CONFIGURATION

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by AC 120V/60Hz during the test. The worst case data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

The frequency range from 30MHz to 1GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

2.2 EUT Exercising Software

N/A

2.3 Special Accessories

N/A

2.4 Equipment Modification

Any modifications installed previous to testing by Guangdong Changhong Electronics Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

TRF No.: FCC 15C_PC_b

Measurement Uncertainty 2.5

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

Support Equipment List and Description 2.6

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
Laptop	Lenovo	T420
Hard Disk	Smart.drive	HD-003
USB Memory	TOSHIBA	UHYBS-004G-BL
1394 Cable	Smart.drive	Unshielded, Length 180cm
USB Cable	Smart.drive	Unshielded, Length 155cm
Dummy Load	N/A	N/A
VGA Cable	HP	Unshielded, Length 180cm
HDMI Cable*3	N/A	Unshielded, Length 110cm
HDMI Streaming Stick	ROKU	3400X
Component In Cable	N/A	Unshielded, Length 120cm
PC Audio Input Cable	N/A	Unshielded, Length 150cm
Digital Audio Out Cable	N/A	Unshielded, Length 120cm
Audio Cable (RL)	N/A	Unshielded, Length 120cm
Audio Output Cable	N/A	Unshielded, Length 120cm
Tuner Resister	N/A	75ohm
Remote controller	CHANGHONG	N/A

EXHIBIT 3

EMISSION RESULTS

Emission Results 3.0

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in $dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in $dB\mu V$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

FS = RA + AF + CF - AG + PD + AV

TRF No.: FCC 15C_PC_b

3.1 Field Strength Calculation (cont'd)

Example

Assume a receiver reading of $62.0dB\mu V$ is obtained. The antenna factor of 7.4dB/m and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0dB, and the resultant average factor was -10dB. The net field strength for comparison to the appropriate emission limit is $32dB\mu V/m$. This value in $dB\mu V/m$ was converted to its corresponding level in $\mu V/m$.

 $RA = 62.0dB\mu V$ AF = 7.4dB/m CF = 1.6dB AG = 29.0dBPD = 0dB

AV = -10dB

 $FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32dB\mu V/m$

Level in $\mu V/m$ = Common Antilogarithm [(32dB $\mu V/m$)/20] = 39.8 $\mu V/m$

TRF No.: FCC 15C PC b

3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission At 445.523MHz (HDMI In Mode)

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf.

TRF No.: FCC 15C_PC_b

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 4.7dB margin (HDMI In Mode)

TEST PERSONNEL:

Sign on file

Hardy Suo, Assistant Engineer
Typed/Printed Name

May 25, 2014 Date

TRF No.: FCC 15C PC b

Company: Guangdong Changhong Electronics Co., Ltd. Date of Test: May 25, 2014

Model: UD55YC5500UA Operating Mode: HDMI In

Table 1

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	213.330	50.6	20.0	6.9	37.5	43.5	-6.0
Horizontal	445.523	46.5	20.0	14.8	41.3	46.0	-4.7
Horizontal	742.414	37.5	20.0	21.9	39.4	46.0	-6.6
Vertical	118.270	38.9	20.0	16.8	35.7	43.5	-7.8
Vertical	187.140	41.9	20.0	11.3	33.2	43.5	-10.3
Vertical	742.440	50.6	20.0	7.1	37.7	46.0	-8.3

NOTES:

- 1. Quasi-Peak detector is used for frequency up to 1GHz.
- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.

Test Engineer: Hardy Suo

TRF No.: FCC 15C PC b

Company: Guangdong Changhong Electronics Co., Ltd. Date of Test: May 25, 2014

Model: UD55YC5500UA Operating Mode: VGA

Table 1

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	179.380	40.7	20.0	14.6	35.3	43.5	-8.2
Horizontal	213.330	38.9	20.0	19.7	38.6	43.5	-4.9
Horizontal	452.920	38.2	20.0	22.1	40.3	46.0	-5.7
Vertical	53.765	36.9	20.0	16.6	33.5	40.0	-6.5
Vertical	200.235	49.5	20.0	7.3	36.8	43.5	-6.7
Vertical	460.680	45.1	20.0	15.3	40.4	46.0	-5.6

NOTES:

- 1. Quasi-Peak detector is used for frequency up to 1GHz.
- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3 meter distances were measured at 0.3- meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.

Test Engineer: Hardy Suo

TRF No.: FCC 15C PC b

3.4 Conducted Emission Configuration Photograph

Worst Case Conducted Configuration at 21.358 MHz (HDMI In Mode)

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

TRF No.: FCC 15C_PC_b

Conducted Emission Data 3.5

Judgement: Passed by 8.9 dB margin(HDMI In Mode)

TEST PERSONNEL:

Sign on file

Hardy Suo, Assistant Engineer Typed/Printed Name


May 25, 2014 Date

Company: Guangdong Changhong Electronics Co., Ltd. Date of Test: May 25, 2014

Model: UD55YC5500UA Operating Mode: HDMI In

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency	QuasiPeak	Line	Corr.	Margin	Limit
(MHz)	(dB µ V)		(dB)	(dB)	(dB µ V)
0.206	43.5	L1	9.8	19.9	63.4
0.314	35.7	L1	9.7	24.2	59.9
0.702	37.1	L1	9.5	18.9	56.0
1.674	35.8	L1	9.8	20.2	56.0
10.338	40.1	L1	10.0	19.9	60.0
21.358	42.7	L1	10.6	17.3	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.206	34.5	L1	9.8	18.9	53.4
0.314	34.9	L1	9.7	15.0	49.9
0.702	25.9	L1	9.5	20.1	46.0
1.674	24.9	L1	9.8	21.1	46.0
10.338	36.7	L1	10.0	13.3	50.0
21.358	41.1	L1	10.6	8.9	50.0

Test Engineer: Hardy Suo


TRF No.: FCC 15C PC b

Company: Guangdong Changhong Electronics Co., Ltd. Date of Test: May 25, 2014

Model: UD55YC5500UA Operating Mode: HDMI In

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency	QuasiPeak	Line	Corr.	Margin	Limit
(MHz)	(dB µ V)	Line	(dB)	(dB)	(dB µ V)
0.178	38.8	N	9.9	25.8	64.6
0.314	28.8	N	9.7	31.1	59.9
0.386	28.7	N	9.6	29.4	58.1
0.698	31.3	N	9.4	24.7	56.0
0.902	29.7	N	9.7	26.3	56.0
10.338	33.3	N	10.1	26.8	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.178	25.9	N	9.9	28.7	54.6
0.314	27.8	N	9.7	22.1	49.9
0.386	23.0	N	9.6	25.1	48.1
0.698	20.4	N	9.4	25.6	46.0
0.902	20.1	N	9.7	25.9	46.0
10.338	30.0	N	10.1	20.0	50.0

Test Engineer: Hardy Suo


TRF No.: FCC 15C PC b

Company: Guangdong Changhong Electronics Co., Ltd. Date of Test: May 25, 2014

Model: UD55YC5500UA Operating Mode: VGA

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency	QuasiPeak	Lina	Corr.	Margin	Limit
(MHz)	(dB µ V)	Line	(dB)	(dB)	(dB µ V)
0.206	44.3	L1	9.8	19.1	63.4
0.314	35.5	L1	9.7	24.4	59.9
0.694	35.2	L1	9.5	20.8	56.0
1.610	33.6	L1	9.8	22.4	56.0
14.850	44.1	L1	10.3	15.9	60.0
22.274	38.6	L1	10.6	21.4	60.0

Result Table AV

Frequency	Average	Line	Corr.	Margin	Limit
(MHz)	(dB µ V)	Lille	(dB)	(dB)	(dB μ V)
0.206	35.6	L1	9.8	17.8	53.4
0.314	33.6	L1	9.7	16.3	49.9
0.694	24.7	L1	9.5	21.3	46.0
1.610	22.8	L1	9.8	23.2	46.0
14.850	39.4	L1	10.3	10.6	50.0
22.274	33.8	L1	10.6	16.2	50.0

Test Engineer: Hardy Suo


TRF No.: FCC 15C PC b

Company: Guangdong Changhong Electronics Co., Ltd. Date of Test: May 25, 2014

Model: UD55YC5500UA Operating Mode: VGA

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency	QuasiPeak	Line	Corr.	Margin	Limit
(MHz)	(dB µ V)		(dB)	(dB)	(dB µ V)
0.186	43.0	N	9.9	21.2	64.2
0.206	41.1	N	9.8	22.3	63.4
0.314	32.3	N	9.7	27.6	59.9
0.698	33.4	N	9.4	22.6	56.0
1.610	31.5	N	9.8	24.5	56.0
14.850	42.1	N	10.3	17.9	60.0

Result Table AV

Frequency (MHz)	Average (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.186	30.9	N	9.9	23.3	54.2
0.206	32.4	N	9.8	21.0	53.4
0.314	30.7	N	9.7	19.2	49.9
0.698	23.4	N	9.4	22.6	46.0
1.610	21.0	N	9.8	25.0	46.0
14.850	37.3	N	10.3	12.7	50.0

Test Engineer: Hardy Suo

TRF No.: FCC 15C PC b

EXHIBIT 4 EQUIPMENT PHOTOGRAPHS

4.0 **Equipment Photographs**

For electronic filing, photographs of the tested EUT are saved with filename: external photos.pdf and internal photos.pdf.

TRF No.: FCC 15C_PC_b

EXHIBIT 5 PRODUCT LABELLING

Product Labelling 5.0

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

EXHIBIT 6

TECHNICAL SPECIFICATIONS

Technical Specifications 6.0

For electronic filing, the block diagram of the tested EUT is saved with filename: block.pdf.

EXHIBIT 7 INSTRUCTION MANUAL

Instruction Manual 7.0

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold / leased in the United States.

EXHIBIT 8

MISCELLANEOUS INFORMATION

8.0 **Miscellaneous Information**

This miscellaneous information includes emission measuring procedure.

8.1 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of computer peripheral operating under Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 – 2009.

The computer peripheral equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions are in QP mode from the frequency band 30MHz to 1GHz with RBW setting 120kHz. Detector function for conducted emissions are in QP & AV mode and IFBW setting is 9kHz from the frequency band 150kHz to 30MHz.

For radiated emission, the frequency range scanned is 30MHz to 1GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz.

TRF No.: FCC 15C PC b

8.1 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

Conducted measurements are made as described in ANSI C63.4 – 2009.

EXHIBIT 9

TEST EQUIPMENT LIST

9.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	Biconilog Antenna	ETS	3142C	00078828	29-Jun-2013	29-Jun-2014
SZ185-01	EMI Receiver	R&S	ESCI	100547	10-Mar-2014	10-Mar-2015
SZ188-01	Anechoic Chamber	ETS	RFD-F/A- 100	4102	19-Apr-2014	19-Apr-2015
SZ062-04	RF Cable	RADIALL	RG 213U		08-Jan-2014	08-Jul-2014
SZ062-06	RF Cable	RADIALL	0.04- 26.5GHz	083388	09-Nov-2013	09-Nov-2014
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	09-Nov-2013	09-Nov-2014
SZ187-01	Two-Line V- Network	R&S	ENV216	100072	09-Nov-2013	09-Nov-2014
SZ187-02	Two-Line V- Network	R&S	ENV216	100073	23-Aug-2013	23-Aug-2014
SZ188-03	Shielding Room	ETS	RFD-100	4100	29-Jun-2013	29-Jun-2014