



RF Exposure Evaluation

FOR

Guangzhou BDE Technology Inc.

BDE Multi-Band & Multi-Protocol Wireless Module with PA

Test Model: BDE-MB1354P102UA32

Additional Model No.: Please Refer to Page 6

Prepared for : Guangzhou BDE Technology Inc.
Address : B2-403, Chuangyi Building, 162 Science Avenue, Huangpu District, Guangzhou 510663, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 08, 2024
Number of tested samples : 2
Sample No. : A240508051-1, A240508051-2
Serial number : Prototype
Date of Test : May 08, 2024 ~ July 02, 2025
Date of Report : July 03, 2025





RF Exposure Evaluation	
Report Reference No.	: LCSA05074065ED
Date of Issue.....	: July 03, 2025
Testing Laboratory Name	: Shenzhen LCS Compliance Testing Laboratory Ltd.
Address.....	: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
	: Full application of Harmonised standards ■
Testing Location/ Procedure.....	: Partial application of Harmonised standards □
	: Other standard testing method □
Applicant's Name.....	: Guangzhou BDE Technology Inc.
Address.....	: B2-403, Chuangyi Building, 162 Science Avenue, Huangpu District, Guangzhou 510663, China
Test Specification	
Standard	: FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06
	: FCC CFR 47 part1 1.1310
	: FCC CFR 47 part2 2.1091
Test Report Form No.....	: TRF-4-E-214 A/0
TRF Originator	: Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	: Dated 2011-03
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description.	: BDE Multi-Band & Multi-Protocol Wireless Module with PA
Trade Mark.....	: BDE
Test Model	: BDE-MB1354P102UA32
Ratings.....	: Input: DC 3.3V
Result	: Positive

Compiled by:

Jack Liu/Administrator

Supervised by:

Cary Luo/ Technique principal

Approved by:

Gavin Liang/ Manager





RF Exposure Evaluation

Test Report No. : LCSA05074065ED	<u>July 03, 2025</u> Date of issue
---	---------------------------------------

Test Model.....	: BDE-MB1354P102UA32
EUT.....	: BDE Multi-Band & Multi-Protocol Wireless Module with PA
Applicant.....	: Guangzhou BDE Technology Inc.
Address.....	: B2-403, Chuangyi Building, 162 Science Avenue, Huangpu District, Guangzhou 510663, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Guangzhou BDE Technology Inc.
Address.....	: B2-403, Chuangyi Building, 162 Science Avenue, Huangpu District, Guangzhou 510663, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Guangzhou BDE Technology Inc.
Address.....	: B2-403, Chuangyi Building, 162 Science Avenue, Huangpu District, Guangzhou 510663, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	July 03, 2025	Initial Issue	---



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



TABLE OF CONTENTS

Description	Page
1. Product Information.....	6
2. Evaluation Method and Limit	8
3. Refer Evaluation Method	8
4. MPE Calculation Method	9
5. Antenna Information.....	9
6. Conducted Power.....	9
7. Manufacturing Tolerance	10
8. Measurement Results	11
9. Conclusion	12
10. Description of Test Facility	12
11. Measurement Uncertainty.....	12





1. Product Information

FCC ID	2ABRU-MB13P2
Product name	BDE Multi-Band & Multi-Protocol Wireless Module with PA
Test Model	BDE-MB1354P102UA32
Additional Model No.	BDE-MB1354P102NA32, BDE-MB1354P102UU32, BDE-MB1354P102NU32, BDE-MB1354P102UN32, BDE-MB1354P102NN32, BDE-MB1354P102UA0, BDE-MB1354P102NA0, BDE-MB1354P102UU0, BDE-MB1354P102NU0, BDE-MB1354P102UN0, BDE-MB1354P102NN0, BDE-MB1354P102UA32-IN, BDE-MB1354P102NA32-IN, BDE-MB1354P102UU32-IN, BDE-MB1354P102NU32-IN, BDE-MB1354P102UN32-IN, BDE-MB1354P102NN32-IN, BDE-MB1354P102UA0-IN, BDE-MB1354P102NA0-IN, BDE-MB1354P102UU0-IN, BDE-MB1354P102NU0-IN, BDE-MB1354P102UN0-IN, BDE-MB1354P102NN0-IN, BDE-MB1352P72UA32, BDE-MB1352P72NA32, BDE-MB1352P72UU32, BDE-MB1352P72NU32, BDE-MB1352P72UN32, BDE-MB1352P72NN32, BDE-MB1352P72UA0, BDE-MB1352P72NA0, BDE-MB1352P72UU0, BDE-MB1352P72NU0, BDE-MB1352P72UN0, BDE-MB1352P72NN0, BDE-MB1352P72UA32-IN, BDE-MB1352P72NA32-IN, BDE-MB1352P72UU32-IN, BDE-MB1352P72NU32-IN, BDE-MB1352P72UN32-IN, BDE-MB1352P72NN32-IN, BDE-MB1352P72UA0-IN, BDE-MB1352P72NA0-IN, BDE-MB1352P72UU0-IN, BDE-MB1352P72NU0-IN, BDE-MB1352P72UN0-IN, BDE-MB1352P72NN0-IN, BDE-MB1352P2UA32, BDE-MB1352P2NA32, BDE-MB1352P2UU32, BDE-MB1352P2NU32, BDE-MB1352P2UN32, BDE-MB1352P2NN32, BDE-MB1352P2UA0, BDE-MB1352P2NA0, BDE-MB1352P2UU0, BDE-MB1352P2NU0, BDE-MB1352P2UN0, BDE-MB1352P2NN0, BDE-MB1352P2UA32-IN, BDE-MB1352P2NA32-IN, BDE-MB1352P2UU32-IN, BDE-MB1352P2NU32-IN, BDE-MB1352P2UN32-IN, BDE-MB1352P2NN32-IN, BDE-MB1352P2UA0-IN, BDE-MB1352P2NA0-IN, BDE-MB1352P2UU0-IN, BDE-MB1352P2NU0-IN, BDE-MB1352P2UN0-IN, BDE-MB1352P2NN0-IN
Ratings	Input: DC 3.3V
Hardware version	V1
Software version	7.40.00
Bluetooth	
Frequency Range	2402MHz~2480MHz
Channel Number	40 channels for Bluetooth V5.3 (DTS)
Channel Spacing	2MHz for Bluetooth V5.3 (DTS)
Modulation Type	GFSK for Bluetooth V5.3 (DTS)
Bluetooth Version	V5.3
Antenna Description	For PCB Trace Antenna: Integrated PCB trace antenna, 0.8dBi(Max.) For ANT: Whip Antenna, 3.0dBi(Max.) For U.FL Connector: Whip Antenna, 3.0dBi(Max.)





Zigbee	
Frequency Range	2405MHz-2480MHz
Channel Spacing	5MHz
Channel Number	16 Channels
Modulation Type	O-QPSK
Antenna Description	For PCB Trace Antenna: Integrated PCB trace antenna, 0.8dBi(Max.) For ANT: Whip Antenna, 3.0dBi(Max.) For U.FL Connector: Whip Antenna, 3.0dBi(Max.)
915 MHz	
Frequency Range	50Kbps, 100Kbps: 902.2MHz ~ 927.8MHz 150Kbps, 200Kbps: 902.4MHz ~ 927.6MHz
Channel Number	129 Channels (50Kbps, 100Kbps) 64 Channels (150Kbps, 200Kbps)
Modulation Type	2-GFSK
Antenna Description	For U.FL Connector: Whip Antenna, 3.8dBi(Max.) For ANT Pin: Whip Antenna, 3.8dBi(Max.)
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Devices

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.





2. Evaluation Method and Limit

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Refer Evaluation Method

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density





4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Internal	PCB trace antenna	2400MHz ~ 2500MHz	0.8dBi
External	Whip antenna	2400MHz ~ 2500MHz	3.0dBi
	Whip antenna	902MHz ~ 928MHz	3.8dBi

6. Conducted Power

[BT LE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE 1M	0	2402	18
	19	2440	17.75
	39	2480	17.18
BLE 2M	0	2402	18.03
	19	2440	17.77
	39	2480	8.05
BLE 125Kbps	0	2402	18.09
	19	2440	17.76
	39	2480	17.24
BLE 500Kbps	0	2402	18.1
	19	2440	17.77
	39	2480	17.25

[Zigbee]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
O-QPSK	0	2405	17.97
	7	2440	17.75
	15	2480	-3.72





< 900MHz Max. Conducted Power >

Mode	Channel	Frequency(MHz)	Max Conducted Power (dBm)
50Kbps	0	902.2	14.064
	64	915.0	13.958
	128	927.8	13.723
100Kbps	0	902.2	14.096
	64	915.0	13.943
	128	927.8	13.717
150Kbps	0	902.4	14.089
	32	915.2	13.932
	63	927.6	13.709
200Kbps	0	902.4	14.080
	32	915.2	13.932
	63	927.6	13.717

7. Manufacturing Tolerance

BLE 1M(Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	18.0	17.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE 2M(Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	18.0	17.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE 125Kbps(Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	18.0	17.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE 500Kbps (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	18.0	17.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[Zigbee]

O-QPSK (Peak)			
Channel	Channel 0	Channel 7	Channel 15
Target (dBm)	17.0	17.0	-3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0





< 900MHz >

GFSK 50Kbps(Peak)			
Channel	Channel 0	Channel 64	Channel 128
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK 100Kbps(Peak)			
Channel	Channel 0	Channel 64	Channel 128
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK 150Kbps(Peak)			
Channel	Channel 0	Channel 32	Channel 63
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK 200Kbps(Peak)			
Channel	Channel 0	Channel 32	Channel 63
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

8. Measurement Results

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT LE]

Modulation Type	Output power		Max. Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BLE 1M	19.0	79.4328	3.0	1.9953	0.0315	1.0000
BLE 2M	19.0	79.4328	3.0	1.9953	0.0315	1.0000
BLE 125Kbps	19.0	79.4328	3.0	1.9953	0.0315	1.0000
BLE 500Kbps	19.0	79.4328	3.0	1.9953	0.0315	1.0000

[Zigbee]

Modulation Type	Output power		Max. Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
O-QPSK	18.0	63.0957	3.0	1.9953	0.0251	1.0000

[900MHz]

Modulation Type	Output power		Max. Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
50Kbps	15.0	31.6228	3.8	2.3988	0.0151	1.0000
100Kbps	15.0	31.6228	3.8	2.3988	0.0151	1.0000
150Kbps	15.0	31.6228	3.8	2.3988	0.0151	1.0000
200Kbps	15.0	31.6228	3.8	2.3988	0.0151	1.0000





8.2 Simultaneous Transmission MPE

The EUT has one Sub-1G band and other one 2.4G band. So no need consider simultaneous transmission. According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations; $\sum$ of MPE ratios ≤ 1.0

Simultaneous Transmission				
Sub-1G band antenna Max. MPE ratios	2.4G band antenna Max. MPE ratios	$\sum$ MPE ratios	Limit	Results
0.0151	0.0315	0.0466	1.0	Pass

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate is assessed based on the maximum antenna gain value(worst case)
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024.
CAB identifier is CN0071.
CNAS Registration Number is L4595.
Test Firm Registration Number: 254912.

11. Measurement Uncertainty

BLE/Zigbee/900MHz:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	± 0.57 dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----

