



■ Report No.: DDT-R18121703-1E3

■ Issued Date: Dec. 28, 2018

RF EXPOSURE REPORT

FOR

Applicant	:	VOXOA Inc.
Address	:	5500 Stewart Ave Ste 108, Fremont, California, United States 94538
Equipment under Test	:	Bluetooth Audio Receiver
Type No.	:	BTunes 5
Model No.	:	BTunes QC25/5, BTunes QC15/5, BTunes M50X/5
Trade Mark	:	VOXOA
FCC ID	:	2ABSDBTUNESQ5
Manufacturer	:	Zhongshan K-mate General Electronics Co.,Ltd
Address	:	NO.2 ,5th Xinsheng Street,Gangkou Town, Zhongshan City, Guangdong,China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

Test report declares.....	3
1. General information	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC.....	5

TEST REPORT DECLARE

Applicant	:	VOXOA Inc.
Address	:	5500 Stewart Ave Ste 108, Fremont, California, United States 94538
Equipment under Test	:	Bluetooth Audio Receiver
Type No.	:	BTunes 5
Model No.	:	BTunes QC25/5, BTunes QC15/5, BTunes M50X/5
Trade mark	:	VOXOA
Manufacturer	:	Zhongshan K-mate General Electronics Co.,Ltd
Address	:	NO.2 ,5th Xinsheng Street,Gangkou Town, Zhongshan City, Guangdong,China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R18121703-1E3		
Date of Receipt:	Dec. 28, 2018	Dec. 28, 2018	Dec. 28, 2018

Prepared By:



Sam Li/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Dec. 28, 2018	

1. General information

1.1. Description of Equipment

EUT* Name	: Bluetooth Audio Receiver
Model Number	: BTunes QC25/5, BTunes QC15/5, BTunes M50X/5
Difference of model number	: All models are identical except the appearance, BTunes QC25/5 and BTunes QC15/5 have the same batteries, but BTunes M50X/5's battery is different. Therefore, the test performed on the model BTunes QC25/5, only radiated emission (below 1GHz) and Power Line Conducted Emissions were tested on the model BTunes M50X/5 additional and recorded in this report
EUT function description	: Please reference user manual of this device
Power supply	: DC 5V from external AC Adapter : DC 3.7V 160mAh(80mAhx2) Polymer Li-ion built-in battery
Radio Specification	: Bluetooth V5.0
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data rate	: 1Mbps, 2Mbps, 3Mbps
Antenna Type	: Chip antenna, maximum PK gain: 0.5dBi
Sample Type	: Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2480MHz, 6.59dBm (4.56mW) output power]

$(4.56/5) \cdot [\sqrt{2.480(\text{GHz})}] = 1.436 < 3.0$ for 1-g SAR

Then SAR evaluation is not required

END OF REPORT