

EMC Test Data

Client:	Neato Robotics, Inc.	Job Number:	PR087406				
Model	BotVac D7 Connected	T-Log Number:	TL087406				
Model.	Botvac D7 Connected	Project Manager:	Christine Krebill				
Contact:	Kelvin Law	Project Coordinator:	-				
Standard:	FCC 15E, RSS-247	Class:	N/A				

Maximum Permissible Exposure

Test Specific Details

The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 12/26/2018 Test Engineer: Deniz Demirci

General Test Configuration

Calculation uses the free space transmission formula:

 $S = (PG)/(4 \pi d^2)$

Where: S is power density (W/m²), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20 cm separation: Yes
--

Deviations From The Standard

No deviations were made from the requirements of the standard.

FCC MPE Calculation

For 1.5-15 GHz single transmitters (General use)

1 01 110 10 1	one oningio ti	anomittoro	Scholar acc)					
	El	JT	Cable Loss	Ant	Power		Power Density (S)	MPE Limit
Freq.	Power		Loss	Gain	at Ant	EIRP	at 20 cm	at 20 cm
MHz	dBm	mW*	dB	dBi	dBm	mW	mW/cm^2	mW/cm^2
2462	13.2	20.9	0	2.1	13.2	33.88	0.007	1.000
5240	9.6	9.1	0	0.7	9.6	10.72	0.002	1.000
5745	12.6	18.2	0	0.1	12.6	18.62	0.004	1.000

ISED Canada MPE Calculation

For 300-6000 MHz single transmitters (General use)

		EUT		Cable Loss	Ant	Power		Power Density (S)	MPE Limit
	Freq.	Power		Loss	Gain	at Ant	EIRP	at 20 cm	at 20 cm
	MHz	dBm	mW*	dB	dBi	dBm	mW	mW/cm^2	mW/cm^2
	2462	13.2	20.9	0	2.1	13.2	33.88	0.007	0.544
	5240	9.6	9.1	0	0.7	9.6	10.72	0.002	0.912
	5745	12.6	18.2	0	0.1	12.6	18.62	0.004	0.971