

RF Exposure Report

Report No.: SA180625E05A

FCC ID: 2ABTEG1500

Test Model: Fios-G1500

Received Date: July 30, 2018

Test Date: Aug. 27, 2018

Issued Date: Nov. 27, 2018

Applicant: Verizon Online LLC

Address: 1300 I Street NW, Room 400W, Washington, District of Columbia, 20005

United State

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

FCC Registration /

723255 / TW2022 **Designation Number:**

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Report No.: SA180625E05A Page No. 1 / 6 Report Format Version: 6.1.1 Reference No.: 180730E05



Table of Contents

Relea	se Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.1	Limits for Maximum Permissible Exposure (MPE)	. 5
	MPE Calculation Formula	
	Classification	
	Antenna Gain	
2.5	Calculation Result	6



Release Control Record

Issue No.	Description	Date Issued
SA180625E05A	Original release.	Nov. 27, 2018

Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SA180625E05A Reference No.: 180730E05



1 Certificate of Conformity

Product: Fios-G1500

Brand: Verizon

Test Model: Fios-G1500

Applicant: Verizon Online LLC

Test Date: Aug. 27, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by: Nov. 27, 2018

Phoenix Huang / Specialist

Approved by : , Date: Nov. 27, 2018

May Chen / Manager



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f ²)*	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN Directional gain table						
Frequency range (GHz)	Directional Antenna Gain (dBi)	Antenna Type	Antenna Connector			
2.4 ~ 2.4835	2.94					
5.15 ~ 5.25	3.56		i-pex(MHF)			
5.25 ~ 5.35	3.56	Dipole				
5.47 ~ 5.725	3.56					
5.725 ~ 5.85	3.56					
Z-Wave antenna spec.						
Antenna Net Gain (dBi)	Frequency range (MHz)	Antenna Type	Antenna Connector			
1.73	902~928	Dipole	None			
Note: More detailed information, please refer to operating description.						

Report No.: SA180625E05A Page No. 5 / 6 Report Format Version: 6.1.1

Reference No.: 180730E05



2.5 Calculation Result

For Z-Wave technology and 2.4GHz and 5GHz (U-NII-1 band and U-NII-3 band) data was copied from the original test report (Report No.: SA180625E05)

Z-Wave Field Strength Conversion:

Frequency (MHz)	Field Strength of Fundamental (dBuV/m) @3m	(dRm)	EIRP (mW)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm ²)
908.4	93.9	-1.33	0.7362	20	0.00014646	0.6056

Note: 1. Pout EIRP (dBm) = Field Strength of Fundamental (dBuV/m) - 95.23 (dB)

2. Power Density Limit = F/1500

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WLAN 2.4GHz	2462	996.372	2.94	20	0.39008	1
WLAN 5GHz (U-NII-1)	5240	564.338	3.56	20	0.25484	1
WLAN U-NII-2A	5270	247.878	3.56	20	0.11194	1
WLAN U-NII-2C	5500	247.392	3.56	20	0.11172	1
WLAN 5GHz (U-NII-3)	5795	480.318	3.56	20	0.21690	1

Note:

2.4GHz: Directional gain = 2.94dBi 5GHz: Directional gain = 3.56dBi

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz + Z-Wave = 0.39008 / 1 + 0.25484 / 1 + 0.00014646 / 0.6056 = 0.64517Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---