FCC TEST REPORT for Cheng Fong International Limited

Tablet PC Model No.: TBQG774B, M720C

Prepared for : Cheng Fong International Limited

Address : RM A1701, High Tech Plaza Phase I, Tianan Cyber Park, Futian

District, Shenzhen, China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,

Nanshan District, Shenzhen, Guangdong, China

Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : 201402700F

Date of Test : Feb. 26~ Mar. 11, 2014

Date of Report : Mar. 12, 2014

TABLE OF CONTENT

Description

Page Test Report 1. GENERAL INFORMATION......4 2.3. List of channels: 3. CONDUCTED EMISSION TEST......9 3.5. Test Procedure 10 4. FCC PART 15.247 REQUIREMENTS FOR DSSS & OFDM MODULATION.......13 4.6. Radiated Emissions 50 5.2. Photo of Radiation Emission Test. APPENDIX I (EXTERNAL PHOTOS)......63 APPENDIX II (INTERNAL PHOTOS)......65

APPENDIX I (External Photos) (2 Pages)

APPENDIX II (Internal Photos) (4 Pages)

TEST REPORT

Applicant : Cheng Fong International Limited

Manufacturer : Cheng Fong International Limited

EUT : Tablet PC

Model No. : TBQG774B, M720C

Serial No. : N/A
Trade Mark : N/A

Rating : Micro-5pin, 2A Via Adapter

(AC 100-240V, 50/60Hz, 0.65A Max.)

Measurement Procedure Used:

FCC Part15 Subpart C, Paragraph 15.247

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test:	Feb. 26~ Mar. 11, 2014
Prepared by:	Zock zeng
	(Tested Engineer / Rock Zeng)
Reviewer :	Amy Ding
	(Project Manager / Amy Ding)
Approved & Authorized Signer:	Ton Chen
	(Manager / Tom Chen)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Tablet PC

Model Number : TBQG774B, M720C

(Note: All samples are the same except the model number and appearance, so we prepare "TBQG774B" for EMC test only.)

Test Power Supply : AC 120V/60Hz for adapter/

DC 5V(With DC 3.7V battery inside)

Adapter : Model:THX-050200KE

Input: AC 100-240V, 50/60Hz, 0.65A

Output: DC 5V, 2000mA

RF Transmission : 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20))

Frequency 2422MHz~2452MHz (802.11n(HT40))

Channels : 11 For (802.11b/802.11g/802.11n(HT20))

7 For (802.11n(HT40))

Modulation 802.11b CCK

802.11g OFDM 802.11n MCS

Antenna Gain: : 0dBi

Applicant : Cheng Fong International Limited

Address : RM A1701, High Tech Plaza Phase I, Tianan Cyber Park, Futian

District, Shenzhen, China

Manufacturer : Cheng Fong International Limited

Address : RM A1701, High Tech Plaza Phase I, Tianan Cyber Park, Futian

District, Shenzhen, China

Factory : Cheng Fong International Limited

Address : RM A1701, High Tech Plaza Phase I, Tianan Cyber Park, Futian

District, Shenzhen, China

Date of receiver : Feb. 26, 2014

Date of Test : Feb. 26~ Mar. 11, 2014

1.2. Auxiliary Equipment Used during Test

PC : Manufacturer: DELL

M/N: OPTIPLEX 380

S/N: 1J63X2X CE , FCC: DOC

MONITOR : Manufacturer: DELL

M/N: E170Sc

S/N: CN-00V539-64180-055-0UPS

CE, FCC: DOC

KEYBOARD : Manufacturer: DELL

M/N: SK-8115

S/N: CN-0DJ313-71616-06C-02XN

CE, FCC: DOC

Cable: 1m, unshielded

MOUSE : Manufacturer: DELL

M/N: M-UARDEL7

S/N: N/A

CE, FCC: DOC

Cable: 1m, unshielded

Printer : Manufacturer:Brother

M/N: MFC-3360C

S/N: N/A

CE, FCC:DOC

Power Cord of Printer : Non-shielded, Detachable, 0.8m, w/o core

USB Cable for Printer : Non-Shielded, 1.5m

Power Line Non-Shielded, 1.5m

VGA Cable : Non-Shielded, 1.5m

Network Cable : Non-Shielded, 1.5m

USB Cable for EUT : Non-Shielded, 1.2m

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 463622

EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 463622, June 14, 2011.

IC-Registration No.: 46405-9469

EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 46405-9469, May 02, 2011.

Test Location

All Emissions tests were performed at NINGBO EMTEK CO., LTD. at 1F Building 4, 1177#, Lingyun Road, Ningbo National Hi-Tech Zone, Ningbo, Zhejiang, China

1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3 dB

Conduction Uncertainty : Uc = 3.4dB

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2009 and FCC Part 15, Paragraph 15.247.

2.1. Summary of Test Results

The EUT has been tested according to the following specifications:

	<u> </u>		
Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107, 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15, Paragraph 15.247(b)(1)	Peak Output Power	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(2)	6dB Bandwidth	PASS	Complies
FCC Part 15, Paragraph 15.247(c)	100kHz Bandwidth of Frequency Band Edges	PASS	Complies
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS	Complies
FCC Part 15, Paragraph 15.247(a)(1)	Frequency Separation	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Number of Hopping Frequency	-	N/A
FCC Part 15, Paragraph 15.247(a)(1)(iii)	Time of Occupancy	-	N/A
FCC Part 15, Paragraph 15.247(c)	Peak Power Density	PASS	Complies

2.2. Description of Test Modes

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode isprogrammed.

IEEE802.11b: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 1 Mbps lowest data rate (worst case) are chosen for the final testing.

IEEE802.11g: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 6 Mbps lowest data rate (the worst case) are chosen for the final testing.

IEEE802.11n (HT20): Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with MCS 0 Mbps lowest data rate (the worst case) are chosen for the final testing.

IEEE802.11n (HT40): Channel 3(2422MHz), Channel 6(2437MHz) and Channel 9(2452MHz) with MCS 0 Mbps lowest data rate (the worst case) are chosen for the final testing.

2.3. List of channels:

√ - available


X - tested

Number	Frequency(MHz)		802.11	802.11
			b/g/n	b/g/n
			(HT20)	(HT40)
1	2412	√	X	
2	2417	√		
3	2422	√		X
4	2427	√		
5	2432	√		
6	2437	√	X	X
7	2442	√		
8	2447	√		
9	2452	√		X
10	2457	√		
11	2462	√	X	

3. Conducted Emission Test

3.1. Block Diagram of Test Setup

3.1.1. Block diagram of connection between the EUT and simulators



3.2. Power Line Conducted Emission Measurement Limits (15.207)

	Frequency	Limits dB(μV)			
	MHz	Quasi-peak Level	Average Level		
0.15	~ 0.50	66 ~ 56*	56 ~ 46*		
0.50	~ 5.00	56	46		
5.00	~ 30.00	60	50		

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

EUT : Tablet PC Model Number : TBQG774B

Applicant : Cheng Fong International Limited

3.4. Operating Condition of EUT

- 3.4.1. Setup the EUT and simulator as shown as Section 3.1.
- 3.4.2. Turn on the power of all equipment.
- 3.4.3. Let the EUT work in test mode (Charging to adapter, Communication) and measure it.

3.5. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.4-2003 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 3.6.

3.6. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Two-Line V-network	Rohde & Schwarz	ENV216	100055	Apr. 23, 2013	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Apr. 23, 2013	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Apr. 23, 2013	1 Year

3.7. Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150KHz to 30 MHz is investigated.

The EUT was tested on (Charging to adapter, Communication) modes, only the worst data of (Communication) are attached in the following pages.

CONDUCTED EMISSION TEST DATA


Test Site: 1# Shielded Room Operating Condition: Communication

Test Specification: DC 5V
Comment: Live Line

Tem:25℃ Hum:50%

SCAN TABLE: "Voltage (150K~30M) FIN"

Short Description: 150K-30M Disturbance Voltages



MEASUREMENT RESULT: "AT1402640104 fin"

2/27/2014 11	:09AM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBuV	dB			
0.195000	49.40	20.1	64	14.4	QP	L1	GND
0.388500	38.40	20.1	58	19.7	QP	L1	GND
0.496500	41.20	20.1	56	14.9	QP	L1	GND
0.847500	34.60	20.1	56	21.4	QP	L1	GND
1.517500	36.40	20.3	56	19.6	QP	L1	GND
2.188000	35.00	20.3	56	21.0	QP	L1	GND

MEASUREMENT RESULT: "AT1402640104 fin2"

2/27/2014	11:09AM						
Frequenc	cy Level Hz dBu		Limit dBuV	Margin dB	Detector	Line	PE
1711	.12 GDA	v QD	αυμν	αD			
0.1950	00 47.3	20.1	54	6.5	AV	L1	GND
0.32550	39.00	0 20.1	50	10.6	AV	L1	GND
0.38850	35.60	0 20.1	48	12.5	AV	L1	GND
0.48300	34.80	20.1	46	11.5	AV	L1	GND
1.51750	00 31.5	20.3	46	14.5	AV	L1	GND
2.15200	00 29.80	20.3	46	16.2	AV	L1	GND

CONDUCTED EMISSION TEST DATA


Test Site: 1# Shielded Room Operating Condition: Communication

Test Specification: DC 5V
Comment: Neutral Line

Tem:25℃ Hum:50%

SCAN TABLE: "Voltage (150K~30M) FIN"

Short Description: 150K-30M Disturbance Voltages



MEASUREMENT RESULT: "AT1402640103_fin"


2	2/27/2014 11	:05AM						
	Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
	0 105000	F1 00	00.1		10.0	0.5		C117D
	0.195000	51.80	20.1	64	12.0	QP	N	GND
	0.258000	44.30	20.1	62	17.2	QP	N	GND
	0.325500	43.70	20.1	60	15.9	QP	N	GND
	0.388500	41.70	20.1	58	16.4	QP	N	GND
	0.519000	42.50	20.1	56	13.5	QP	N	GND
	0.937500	36.90	20.1	56	19.1	QP	N	GND

MEASUREMENT RESULT: "AT1402640103 fin2"

2/27/2014 1	1:05AM						
Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.195000	50.20	20.1	54	3.6	AV	N	GND
0.262500	39.80	20.1	51	11.6	AV	N	GND
0.325500	40.60	20.1	50	9.0	AV	N	GND
0.388500	37.10	20.1	48	11.0	AV	N	GND
0.496500	35.20	20.1	46	10.9	AV	N	GND
0.933000	32.60	20.1	46	13.4	AV	N	GND

4. FCC Part 15.247 Requirements for DSSS & OFDM Modulation

4.1 Test Setup



4.2 6dB Bandwidth

a. Limit

For the direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

b.Test Procedure

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as:

RBW = 100kHz, VBW $\geqslant 3*RBW = 300kHz$,

Detector= Peak

Trace mode= Max hold.

Sweep- auto couple.

- 4. Mark the peak frequency and –6dB (upper and lower) frequency.
- 5. Repeat until all the rest channels are investigated.

c. Test Setup See 4.1

d. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Aug. 09, 2013	1 Year
2.	Preamplifier	Instruments corporation	EMC01183 0	980100	Aug. 09, 2013	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 23, 2013	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Aug. 09, 2013	3 Year
5.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A


e. Test Results


Pass.

f. Test Data


Test mode: IEEE 802	.11b			
Channel	Frequency	Bandwidth	Limit	Results
Low	(MHz) 2412	(MHz) 11.88	(kHz)	Pass
Mid	2437	11.88	>500	Pass
High	2462	11.88		Pass
Test mode: IEEE 902	11 ~			
Test mode: IEEE 802.	Frequency	Bandwidth	Limit	
Channel	(MHz)	(MHz)	(kHz)	Results
Low	2412	16.65	(IIIIZ)	Pass
Mid	2437	16.65	>500	Pass
High	2462	16.65		Pass
Test mode: IEEE 802.	11n (HT20)			
	Frequency	Bandwidth	Limit	D 1
Channel	(MHz)	(MHz)	(kHz)	Results
Low	2412	17.73	, ,	Pass
Mid	2437	17.73	>500	Pass
High	2462	17.73		Pass
Test mode: IEEE 802.	11n (HT40)			
O1 1	,	Bandwidth	Limit	D 1
Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Results
Low	Frequency	(MHz) 36.32		Results Pass
	Frequency (MHz)	(MHz)		


Test Plots See the following page.







Test Mode: 802.11b---Mid










Test Mode: 802.11g---Low










Test Mode: 802.11g---High









Test Mode: 802.11n (HT20)---Mid









Test Mode: 802.11n (HT40)---Low







Test Mode: 802.11n (HT40)---High



4.3. Maximum Peak output power test

a. Limit

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt (30dBm).
- 2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antenna of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

b. Configuration of Measurement



c. Data Rates

IEEE802.11b: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 1 Mbps data rate (worst case) are chosen for the final testing.

IEEE802.11g: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 6 Mbps data rate (the worst case) are chosen for the final testing.

IEEE802.11n (HT20: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 6.5Mbps data rate (the worst case) are chosen for the final testing.

IEEE802.11n (HT40: Channel 3(2422MHz), Channel 6(2437MHz) and Channel 9(2452MHz) with 13.5Mbps data rate (the worst case) are chosen for the final testing.

d. Test Procedure

This test was according the kDB 558074 9.1.2:

- 1. This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.
- 2. Set the RBW = 1 MHz.
- 3. Set the VBW \geq 3*RBW = 3 MHz.
- 4. Set the span ≥ 1.5*DTS bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

e. Test Equipment

Same as the equipment listed in 4.2.

f. Test Results

Pass.

g. Test Data

Test mode: IEEE 802.11b

Channal	Frequency	Maximum transmit power	Li	mit	Dogult
Channel	(MHz)	(dBm)	(dBm)	(watts)	Result
Low	2412	8.43			Pass
Mid	2437	7.51	30	1	Pass
High	2462	6.59			Pass

Test mode: IEEE 802.11g


Channel	Frequency	Maximum transmit power	Li	mit	Pagult
	(MHz)	(dBm)	(dBm)	(watts)	Result
Low	2412	7.36			Pass
Mid	2437	6.73	30	1	Pass
High	2462	6.04			Pass


Test mode: IEEE 802.11n (HT20)


Channel	Frequency	Maximum transmit power	Limit		Result
	(MHz)	(dBm)	(dBm)	(watts)	Kesuit
Low	2412	7.30			Pass
Mid	2437	6.73	30	1	Pass
High	2462	5.93			Pass

Test mode: IEEE 802.11n (HT40)


Channel	Frequency	Maximum transmit power	Li	mit	Result
	(MHz)	(dBm)	(dBm)	(watts)	Resuit
Low	2422	6.91			Pass
Mid	2437	6.36	30	1	Pass
High	2452	5.91			Pass














AC

Span 50 MHz

7.30 dBm



5 MHz/


Power

20 MHz


-80-

Center 2.412 GHz


Tx Channel
Bandwidth












3DB

AC

Span 80 MHz

6.36 dBm



8 MHz/

Power

40 MHz

-80-

Center 2.437 GHz

Tx Channel
Bandwidth




4.4. Band Edges Measurement

a. Limit

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

b. Test Procedure

- 1. Conducted Method:
- 1) Set RBW=100KHz, VBW=300KHz
- 2) Detector=peak
- 3) Sweep time= auto
- 4) Trace mode=max hold.
- 2. Radiated Method:
- 1) The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2) The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4) Peak detector: RBW=1MHz, VBW=3MHz, SWT=AUTO Average detector: RBW=1MHz, VBW=10Hz, SWT=AUTO The EUT is tested in 9*6*6 Chamber.
- 5) Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.



c. Test Equipment


Same as the equipment listed in 4.2.


d. Test Results

Pass.


e. Test Plots


See the following page.







Test Mode: 802.11b --- High









Test Mode: 802.11g ---High









Test Mode: 802.11n (HT20)---High








Test Mode: 802.11n (HT40) --- High




The Worst Mode: 802.11b

2412MHz

Horizontal-PEAK:




Horizontal-AV:




The Worst Mode: 802.11b

2412MHz Vertical-PEAK:




Vertical-AV:




The Worst Mode: 802.11b

2462MHz

Horizontal-PEAK:




Horizontal-AV:




The Worst Mode: 802.11b

2462MHz Vertical-PEAK:



Vertical-AV:



4.5. Peak Power Spectral Density

a. Limit

- 1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
- 2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

b. Test Procedure

- 1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5MHz, Sweep=500s
- 3. Record the max. reading.
- 4. Repeat the above procedure until the measurements for all frequencies are completed.

c. Test Equipment

Same as the equipment listed in 4.2.

d. Test Setup

See 4.1

e. Test Results


Pass

f. Test Data

Please refer to the following data.


g. Test Plot See the following pages

Test mode: IEE Channel Low Mid High	E 802.11b Frequency (MHz) 2412 2437 2462	PPSD (dBm/3KHz) -20.86 -22.01 -23.00	ΣPPSD (dBm/3KHz) - - -	Limit (dBm)	Result Pass Pass Pass
Test mode: IEE Channel Low Mid High	E 802.11g Frequency (MHz) 2412 2437 2462	PPSD (dBm) -25.81 -26.43 -27.89	ΣPPSD (dBm) - - -	Limit (dBm)	Result Pass Pass Pass
Test mode: IEE Channel Low Mid High	E 802.11n (HTZ Frequency (MHz) 2412 2437 2462	PPSD (dBm/3KHz) -26.76 -27.32 -28.33	Σ PPSD (dBm/3KHz) - - -	Limit (dBm) 8.00	Result Pass Pass Pass
Test mode: IEE Channel Low Mid High	E 802.11n (HT4 Frequency (MHz) 2422 2437 2452	PPSD (dBm/3KHz) -28.32 -28.89 -29.47	Σ PPSD (dBm/3KHz) - -	Limit (dBm)	Result Pass Pass Pass






Center 2.412 GHz




1.809 MHz/

Span 18.09 MHz







802.11g CH--Low










802.11g CH--High










802.11n (HT20) CH-Mid










802.11n (HT40) CH—Low







802.11n (HT40) CH—High



4.6. Radiated Emissions

4.6.1.1. Test Limits (< 30 MHZ)

Frequency	Field Strength	Measurement Distance	
(MHz)	(microvolts/meter)	(meter)	
0.009-0.490	2400/F(kHz)	300	
0.490-1.705	24000/F(kHz)	30	
1.705-30.0	30	30	

4.6.1.2. Test Limits (≥ 30 MHZ)


FIELD STRENGTH	FIELD STRENGTH	S15.209	
of Fundamental:	of Harmonics	30 - 88 MHz	40 dBuV/m
@3M			
902-928 MHZ		88 - 216 MHz	43.5
2.4-2.4835 GHz		216 - 960 MHz	46
94 dBμV/m @3m	54 dBμV/m @3m	ABOVE 960 MHz	54dBuV/m

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).


Test Equipment

	1 cst Equipment					
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Preamplifier	Instruments corporation	EMC01183 0	980100	Aug. 09, 2013	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 23, 2013	1 Year
3.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Aug. 09, 2013	3 Year
4.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 23, 2013	3 Year
5.	Pre-amplifier	SONOMA	310N	186860	Apr. 23, 2013	1 Year
6.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A


4.6.2. Test Configuration: 4.6.2.1. 9k to 30MHz emissions:



4.6.2.2. 30M to 1G emissions:



4.6.2.3. 1G to 40G emissions:



4.6.3. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Measurements are made on 9KHz to 30MHz and 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz.

The EUT is tested in 9*6*6 Chamber.

The test results are listed in Section 4.6.4.

4.6.4. Test Results

The EUT was tested on (Charging to adapter, Communication, Camera Mode, WIFI Mode) modes, only the worst data of (WIFI Mode) are attached in the following pages.

Job No.: AT1402640F Polarization: Horizontal

Standard: (RE)FCC PART15 C _3m Power Source: DC 5V

Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: WIFI Mode Distance: 3m


	00 AD-W-											
8	80.0 dBuV/m									Lin Ma	nit: argin:	
	40	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					5. 4. X		6 X		and the state of t	h-Heddingh-
	10		Markey	Market property and the second	All warrang	m January V	LADAY - JAMAA D	MAN MAN		polinia .		
0	30.000 40	50 60	70 30	Mark Stranger	(MHz)	m-training ()	300	400		600		1000.0
				Result (dBuV/m)		Over Limit	300		500	600 gree	700	
No.	30.000 40 Freq.	50 60	70 80	Result	(MHz)	Over Limit	300	400 Height	500	600 gree	700	1000.0
	30.000 40 Freq. (MHz)	Feading (dBuV/m)	70 80 Factor (dB/m)	Result (dBuV/m)	(MHz) Limit (dBuV/	Over Limit (dB)	300 Detector	400 Height	500	600 gree	700	1000.0
No.	30.000 40 Freq. (MHz) 37.2854	Reading (dBuV/m) 48.84	70 90 Factor (dB/m) -15.41	Result (dBuV/m) 33.43	(MHz) Limit (dBuV/ 40.00	Over Limit (dB) -6.57	300 Detector peak	400 Height	500	600 gree	700	1000.0
No.	Freq. (MHz) 37.2854 54.0711	Reading (dBuV/m) 48.84 48.06	Factor (dB/m) -15.41 -14.87	Result (dBuV/m) 33.43 33.19	(MHz) Limit (dBuV/ 40.00 40.00	Over Limit (dB) -6.57 -6.81	300 Detector peak peak	400 Height	500	600 gree	700	1000.0
No.	Freq. (MHz) 37.2854 54.0711 66.2661	Reading (dBuV/m) 48.84 48.06 50.63	Factor (dB/m) -15.41 -14.87	Result (dBuV/m) 33.43 33.19 32.62	(MHz) Limit (dBuV/ 40.00 40.00	Over Limit (dB) -6.57 -6.81 -7.38	300 Detector peak peak peak	400 Height	500	600 gree	700	1000.0
	Freq. (MHz) 37.2854 54.0711 66.2661 307.8312	Reading (dBuV/m) 48.84 48.06 50.63 51.57	Factor (dB/m) -15.41 -14.87 -18.01 -16.73	Result (dBuV/m) 33.43 33.19 32.62 34.84	Limit (dBuV/ 40.00 40.00 40.00 46.00	Over Limit (dB) -6.57 -6.81 -7.38 -11.16	Detector peak peak peak peak	400 Height	500	600 gree	700	1000.0

Job No.: AT1402640F Polarization: Vertical

Standard: (RE)FCC PART15 C _3m Power Source: DC 5V

Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: WIFI Mode Distance: 3m




Job No.: AT1402640F Polarization: Horizontal

Standard: (RE)FCC PART15 C _3m Power Source: DC 5V

Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Note: 802.11b(2412MHz) Distance: 3m




Job No.: AT1402640F Polarization: Vertical

Standard: (RE)FCC PART15 C _3m Power Source: DC 5V

Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Note: 802.11b(2412MHz) Distance: 3m




Job No.: AT1402640F Polarization: Horizontal

Standard: (RE)FCC PART15 C _3m Power Source: DC 5V

Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Note: 802.11b(2437MHz) Distance: 3m



Job No.:		AT	1402640F		F	Polarizati	ion:	Vert	tical	
tandaı	rd:	(RE)FCC PART15 C _3m					Power So	ource:	DC:	5V
Test item:		Radiation Test 802.11b(2437MHz)					Temp.(C)/Hum.(%RH):			(C)/55%RH
							Distance:		3m	
9	16.9 dBuV/m									
										mit: — /G: —
						1 *				
							3			
	47			M				/~/\/	www	mann,
					mm	المستهما لبر	*			
-3										
	1000.000		2000	3000	(MHz)	5000 60	000 7000 (9000 9000		18000.000
No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
		62.53		65.94						

2

3

4

4867.500

7332.500

7332.500

42.72

45.95

28.19

3.41

8.58

8.58

46.13

54.53

36.77

54.00

74.00

54.00

-7.87

-19.47

-17.23

AVG

peak


AVG

Job No.: AT1402640F Polarization: Horizontal

Standard: (RE)FCC PART15 C _3m Power Source: DC 5V

Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Note: 802.11b(2462MHz) Distance: 3m




Job No.: AT1402640F Polarization: Vertical

Standard: (RE)FCC PART15 C _3m Power Source: DC 5V

Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Note: 802.11b(2462MHz) Distance: 3m




5. PHOTOGRAPH

5.1. Photo of Conducted Emission Measurement



5.2. Photo of Radiation Emission Test





APPENDIX I (EXTERNAL PHOTOS)

Figure 1
The EUT-Overall View



Figure 2
The EUT- Front View








Figure 4
The EUT- Side View



$\textbf{APPENDIX} \quad \text{$ \coprod$ (INTERNAL PHOTOS)$ }$

Figure 5
The EUT-Inside View



Figure 6
The EUT-Inside View









Figure 8
PCB of the EUT-Back View








Figure 10 PCB of the EUT-Back View

