

FCC Radio Test Report

FCC ID: 2ABVH-OONA22-1W

Report No. : BTL-FCCP-5-2305G039
Equipment : Kiosk
Model Name : OONA22-1W
Brand Name : AAVA
Applicant : Aava Mobile Oy
Address : Nahkatehtaankatu 2, FI-90130 Oulu, Finland

Radio Function : NFC (13.56 MHz)

FCC Rule Part(s) : FCC CFR Title 47, Part 15, Subpart C (15.225)
Measurement Procedure(s) : ANSI C63.10-2013

Date of Receipt : 2023/5/11
Date of Test : 2023/6/15
 2023/6/26
Issued Date : 2023/6/26

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by : Eric Lee
Eric Lee, Engineer

Approved by : Jerry Chuang
Jerry Chuang, Supervisor

**BTL Inc.**

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

CONTENTS

REVISION HISTORY	4
1 SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
1.3 TEST ENVIRONMENT CONDITIONS	6
2 GENERAL INFORMATION	7
2.1 DESCRIPTION OF EUT	7
2.2 TEST MODES	8
2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 SUPPORT UNITS	9
3 RADIATED EMISSIONS TEST	10
3.1 LIMIT	10
3.2 TEST PROCEDURE	11
3.3 DEVIATION FROM TEST STANDARD	11
3.4 TEST SETUP	11
3.5 EUT OPERATING CONDITIONS	12
3.6 TEST RESULT – 9 KHZ TO 30 MHZ – FCC PART 15.209	12
3.7 TEST RESULT – 30 MHZ TO 1 GHZ – FCC PART 15.209	12
3.8 TEST RESULT – FCC PART 15.225	12
4 FREQUENCY STABILITY	13
4.1 LIMIT	13
4.2 TEST PROCEDURE	13
4.3 DEVIATION FROM TEST STANDARD	13
4.4 EUT OPERATING CONDITIONS	13
4.5 TEST RESULT	13
5 20 DB BANDWIDTH	14
5.1 LIMIT	14
5.2 TEST PROCEDURE	14
5.3 DEVIATION FROM TEST STANDARD	14
5.4 TEST SETUP	14
5.5 EUT OPERATING CONDITIONS	14
5.6 TEST RESULT	14
6 LIST OF MEASURING EQUIPMENTS	15
7 EUT TEST PHOTO	16
8 EUT PHOTOS	16
APPENDIX A RADIATED EMISSIONS - 9 KHZ TO 30 MHZ	17
APPENDIX B RADIATED EMISSIONS - 30 MHZ TO 1 GHZ	22
APPENDIX C RADIATED EMISSIONS - FCC PART 15.225	25
APPENDIX D FREQUENCY STABILITY MEASUREMENT	28
APPENDIX E 20 DB BANDWIDTH	30

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-5-2305G039	R00	Original Report.	2023/6/19	Invalid
BTL-FCCP-5-2305G039	R01	Added Frequency Stability and 20 dB Bandwidth test items.	2023/6/26	Valid

1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards.

Standard(s) Section	Description	Test Result	Judgement	Remark
15.207	AC Power Line Conducted Emissions	NOTE (3)	Pass	-----
15.35 15.205 15.209 15.225	Radiated Emissions	APPENDIX A APPENDIX B APPENDIX C	Pass	-----
15.225(e)	Frequency Stability	APPENDIX D	Pass	-----
15.203	Antenna Requirement	-----	Pass	-----
15.215(c)	20 dB Bandwidth	APPENDIX E	Pass	-----

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) The report format version is TP.1.1.1.
- (3) The differences compared with test report BTL-FCCP-6-2102C297(FCC ID: 2ABVH-INARI8C1):
 - 1) Changed product name, model name, display, product size, shell and adapter.
 - 2) Removed part of main board features and battery.
 - 3) Added 2*USB A-type ports, 2*USB Type-C ports and LAN port.
 - 4) Changed NFC antenna.

After evaluated, the changes with respect to the original one, only radiated emissions, frequency stability and 20 dB bandwidth tests need to be verified.

The test records and results please refer to the test report number: BTL-FCCP-6-2102C297, issued date is Apr. 14, 2021, and issued by:

Test Laboratory: BTL Inc.

Address: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

Which was accredited by A2LA, accreditation number is 5123.02, with the scopes of cited standards in this test report.

This report is only valid conjunction with the above referenced test report.

1.1 TEST FACILITY

The test locations stated below are under the TAF Accreditation Number 0659.

The test location(s) used to collect the test data in this report are:

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
(FCC DN: TW0659)

C05 CB08 CB11 SR10 SR11

No. 68-2, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
(FCC DN: TW0659)

SR05

No. 72, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
(FCC DN: TW0659)

C06 CB21 CB22

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{cisp} requirement.

A. Radiated emissions test:

Test Site	Method	Measurement Frequency Range	U,(dB)
CB21 (3m)	CISPR	9 kHz ~ 150 kHz	2.82
		150 kHz ~ 30 MHz	2.58

Test Site	Measurement Frequency Range	U,(dB)
CB21	0.03 GHz ~ 0.2 GHz	4.17
	0.2 GHz ~ 1 GHz	4.72
	1 GHz ~ 6 GHz	5.21
	6 GHz ~ 18 GHz	5.51
	18 GHz ~ 26 GHz	3.69
	26 GHz ~ 40 GHz	4.23

B. Conducted test :

Test Item	U,(dB)
Occupied Bandwidth	0.5332
Frequency Stability	0.5333

NOTE:

Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Environment Condition	Test Voltage	Tested by
Radiated emissions (9KHz-30MHz)	23°C, 52%	AC 120V	Mark Wang
Radiated emissions (30MHz TO 1000MHz)	23°C, 52%	AC 120V	Mark Wang
Frequency Stability	24.3°C,47%	AC 120V	Jay Tien
20 dB Bandwidth	24.3°C,47%	AC 120V	Jay Tien

2 GENERAL INFORMATION

2.1 DESCRIPTION OF EUT

Equipment	Kiosk
Model Name	OONA22-1W
Brand Name	AAVA
Model Difference	N/A
Power Source	DC voltage supplied from AC adapter. Model: J652-2403000DI
Power Rating	I/P: 100-240V~ 50/60Hz 1.7A O/P: 24.0V ==== 3.0A 72.0W
Products Covered	1* Adapter: J652-2403000DI
Operation Frequency	13.56 MHz
Antenna Designation	LOOP Antenna
Max H-field strength	72.81 dBuV/m@3m(Peak)
Test Model	OONA22-1W
Sample Status	Engineering Sample
EUT Modification(s)	N/A

NOTE:

(1) The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

(2) Channel List:

Channel	Frequency (MHz)
01	13.56

(3) Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
NFC	N/A	N/A	Loop antenna	N/A	N/A

(4) The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2 TEST MODES


Test Items	Test mode	Channel	Note
Radiated emissions (9KHz-30MHz)	TX	01	-
Radiated emissions (30MHz TO 1000MHz)	TX	01	-
Frequency Stability	TX	01	-
20 dB Bandwidth	TX	01	-

NOTE:

(1) The Radiated emissions test was verified based on the worst conducted power and Bandwidth test results reported in the original report.

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Equipment letters and Cable numbers refer to item numbers described in the tables of clause 2.4.



2.4 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	ADP	UL	J652-2403000DI	N/A	Supplied by test requester.
B	USB 2.5" HDD	AKITIO	Neutrino U3.1	SK21D1621D003F	Furnished by test lab.
C	USB 2.5" HDD	AKITIO	Neutrino U3.1	SK21D1621D003F	Furnished by test lab.
D	USB 3.0 HDD	WD	WDBC3C0010BSL-0B	WX81A88ALJUC	Furnished by test lab.
E	USB	KINGSTON	N/A	N/A	Furnished by test lab.
F	NB	HP	TPN-C125	N/A	Furnished by test lab.

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	N/A	N/A	0.6m	USB TO TYPE-C	Furnished by test lab.
2	N/A	N/A	2m	RJ45 Cable	Furnished by test lab.
3	N/A	N/A	1.2m	POWER CORD	Supplied by test requester.
4	No	No	0.6m	TypeC to TypeC	Furnished by test lab.
5	No	No	1m	TypeC to TypeC	Furnished by test lab.
6	No	No	0.4m	TypeC to USB	Furnished by test lab.

3 RADIATED EMISSIONS TEST

3.1 LIMIT

FCC Part 15.209				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100* 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

FCC Part 15.225(a)/(b)/(c)				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
13.553 – 13.567	15,848	30 m	15,848*100	124
13.567 – 13.710	334	30 m	334*100	90.5
13.110 – 13.410	106	30 m	106*100	80.5
13.710 – 14.010				

NOTE:

- (1) The tighter limit shall apply at the boundary between two frequency range.
- (2) Limitation expressed in dBuV/m is calculated by 20log Emission Level (uV/m).
- (3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $L_{d1} = L_{d2} * (d_2/d_1)^2$.

Example:

F.S Limit at 30m distance is 30uV/m , then F.S Limitation at 3m distance is adjusted as $L_{d1} = L_1 = 30uV/m * (10)^2 = 100 * 30 uV/m$

- (4) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)

Margin Level = Measurement Value – Limit Value

3.2 TEST PROCEDURE

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz).
- b. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- d. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

NOTE: (FCC PART 15.209)

- a. Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode with Detector BW=120 kHz.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.


NOTE: (FCC PART 15.225)


- a. Spectrum Setting:
9 KHz – 150 KHz, RBW= 200Hz, VBW=200Hz, Sweep time = 200 ms.
150 K Hz – 30 MHz, RBW= 10 KHz, VBW=10 KHz, Sweep time = 200 ms.
30 MHz – 1000 MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- c. The Log-Bicon Antenna will use to test frequency range from 30MHz to 1000MHz and the Loop Antenna will use to test frequency below 30MHz.

3.3 DEVIATION FROM TEST STANDARD

No deviation.

3.4 TEST SETUP



30 MHz to 1 GHz

3.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULT – 9 kHz TO 30 MHz – FCC PART 15.209

Please refer to the APPENDIX A

3.7 TEST RESULT – 30 MHz TO 1 GHz – FCC PART 15.209

Please refer to the APPENDIX B.

3.8 TEST RESULT – FCC PART 15.225

Please refer to the APPENDIX C.

NOTE:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

4 FREQUENCY STABILITY

4.1 LIMIT

FCC Part 15.225(e)

The frequency tolerance of the carrier signal shall be maintained within +/-0.01% of the operating frequency over a temperature variation of - 20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

For battery operated equipment, the equipment tests shall be performed using a new battery.

4.2 TEST PROCEDURE

- a. The equipment under test was connected to an external AC power supply and the RF output was connected to a frequency counter via feed through attenuators. The EUT was placed inside the temperature chamber.
- b. At room temperature ($25\pm5^{\circ}\text{C}$), an external variable AC power supply was connected to the EUT. The frequency of the transmitter was measured for 115%, 100% and 85% of the nominal operating input voltage.

4.3 DEVIATION FROM TEST STANDARD

No deviation.

4.4 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.5 TEST RESULT

Please refer to the APPENDIX D.

5 20 DB BANDWIDTH

5.1 LIMIT

FCC Part 15.215(c)

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through §15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


5.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 1 kHz, VBW=1 kHz, Sweep time = 20 ms.

5.3 DEVIATION FROM TEST STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULT

Please refer to the APPENDIX E.

6 LIST OF MEASURING EQUIPMENTS

Radiated Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Preamplifier	EMCI	EMC330N	980850	2022/9/19	2023/9/18
2	Preamplifier	EMCI	EMC001340	980579	2022/9/30	2023/9/29
3	Test Cable	EMCI	EMC104-SM-SM-1000	220319	2023/3/14	2024/3/13
4	Test Cable	EMCI	EMC104-SM-SM-3000	220322	2023/3/14	2024/3/13
5	Test Cable	EMCI	EMC104-SM-SM-7000	220324	2023/3/14	2024/3/13
6	EXA Signal Analyzer	keysight	N9020B	MY57120120	2023/2/24	2024/2/23
7	Loop Ant	Electro-Metrics	EMCI-LPA600	291	2022/9/19	2023/9/18
8	Log-bicon Antenna	Schwarzbeck	VULB9168	1369	2023/5/9	2024/5/8
9	6dB Attenuator	EMCI	EMCI-N-6-06	AT-06001	2023/5/9	2024/5/8
10	Measurement Software	EZ	EZ_EMC (Version NB-03A1-01)	N/A	N/A	N/A

Frequency Stability & 20 dB Bandwidth						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Spectrum Analyzer	R&S	FSV7	103032	2022/8/9	2023/8/8
2	Thermal Chamber	HOLINK	H-TH-2SP-B	EK04101902	2023/6/21	2024/6/20

Remark: "N/A" denotes no model name, no serial no. or no calibration specified.
All calibration period of equipment list is one year.

7 EUT TEST PHOTO


Please refer to document Appendix No.: TP-2305G039-1 (APPENDIX-TEST PHOTOS).

8 EUT PHOTOS

Please refer to document Appendix No.: EP-2305G039-1 (APPENDIX-EUT PHOTOS).

APPENDIX A RADIATED EMISSIONS - 9 KHZ TO 30 MHZ

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Vertical
Temp	23°C	Hum.	52%




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	0.0380	69.97	26.11	96.08	135.09	-39.01	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Vertical
Temp	23°C	Hum.	52%




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	1.2982	69.87	-0.31	69.56	84.41	-14.85	QP	
2		3.8942	59.99	-5.22	54.77	88.62	-33.85	QP	
3		8.6891	53.51	-4.38	49.13	88.62	-39.49	QP	
4		11.2930	51.97	-4.03	47.94	88.62	-40.68	QP	
5		17.6262	48.16	-4.68	43.48	88.62	-45.14	QP	
6		26.6240	50.96	-1.78	49.18	88.62	-39.44	QP	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	23°C	Hum.	52%



No.	Mk.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1	*	0.0377	74.10	26.18	100.28	135.16	-34.88	AVG

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	23°C	Hum.	52%




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.2553	67.92	10.06	77.98	118.54	-40.56	QP	
2	*	2.1618	67.60	-3.09	64.51	88.62	-24.11	QP	
3		4.7578	57.82	-5.64	52.18	88.62	-36.44	QP	
4		10.2383	44.38	-3.91	40.47	88.62	-48.15	QP	
5		22.5275	47.25	-3.72	43.53	88.62	-45.09	QP	
6		26.6230	51.68	-1.78	49.90	88.62	-38.72	QP	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.

APPENDIX B RADIATED EMISSIONS - 30 MHZ TO 1 GHZ

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Vertical
Temp	23°C	Hum.	52%




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	47.1043	45.06	-11.26	33.80	40.00	-6.20	QP	
2		249.9960	46.79	-13.14	33.65	46.00	-12.35	peak	
3		372.6686	48.47	-9.54	38.93	46.00	-7.07	peak	
4		674.9853	37.15	-2.98	34.17	46.00	-11.83	peak	
5		729.3376	37.66	-2.00	35.66	46.00	-10.34	QP	
6		960.0036	38.50	1.39	39.89	54.00	-14.11	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	23°C	Hum.	52%




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	155.9706	50.68	-11.97	38.71	43.50	-4.79	QP	
2	!	250.0283	54.21	-13.14	41.07	46.00	-4.93	QP	
3		295.7477	49.88	-11.39	38.49	46.00	-7.51	QP	
4		340.5293	48.42	-10.44	37.98	46.00	-8.02	peak	
5		499.9973	40.58	-6.33	34.25	46.00	-11.75	peak	
6		960.0037	36.58	1.39	37.97	54.00	-16.03	peak	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.

APPENDIX C RADIATED EMISSIONS - FCC PART 15.225

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Vertical
Temp	23°C	Hum.	52%




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	13.5597	72.50	-4.26	68.24	143.07	-74.83	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX	Test Date	2023/6/15
Test Frequency	13.56MHz	Polarization	Horizontal
Temp	23°C	Hum.	52%



No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
			MHz	dBuV	dB	dBuV/m	dB	
1	*	13.5597	77.07	-4.26	72.81	143.07	-70.26	peak

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

APPENDIX D FREQUENCY STABILITY MEASUREMENT

Test Mode	TX	Tested Date	2023/6/26
-----------	----	-------------	-----------


Temperature	Modulation Mode	Test Freq.	0 min	2 min	5 min	10 min	0 min	2 min	5 min	10 min	Limit (ppm)	Result
Normal												
T _{20°C} Vmax	CW	13.56	13.559 711	13.559 711	13.559 711	13.559 711	-21.3 1	-21.3 1	-21.3 1	-21.31	100	Pass
T _{20°C} Vmin	CW	13.56	13.559 711	13.559 711	13.559 711	13.559 711	-21.3 1	-21.3 1	-21.3 1	-21.31		Pass
Extreme												
T _{50°C} Vnom	CW	13.56	13.559 711	13.559 711	13.559 711	13.559 720	-21.3 1	-21.3 1	-21.3 1	-20.65	100	Pass
T _{40°C} Vnom	CW	13.56	13.559 711	13.559 711	13.559 720	13.559 720	-21.3 1	-21.3 1	-20.6 5	-20.65		Pass
T _{30°C} Vnom	CW	13.56	13.559 682	13.559 682	13.559 711	13.559 720	-23.4 5	-23.4 5	-21.3 1	-20.65		Pass
T _{20°C} Vnom	CW	13.56	13.559 740	13.559 740	13.559 720	13.559 711	-19.1 7	-19.1 7	-20.6 5	-21.31		Pass
T _{10°C} Vnom	CW	13.56	13.559 711	13.559 711	13.559 711	13.559 711	-21.3 1	-21.3 1	-21.3 1	-21.31		Pass
T _{0°C} Vnom	CW	13.56	13.559 711	13.559 711	13.559 720	13.559 740	-21.3 1	-21.3 1	-20.6 5	-19.17		Pass
T _{-10°C} Vnom	CW	13.56	13.559 711	13.559 720	13.559 720	13.559 720	-21.3 1	-20.6 5	-20.6 5	-20.65		Pass

NOTE: 0.01 % = 100 ppm.


APPENDIX E 20 DB BANDWIDTH

Test Mode	TX
-----------	----

Frequency (MHz)	20 dB Bandwidth (MHz)	Operated Frequency Range (MHz)	Designated Frequency Band (MHz)	Result
13.56	13.56	0.0249	0.0211	Complied



Date: 26.JUN.2023 18:14:17



Date: 26.JUN.2023 18:14:58

End of Test Report