

802 N. Twin Oaks Valley Road, Suite 105 • San Marcos, CA 92069 • U.S.A. TEL (760) 471-2100 • FAX (760) 471-2121 http://www.rfexposurelab.com

# CERTIFICATE OF COMPLIANCE SAR EVALUATION

GoTenna, Inc. 102 S 6<sup>th</sup> Street Brooklyn, NY 11249 Dates of Test: Februa Test Report Number: S

February 19-23, 2018 SAR.20180207

Revision A

FCC ID: 2ABVK37337 IC Certificate: 21842-37337 Model(s): 37337

Test Sample: Engineering Unit Same as Production

Serial Number: 004

Equipment Type: Wireless Texting Device

Classification: Portable Transmitter Next to Body TX Frequency Range: 150 – 174 MHz; 450 – 479 MHz

Frequency Tolerance: ± 2.5 ppm

Maximum RF Output: 150 MHz – 37.0 dBm; 450 MHz – 37.0 dBm Conducted

Signal Modulation: FM
Antenna Type: External
Application Type: Certification
FCC Rule Parts: Part 2, 90

KDB Test Methodology: KDB 447498 D01 v06

Industry Canada: RSS-102 Issue 5, Safety Code 6

Maximum SAR Value: 5.46 W/kg Reported Max. Simultaneous SAR: 5.52 W/kg Reported

Separation Distance: 0 mm

This wireless mobile and/or portable device has been shown to be compliant for localized specific absorption rate (SAR) for controlled environment/occupational exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and IEC 62209-2:2010 (See test report).

I attest to the accuracy of the data. All measurements were performed by myself or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RF Exposure Lab, LLC certifies that no party to this application is subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).

Jay M. Moulton Vice President ACCREDITED
Testing Cert. # 2387.01



# **Table of Contents**

1. Introduction	3
SAR Definition [5]	4
2. SAR Measurement Setup	5
Robotic System	5
System Hardware	5
System Electronics	
Probe Measurement System	
3. Probe and Dipole Calibration	
4. Phantom & Simulating Tissue Specifications	15
Head & Body Simulating Mixture Characterization	
5. ANSI/IEEE C95.1 – 1992 RF Exposure Limits [2]	
Uncontrolled Environment	
Controlled Environment	_
6. Measurement Uncertainty	
7. System Validation	
Tissue Verification	
Test System Verification	
8. SAR Test Data Summary	
Procedures Used To Establish Test Signal	
Device Test Condition	
SAR Data Summary – 150 MHz Body	
SAR Data Summary – 450 MHz Body	
SAR Data Summary – Simultaneous Evaluation	
9. Test Equipment List	
10. Conclusion	_
11. References	_
Appendix A – System Validation Plots and Data	
Appendix B – SAR Test Data Plots	
Appendix C – SAR Test Setup Photos	
Appendix D – Probe Calibration Data Sheets	
Appendix E – Dipole Calibration Data Sheets	
Appendix F – Phantom Calibration Data Sheets	
Appendix G – Validation Summary	73



## 1. Introduction

This measurement report shows compliance of the GoTenna, Inc. Model 37337 FCC ID: 2ABVK37337 with FCC Part 2, 1093, ET Docket 93-62 Rules for mobile and portable devices and IC certificate: 21842-37337 with RSS-102 Issue 5 and Safety Code 6. The FCC have adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on August 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC regulated portable devices. [1], [6]

The test results recorded herein are based on a single type test of GoTenna, Inc. Model 37337 and therefore apply only to the tested sample.

The test procedures, as described in ANSI C95.1 – 1999 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [2], ANSI C95.3 – 2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields [3], IEEE Std.1528 – 2003 Recommended Practice [4], and Industry Canada Safety Code 6 Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3kHz to 300 GHz were employed.

The following table indicates all the wireless technologies operating in the 37337 wireless texting device. The table also shows the tolerance for the power level for each mode.

Band	Technology	3GPP Setpoint Nominal Nominal Power Power dBm dBm		Tolerance dBm	Lower Tolerance dBm	Upper Tolerance dBm
150 MHz	FM	N/A	N/A	N/A	N/A	37.0
450 MHz	FM	N/A	N/A	N/A	N/A	37.0
BT	GFSK	N/A	N/A	N/A	N/A	0.00



# **SAR Definition [5]**

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ).

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dV} \right)$$

SAR is expressed in units of watts per kilogram (W/kg). SAR can be related to the electric field at a point by

$$SAR = \frac{\sigma \mid E \mid^2}{\rho}$$

where:

 $\sigma$  = conductivity of the tissue (S/m)

 $\rho$  = mass density of the tissue (kg/m<sup>3</sup>)

E = rms electric field strength (V/m)



# 2. SAR Measurement Setup

## **Robotic System**

These measurements are performed using the DASY52 automated dosimetric assessment system. The DASY52 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Intel Core2 computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Fig. 2.1).

# **System Hardware**

A cell controller system contains the power supply, robot controller teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the HP Intel Core2 computer with Windows XP system and SAR Measurement Software DASY52, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 2.1 SAR Measurement System Setup



# **System Electronics**

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in.

# **Probe Measurement System**

The SAR measurements were conducted with the dosimetric probe EX3DV4, designed in the classical triangular configuration (see Fig. 2.2) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi fiber line ending at the front of the probe tip. (see Fig. 2.3) It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY52 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped at reaching the maximum.



**DAE System** 



## **Probe Specifications**

**Calibration:** In air from 10 MHz to 6.0 GHz

In brain and muscle simulating tissue at Frequencies of 450 MHz, 835 MHz, 1750 MHz, 1900 MHz, 2450 MHz, 2600 MHz, 3500 MHz, 5200

MHz, 5300 MHz, 5600 MHz, 5800 MHz

Frequency: 10 MHz to 6 GHz

**Linearity:** ±0.2dB (30 MHz to 6 GHz)

**Dynamic:** 10 mW/kg to 100 W/kg

Range: Linearity: ±0.2dB

**Dimensions:** Overall length: 330 mm

**Tip length:** 20 mm

Body diameter: 12 mm

Tip diameter: 2.5 mm

Distance from probe tip to sensor center: 1 mm

**Application:** SAR Dosimetry Testing

Compliance tests of wireless device




Figure 2.2 Triangular Probe Configurations



Figure 2.3 Probe Thick-Film Technique



### **Probe Calibration Process**

## **Dosimetric Assessment Procedure**

Each probe is calibrated according to a dosimetric assessment procedure described in with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in and found to be better than +/-0.25dB. The sensitivity parameters (Norm X, Norm Y, Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe is tested.

### **Free Space Assessment**

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a waveguide above 1GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm<sup>2</sup>.

## Temperature Assessment \*

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium, correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor based temperature probe is used in conjunction with the E-field probe

$$SAR = C \frac{\Delta T}{\Delta t}$$

$$SAR = \frac{\left|E\right|^2 \cdot \sigma}{\rho}$$

where: where:

 $\Delta t$  = exposure time (30 seconds),  $\sigma$  = simulated tissue conductivity,

C = heat capacity of tissue (brain or muscle),  $\rho$  = Tissue density (1.25 g/cm<sup>3</sup> for brain tissue)

 $\Delta T$  = temperature increase due to RF exposure.

SAR is proportional to  $\Delta T \, / \, \Delta t$  , the initial rate of tissue

heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by

equating the thermally derived SAR to the E- field;




Figure 2.4 E-Field and Temperature Measurements at 900MHz




Figure 2.5 E-Field and Temperature Measurements at 1800MHz



## **Data Extrapolation**

The DASY52 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given like below:

with 
$$V_i = \text{compensated signal of channel i}$$
 (i=x,y,z)
$$U_i = \text{input signal of channel i}$$
 (i=x,y,z)
$$C_i = \text{crest factor of exciting field}$$
 (DASY parameter)
$$C_i = C_i + U_i^2 \cdot \frac{cf}{dcp_i}$$
 (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: with 
$$V_i$$
 = compensated signal of channel i (i = x,y,z) Norm<sub>i</sub> = sensor sensitivity of channel i (i = x,y,z)  $\mu V/(V/m)^2$  for E-field probes ConvF = sensitivity of enhancement in solution  $E_i$  = electric field strength of channel i in V/m

The RSS value of the field components gives the total field strength (Hermetian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^{\,2} \cdot \frac{\sigma}{\rho \cdot 1000} \hspace{1cm} \text{with} \hspace{1cm} \begin{array}{ll} \text{SAR} & = \text{local specific absorption rate in W/g} \\ E_{tot} & = \text{total field strength in V/m} \\ \sigma & = \text{conductivity in [mho/m] or [Siemens/m]} \\ \rho & = \text{equivalent tissue density in g/cm}^3 \end{array}$$

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770}$$
 with  $P_{pwe} = \text{equivalent power density of a plane wave in W/cm}^2$  = total electric field strength in V/m



## Scanning procedure

- The DASY installation includes predefined files with recommended procedures for measurements and system check. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.
- The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. +/- 5 %.
- The highest integrated SAR value is the main concern in compliance test applications. These values can mostly be found at the inner surface of the phantom and cannot be measured directly due to the sensor offset in the probe. To extrapolate the surface values, the measurement distances to the surface must be known accurately. A distance error of 0.5mm could produce SAR errors of 6% at 1800 MHz. Using predefined locations for measurements is not accurate enough. Any shift of the phantom (e.g., slight deformations after filling it with liquid) would produce high uncertainties. For an automatic and accurate detection of the phantom surface, the DASY5 system uses the mechanical surface detection. The detection is always at touch, but the probe will move backward from the surface the indicated distance before starting the measurement.
- The "area scan" measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The scan uses different grid spacings for different frequency measurements. Standard grid spacing for head measurements in frequency ranges 2GHz is 15 mm in x and y- dimension. For higher frequencies a finer resolution is needed, thus for the grid spacing is reduced according the following table:

Area scan grid spacing for different frequency ranges					
Frequency range	Grid spacing				
≤ 2 GHz	≤ 15 mm				
2 – 4 GHz	≤ 12 mm				
4 – 6 GHz	≤ 10 mm				

Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation. Results of this coarse scan are shown in annex B.



• A "zoom scan" measures the field in a volume around the 2D peak SAR value acquired in the previous "coarse" scan. It uses a fine meshed grid where the robot moves the probe in steps along all the 3 axis (x,y and z-axis) starting at the bottom of the Phantom. The grid spacing for the cube measurement is varied according to the measured frequency range, the dimensions are given in the following table:

Zoom scan grid spacing and volume for different frequency ranges						
Frequency range	Grid spacing	Grid spacing	Minimum zoom			
rrequency range	for x, y axis	for z axis	scan volume			
≤ 2 GHz	≤ 8 mm	≤ 5 mm	≥ 30 mm			
2 – 3 GHz	≤ 5 mm	≤ 5 mm	≥ 28 mm			
3 – 4 GHz	≤ 5 mm	≤ 4 mm	≥ 28 mm			
4 – 5 GHz	≤ 4 mm	≤ 3 mm	≥ 25 mm			
5 – 6 GHz	≤ 4 mm	≤ 2 mm	≥ 22 mm			

DASY is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in annex B. Test results relevant for the specified standard (see section 3) are shown in table form in section 7.



### **Spatial Peak SAR Evaluation**

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of all points in the three directions x, y and z. The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 1 to 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting 'Graph Evaluated'.
- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.
- All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.

## **Extrapolation**

The extrapolation is based on a least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

#### Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computermathematik, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff].

#### **Volume Averaging**

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

### **Advanced Extrapolation**

DASY uses the advanced extrapolation option which is able to compensate boundary effects on Efield probes.



## **SAM PHANTOM**

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 2.6)

## **Phantom Specification**

**Phantom:** SAM Twin Phantom (V4.0) **Shell Material:** Vivac Composite

Thickness:  $2.0 \pm 0.2 \text{ mm}$ 




Figure 2.6 SAM Twin Phantom

#### **Device Holder for Transmitters**

In combination with the SAM Twin Phantom V4.0 the Mounting Device (see Fig. 2.7), enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can be easily, accurately, and repeat ably be positioned according to the FCC, CENELEC, IEC and IEEE specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



**Figure 2.7 Mounting Device** 

Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produce infinite number of configurations. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



# 3. Probe and Dipole Calibration

See Appendix D and E.



# 4. Phantom & Simulating Tissue Specifications

## **Head & Body Simulating Mixture Characterization**

The head and body mixtures consist of the material based on the table listed below. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. Body tissue parameters that have not been specified in IEEE1528-2013 are derived from the issue dielectric parameters computed from the 4-Cole-Cole equations.

**Table 4.1 Typical Composition of Ingredients for Tissue** 

		Simulating Tissue			
Ingredients		Simulating rissue			
		150 MHz Body	450 MHz Body		
Mixing Percentage					
Water			51.16		
Sugar		Proprietary Procured	46.78		
Salt			1.49		
HEC		from Speag	0.52		
Bactericide			0.05		
DGBE			0.00		
Dielectric Constant	Target	61.90	56.70		
Conductivity (S/m) Target		0.80	0.94		



# 5. ANSI/IEEE C95.1 – 1992 RF Exposure Limits [2]

### **Uncontrolled Environment**

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

## **Controlled Environment**

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 5.1 Human Exposure Limits** 

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIROMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR <sup>1</sup> Head	1.60	8.00
SPATIAL AVERAGE SAR <sup>2</sup> Whole Body	0.08	0.40
SPATIAL PEAK SAR <sup>3</sup> Hands, Feet, Ankles, Wrists	4.00	20.00

<sup>&</sup>lt;sup>1</sup> The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

<sup>&</sup>lt;sup>2</sup> The Spatial Average value of the SAR averaged over the whole body.

<sup>&</sup>lt;sup>3</sup> The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.



# 6. Measurement Uncertainty

Measurement uncertainty table is not required per KDB 865664 D01 v01r04 section 2.8.2 page 12. SAR measurement uncertainty analysis is required in the SAR report only when the highest measured SAR in a frequency band is  $\geq$  1.5 W/kg for 1-g SAR. The equivalent ratio (1.5/1.6) should be applied to extremity and occupational exposure conditions. The highest reported value is less than 1.5 W/kg. Therefore, the measurement uncertainty table is not required.



# 7. System Validation

## **Tissue Verification**

**Table 7.1 Measured Tissue Parameters** 

Table 111 measured floods farameters							
		150 MHz Body		450 MHz Body			
Date(s)	(s)		Feb. 21, 2018		19, 2018		
Liquid Temperature (°C)	20.0	Target	Measured	Target	Measured		
Dielectric Constant: ε		61.90	61.72	56.70	56.71		
Conductivity: σ		0.80	0.81	0.94	0.95		

See Appendix A for data printout.

# **Test System Verification**

Prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at the test frequency by using the system kit. Power is normalized to 1 watt. (Graphic Plots Attached)

**Table 7.2 System Dipole Validation Target & Measured** 

	Test Frequency	Targeted SAR <sub>1g</sub> (W/kg)	Measure SAR <sub>1g</sub> (W/kg)	Tissue Used for Verification	Deviation Target and Fast SAR to SAR (%)	Plot Number
21-Feb-2018	150 MHz	3.95	3.90	Body	- 1.27	1
19-Feb-2018	450 MHz	4.53	4.52	Body	- 0.22	2

See Appendix A for data plots.




Figure 7.1 Dipole Validation Test Setup



# 8. SAR Test Data Summary See Measurement Result Data Pages

See Appendix B for SAR Test Data Plots. See Appendix C for SAR Test Setup Photos.

## **Procedures Used To Establish Test Signal**

The device was either placed into simulated transmit mode using the manufacturer's test codes or the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

## **Device Test Condition**

In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power unless otherwise noted. If a conducted power deviation of more than 5% occurred, the test was repeated. The power drift of each test is measured at the start of the test and again at the end of the test. The drift percentage is calculated by the formula ((end/start)-1)\*100 and rounded to three decimal places. The drift percentage is calculated into the resultant SAR value on the data sheet for each test.

The EUT was tested in on all sides of the device. The Bluetooth transmitter does simultaneously transmit with the main transmitter. Simultaneous transmission is evaluated on page 23.

The device was not able to operate at a duty cycle higher than 25%. All testing was conducted with the 25% duty cycle. The SAR value was than scaled to 20% duty cycle as that is the highest duty cycle the device will be allowed to operate based on the firmware control.

The antenna was on a minimum of 10 cm of Styrofoam during each test.

VHF/UHF					
Freq (MHz)	Channel	Power (dBm)			
150.025	1	35.97			
158	2	35.95			
166	3	35.98			
173.275	4	35.96			
450.025	5	35.98			
469.975	6	35.97			
479	7	35.98			



Figure 8.1 Test Reduction Table – 150/450 MHz

<u> </u>	<u> </u>	1 CSt 1 Cau	ction rable – i	130/430 WII IZ	
Band	Mode	Side	Required Channel	Tested/Reduced	
			1 – 150.025 MHz	Tested	
		Front	2 – 158 MHz	Tested	
		FION	3 – 166 MHz	Tested	
			4 – 173.275 MHz	Tested	
			1 – 150.025 MHz	Tested	
		Back	2 – 158 MHz	Tested	
		Dack	3 – 166 MHz	Tested	
150 MHz			4 – 173.275 MHz	Tested	
130 MITZ			1 – 150.025 MHz	Tested	
		Left	2 – 158 MHz	Tested	
	FM	Leit	3 – 166 MHz	Tested	
			4 – 173.275 MHz	Tested	
		Right	1 – 150.025 MHz	Tested	
			2 – 158 MHz	Tested	
	1 101	Right	3 – 166 MHz	Tested	
			4 – 173.275 MHz	Tested	
			5 – 450.025 MHz	Tested	
		Front	6 – 469.975 MHz	Tested	
			7 – 479 MHz	Tested	
			5 – 450.025 MHz	Tested	
		Back	6 – 469.975 MHz	Tested	
450 MHz			7 – 479 MHz	Tested	
750 WII IZ			5 – 450.025 MHz	Tested	
		Left	6 – 469.975 MHz	Tested	
			7 – 479 MHz	Tested	
			5 – 450.025 MHz	Tested	
		Right	6 – 469.975 MHz	Tested	
			7 – 479 MHz	Tested	



# SAR Data Summary - 150 MHz Body

MEASUREMENT RESULTS									
Plot	Gap	Position	Freque	ncy	Modulation	Antenna	End Power	Measured	Reported
	- Gup		MHz	Ch.		7	(dBm)	SAR (W/kg)	SAR (W/kg)
1			150.025	1	FM		35.97	0.976	0.99
		Front	158.000	2	FM		35.95	0.475	0.48
		Front	166.000	3	FM		35.98	0.426	0.43
			173.275	4	FM		35.96	0.425	0.43
			150.025	1	FM		35.97	0.791	0.80
		Back	158.000	2	FM		35.95	0.608	0.62
		Dack	166.000	3	FM		35.98	0.419	0.42
	0		173.275	4	FM	Main	35.96	0.338	0.34
	mm		150.025	1	FM	IVIAIII	35.97	0.596	0.60
		Left	158.000	2	FM		35.95	0.629	0.64
		Leit	166.000	3	FM		35.98	0.511	0.52
	]		173.275	4	FM		35.96	0.418	0.42
			150.025	1	FM		35.97	0.917	0.93
		Right	158.000	2	FM		35.95	0.645	0.66
		Right	166.000	3	FM		35.98	0.450	0.46
			173.275	4	FM		35.96	0.435	0.44

Body 8.0 W/kg (mW/g) averaged over 1 gram

1.	Battery is fully charged for a	all tests.		
	Power Measured	⊠Conducted	□ERP	☐EIRP
2.	SAR Measurement			
	Phantom Configuration	Left Head	⊠Eli4	Right Head
	SAR Configuration	Head	$\boxtimes$ Body	
3.	Test Signal Call Mode	⊠Test Code	☐Base Station Sim	
4.	Test Configuration	☐With Belt Clip	Without Belt Clip	p ⊠N/A
5	Tissue Depth is at least 15.0	cm		

Jay M. Moulton Vice President

Note: The Reported SAR value was calculated by first scaling the measured SAR value to 100% duty cycle. The 100% duty cycle value was then scaled to the upper end of the tune up procedure value (37 dBm). The upper end of the tune up procedure was then scaled to the 20% duty cycle for a final reported SAR value.



# SAR Data Summary – 450 MHz Body

MEASUREMENT RESULTS									
Plot	Gap	Position	Frequency		Modulation	Antenna	End Power	Measured	Reported
			MHz	Ch.	modulation	,a	(dBm)	SAR (W/kg)	SAR (W/kg)
		Front	450.025	5	FM	Main	35.98	3.83	3.88
			469.975	6	FM		35.97	2.86	2.90
			479.000	7	FM		35.98	2.71	2.74
		Back	450.025	5	FM		35.98	2.35	2.38
			469.975	6	FM		35.97	3.24	3.29
	0		479.000	7	FM		35.98	3.41	3.45
	_	Left	450.025	5	FM		35.98	3.59	3.63
	mm		469.975	6	FM		35.97	3.84	3.89
			479.000	7	FM		35.98	3.49	3.53
2		Right	450.025	5	FM		35.98	5.40	5.46
			469.975	6	FM		35.97	3.97	4.03
			479.000	7	FM		35.98	4.45	4.50
		Repeat	450.025	5	FM		35.98	5.38	5.44

Body 8.0 W/kg (mW/g) averaged over 1 gram

1.	Battery is fully charged for all tests.						
	Power Measured		□ERP	☐EIRP			
2.	SAR Measurement						
	Phantom Configuration	Left Head	⊠Eli4	Right Head			
	SAR Configuration	Head	$\boxtimes$ Body				
3.	Test Signal Call Mode	☐Test Code	☐Base Station S	Simulator			
4.	Test Configuration	☐With Belt Clip	☐Without Belt	Clip ⊠N/A			
5.	Tissue Depth is at least 15.0	cm					

Jay M. Moulton Vice President

Note: The Reported SAR value was calculated by first scaling the measured SAR value to 100% duty cycle. The 100% duty cycle value was then scaled to the upper end of the tune up procedure value (37 dBm). The upper end of the tune up procedure was then scaled to the 20% duty cycle for a final reported SAR value.



# **SAR Data Summary – Simultaneous Evaluation**

MEASUREMENT RESULTS								
Frequency		Modulation	Frequency		Modulation	SAR₁	SAR <sub>2</sub>	SAR Total
MHz	Ch.		MHz	Ch.	oud.ut.o	0(	<b>37 12</b>	07111 7 0 1 1 1 1
150.025	1	FM	2440	39	GFSK	0.99	0.06	1.05
450.025	5	FM	2440	39	GFSK	5.46	0.06	5.52

Body 8.0 W/kg (mW/g) averaged over 1 gram

The sum of the two transmitters is less than the limit; therefore, the simultaneous transmission meets the requirements of KDB447498 D01 v05r02 section 4.3.2 page 11.

BT Calculated SAR per KDB 447498 D01 v05r02 section 4.3.2 2) page 13.

SAR = [(Max power including tolerance, mW)/(Min test separation distance, mm)]\*[ $\sqrt{f_{(GHz)}/7.5}$ ]

 $\begin{aligned} &\text{Max power} = 1 \text{ mW} \\ &\text{Test Separation} = 3 \text{ mm} \\ &f_{\text{(GHz)}} = 2.48 \end{aligned}$ 

 $SAR = (1/3)*(\sqrt{2.48/7.5}) = 0.06$ 



# 9. Test Equipment List

**Table 9.1 Equipment Specifications** 

Туре	Calibration Due Date	<b>Calibration Done Date</b>	Serial Number
Staubli Robot TX60L	N/A	N/A	F07/55M6A1/A/01
Measurement Controller CS8c	N/A	N/A	1012
ELI4 Flat Phantom	N/A	N/A	1065
Device Holder	N/A	N/A	N/A
Data Acquisition Electronics 4	04/24/2018	04/24/2017	1416
SPEAG E-Field Probe EX3DV4	04/27/2018	04/27/2017	3662
Speag Validation Loop Antenna CLA150	12/06/2018	12/06/2016	4002
Speag Validation Dipole Antenna D450V3	01/14/2019	01/14/2016	1085
Agilent N1911A Power Meter	05/20/2019	03/20/2017	GB45100254
Agilent N1922A Power Sensor	06/21/2019	06/21/2017	MY45240464
Advantest R3261A Spectrum Analyzer	03/26/2019	03/20/2017	31720068
Agilent (HP) 8350B Signal Generator	03/26/2019	03/20/2017	2749A10226
Agilent (HP) 83525A RF Plug-In	03/26/2019	03/20/2017	2647A01172
Agilent (HP) 8753C Vector Network Analyzer	03/26/2019	03/20/2017	3135A01724
Agilent (HP) 85047A S-Parameter Test Set	03/26/2019	03/20/2017	2904A00595
Agilent (HP) 8960 Base Station Sim.	03/30/2019	03/30/2017	MY48360364
Anritsu MT8820C	07/27/2019	07/27/2017	6201176199
Agilent 778D Dual Directional Coupler	N/A	N/A	MY48220184
MiniCircuits BW-N20W5+ Fixed 20 dB	N/A	N/A	N/A
Attenuator			
MiniCircuits SPL-10.7+ Low Pass Filter	N/A	N/A	R8979513746
Aprel Dielectric Probe Assembly	N/A	N/A	0011
Body Equivalent Matter (150 MHz)	N/A	N/A	N/A
Body Equivalent Matter (450 MHz)	N/A	N/A	N/A



## 10. Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC/IC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body is a very complex phenomena that depends on the mass, shape, and size of the body; the orientation of the body with respect to the field vectors; and, the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.



## 11. References

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio Frequency Radiation, August 1996
- [2] ANSI/IEEE C95.1 1992, American National Standard Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 300kHz to 100GHz, New York: IEEE, 1992.
- [3] ANSI/IEEE C95.3 1992, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields RF and Microwave, New York: IEEE, 1992.
- [4] International Electrotechnical Commission, IEC 62209-2 (Edition 1.0), Human Exposure to radio frequency fields from hand-held and body mounted wireless communication devices Human models, instrumentation, and procedures Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), March 2010.
- [5] IEEE Standard 1528 2013, IEEE Recommended Practice for Determining the Peak-Spatial Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communication Devices: Measurement Techniques, June 2013.
- [6] Industry Canada, RSS 102e, Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), March 2010.
- [7] Health Canada, Safety Code 6, Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3kHz to 300 GHz, 2009.





# Appendix A – System Validation Plots and Data

```
Test Result for UIM Dielectric Parameter
Wed 21/Feb/2018
Freq Frequency(GHz)
FCC_eH FCC Limits for Head Epsilon
FCC_sH FCC Limits for Head Sigma
FCC_eB FCC Limits for Body Epsilon
FCC_sB FCC Limits for Body Sigma
Test_e Epsilon of UIM
Test s Sigma of UIM
 *************
Freq FCC_eB FCC_sB Test_e Test_s
0.1300 62.39 0.78 62.22 0.80
0.1400 62.15 0.79 61.97 0.81
0.1500 61.90 0.80 61.72 0.81
0.150025 61.90 0.80 61.72 0.81*
0.1580 61.831 0.803 61.656 0.813*
0.1600 61.65 0.81 61.46 0.82
0.1660 61.506 0.816 61.31 0.826*
0.1700 61.41 0.82 61.21 0.83
0.173275 61.328 0.82 61.125 0.833*
0.1800 61.16 0.82 60.95 0.84
0.1900 60.91 0.83 60.70 0.85
* value interpolated
 *****************
Test Result for UIM Dielectric Parameter
Wed 19/Feb/2018
Freq Frequency(GHz)
FCC_eH Limits for Head Epsilon
FCC_sH Limits for Head Sigma
FCC_eB Limits for Body Epsilon
FCC_sB Limits for Body Sigma
Test_e Epsilon of UIM
Test_s Sigma of UIM
*****************
```

<sup>\*</sup> value interpolated



# RF Exposure Lab

## Plot 1

DUT: Loop 150 MHz CLA150; Type: CLA150; Serial: CLA150 - SN:4002

Communication System: CW; Frequency: 150 MHz; Duty Cycle: 1:1

Medium: MSL150; Medium parameters used: f = 150 MHz;  $\sigma$  = 0.81 S/m;  $\epsilon_r$  = 61.72;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Test Date: Date: 2/21/2018; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(11.22, 11.22, 11.22); Calibrated: 4/27/2017;

Sensor-Surface: 2mm (Mechanical Surface Detection) Electronics: DAE4 Sn1416; Calibrated: 4/24/2017 Phantom: ELI v4.0; Type: QDOVA001BB; Serial: 1065

Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

#### **Procedure Notes:**


**150 MHz Head/Verification/Area Scan (11x15x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 2.12 W/kg

150 MHz Head/Verification/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 53.572 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.22 W/kg

SAR(1 g) = 1.95 W/kg; SAR(10 g) = 1.26 W/kg Maximum value of SAR (measured) = 2.15 W/kg  $P_{in} = 500 \text{ mW}$ 









# RF Exposure Lab

## Plot 2

DUT: Dipole 450 MHz D450V2; Type: D450V2; Serial: D450V2 - SN:1085

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium: MSL450; Medium parameters used: f = 450 MHz;  $\sigma$  = 0.95 S/m;  $\epsilon_r$  = 56.71;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Test Date: Date: 2/19/2018; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(10.58, 10.58, 10.58); Calibrated: 4/27/2017;

Sensor-Surface: 2mm (Mechanical Surface Detection) Electronics: DAE4 Sn1321; Calibrated: 1/10/2018 Phantom: ELI v4.0; Type: QDOVA001BB; Serial: 1065

Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

#### **Procedure Notes:**

**450 MHz Body/Verification/Area Scan (7x17x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 3.05 W/kg

450 MHz Body/Verification/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 49.718 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 4.47 W/kg


SAR(1 g) = 2.26 W/kg; SAR(10 g) = 1.45 W/kg

P<sub>IN</sub>=500 mW

Maximum value of SAR (measured) = 3.10 W/kg









# **Appendix B – SAR Test Data Plots**



# RF Exposure Lab

## Plot 1

DUT: 37337; Type: Communications Link; Serial: 004

Communication System: FM; Frequency: 150.025 MHz; Duty Cycle: 1:4.00037

Medium: MSL150; Medium parameters used (interpolated): f = 150.025 MHz;  $\sigma = 0.81 \text{ S/m}$ ;  $\epsilon_r = 61.72$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Test Date: Date: 2/22/2018; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(11.22, 11.22, 11.22); Calibrated: 4/27/2017;

Sensor-Surface: 2mm (Mechanical Surface Detection) Electronics: DAE4 Sn1416; Calibrated: 4/24/2017 Phantom: ELI v4.0; Type: QDOVA001BB; Serial: 1065

Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

#### **Procedure Notes:**

150 MHz/Front 150.025 MHz/Area Scan (5x15x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.38 W/kg

150 MHz/Front 150.025 MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 31.90 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 2.33 W/kg

SAR(1 g) = 0.976 W/kg; SAR(10 g) = 0.526 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.50 W/kg





# RF Exposure Lab

## Plot 2

DUT: 37337; Type: Communications Link; Serial: 004

Communication System: FM; Frequency: 450.025 MHz; Duty Cycle: 1:4.00037

Medium: MSL450; Medium parameters used (interpolated): f = 450.025 MHz;  $\sigma = 0.95 \text{ S/m}$ ;  $\epsilon_r = 56.71$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Test Date: Date: 2/21/2018; Ambient Temp: 23 °C; Tissue Temp: 21 °C

Probe: EX3DV4 - SN3662; ConvF(10.58, 10.58, 10.58); Calibrated: 4/27/2017;

Sensor-Surface: 2mm (Mechanical Surface Detection) Electronics: DAE4 Sn1416; Calibrated: 4/24/2017 Phantom: ELI v4.0; Type: QDOVA001BB; Serial: 1065

Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

#### **Procedure Notes:**

450 MHz/Right 450.025 MHz/Area Scan (5x21x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 8.82 W/kg

450 MHz/Right 450.025 MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 65.97 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 13.7 W/kg

SAR(1 g) = 5.4 W/kg; SAR(10 g) = 2.78 W/kg

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 9.06 W/kg







# **Appendix C – SAR Test Setup Photos**



**Test Position Back 0 mm Gap** 





**Test Position Front 0 mm Gap** 





**Test Position Left Side 0 mm Gap** 





Test Position Right Side 0 mm Gap





**Front of Device** 





**Back of Device** 





**Device with Antennas** 



# **Appendix D – Probe Calibration Data Sheets**



#### Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA

Multilateral Agreement for the recognition of calibration certificates

Client

**RF Exposure Lab** 

Certificate No: EX3-3662\_Apr17

## **CALIBRATION CERTIFICATE**

Object

EX3DV4 - SN:3662

Calibration procedure(s)

QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v4, QA CAL-23.v5,

**QA CAL-25.v6** 

Calibration procedure for dosimetric E-field probes

Calibration date:

April 27, 2017

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Drimen, Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Primary Standards	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power meter NRP	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Power sensor NRP-Z91	SN: S5277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference 20 dB Attenuator	SN: 3013	31-Dec-16 (No. ES3-3013_Dec16)	Dec-17
Reference Probe ES3DV2	SN: 660	7-Dec-16 (No. DAE4-660_Dec16)	Dec-17
DAE4	SIN: 000	7-Dec 10 (No. 5) (2 : 555_2 = 5555)	
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power meter E4413B	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C  Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by:

Name

Function

Laboratory Technician

Approved by:

Katja Pokovic

Jeton Kastrati

**Technical Manager** 

Issued: April 27, 2017

Signature

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX3-3662\_Apr17

Page 1 of 11

#### Calibration Laboratory of

Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst

Service suisse d'étalonnage

C Servizio svizzero di taratura S **Swiss Calibration Service** 

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates Accreditation No.: SCS 0108

#### Glossary:

tissue simulating liquid TSL sensitivity in free space NORMx,y,z

sensitivity in TSL / NORMx,y,z ConvF diode compression point DCP

crest factor (1/duty\_cycle) of the RF signal CF modulation dependent linearization parameters A, B, C, D

o rotation around probe axis Polarization φ

9 rotation around an axis that is in the plane normal to probe axis (at measurement center), Polarization 9

i.e.,  $\vartheta = 0$  is normal to probe axis

information used in DASY system to align probe sensor X to the robot coordinate system Connector Angle

## Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013

IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010

d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- NORMx, y, z: Assessed for E-field polarization 9 = 0 (f  $\leq 900$  MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E2-field uncertainty inside TSL (see below ConvF).
- $NORM(f)x,y,z = NORMx,y,z * frequency_response$  (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal
- Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).

Certificate No: EX3-3662\_Apr17 Page 2 of 11 EX3DV4 – SN:3662

# Probe EX3DV4

SN:3662

Manufactured:

October 20, 2008

Repaired:

April 20, 2017

Calibrated:

April 27, 2017

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)

April 27, 2017 EX3DV4-SN:3662

# DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

**Basic Calibration Parameters** 

Basic Cambration Fara	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm (μV/(V/m) <sup>2</sup> ) <sup>A</sup>	0.43	0.46	0.48	± 10.1 %
DCP (mV) <sup>B</sup>	98.0	97.9	93.7	

**Modulation Calibration Parameters** 

UID	Communication System Name		A dB	B dB√μV	С	D dB	VR mV	Unc <sup>E</sup> (k=2)
0	CW	X	0.0	0.0	1.0	0.00	139.8	±3.3 %
-		Y	0.0	0.0	1.0		134.3	
		Z	0.0	0.0	1.0		148.5	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>&</sup>lt;sup>^</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:3662

# DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

# Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) F	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unc (k=2)
150	52.3	0.76	11.34	11.34	11.34	0.00	1.00	± 13.3 %
220	49.0	0.81	11.12	11.12	11.12	0.00	1.00	± 13.3 %
450	43.5	0.87	11.08	11.08	11.08	0.15	1.20	± 13.3 %
750	41.9	0.89	9.72	9.72	9.72	0.57	0.80	± 12.0 %
835	41.5	0.90	9.44	9.44	9.44	0.37	1.02	± 12.0 %
900	41.5	0.97	9.19	9.19	9.19	0.32	1.09	± 12.0 %
1900	40.0	1.40	7.91	7.91	7.91	0.36	0.80	± 12.0 %
2450	39.2	1.80	7.45	7.45	7.45	0.33	0.86	± 12.0 %
5200	36.0	4.66	5.12	5.12	5.12	0.35	1.80	± 13.1 9
5300	35.9	4.76	4.91	4.91	4.91	0.35	1.80	± 13.1 9
5500	35.6	4.96	4.97	4.97	4.97	0.40	1.80	± 13.1 9
5600	35.5	5.07	4.85	4.85	4.85	0.40	1.80	± 13.1 °
5800	35.3	5.27	4.88	4.88	4.88	0.40	1.80	± 13.1 °

<sup>&</sup>lt;sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

validity can be extended to  $\pm$  110 MHz. F At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to  $\pm$  10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to  $\pm$  5%. The uncertainty is the RSS of the ConyE uncertainty for indicated target tissue parameters

Certificate No: EX3-3662\_Apr17 Page 5 of 11

the ConvF uncertainty for indicated target tissue parameters.

Galpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3662

# DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

# Calibration Parameter Determined in Body Tissue Simulating Media

(MHz) <sup>c</sup>	Parameter Do  Relative  Permittivity F	Conductivity (S/m) F	ConvF X	ConvF Y	ConvF Z	Alpha <sup>G</sup>	Depth <sup>G</sup> (mm)	Unc (k=2)
150	61.9	0.80	11.22	11.22	11.22	0.00	1.00	± 13.3 %
220	60.2	0.86	10.62	10.62	10.62	0.00	1.00	± 13.3 %
450	56.7	0.94	10.58	10.58	10.58	0.09	1.20	± 13.3 %
750	55.5	0.96	9.66	9.66	9.66	0.48	0.80	± 12.0 %
835	55.2	0.97	9.34	9.34	9.34	0.45	0.80	± 12.0 %
900	55.0	1.05	9.27	9.27	9.27	0.42	0.80	± 12.0 %
1900	53.3	1.52	7.87	7.87	7.87	0.37	0.80	± 12.0 %
2450	52.7	1.95	7.49	7.49	7.49	0.30	0.90	± 12.0 %
5200	49.0	5.30	4.64	4.64	4.64	0.40	1.90	± 13.1 %
5300	48.9	5.42	4.51	4.51	4.51	0.40	1.90	± 13.1 9
5500	48.6	5.65	4.11	4.11	4.11	0.45	1.90	± 13.1 9
5600	48.5	5.77	3.96	3.96	3.96	0.45	1.90	± 13.1 9
5800	48.2	6.00	4.07	4.07	4.07	0.50	1.90	± 13.1 9

<sup>&</sup>lt;sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

Certificate No: EX3-3662\_Apr17 Page 6 of 11

validity can be extended to  $\pm$  110 MHz.


F At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to  $\pm$  10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to  $\pm$  5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

See Alpha Death are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is

<sup>&</sup>lt;sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

April 27, 2017 EX3DV4-SN:3662

# Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

Certificate No: EX3-3662\_Apr17

Certificate No: EX3-3662\_Apr17

# Receiving Pattern ( $\phi$ ), $\vartheta = 0^{\circ}$







Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

EX3DV4- SN:3662

# Dynamic Range f(SAR<sub>head</sub>) (TEM cell , f<sub>eval</sub>= 1900 MHz)







Uncertainty of Linearity Assessment: ± 0.6% (k=2)

EX3DV4- SN:3662 April 27, 2017

# **Conversion Factor Assessment**



Deviation from Isotropy in Liquid Error (φ, θ), f = 900 MHz



EX3DV4- SN:3662 April 27, 2017

# DASY/EASY - Parameters of Probe: EX3DV4 - SN:3662

#### **Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	-22.8
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm



# **Appendix E – Dipole Calibration Data Sheets**

#### Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

**RF Exposure Lab** 

Certificate No: CLA150-4002\_Dec16

#### **CALIBRATION CERTIFICATE**

Object

CLA150 - SN: 4002

Calibration procedure(s)

**QA CAL-15.v8** 

Calibration procedure for system validation sources below 700 MHz

Calibration date:

December 06, 2016

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	06-Apr-16 (No. 217-02288/02289)	Apr-17
Power sensor NRP-Z91	SN: 103244	06-Apr-16 (No. 217-02288)	Apr-17
Power sensor NRP-Z91	SN: 103245	06-Apr-16 (No. 217-02289)	Apr-17
Reference 30 dB Attenuator	SN: 5129 (30b)	05-Apr-16 (No. 217-02294)	Apr-17
Type-N mismatch combination	SN: 5047.2 / 06327	05-Apr-16 (No. 217-02295)	Apr-17
Reference Probe EX3DV4	SN: 3877	31-Dec-15 (No. EX3-3877_Dec15)	Dec-16
DAE4	SN: 654	12-Aug-16 (No. DAE4-654_Aug16)	Aug-17
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (No. 217-02285/02284)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (No. 217-02285)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (No. 217-02284	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17
	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	
			youh
Approved by:	Katja Pokovic	Technical Manager	

Issued: December 6, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

### **Calibration Laboratory of**

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL

tissue simulating liquid

ConvF N/A sensitivity in TSL / NORM x,y,z not applicable or not measured

#### Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### **Additional Documentation:**

e) DASY4/5 System Handbook

#### **Methods Applied and Interpretation of Parameters:**

- Measurement Conditions: Further details are available from the Validation Report at the end
  of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The source is mounted in a touch configuration below the center marking of the flat phantom.
- Return Loss: This parameter is measured with the source positioned under the liquid filled phantom (as described in the measurement condition clause). The Return Loss ensures low reflected power. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: CLA150-4002\_Dec16 Page 2 of 8

#### **Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	ELI4 Flat Phantom	Shell thickness: 2 ± 0.2 mm
EUT Positioning	Touch Position	
Zoom Scan Resolution	dx, dy = 4.0  mm, dz = 1.4  mm	Graded Ratio = 1.4 (Z direction)
Frequency	150 MHz ± 1 MHz	

#### **Head TSL parameters**

The following parameters and calculations were applied.

The following parameters and calculations were appr	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	52.3	0.76 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	50.1 ± 6 %	0.75 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C		

#### **SAR** result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	1 W input power	3.83 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	3.84 W/kg ± 18.4 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	1 W input power	2.54 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	2.55 W/kg ± 18.0 % (k=2)

#### **Body TSL parameters**

The following parameters and calculations were applied.

The following parameters and calculations were appropriate to the calculations and the calculations were appropriate to the calculations and the calculations were appropriate to the calculations and the calculations are also appropriate to the calculations and the calculations are also appropriate to the calculations and the calculations are also appropriate to the calculations and the calculations are also appropriate to the calculations are also appropriate to the calculations and the calculations are also appropriate to the calcula	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	61.9	0.80 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	61.4 ± 6 %	0.82 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		

## **SAR result with Body TSL**

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	1 W input power	4.03 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	3.95 W/kg ± 18.4 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	1 W input power	2.67 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	2.62 W/kg ± 18.0 % (k=2)

Certificate No: CLA150-4002\_Dec16 Page 3 of 8

#### Appendix (Additional assessments outside the scope of SCS 0108)

#### **Antenna Parameters with Head TSL**

Impedance, transformed to feed point	42.4 Ω - 3.9 jΩ
Return Loss	- 20.7 dB

#### **Antenna Parameters with Body TSL**

Impedance, transformed to feed point	44.5 Ω - 6.9 jΩ
Return Loss	- 20.6 dB

#### **Additional EUT Data**

Manufactured by	SPEAG
Manufactured on	August 23, 2013

#### **Extended Calibration**

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (<-20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB Publication 865664 D01 v01r04.

CLA150 SN: 4002 - Head						
Date of Measurement	Return Loss (dB)	Δ%	Impedance Real (Ω)	ΔΩ	Impedance Imaginary (jΩ)	ΔΩ
12/6/2016	-20.7		42.4		-3.9	
12/6/2017	-21.1	1.9	43.6	1.2	-3.8	0.1
CLA150 SN: 4002 - Body						
		CLA150	SN: 4002 -	Body		
Date of	Return Loss		SN: 4002 -	-	Impedance	40
Date of Measurement	Return Loss (dB)	CLA150 Δ%		Body ΔΩ	Impedance Imaginary (jΩ)	ΔΩ
	i		Impedance	-	1 1	ΔΩ
Measurement	(dB)		Impedance Real (Ω)	-	lmaginary (jΩ)	ΔΩ

#### **DASY5 Validation Report for Head TSL**

Date: 05.12.2016

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: CLA150; Type: CLA150; Serial: CLA150 - SN: 4002

Communication System: UID 0 - CW; Frequency: 150 MHz

Medium parameters used: f = 150 MHz;  $\sigma = 0.75 \text{ S/m}$ ;  $\varepsilon_r = 50.1$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### **DASY52** Configuration:

• Probe: EX3DV4 - SN3877; ConvF(12.02, 12.02, 12.02); Calibrated: 31.12.2015;

• Sensor-Surface: 1.4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn654; Calibrated: 12.08.2016

Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003

• DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

# CLA Calibration for HSL-LF Tissue/CLA150, touch configuration, Pin=1W/Area Scan

(81x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.35 W/kg

# CLA Calibration for HSL-LF Tissue/CLA150, touch configuration, Pin=1W/Zoom Scan,


dist=1.4mm (8x10x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 84.04 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 7.16 W/kg

SAR(1 g) = 3.83 W/kg; SAR(10 g) = 2.54 W/kg


Maximum value of SAR (measured) = 5.37 W/kg



0 dB = 5.35 W/kg = 7.28 dBW/kg

Certificate No: CLA150-4002\_Dec16

## Impedance Measurement Plot for Head TSL



#### **DASY5 Validation Report for Body TSL**

Date: 06.12.2016

Test Laboratory: SPEAG, Zurich, Switzerland

#### **DUT: CLA150; Type: CLA150; Serial: CLA150 - SN: 4002**

Communication System: UID 0 - CW; Frequency: 150 MHz

Medium parameters used: f = 150 MHz;  $\sigma = 0.82 \text{ S/m}$ ;  $\varepsilon_r = 61.4$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY52 Configuration:

• Probe: EX3DV4 - SN3877; ConvF(11.44, 11.44, 11.44); Calibrated: 31.12.2015;

• Sensor-Surface: 1.4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn654; Calibrated: 12.08.2016

Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003

• DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

# CLA Calibration for MSL-LF Tissue/CLA150, touch configuration, Pin=1W/Area Scan

(81x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 5.72 W/kg


CLA Calibration for MSL-LF Tissue/CLA150, touch configuration, Pin=1W/Zoom Scan, dist=1.4mm (8x10x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 83.56 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 7.81 W/kg


SAR(1 g) = 4.03 W/kg; SAR(10 g) = 2.67 W/kg

Maximum value of SAR (measured) = 5.68 W/kg



0 dB = 5.72 W/kg = 7.57 dBW/kg

## Impedance Measurement Plot for Body TSL





Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

**RF Exposure Lab** 

Accreditation No.: SCS 0108

Certificate No: D450V3-1085\_Jan16

## CALIBRATION CERTIFICATE

Object

D450V3 - SN: 1085

Calibration procedure(s)

QA CAL-15.v8

Calibration procedure for dipole validation kits below 700 MHz

Calibration date:

January 14, 2016

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	01-Apr-15 (No. 217-02128)	Mar-16
Power sensor E4412A	MY41498087	01-Apr-15 (No. 217-02128)	Mar-16
Reference 3 dB Attenuator	SN: S5054 (3c)	01-Apr-15 (No. 217-02129)	Mar-16
Reference 20 dB Attenuator	SN: S5058 (20k)	01-Apr-15 (No. 217-02131)	Mar-16
Type-N mismatch combination	SN: 5047.2 / 06327	01-Apr-15 (No. 217-02134)	Mar-16
Reference Probe ET3DV6	SN: 1507	31-Dec-15 (No. ET3-1507_Dec15)	Dec-16
DAE4	SN: 654	08-Jul-15 (No. DAE4-654_Jul15)	Jul-16
Secondary Standards	ID#	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	04-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-15)	In house check: Oct-16
	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	Seef Illan
Approved by:	Katja Pokovic	Technical Manager	MM

Issued: January 18, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D450V3-1085\_Jan16

Page 1 of 8

#### **Calibration Laboratory of**

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL

tissue simulating liquid

ConvF N/A sensitivity in TSL / NORM x,y,z not applicable or not measured

#### Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### **Additional Documentation:**

e) DASY4/5 System Handbook

#### **Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: D450V3-1085\_Jan16 Page 2 of 8

#### **Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	ELI4 Flat Phantom	Shell thickness: 2 ± 0.2 mm
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, $dy$ , $dz = 5 mm$	
Frequency	450 MHz ± 1 MHz	

#### **Head TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	43.5	0.87 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	44.2 ± 6 %	0.90 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C		

#### **SAR** result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.15 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	4.50 W/kg ± 18.1 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	0.770 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	3.02 W/kg ± 17.6 % (k=2)

#### **Body TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	56.7	0.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	56.9 ± 6 %	0.95 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		

## **SAR result with Body TSL**

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.14 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	4.53 W/kg ± 18.1 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	0.748 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	2.97 W/kg ± 17.6 % (k=2)

Certificate No: D450V3-1085\_Jan16 Page 3 of 8

## Appendix (Additional assessments outside the scope of SCS 0108)

#### **Antenna Parameters with Head TSL**

Impedance, transformed to feed point	57.6 Ω - 3.4 jΩ					
Return Loss	- 22.2 dB					

#### **Antenna Parameters with Body TSL**

Impedance, transformed to feed point	54.3 Ω - 8.2 jΩ				
Return Loss	- 21.1 dB				

#### General Antenna Parameters and Design

lectrical Delay (one direction)	1.348 ns
---------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

#### **Additional EUT Data**

Manufactured by	SPEAG
Manufactured on	October 10, 2012

#### **Extended Calibration**

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (<-20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB Publication 865664 D01 v01r04.

D450V2 SN:1085 - Head										
Date of Measurement	$\Delta \%$ $\Delta \Omega$ $\Delta \Omega$									
1/14/2016	-22.2		57.6		-3.4					
1/17/2017	-21.9	-1.4	58.2	0.6	-3.1	0.3				
1/15/2018	-22.6	1.8	58.3	0.7	-3.6	-0.2				
	D450V2 SN:1085 - Body									
Date of Measurement	$\Delta \%$									
1/14/2016	-21.1		54.3		-8.2					
1/17/2017	-22.2	5.2	55.3	1.0	-7.5	0.7				
1/15/2018	-21.6	2.4	53.9	-0.4	-7.9	0.3				

Certificate No: D450V3-1085 Jan16 Page 4 of 8

#### **DASY5 Validation Report for Head TSL**

Date: 11.01.2016

Test Laboratory: SPEAG, Zurich, Switzerland

#### **DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN: 1085**

Communication System: UID 0 - CW; Frequency: 450 MHz

Medium parameters used: f = 450 MHz;  $\sigma = 0.9 \text{ S/m}$ ;  $\varepsilon_r = 44.2$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### **DASY52** Configuration:

• Probe: ET3DV6 - SN1507; ConvF(6.58, 6.58, 6.58); Calibrated: 31.12.2015;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn654; Calibrated: 08.07.2015

Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003

• DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

## Dipole Calibration for Head Tissue/d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.28 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.66 W/kg


SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.770 W/kg

Maximum value of SAR (measured) = 1.24 W/kg



0 dB = 1.24 W/kg = 0.93 dBW/kg

## Impedance Measurement Plot for Head TSL



#### **DASY5 Validation Report for Body TSL**

Date: 14.01.2016

Test Laboratory: SPEAG, Zurich, Switzerland

#### **DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN: 1085**

Communication System: UID 0 - CW; Frequency: 450 MHz

Medium parameters used: f = 450 MHz;  $\sigma = 0.95 \text{ S/m}$ ;  $\varepsilon_r = 56.9$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY52 Configuration:

• Probe: ET3DV6 - SN1507; ConvF(6.99, 6.99, 6.99); Calibrated: 31.12.2015;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn654; Calibrated: 08.07.2015

Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003

• DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

#### Dipole Calibration for Body Tissue/d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 36.96 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.79 W/kg


SAR(1 g) = 1.14 W/kg; SAR(10 g) = 0.748 W/kg

Maximum value of SAR (measured) = 1.21 W/kg



0 dB = 1.21 W/kg = 0.83 dBW/kg

## Impedance Measurement Plot for Body TSL



Page 8 of 8



# **Appendix F – Phantom Calibration Data Sheets**

Zeughausstrasse 43, 8004 Zurich, Switzerland Phone +41 44 245 9700, Fax +41 44 245 9779 info@speag.com, http://www.speag.com

#### **Certificate of Conformity / First Article Inspection**

Item	Oval Flat Phantom ELI 4.0
Type No	QD OVA 001 B
Series No	1003 and higher
Manufacturer	Untersee Composites
	Knebelstrasse 8
	CH-8268 Mannenbach, Switzerland

#### Tests

Complete tests were made on the prototype units QD OVA 001 AA 1001, QD OVA 001 AB 1002, pre-series units QD OVA 001 BA 1003-1005 as well as on the series units QD OVA 001 BB, 1006 ff.

Test	Requirement	Details	Units tested
Material	Compliant with the standard	Bottom plate:	all
thickness	requirements	2.0mm +/- 0.2mm	
Material	Dielectric parameters for required	< 6 GHz: Rel. permittivity = 4	Material
parameters	frequencies	+/-1, Loss tangent ≤ 0.05	sample
Material	The material has been tested to be	DGBE based simulating	Equivalent
resistivity	compatible with the liquids defined in	liquids.	phantoms,
	the standards if handled and cleaned	Observe Technical Note for	Material
	according to the instructions.	material compatibility.	sample
Shape	Thickness of bottom material,	Bottom elliptical 600 x 400 mm	Prototypes,
	Internal dimensions,	Depth 190 mm,	Sample
	Sagging	Shape is within tolerance for	testing
	compatible with standards from	filling height up to 155 mm,	
	minimum frequency	Eventual sagging is reduced or	
		eliminated by support via DUT	

#### **Standards**

- [1] CENELEC EN 50361-2001, 
   « Basic standard for the measurement of the Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz 3 GHz) », July 2001
- [2] IEEE 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques, December 2003
- [3] IEC 62209 1, "Specific Absorption Rate (SAR) in the frequency range of 300 MHz to 3 GHz Measurement Procedure, Part 1: Hand-held mobile wireless communication devices", February 2005
- [4] IEC 62209 2, Draft, "Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices Human models, Instrumentation and Procedures Part 2: Procedure to determine the Specific Absorption Rate (SAR) in the head and body for 30 MHz to 6 GHz Handheld and Body-Mounted Devices used in close proximity to the Body.", February 2005
- [5] OET Bulletin 65, Supplement C, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", Edition January 2001

Based on the tests above, we certify that this item is in compliance with the standards [1] to [5] if operated according to the specific requirements and considering the thickness. The dimensions are fully compliant with [4] from 30 MHz to 6 GHz. For the other standards, the minimum lower frequency limit is limited due to the dimensional requirements ([1]: 450 MHz, [2]: 300 MHz, [3]: 800 MHz, [5]: 375 MHz) and possibly further by the dimensions of the DUT.

Date

28.4.2008

Signature / Stamp

Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland Phone +41 44 245 9700, Fax +41,44 245 9779 info@speag.com; http://www.speag.com



## **Appendix G – Validation Summary**

Per FCC KDB 865664 D02 v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue equivalent media for system validation according to the procedures outlined in FCC KDB 865664 D01 v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point using the system that normally operates with the probe for routine SAR measurements and according to the required tissue equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table G-1 SAR System Validation Summary

SAR	SAR System # Freq. (MHz) Date Probe S/N	' I Date I I I I	- C-I	Canal	Canal Danna	CW Validation			Modulation Valildation					
			1.11					Perm. (ε <sub>r</sub> )	Sens- itivity	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
2	150	5/8/2017	3662	EX3DV4	150	Body	0.82	61.58	Pass	Pass	Pass	FM	N/A	N/A
2	450	5/9/2017	3662	EX3DV4	450	Body	0.96	56.52	Pass	Pass	Pass	FM	N/A	N/A