



# Part 22 TEST REPORT

Product Name Neptune pine

FCC ID 2ABWUP312

Model P312

Client NEPTUNE COMPUTER INC.

Manufacturer NEPTUNE COMPUTER INC.

Date of issue June 10, 2014

TA Technology (Shanghai) Co., Ltd.

Report No.: RXC1312-0222RF01R2 Page 2of 54

# **GENERAL SUMMARY**

	FCC CFR47 Part 2 (2012) Frequency Allocations And Radio Treaty Matters; General Rules And Regulations
Reference	FCC CFR 47 Part 22H (2012) Public Mobile Services(850MHz)
Standard(s)	ANSI/TIA-603-C(2004) Land mobile FM or PM Communications Equipment Measurements and Performance Standards.
	KDB 971168 D01 Power Meas License Digital Systems v02r01 Measurement Guidance for Certification of Licensed Digital Transmitters
Conclusion	This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 2 of this test report are below limits specified in the relevant standards.  General Judgment: Pass
Comment	The test result only responds to the measured sample.

Approved by\_\_\_\_

Weizhong Yang

Director

Revised by

Lingling Kang

RF Manager

Performed by\_

Yiqi Chen RF Engineer

Report No.: RXC1312-0222RF01R2 Page 3of 54

# **TABLE OF CONTENT**

1.	Ger	neral Information	4
	1.1.	Notes of the test report	4
	1.2.	Testing laboratory	5
	1.3.	Applicant Information	5
	1.4.	Manufacturer Information	5
	1.5.	Information of EUT	6
	1.6.	Test Date	7
2.	Tes	t Information	٤
	2.1.	Summary of test results	8
	2.2.	RF Power Output	9
	2.3.	Effective Radiated Power	11
	2.4.	Occupied Bandwidth	11
	2.5.	Band Edge Compliance	26
	2.6.	Peak-to-Average Power Ratio (PAPR)	35
	2.7.	Frequency Stability	37
	2.8.	Spurious Emissions at Antenna Terminals	40
	2.9.	Radiates Spurious Emission	47
3.	Mai	n Test Instruments	49
A١	INEX	A: EUT Appearance and Test Setup	53
	A.1	EUT Appearance	
	A.2	Test Setup	54

Report No.: RXC1312-0222RF01R2 Page 4of 54

# 1. General Information

### 1.1. Notes of the test report

**TA Technology (Shanghai) Co., Ltd.** has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L2264.

**TA Technology (Shanghai) Co., Ltd.** has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 428261.

**TA Technology (Shanghai) Co., Ltd.** has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 8510A.

**TA Technology (Shanghai) Co., Ltd.** guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at TA Technology (Shanghai) Co., Ltd. at the time of execution of the test.

**TA Technology (Shanghai) Co., Ltd.** is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. The sample under test was selected by the Client. This report only refers to the item that has undergone the test.

This report alone does not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of **TA Technology (Shanghai) Co., Ltd.** and the Accreditation Bodies, if it applies.

If the electronic report is inconsistent with the printed one, it should be subject to the latter.

Report No.: RXC1312-0222RF01R2 Page 5of 54

# 1.2. Testing laboratory

Company: TA Technology (Shanghai) Co., Ltd.

Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong

City: Shanghai
Post code: 201201
Country: P. R. China

Contact: Yang Weizhong

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000 Website: http://www.ta-shanghai.com

E-mail: yangweizhong@ta-shanghai.com

# 1.3. Applicant Information

Company: NEPTUNE COMPUTER INC.

Address: 666 SHERBROOKE ST. W., SUITE 1000

City: MONTREAL

Postal Code: H3A 1E7

Country: CANADA

### 1.4. Manufacturer Information

Company: NEPTUNE COMPUTER INC.

Address: 666 SHERBROOKE ST. W., SUITE 1000

City: MONTREAL

Postal Code: H3A 1E7

Country: CANADA

Report No.: RXC1312-0222RF01R2 Page 6of 54

# 1.5. Information of EUT

# **General information**

Name of EUT:	Neptune pine		
IMEI :	354727049900715		
Hardware Version:	P1		
Software Version:	JB_V0.29		
Antenna Type:	Internal Antenna		
Device Operating Configurations:	L		
Operating Mode(s):	GSM 850:(tested) WCDMA Band V;(		
Test Modulation:	(GSM)GMSK,8PS	K; (WCDMA)QPSK	
GPRS Multislot Class:	12		
EGPRS Multislot Class:	12		
HSDPA UE Category:	8		
HSUPA UE Category:	6		
Maximum E.R.P.	GSM 850: 20.67 dBm WCDMA Band V: 9.90 dBm		
Power Supply:	Battery or Charger (AC adaptor)		
Rated Power Supply Voltage:	3.8V		
Extreme Voltage:	Minimum: 3.5V	Maximum: 4.2V	
Extreme Temperature:	Lowest: -20°C	Highest: +60°C	
Test Channel:	128 - 190 - 251	(GSM 850)	
(Low - Middle - High)	4132 - 4183 - 423	,	
	Band	Tx (MHz)	Rx (MHz)
Operating Frequency Range(s)	GSM850	824.2 ~ 848.8	869.2 ~ 893.8
	WCDMA Band V	826.4 ~ 846.6	871.4 ~ 891.6

Report No.: RXC1312-0222RF01R2 Page 7of 54

# **Auxiliary Equipment Details**

AE1: Battery

Model: Mini Phone

Manufacture: Tian Yu Communication Technology (Kun Shan) CO.,Ltd

S/N: /

# 1.6. Test Date

The test is performed from March 6, 2014 to March 10, 2014.

Report No.: RXC1312-0222RF01R2 Page 8of 54

# 2. Test Information

# 2.1. Summary of test results

Number	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(2)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	22.917	PASS
5	Peak-to-Average Power Ratio	KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 22.355	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
8	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS

PASS: The EUT complies with the essential requirements in the standard.

FAIL: The EUT does not comply with the essential requirements in the standard.

Report No.: RXC1312-0222RF01R2 Page 9of 54

# 2.2. RF Power Output


### **Ambient condition**

Temperature	Relative humidity
21°C ~25°C	40%~60%

#### **Methods of Measurement**

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

### **Test Setup**



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

### Limits

No specific RF power output requirements in part 2.1046.

### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U = 0.4 dB.

Report No.: RXC1312-0222RF01R2 Page 10of 54

### **Test Results**

		Cone	ducted Power(dBm	1)
GSI	GSM 850		Channel 190	Channel 251
			836.6 (MHz)	848.8 (MHz)
GSM	Results	29.19	29.22	29.04
	1TXslot	29.17	29.19	29.09
GPRS	2TXslots	26.71	26.73	26.6
(GMSK)	3TXslots	24.69	24.71	24.62
	4TXslots	23.16	23.18	23.11
	1TXslot	27.03	27.21	27.06
EGPRS	2TXslots	24.12	24.12	24.08
(8-PSK)	3TXslots	23.05	23.08	23.07
	4TXslots	22.11	22.14	22.07

# Note:

- 1) The maximum RF Output Power numbers are marks in bold.
- 2)The following testing in GPRS/EGPRS is set to 1TXslot based on the maximum RF Output Power.

		Cond	lucted Power(dBm	n)
WCDMA	WCDMA Band V		Channel 4183	Channel 4233
		826.4(MHz)	836.6(MHz)	846.6(MHz)
RM	С	20.20	20.39	20.45
	Sub - Test 1	20.00	20.36	20.54
HSDPA	Sub - Test 2	19.90	20.31	20.50
ПЭДРА	Sub - Test 3	19.40	19.83	19.96
	Sub - Test 4	19.47	19.82	19.96
	Sub - Test 1	19.19	19.60	19.87
	Sub - Test 2	18.03	18.33	18.50
HSUPA	Sub - Test 3	18.30	18.69	18.86
	Sub - Test 4	18.05	18.44	18.63
	Sub - Test 5	18.96	19.34	19.52

# Note:

- 1) The maximum RF Output Power numbers are marks in bold.
- 2)The following testing in HSDPA/HSUPA is set to Sub Test 1 /Sub Test1 based on the maximum RF Output Power.

Report No.: RXC1312-0222RF01R2 Page 11of 54

### 2.3. Effective Radiated Power

#### **Ambient condition**

Temperature	Relative humidity
21°C ~25°C	40%~60%

### **Methods of Measurement**

The measurement procedures in TIA- 603C are used.

- 1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
- 2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower
- 3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst; UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
- 4. The table was rotated 360 degrees to determine the position of the highest radiated power.
- 5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
- 6. Taking the record of maximum ERP/EIRP.
- 7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
- 8. The conducted power at the terminal of the dipole antenna is measured.
- 9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
- 10. ERP/EIRP = Ps + Et Es + Gs = Ps + Rt Rs + Gs

Ps (dBm): Input power to substitution antenna.

Gs (dBi or dBd): Substitution antenna Gain.

Et = Rt + AF


Es = Rs + AF

AF (dB/m): Receive antenna factor

Rt: The highest received signal in spectrum analyzer for EUT.

Rs: The highest received signal in spectrum analyzer for substitution antenna.

### **Test Setup**



Report No.: RXC1312-0222RF01R2 Page 12of 54

# Limits

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	≤ 7 W (38.45 dBm)

# **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U = 1.19 dB

Report No.: RXC1312-0222RF01R2 Page 13of 54

# **Test Results:Pass**

GSM850							
	Horizontal Polarization						
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)		
824.2	-28.80	-45.53	0	-1.09	15.65		
836.6	-27.76	-45.38	0	-0.91	16.71		
848.8	-27.79	-45.37	0	-0.77	16.82		
1		Vertical Pol	arization		T		
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)		
824.2	-25.11	-45.65	0	-1.09	19.44		
836.6	-23.96	-45.46	0	-0.91	20.59		
848.8	-24.32	-45.49	0	-0.77	20.40		
		GPRS	850				
		Horizontal Po	olarization				
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)		
824.2	-28.81	-45.53	0	-1.09	15.63		
836.6	-28.00	-45.38	0	-0.91	16.47		
848.8	-27.64	-45.37	0	-0.77	16.96		
		Vertical Pol	arization				
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)		
824.2	-24.99	-45.65	0	-1.09	19.57		
836.6	-23.88	-45.46	0	-0.91	20.67		
848.8	-24.18	-45.49	0	-0.77	20.54		
		EGPRS					
		Horizontal Po	olarization				
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)		
824.2	-30.49	-45.53	0	-1.09	13.95		
836.6	-29.69	-45.38	0	-0.91	14.78		
848.8	-29.54	-45.37	0	-0.77	15.06		
Т		Vertical Pol	arization				
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)		
824.2	-26.60	-45.65	0	-1.09	17.96		
836.6	-26.05	-45.46	0	-0.91	18.50		
848.8	-26.10	-45.49	0	-0.77	18.62		

Report No.: RXC1312-0222RF01R2 Page 14of 54

WCDMA Band V						
		Horizontal Po	olarization			
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)	
826.4	-38.75	-45.44	0	-1.09	5.67	
836.6	-39.69	-45.38	0	-0.91	4.78	
846.6	-39.66	-45.38	0	-0.77	4.92	
	Vertical Polarization					
Frequency(MHz)	Rt(dBm)	Rs(dBm)	Ps(dBm)	Gs(dBd)	ERP(dBm)	
826.4	-34.62	-45.54	0	-1.09	9.90	
836.6	-35.72	-45.46	0	-0.91	8.83	
846.6	-35.65	-45.49	0	-0.77	9.04	

Note: ERP = EIRP - 2.15

Report No.: RXC1312-0222RF01R2 Page 15of 54

# 2.4. Occupied Bandwidth


#### **Ambient condition**

Temperature	Relative humidity
21°C ~25°C	40%~60%

### **Method of Measurement**

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz,VBW is set to 10kHz for GSM 850 and RBW is set to 51kHz,VBW is set to 100kHz for WCDMA Band V. 99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

### **Test Setup**



#### Limits

No specific occupied bandwidth requirements in part 2.1049.


### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U = 624Hz.

Report No.: RXC1312-0222RF01R2 Page 16of 54


### **Test Result**

GSM 850	Channel	Frequency (MHz)	99% Power Bandwidth (kHz)	-26dBc Bandwidth(kHz)	
	128	824.2	247.4957	301.295	
GSM	190	836.6	248.7849	304.595	
	251	848.8	246.1890	312.503	
GPRS (GMSK)	128	824.2	243.9748	318.687	
	190	836.6	246.1776	313.107	
	251	848.8	245.8903	311.558	
	128	824.2	241.7510	307.230	
EGPRS (8-PSK)	190	836.6	241.1495	305.040	
(0-1-314)	251	848.8	242.6392	293.457	




GSM 850 CH128 Occupied Bandwidth

Report No.: RXC1312-0222RF01R2 Page 17of 54




GSM 850 CH190 Occupied Bandwidth




GSM 850 CH251 Occupied Bandwidth

Report No.: RXC1312-0222RF01R2 Page 18of 54




GSM 850 GPRS CH128 Occupied Bandwidth




GSM 850 GPRS CH190 Occupied Bandwidth

Report No.: RXC1312-0222RF01R2 Page 19of 54



GSM 850 GPRS CH251 Occupied Bandwidth




GSM 850 EGPRS CH128 Occupied Bandwidth

Report No.: RXC1312-0222RF01R2 Page 20of 54




GSM 850 EGPRS CH190 Occupied Bandwidth



GSM 850 EGPRS CH251 Occupied Bandwidth


Report No.: RXC1312-0222RF01R2 Page 21of 54

WCDMA Band V	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
	4132	826.4	4.1584	4.614
RMC	4183	836.6	4.1748	4.621
	4233	846.6	4.1617	4.641
HSDPA	4132	826.4	4.1495	4.633
	4183	836.6	4.1911	4.654
	4233	846.6	4.1606	4.645
	4132	826.4	4.1544	4.612
HSUPA	4183	836.6	4.1821	4.652
	4233	846.6	4.1739	4.651




WCDMA Band V CH4132 Occupied Bandwidth


Report No.: RXC1312-0222RF01R2 Page 22of 54




WCDMA Band V CH4183 Occupied Bandwidth




Report No.: RXC1312-0222RF01R2 Page 23of 54




WCDMA Band V HSDPA CH4132 Occupied Bandwidth



Report No.: RXC1312-0222RF01R2 Page 24of 54




WCDMA Band V HSDPA CH4233 Occupied Bandwidth




WCDMA Band V HSUPA CH4132 Occupied Bandwidth

Report No.: RXC1312-0222RF01R2 Page 25of 54



WCDMA Band V HSUPA CH4183 Occupied Bandwidth



Report No.: RXC1312-0222RF01R2 Page 26of 54

# 2.5. Band Edge Compliance


#### **Ambient condition**

Temperature	Relative humidity		
21°C ~25°C	40%~60%		

#### **Method of Measurement**

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used. RBW is set to 3kHz,VBW is set to 10kHz for GSM 850 and RBW is set to 51kHz,VBW is set to 100kHz for WCDMA Band V. Spectrum analyzer plots are included on the following pages.

### **Test Setup**



### Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB."


### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U=0.684dB.

Report No.: RXC1312-0222RF01R2 Page 27of 54


### **Test Result:**

GSM 850	Carrier frequency (MHz)	Reference value (dBm)	Limit (dBm)	Conclusion
CSM	824.0	-19.67	-13	PASS
GSM	849.0	-17.86	-13	PASS
GPRS (GMSK)	824.0	-18.77	-13	PASS
	849.0	-18.93	-13	PASS
EGPRS (8-PSK)	824.0	-26.73	-13	PASS
	849.0	-27.23	-13	PASS




GSM 850 128 Channel


Report No.: RXC1312-0222RF01R2 Page 28of 54




GSM 850 251 Channel



Report No.: RXC1312-0222RF01R2 Page 29of 54




GSM 850 GPRS 251 Channel



GSM 850 EGPRS 128 Channel


Report No.: RXC1312-0222RF01R2 Page 30of 54



GSM 850 EGPRS 251 Channel


Report No.: RXC1312-0222RF01R2 Page 31of 54

WCDMA Band V	Carrier frequency (MHz)	Reference value (dBm)	Limit (dBm)	Conclusion
RMC	824	-26.43	-13	PASS
	849	-28.33	-13	PASS
HSDPA	824	-26.29	-13	PASS
	849	-26.49	-13	PASS
HSUPA	824	-30.16	-13	PASS
	849	-28.80	-13	PASS




WCDMA Band V 4132 Channel

Report No.: RXC1312-0222RF01R2 Page 32of 54




WCDMA Band V 4233 Channel




WCDMA Band V HSDPA 4132 Channel

Report No.: RXC1312-0222RF01R2 Page 33of 54




WCDMA Band V HSDPA 4233 Channel



WCDMA Band V HSUPA 4132 Channel

Report No.: RXC1312-0222RF01R2 Page 34of 54



WCDMA Band V HSUPA 4233 Channel

Report No.: RXC1312-0222RF01R2 Page 35of 54

# 2.6. Peak-to-Average Power Ratio (PAPR)

#### **Ambient condition**

Temperature	Relative humidity		
21°C ~25°C	40%~60%		

#### **Methods of Measurement**

For WCDMA test, which OBW is more than 1MHz, the measurement procedures in KDB971168 are used.


The inherent randomness of the power peaks in a noise-like signal makes it difficult to quantify the peak power using traditional measurement techniques for determining the peak power of an analog signal. The peak power of a digitally-modulated signal is predictable only on a statistical basis. Thus, for these types of signals, a statistical measurement of the peak power is necessary.

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth.

- Step 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- Step 2. Set the CCDF option in Spectrum analyzer.
- Step 3. Record the maximum PAPR level associated with a probability of 0.1%.

For GSM PAPR test, the peak power and the average power were measured separately via the spectrum analyzer.

### **Test Setup**



#### Limits

No specific Peak-to-Average Ratio requirements in KDB 971168.

#### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the

Report No.: RXC1312-0222RF01R2 Page 36of 54

normal distribution is with the coverage factor k = 2, U = 0.4 dB.

# **Test Results**

GSM 850	Channel	Frequency (MHz)	Peak(dBm)	Avg(dBm)	PAPR(dB)
	128	824.2	29.92	29.19	0.73
GSM	190	836.6	29.78	29.22	0.56
	251	848.8	29.66	29.04	0.62
	128	824.2	29.72	29.17	0.55
GPRS	190	836.6	29.68	29.19	0.49
	251	848.8	29.6	29.09	0.51
	128	824.2	27.4	27.03	0.37
EGPRS(8PSK)	190	836.6	27.63	27.21	0.42
	251	848.8	27.51	27.06	0.45

WCDMA Band V	Channel	Frequency (MHz)	Peak(dBm)	Avg(dBm)	PAPR(dB)
	4132	826.4	23.44	20.2	3.24
RMC	4183	836.6	23.68	20.39	3.29
	4233	846.6	23.74	20.45	3.29
	4132	826.4	23.29	20.00	3.29
HSDPA	4183	836.6	23.67	20.36	3.31
	4233	846.6	23.83	20.54	3.29
	4132	826.4	22.45	19.19	3.26
HSUPA	4183	836.6	22.85	19.6	3.25
	4233	846.6	23.16	19.87	3.29

Report No.: RXC1312-0222RF01R2 Page 37of 54

### 2.7. Frequency Stability

### **Ambient condition**

Temperature	Relative humidity	
21°C ~25°C	40%~60%	

#### **Method of Measurement**

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -20°C to +50°C in 10°C step size,


- (1) With all power removed, the temperature was decreased to -20°C and permitted to stabilize for three hours.
- (2) Measure the carrier frequency with the test equipment in a "call mode". These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.
- (3) Repeat the above measurements at 10°C increments from -20°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.
- 2. Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.5 V and 4.2 V, with a nominal voltage of 3.8V.

### **Test setup**



Report No.: RXC1312-0222RF01R2 Page 38of 54

### Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	-----------

### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor k = 3, U = 0.01ppm.

### **Test Result**

### **GSM850**

Temperature	Test Results (ppm) / 3.8 V Power supply			
(°C)	Channel 190			
( - /	GSM(GMSK)	EGPRS(8PSK)		
-20	-0.027	-0.041		
-10	-0.021	-0.039		
0	-0.022	-0.033		
10	-0.025	-0.034		
20	-0.028	-0.037		
30	-0.029	-0.031		
40	-0.025	0.029		
50	-0.026	-0.030		
60	-0.024	-0.031		

Voltage	Test Results(ppm) / 20°C		
(V)	Channel 190		
	GSM(GMSK)	EGPRS(8PSK)	
3.5	-0.029	-0.027	
3.8	-0.028	-0.031	
4.2	-0.027	-0.029	

Report No.: RXC1312-0222RF01R2 Page 39of 54

### WCDMA Band V

Temperature	Test Results (ppm) / 3.8 V Power supply
(°C)	Channel 4183
-20	0.004
-10	0.001
0	-0.002
10	-0.002
20	-0.002
30	0.004
40	-0.003
50	0.003
60	0.004

Voltage	Test Results(ppm) / 20°C
(V)	Channel 4183
3.5	0.002
3.8	-0.002
4.2	0.001

Report No.: RXC1312-0222RF01R2 Page 40of 54

### 2.8. Spurious Emissions at Antenna Terminals


#### **Ambient condition**

Temperature	Relative humidity	
21°C ~25°C	40%~60%	

#### **Method of Measurement**

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. For GSM 850, RBW and VBW are set to 100 kHz, Sweep is set to ATUO. For WCDMA Band V, RBW and VBW are set to 100 kHz for the carrier frequency, or RBW and VBW are set to 1MHz(other frequency), Sweep is set to ATUO.

### **Test setup**



### Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB."

Limit
-------

### **Measurement Uncertainty**


The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor k = 1.96.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-12.75GHz	1.407 dB

Report No.: RXC1312-0222RF01R2 Page 41of 54

### **Test Result**

### GSM 850 CH128




Note: The signal beyond the limit is carrier GSM 850 128 Channel 30MHz~9GHz

Harmonic	TX ch.128 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1648.5	-49.692	-13	36.692
3	2472.937	-42.453	-13	29.453

Report No.: RXC1312-0222RF01R2 Page 42of 54

### GSM 850 CH190




Note: The signal beyond the limit is carrier GSM 850 190 Channel 30MHz~9GHz

Harmonic	TX ch.190 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1673.4375	-51.610	-13	38.610
3	2510.25	-41.552	-13	28.552

Report No.: RXC1312-0222RF01R2 Page 43of 54

### GSM 850 CH251




Note: The signal beyond the limit is carrier GSM 850 251 Channel 30MHz~9GHz

Harmonic	TX ch.251	Level	Limit	Margin
Tiarmonio	Frequency (MHz)	(dBm)	(dBm)	(dB)
2	1697.4375	-52.856	-13	39.856
3	2546.4375	-43.010	-13	30.010

Report No.: RXC1312-0222RF01R2 Page 44of 54

### WCDMA Band V CH4132




Note: The signal beyond the limit is carrier WCDMA Band V 4132 Channel 30MHz~9GHz

Harmonic	TX ch.4132	Level	Limit	Margin	
	Frequency (MHz)	(dBm)	(dBm)	(dB)	
2	1654.125	-53.007	-13	40.007	

Report No.: RXC1312-0222RF01R2 Page 45of 54

### WCDMA Band V CH4183




Note: The signal beyond the limit is carrier WCDMA Band V 4183 Channel 30MHz~9GHz

Harmonic	TX ch.4183	Level	Limit	Margin	
	Frequency (MHz)	(dBm)	(dBm)	(dB)	
2	1671.375	-51.705	-13	38.705	

Report No.: RXC1312-0222RF01R2 Page 46of 54

### WCDMA Band V CH4233



Note: The signal beyond the limit is carrier WCDMA Band V 4233 Channel 30MHz~9GHz

Harmonic	TX ch.4233 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	
2	1691.25	-47.431	-13	34.431	
3	2542.6875	-53.253	-13	40.253	

Report No.: RXC1312-0222RF01R2 Page 47of 54

### 2.9. Radiates Spurious Emission

#### **Ambient condition**

Temperature	Relative humidity			
21°C ~25°C	40%~60%			

#### **Method of Measurement**


The measurements procedures in TIA -603C are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment.

The procedure of Radiates Spurious Emission is as follows:

### Step 1:


The measurement is carried out in the semi-anechoic chamber. EUT was placed on a 1.5 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used while RBW and VBW are both set to 3MHz. During the measurement, the highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna moved up and down over a range from 1 to 4 meters in both horizontally and vertically polarized orientations. The test setup refers to figure below.



Step 2:

A dipole antenna shall be substituted in place of the EUT. The antenna will be driven by a signal generator with a adjustable S.G. applied through a Tx cable. Adjust the level of the signal generator output until the value of the receiver reach the previously recorded analyzer power level (LVL). Then The E.R.P. /E.I.R.P. of the EUT can be calculated through the level of the signal generator, Tx cable loss and the gain of the substitution antenna. The test setup refers to figure below.

Report No.: RXC1312-0222RF01R2 Page 48of 54



E.R.P (peak power) =S.G. - Tx Cable loss + Substitution antenna gain – 2.15. EIRP= E.R.P+2.15

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the antenna is vertical.

Of those disturbances below (limit – 20 dB), the mark is not required for the EUT

### Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB."

### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U = 3.55 dB.

Report No.: RXC1312-0222RF01R2 Page 49of 54

### **Test Result**

GSM 850 CH128

Harmonic	TX ch.128 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1647.8	-45.6	2	10.15	Vertical	-39.60	-13	26.60	0
3	2473.5	-40.35	2.51	11.35	Vertical	-33.66	-13	20.66	0
4	3296.3	-59.2	4.2	10.85	Vertical	-54.70	-13	41.70	135
5	4121.6	-55.9	5.2	11.35	Vertical	-51.90	-13	38.90	45
6	4945.1	-57.1	5.5	11.95	Vertical	-52.80	-13	39.80	180
7	5769.4	-61.76	5.7	13.55	Vertical	-56.06	-13	43.06	270
8	6256.5	-57.56	6.3	13.75	Vertical	-52.26	-13	39.26	270
9	7417.8	-61.08	6.8	13.85	Vertical	-56.18	-13	43.18	0
10	8242	-59.52	6.9	14.25	Vertical	-54.32	-13	41.32	180

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

### GSM 850 CH190

Harmonic	TX ch.190 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.4	-46.78	2	10.75	Vertical	-40.18	-13	27.18	135
3	2509.7	-39.89	2.51	11.05	Vertical	-33.50	-13	20.50	225
4	3346.4	-64.61	4.2	11.15	Vertical	-59.81	-13	46.81	180
5	4183.125	-56.17	5.2	11.15	Vertical	-52.37	-13	39.37	315
6	5019.6	-61.23	5.5	11.95	1.95 Vertical		-13	43.93	0
7	5856.2	-62.70	5.7	13.55	Vertical	-57.00	-13	44.00	270
8	6692.8	-61.77	6.3	13.75	Vertical	-56.47	-13	43.47	180
9	7529.4	-60.26	6.8	13.85	Vertical	-55.36	-13	42.36	0
10	8366	-61.88	6.9	14.25	Vertical	-56.68	-13	43.68	90

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

<sup>2.</sup> The worst emission was found in the antenna is vertical position.

<sup>2.</sup> The worst emission was found in the antenna is vertical position.

Report No.: RXC1312-0222RF01R2 Page 50of 54

### GSM 850 CH251

Harmonic	TX ch.251 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1696.9	-48.03	2	10.15	Vertical	-42.03	-13	29.03	180
3	2546.6	-41.16	2.51	11.05	Vertical	-34.77	-13	21.77	225
4	3395.2	-64.16	4.2	11.15	Vertical	-59.36	-13	46.36	0
5	4244.6	-54.35	5.2	11.15	Vertical	-50.55	-13	37.55	225
6	5092.8	-62.89	5.5	11.95	Vertical	-58.59	-13	45.59	90
7	5941.6	-63.04	5.7	13.55	Vertical	-57.34	-13	44.34	0
8	6790.4	-60.84	6.3	13.75	Vertical	-55.54	-13	42.54	270
9	7639.2	-60.52	6.8	13.85	Vertical	-55.62	-13	42.62	180
10	8488	-62.22	6.9	14.25	Vertical	-57.02	-13	44.02	0

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

### WCDMA Band V CH4132

Harmonic	TX ch.4132 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1652.8	-69.24	2	10.15	Vertical	-63.24	-13	50.24	180
3	2479.2	-66.74	2.51	11.35	Vertical	-60.05	-13	47.05	135
4	3305.6	-64.45	4.2	10.85	Vertical	-59.95	-13	46.95	90
5	4132	-62.89	5.2	11.35	Vertical	-58.89	-13	45.89	180
6	4958.4	-63.43	5.5	11.95	Vertical	-59.13	-13	46.13	270
7	5784.8	-61.76	5.7	13.55	Vertical	-56.06	-13	43.06	0
8	6611.2	-61.10	6.3	13.75	Vertical	-55.80	-13	42.80	180
9	7437.6	-61.08	6.8	13.85	Vertical	-56.18	-13	43.18	90
10	8264	-61.86	6.9	14.25	Vertical	-56.66	-13	43.66	0

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

<sup>2.</sup> The worst emission was found in the antenna is vertical position.

<sup>2.</sup> The worst emission was found in the antenna is vertical position.

Report No.: RXC1312-0222RF01R2 Page 51of 54

### WCDMA Band V CH4183

Harmonic	TX ch.4183 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.2	-66.58	2	10.75	Vertical	-59.98	-13	46.98	0
3	2509.8	-62.78	2.51	11.05	Vertical	-56.39	-13	43.39	90
4	3346.4	-64.61	4.2	11.15	Vertical	-59.81	-13	46.81	180
5	4183	-62.67	5.2	11.15	Vertical	-58.87	-13	45.87	270
6	5019.6	-61.23	5.5	11.95	Vertical	-56.93	-13	43.93	0
7	5856.2	-62.70	5.7	13.55	Vertical	-57.00	-13	44.00	180
8	6692.8	-61.77	6.3	13.75	Vertical	-56.47	-13	43.47	90
9	7529.4	-60.26	6.8	13.85	Vertical	-55.36	-13	42.36	0
10	8366	-61.88	6.9	14.25	Vertical	-56.68	-13	43.68	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is vertical position.

### WCDMA Band V CH4233

Harmonic	TX ch.4233 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1693.2	-60.63	2	10.15	Vertical	-54.63	-13	41.63	180
3	2539.8	-56.6	2.51	11.05	Vertical	-50.21	-13	37.21	270
4	3386.4	-64.16	4.2	11.15	Vertical	-59.36	-13	46.36	0
5	4233	-61.50	5.2	11.15	Vertical	-57.70	-13	44.70	180
6	5079.6	-62.89	5.5	11.95	Vertical	-58.59	-13	45.59	90
7	5926.2	-63.04	5.7	13.55	Vertical	-57.34	-13	44.34	0
8	6772.8	-60.84	6.3	13.75	Vertical	-55.54	-13	42.54	90
9	7619.4	-60.52	6.8	13.85	Vertical	-55.62	-13	42.62	0
10	8466	-62.22	6.9	14.25	Vertical	-57.02	-13	44.02	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is vertical position.

Report No.: RXC1312-0222RF01R2 Page 52of 54

## 3. Main Test Instruments

No.	Name	Туре	Manufacturer	Serial	Calibration	Valid
		<b>.</b>		Number	Date	Period
01	Base Station Simulator	CMU200	R&S	118133	2013-06-29	One year
02	Power Splitter	SHX-GF2-2-13	Hua Xiang	10120101	NA	NA
03	Spectrum Analyzer	E4445A	Agilent	MY46181146	2013-06-29	One year
04	Universal Radio Communication Tester	E5515C	Agilent	MY48367192	2013-06-29	One year
05	Signal Analyzer	FSV30	R&S	100815	2013-06-29	One year
06	Signal generator	SMB 100A	R&S	102594	2013-06-29	One year
07	EMI Test Receiver	ESCI	R&S	100948	2013-06-29	One year
08	Trilog Antenna	VUBL 9163	SCHWARZB ECK	9163-201	2013-06-19	Three years
09	Horn Antenna	HF907	R&S	100126	2012-07-01	Three years
10	Climatic Chamber	PT-30B	Re Ce	20101891	2013-09-09	Three years

\*\*\*\*\*END OF REPORT BODY\*\*\*\*\*

Report No.: RXC1312-0222RF01R2 Page 53of 54

## **ANNEX A: EUT Appearance and Test Setup**

### A.1 EUT Appearance





Picture 1 EUT and Auxiliary

Report No.: RXC1312-0222RF01R2 Page 54of 54

## A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup