

MRT Technology (Suzhou) Co., Ltd

Phone: +86-512-66308358 +86-512-66308368 www.mrt-cert.com

Report No.: 1508RSU01101 Report Version: V01 Issue Date: 09-24-2015

MEASUREMENT REPORT

FCC PART 15.247 / RSS-247 ZigBee 802.15.4

FCC ID: 2ABX8SH-000000010

IC: 12219A-00000000010

APPLICANT: Zhejiang shenghui lighting Co., Ltd. Shanghai Branch

Application Type: Certification

Product: sengled element

Model No.: Z01-A19NAE26

Trademark: sengled

FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part 15.247

IC Rule(s): RSS-247 Issue 1

Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v03r03

Test Date: September 22 ~ 24, 2015

Reviewed By : Robin Wu (Robin Wu)

Approved By : Marlinchen

(Marlin Chen)





The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01v03r03. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.



Page Number: 2 of 54



Revision History

Report No.	Version	Description	Issue Date
1508RSU01101	Rev. 01	Initial report	09-24-2015



CONTENTS

De	scriptio	n l	Page
§2.	1033 G	eneral Information	5
1.	INTRO	ODUCTION	6
	1.1.	Scope	6
	1.2.	MRT Test Location	
2.	PROE	DUCT INFORMATION	7
	2.1.	Equipment Description	7
	2.2.	Operation Frequency / Channel List	
	2.3.	Test Mode	
	2.4.	Test Software	
	2.5.	Device Capabilities	
	2.6.	Test Configuration	
	2.7.	EMI Suppression Device(s)/Modifications	
	2.8.	Labeling Requirements	
_	-		
3.	DESC	CRIPTION OF TEST	10
	3.1.	Evaluation Procedure	10
	3.2.	AC Line Conducted Emissions	10
	3.3.	Radiated Emissions	11
4.	ANTE	NNA REQUIREMENTS	12
5.	TEST	EQUIPMENT CALIBRATION DATE	13
6.	MEAS	SUREMENT UNCERTAINTY	14
7.	TEST	RESULT	15
	7.1.	Summary	15
	7.2.	6dB Bandwidth Measurement	
	7.2.1.	Test Limit	16
	7.2.2.	Test Procedure used	
	7.2.3.	Test Setting	
	7.2.4.	Test Setup	
	7.2.5.	Test Result	17
	7.3.	Output Power Measurement	
	7.3.1.	Test Limit	
	7.3.2.	Test Procedure Used	
	7.3.3.	Test Setting	18
	7.3.4.	Test Setup	18



7.3.5.	Test Result of Peak Output Power	19
7.4.	Power Spectral Density Measurement	20
7.4.1.	Test Limit	20
7.4.2.	Test Procedure Used	20
7.4.3.	Test Setting	20
7.4.4.	Test Setup	20
7.4.5.	Test Result of Power Spectral Density	21
7.5.	Conducted Band Edge and Out-of-Band Emissions	22
7.5.1.	Test Limit	22
7.5.2.	Test Procedure Used	22
7.5.3.	Test Settitng	22
7.5.4.	Test Setup	23
7.5.5.	Test Result	24
7.6.	Radiated Spurious Emission Measurement	26
7.6.1.	Test Limit	26
7.6.2.	Test Procedure Used	26
7.6.3.	Test Setting	26
7.6.4.	Test Setup	28
7.6.5.	Test Result	30
7.7.	Radiated Restricted Band Edge Measurement	39
7.7.1.	Test Result	39
7.8.	AC Conducted Emissions Measurement	
7.8.1.	Test Limit	51
7.8.2.	Test Setup	51
7.8.3.	Test Result	52
0011		- 4



§2.1033 General Information

Applicant:	Zhejiang shenghui lighting Co., Ltd. Shanghai Branch				
Applicant Address:	Rm. 801, 1st Xinye Building, 388 Tianlin Rd., Caohejing				
	Development Zone, Shanghai, 200233, China				
Manufacturer:	ZHEJIANG SHENGHUI LIGHTING Co., Ltd				
Manufacturer Address:	South Jiachuang Rd., Xiuzhou Industrial Park Jiaxing, Zhejiang				
	314015 P.R. China				
Test Site:	MRT Technology (Suzhou) Co., Ltd				
Test Site Address:	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic				
	Development Zone, Suzhou, China				
MRT FCC Registration No.:	809388				
MRT IC Registration No.:	11384A				
FCC Rule Part(s):	Part 15.247				
IC Rule:	RSS-247 Issue 1				
Model No.:	Z01-A19NAE26				
FCC ID:	2ABX8SH-000000010				
IC:	12219A-0000000010				
Test Device Serial No.:	N/A ☐ Production ☐ Pre-Production ☐ Engineering				

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



Page Number: 5 of 54



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.





Page Number: 7 of 54



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	sengled element
Model No.	Z01-A19NAE26
ZigBee Specification	802.15.4
Frequency Range	2405 ~ 2480 MHz
Maximum Peak Output Power	5.77dBm
Type of Modulation	O-QPSK
Antenna Type	PIFA Antenna
Antenna Gain	-6.20dBi

2.2. Operation Frequency / Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
11	2405 MHz	12	2410 MHz	13	2415 MHz
14	2420 MHz	15	2425 MHz	16	2430 MHz
17	2435 MHz	18	2440 MHz	19	2445 MHz
20	2450 MHz	21	2455 MHz	22	2460 MHz
23	2465 MHz	24	2470 MHz	25	2475 MHz
26	2480 MHz				

2.3. Test Mode

Test Mode 1: Transmit by 802.15.4

2.4. Test Software

The test utility software used during testing was "sscom32.exe".






2.5. Device Capabilities

This device contains the following capabilities:

2.4GHz ZigBee (DTS)

Note: 2.4GHz ZigBee (DTS) operation is possible in 5MHz channel bandwidth. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:



2.6. Test Configuration

The **sengled element FCC ID: 2ABX8SH-000000010** was tested per the guidance of KDB 558074 D01v03r03. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.



Page Number: 9 of 54



2.7. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.8. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.



3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v03r03 were used in the measurement of the **sengled element FCC ID: 2ABX8SH-000000010.**

Deviation from measurement procedure......None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, $50\Omega/50$ uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.8.

FCC ID: 2ABX8SH-000000010 IC:12219A-00000000000




3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-25GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

FCC ID: 2ABX8SH-000000010 IC:12219A-00000000000





4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the sengled element is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **sengled element FCC ID: 2ABX8SH-000000010** unit complies with the requirement of §15.203.

FCC ID: 2ABX8SH-000000010 Page Number: 12 of 54

IC:12219A-00000000010



5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2015/11/07
Temperature/ Meter Humidity	Ouleinuo	N/A	MRTSUE06112	1 year	2015/11/20

Radiated Emission

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	E4447A	MRTSUE06028	1 year	2015/10/09
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2015/11/07
Preamplifier	Agilent	83017A	MRTSUE06020	1 year	2015/12/13
Preamplifier	Schwarzbeck	BBV9721	MRTSUE06121	1 year	2016/04/15
Loop Antenna	Schwarzbeck	FMZB1519	MRTSUE06025	1 year	2015/11/08
TRILOG Antenna	Schwarzbeck	VULB9162	MRTSUE06022	1 year	2015/11/08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06023	1 year	2015/11/08
Broadband Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06024	1 year	2016/01/05
Temperature/Humidity Meter	Ouleinuo	N/A	MRTSUE06114	1 year	2015/11/20

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2016/04/23
USB Wideband Power Sensor	Boonton	55006	MRTSUE06109	1 year	2015/10/15
Temperature/Humidity Meter	Ouleinuo	N/A	MRTSUE06113	1 year	2015/11/20

Software	Version	Function
e3	V8.3.5	EMI Test Software

FCC ID: 2ABX8SH-000000010 IC:12219A-00000000010





6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

150kHz~30MHz: 3.46dB

Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

9kHz ~ 1GHz: 4.18dB 1GHz ~ 25GHz: 4.76dB

FCC ID: 2ABX8SH-000000010 Page Number: 14 of 54



7. TEST RESULT

7.1. Summary

Company Name: Zhejiang shenghui lighting Co., Ltd. Shanghai Branch

FCC ID: 2ABX8SH-000000010 IC: 12219A-0000000010

FCC Classification: Digital Transmission System (DTS)

Data Rate(s) Tested: 250kbps

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	≥ 500kHz		Pass	Section 7.2	
15.247(b)(3)	RSS-247 [5.4(4)]	Output Power	≤ 1Watt & EIRP ≤ 4Watt		Pass	Section 7.3	
15.247(e)	RSS-247 [5.2]	Power Spectral Density	≤ 8dBm / 3kHz	Conducted		Pass	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc(Peak)		Pass	Section 7.5	
15.205 15.209	RSS-247 [5.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6&7.7	
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.8	

Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

FCC ID: 2ABX8SH-000000010 Page Number: 15 of 54

IC:12219A-0000000010



Page Number: 16 of 54



7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

7.2.2. Test Procedure used

KDB 558074 D01v03r03 - Section 8.2 Option 2

7.2.3. Test Setting

- The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. Set RBW = 100 kHz
- 3. VBW ≥ 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace was allowed to stabilize

7.2.4. Test Setup


Spectrum Analyzer Attenuator EUT





7.2.5. Test Result

Test Mode	Modulation Mode	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
802.15.4	O-QPSK	11	2405	1.62	≥ 0.5	Pass
802.15.4	O-QPSK	19	2445	1.60	≥ 0.5	Pass
802.15.4	O-QPSK	26	2480	1.59	≥ 0.5	Pass





7.3. Output Power Measurement

7.3.1. Test Limit

For FCC

The maximum output power shall be less 1 Watt (30dBm). If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For IC

The maximum conducted output power shall be exceed 1 Watt (30dBm) and the E.I.R.P shall not exceed 4 Watt (36dBm).

7.3.2. Test Procedure Used


KDB 558074 D01v03r03 - Section 9.1.2 PKPM1 Peak Power Method (for signals with BW ≤ 50MHz)

7.3.3. Test Setting

Method PKPM1 (Peak Power Measurement of Signals with DTS BW ≤ 50MHz)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

7.3.4. Test Setup





Page Number: 19 of 54



7.3.5. Test Result of Peak Output Power

Test Mode	Modulation Mode	Channel No.	Frequency (MHz)	Peak Output Power	Limit (dBm)	E.I.R.P (dBm)	Limit (dBm)	Result
	ivioue	NO.	(1711 12)	(dBm)	(ubiii)	(ubiii)	(ubiii)	
				(abiii)				
802.15.4	O-QPSK	11	2405	5.77	≤ 30	-0.43	≤ 36	Pass
802.15.4	O-QPSK	19	2445	4.75	≤ 30	-1.45	≤ 36	Pass
802.15.4	O-QPSK	25	2475	3.56	≤ 30	-2.64	≤ 36	Pass
802.15.4	O-QPSK	26	2480	3.36	≤ 30	-2.84	≤ 36	Pass

Note: E.I.R.P. (dBm) = Peak Output Power (dBm) + Antenna Gain (dBi).

Test Result of Average Output Power for Report Only

Test Mode	Modulation	Channel	Frequency	Average	Limit	E.I.R.P	Limit	Result
	Mode	No.	(MHz)	Output	(dBm)	(dBm)	(dBm)	
				Power				
				(dBm)				
802.15.4	O-QPSK	11	2405	5.66	≤ 30	-0.54	≤ 36	Pass
802.15.4	O-QPSK	19	2445	4.60	≤ 30	-1.60	≤ 36	Pass
802.15.4	O-QPSK	25	2475	3.38	≤ 30	-2.82	≤ 36	Pass
802.15.4	O-QPSK	26	2480	3.17	≤ 30	-3.03	≤ 36	Pass

Note: E.I.R.P. (dBm) = Average Output Power (dBm) + Antenna Gain (dBi).



7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


7.4.2. Test Procedure Used

KDB 558074 D01v03r03 - Section 10.2 Method PKPSD

7.4.3. Test Setting

- 1. Analyzer was set to the center frequency of the DTS channel under investigation
- 2. Span = 1.5 times the DTS channel bandwidth
- 3. RBW = 3kHz
- 4. VBW = 10kHz
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Trace was allowed to stabilize

7.4.4. Test Setup








7.4.5. Test Result of Power Spectral Density

Test Mode	Modulation Mode	Channel No.	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.15.4	O-QPSK	11	2405	-9.58	≤ 8	Pass
802.15.4	O-QPSK	19	2445	-10.64	≤ 8	Pass
802.15.4	O-QPSK	26	2480	-11.30	≤ 8	Pass





7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

7.5.2. Test Procedure Used

KDB 558074 D01v03r03 - Section 11.2 & Section 11.3

7.5.3. Test Settitng

1. Reference level measurement

- (a) Set instrument center frequency to DTS channel center frequency
- (b) Set the span to ≥ 1.5 times the DTS bandwidth
- (c) Set the RBW = 100 kHz
- (d) Set the VBW \geq 3 x RBW
- (e) Detector = peak
- (f) Sweep time = auto couple
- (g) Trace mode = max hold
- (h) Allow trace to fully stabilize


2. Emission level measurement

- (a) Set the center frequency and span to encompass frequency range to be measured
- (b) RBW = 100kHz
- (c) VBW = 300kHz
- (d) Detector = Peak
- (e) Trace mode = max hold
- (f) Sweep time = auto couple
- (g) The trace was allowed to stabilize





7.5.4. Test Setup








7.5.5. Test Result

Test Mode	Modulation Mode	Channel No.	Frequency (MHz)	Limit	Result
802.15.4	O-QPSK	11	2405	20dBc	Pass
802.15.4	O-QPSK	19	2445	20dBc	Pass
802.15.4	O-QPSK	26	2480	20dBc	Pass









Page Number: 26 of 54



7.6. Radiated Spurious Emission Measurement

7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

F	FCC Part 15 Subpart C Paragraph 15.209								
Frequency [MHz]									
0.009 - 0.490	2400/F (kHz)	300							
0.490 – 1.705	24000/F (kHz)	30							
1.705 - 30	30	30							
30 - 88	100	3							
88 - 216	150	3							
216 - 960	200	3							
Above 960	500	3							

7.6.2. Test Procedure Used

KDB 558074 D01v03r03 – Section 12.2.3 (quasi-peak measurements)

KDB 558074 D01v03r03 – Section 12.2.4 (peak power measurements)

KDB 558074 D01v03r03 – Section 12.2.5 (average power measurements)

7.6.3. Test Setting

Peak Field Strength Measurements per Section 12.2.4 of KDB 558074 D01v03r03

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in Table 1
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple



- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

Table 1 - RBW as a Function of Frequency

Frequency	RBW		
9 ~ 150 kHz	200 ~ 300 Hz		
0.15 ~ 30 MHz	9 ~ 10 kHz		
30 ~ 1000 MHz	100 ~ 120 kHz		
> 1000 MHz	1 MHz		

Average Field Strength Measurements per Section 12.2.5.3 of KDB 558074 D01v03r03


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ 1/T
- 4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
- 5. Detector = Peak
- 6. Sweep time = auto
- 7. Trace mode = max hold
- 8. Allow max hold to run for at least 50 times (1/duty cycle) traces






7.6.4. Test Setup

9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:








1GHz ~ 18GHz Test Setup:



18GHz ~25GHz Test Setup:







7.6.5. Test Result


Test Mode:	802.15.4	Test Site:	AC1					
Test Channel:	11	Test Engineer:	Roy Cheng					
Remark:	1. Average measurement was no	Average measurement was not performed if peak level lower than average						
	limit.							
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show							
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	4808.0	37.0	2.7	39.7	74.0	-34.3	Peak	Horizontal
	5377.9	34.9	3.0	37.9	74.0	-36.1	Peak	Horizontal
*	6018.5	35.5	4.2	39.7	74.0	-34.3	Peak	Horizontal
*	6659.9	35.5	6.0	41.5	74.0	-32.5	Peak	Horizontal
	4588.2	35.9	2.0	37.9	74.0	-36.1	Peak	Vertical
	5013.8	36.3	3.1	39.4	74.0	-34.6	Peak	Vertical
*	5879.3	35.0	4.1	39.1	74.0	-34.9	Peak	Vertical
*	6138.7	35.6	4.5	40.1	74.0	-33.9	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (91.0dBµV/m) or 15.209 which is higher.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre-Amplifier Gain (dB)






Test Mode:	802.15.4	Test Site:	AC1					
Test Channel:	19	Test Engineer:	Roy Cheng					
Remark:	1. Average measurement was no	Average measurement was not performed if peak level lower than average						
	limit.							
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show							
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	4893.0	40.6	2.7	43.3	74.0	-30.7	Peak	Horizontal
	5407.8	34.8	3.2	38.0	74.0	-36.0	Peak	Horizontal
*	5963.2	34.9	4.3	39.2	74.0	-34.8	Peak	Horizontal
*	6687.9	35.6	5.8	41.4	74.0	-32.6	Peak	Horizontal
	4893.0	38.0	2.7	40.7	74.0	-33.3	Peak	Vertical
	5389.7	34.8	3.1	37.9	74.0	-36.1	Peak	Vertical
*	6018.7	35.3	4.2	39.5	74.0	-34.5	Peak	Vertical
*	6388.9	34.5	5.3	39.8	74.0	-34.2	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (88.3dB μ V/m) or 15.209 which is higher.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre-Amplifier Gain (dB)



Page Number: 32 of 54



Test Mode:	802.15.4	Test Site:	AC1					
Test Channel:	26	Test Engineer:	Roy Cheng					
Remark:	1. Average measurement was no	Average measurement was not performed if peak level lower than average						
	limit.							
	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show							
	in the report.							

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
	4961.0	42.0	2.9	44.9	74.0	-29.1	Peak	Horizontal
	5123.3	35.4	3.3	38.7	74.0	-35.3	Peak	Horizontal
*	6011.5	35.4	4.2	39.6	74.0	-34.4	Peak	Horizontal
*	6533.7	34.8	5.9	40.7	74.0	-33.3	Peak	Horizontal
	4961.0	40.4	2.9	43.3	74.0	-30.7	Peak	Vertical
	5399.1	35.0	3.1	38.1	74.0	-35.9	Peak	Vertical
*	6511.2	34.7	6.0	40.7	74.0	-33.3	Peak	Vertical
*	7155.4	34.9	7.7	42.6	74.0	-31.4	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (84.5dB μ V/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre-Amplifier Gain (dB)



The worst case of radiated emission below 1GHz:

Worse Case Mode: Transmit at channel 2445MHz						
EUT: sengled element	Power: AC 120V/60Hz					
Probe: VULB9162_0.03-8GHz	Polarity: Horizontal					
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li					
Site: AC 1	Time: 2015/09/24 - 15:09					


No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	49.897	16.798	1.890	-23.202	40.000	14.908	QP
2			57.533	15.387	1.132	-24.613	40.000	14.255	QP
3			104.012	13.668	0.566	-29.832	43.500	13.102	QP
4			228.156	15.100	2.155	-30.900	46.000	12.945	QP
5			337.863	20.136	4.589	-25.864	46.000	15.547	QP
6			566.187	20.478	1.084	-25.522	46.000	19.394	QP

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)



Worse Case Mode: Transmit at channel 2445MHz					
EUT: sengled element	Power: AC 120V/60Hz				
Probe: VULB9162_0.03-8GHz	Polarity: Vertical				
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li				
Site: AC 1	Time: 2015/09/24 - 15:12				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			36.456	26.758	13.577	-13.242	40.000	13.181	QP
2		*	50.622	27.773	12.877	-12.227	40.000	14.897	QP
3			55.897	25.575	11.055	-14.425	40.000	14.519	QP
4			169.797	21.250	11.032	-22.250	43.500	10.217	QP
5			228.556	23.860	10.897	-22.140	46.000	12.963	QP
6			342.156	23.830	8.173	-22.170	46.000	15.657	QP

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)



Note: There is the ambient noise within frequency range 9kHz~30MHz					
EUT: sengled element	Power: AC 120V/60Hz				
Probe: FMZB1519_0.009-30MHz	Polarity: Face on				
Limit: FCC_Part15.209_RE(3m)	Engineer: Roy Cheng				
Site: AC1	Time: 2015/09/24 - 18:12				



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			0.049	50.367	29.861	-63.422	113.789	20.505	QP
2		*	0.105	44.143	23.996	-63.029	107.173	20.147	QP


Note: Measure Level $(dB\mu V/m)$ = Reading Level $(dB\mu V)$ + Factor. (dB).

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Page Number: 36 of 54



Note: There is the ambient noise within frequency range 9kHz~30MHz					
EUT: sengled element	Power: AC 120V/60Hz				
Probe: FMZB1519_0.009-30MHz	Polarity: Face on				
Limit: FCC_Part15.209_RE(3m)	Engineer: Roy Cheng				
Site: AC1	Time: 2015/09/24 - 18:16				



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2.175	27.894	7.735	-41.606	69.500	20.159	PK
2			6.216	25.672	5.318	-43.828	69.500	20.354	PK


Note: Measure Level $(dB\mu V/m)$ = Reading Level $(dB\mu V)$ + Factor (dB).

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

 $\label{eq:limit} $\lim 3m = 20^* Log(30uV/m) + 20^* Log(30m/3m) = 49.5 dB\mu\nu/m \ (Average \ detector), \ and \ 69.5 dB\mu\nu/m \ (Peak \ detector).$



Note: There is the ambient noise within frequency range 18GHz, 25GHz						
EUT: sengled element	Power: AC 120V/60Hz					
Probe: BBHA9170_18-40GHz	Polarity: Horizontal					
Limit: FCC_Part15.209_RE(1m)	Engineer: Roy Cheng					
Site: AC1	Time: 2015/09/24 - 21:20					



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			23943.000	49.776	35.866	-33.724	83.500	13.910	PK
2		*	24741.000	52.375	37.681	-31.125	83.500	14.694	PK


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) – Pre-Amplifier Gain (dB)

 $Limit@1m = 20*Log(500uV/m) + 20*Log(3m/1m) = 63.5dB\mu\nu/m \ (Average \ detector), \ and \ 83.5dB\mu\nu/m \ (Peak \ detector).$

Page Number: 38 of 54



Note: There is the ambient noise within frequency range 18GHz~25GHz					
EUT: sengled element	Power: AC 120V/60Hz				
Probe: BBHA9170_18-40GHz	Polarity: Vertical				
Limit: FCC_Part15.209_RE(1m)	Engineer: Roy Cheng				
Site: AC1	Time: 2015/09/24 - 21:32				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			23999.000	50.379	36.435	-33.121	83.500	13.944	PK
2		*	24846.000	52.503	37.735	-30.997	83.500	14.768	PK

Note: Measure Level $(dB\mu V/m)$ = Reading Level $(dB\mu V)$ + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) – Pre-Amplifier Gain (dB)

 $\label{limit} Limit@1m = 20*Log(500uV/m) + 20*Log(3m/1m) = 63.5dB\mu\nu/m \ (Average \ detector), \ and \ 83.5dB\mu\nu/m \ (Peak \ detector).$






7.7. Radiated Restricted Band Edge Measurement


7.7.1. Test Result

Site: AC 1	Time: 2015/09/24 - 10:53				
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li				
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal				
EUT: sengled element	Power: AC 120V/60Hz				
Test Mode: Transmit at channel 2405MHz					




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2338.000	59.652	28.313	-14.348	74.000	31.338	PK
2			2390.000	57.475	26.272	-16.525	74.000	31.203	PK
3		*	2404.650	86.306	55.126	N/A	N/A	31.180	PK

Note: Measure Level $(dB\mu V/m)$ = Reading Level $(dB\mu V)$ + Factor (dB)






Site: AC 1	Time: 2015/09/24 - 10:56			
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li			
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal			
EUT: sengled element	Power: AC 120V/60Hz			
Test Mode: Transmit at channel 2405MHz				



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2390.000	45.080	13.877	-8.920	54.000	31.203	AV
2		*	2404.950	83.529	52.349	N/A	N/A	31.180	AV





Site: AC 1	Time: 2015/09/24 - 10:49				
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li				
Probe: BBHA9120D_1-18GHz	Polarity: Vertical				
EUT: sengled element	Power: AC 120V/60Hz				
Test Mode: Transmit at channel 2405MHz					

120 80 70 1 60 40 30 20 2310 2315 2320 2325 2330 2335 2340 2345 2350 2355 2360 2365 2370 2375 2380 2385 2390 2395 2400 2405 2410 Frequency(MHz)


No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2327.700	59.244	27.857	-14.756	74.000	31.386	PK
2			2390.000	57.595	26.392	-16.405	74.000	31.203	PK
3		*	2404.400	90.991	59.810	N/A	N/A	31.181	PK

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)






Site: AC 1	Time: 2015/09/24 - 10:51				
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li				
Probe: BBHA9120D_1-18GHz	Polarity: Vertical				
EUT: sengled element	Power: AC 120V/60Hz				
Test Mode: Transmit at channel 2405MHz					



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1			2390.000	45.155	13.952	-8.845	54.000	31.203	AV
2		*	2404.900	88.493	57.313	N/A	N/A	31.180	AV



Site: AC 1	Time: 2015/09/24 - 11:02				
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li				
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal				
EUT: sengled element	Power: AC 120V/60Hz				
Test Mode: Transmit at channel 2475MHz					




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2475.580	81.855	50.683	N/A	N/A	31.172	PK
2			2483.500	57.936	26.743	-16.064	74.000	31.194	PK
3			2483.785	60.313	29.119	-13.687	74.000	31.194	PK






Site: AC 1	Time: 2015/09/24 - 11:05			
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li			
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal			
EUT: sengled element	Power: AC 120V/60Hz			
Test Mode: Transmit at channel 2475MHz				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2475.070	79.171	48.001	N/A	N/A	31.170	AV
2			2483.500	45.221	14.028	-8.779	54.000	31.194	AV





Site: AC 1	Time: 2015/09/24 - 10:57			
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li			
Probe: BBHA9120D_1-18GHz	Polarity: Vertical			
EUT: sengled element	Power: AC 120V/60Hz			
Test Mode: Transmit at channel 2475MHz				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2474.410	85.065	53.896	N/A	N/A	31.168	PK
2			2483.500	57.916	26.723	-16.084	74.000	31.194	PK
3			2486.485	59.612	28.411	-14.388	74.000	31.201	PK





Site: AC 1	Time: 2015/09/24 - 11:01
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: sengled element	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2475MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2474.995	82.272	51.102	N/A	N/A	31.170	AV
2			2483.500	45.243	14.050	-8.757	54.000	31.194	AV





Site: AC 1	Time: 2015/09/24 - 11:51			
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li			
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal			
EUT: sengled element	Power: AC 120V/60Hz			
Test Mode: Transmit at channel 2480MHz				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2480.475	88.686	57.501	N/A	N/A	31.185	PK
2			2483.500	62.545	31.352	-11.455	74.000	31.194	PK





Site: AC 1	Time: 2015/09/24 - 11:53
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: sengled element	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2480MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2480.125	86.175	54.991	N/A	N/A	31.185	AV
2			2483.500	50.474	19.281	-3.526	54.000	31.194	AV





Site: AC 1	Time: 2015/09/24 - 11:54
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: sengled element	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2480MHz	




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2480.587	86.942	55.756	N/A	N/A	31.185	PK
2			2483.500	61.300	30.107	-12.700	74.000	31.194	PK
3			2483.525	61.863	30.670	-12.137	74.000	31.194	PK





Site: AC 1	Time: 2015/09/24 - 11:56
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: sengled element	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2480MHz	



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	2480.075	84.167	52.983	N/A	N/A	31.184	AV
2			2483.500	49.052	17.859	-4.948	54.000	31.194	AV



7.8. AC Conducted Emissions Measurement


7.8.1. Test Limit

FCC P	art 15 Subpart C Paragraph 15.20	07 Limits
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2. Test Setup





7.8.3. Test Result

Site: SR2	Time: 2015/09/24 - 15:17
Limit: FCC_Part15.207_CE_AC Power	Engineer: Roy Cheng
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: sengled element	Power: AC 120V/60Hz
Note: Mode 1	•

Frequency(MHz)

No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV)	(dB)	
				(dBuV)	(dBuV)				
1			0.154	50.840	40.100	-14.942	65.781	10.740	QP
2			0.154	34.140	23.400	-21.642	55.781	10.740	AV
3			0.170	48.978	38.900	-15.983	64.960	10.078	QP
4			0.170	33.478	23.400	-21.483	54.960	10.078	AV
5			0.186	48.839	38.800	-15.375	64.213	10.039	QP
6			0.186	33.639	23.600	-20.575	54.213	10.039	AV
7		*	0.198	48.805	38.800	-14.889	63.694	10.005	QP
8			0.198	34.205	24.200	-19.489	53.694	10.005	AV
9			0.214	48.057	38.100	-14.992	63.049	9.957	QP
10			0.214	33.257	23.300	-19.792	53.049	9.957	AV
11			0.274	45.683	35.700	-15.313	60.996	9.983	QP
12			0.274	31.583	21.600	-19.413	50.996	9.983	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)



Site: SR2	Time: 2015/09/24 - 15:35
Limit: FCC_Part15.207_CE_AC Power	Engineer: Roy Cheng
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: sengled element	Power: AC 120V/60Hz
Note: Mode 1	

80 70 60 50 40 40 40 50 810 12 10 10 10 20 0.15 1 10 30

Frequency(MHz)

No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV)	(dB)	
				(dBuV)	(dBuV)				
1			0.158	50.490	40.200	-15.079	65.568	10.290	QP
2			0.158	29.090	18.800	-26.479	55.568	10.290	AV
3			0.202	48.608	38.600	-14.920	63.528	10.008	QP
4			0.202	34.508	24.500	-19.020	53.528	10.008	AV
5		*	0.214	48.588	38.600	-14.461	63.049	9.988	QP
6			0.214	33.088	23.100	-19.961	53.049	9.988	AV
7			0.242	47.095	37.100	-14.932	62.027	9.995	QP
8			0.242	30.995	21.000	-21.032	52.027	9.995	AV
9			0.262	46.110	36.100	-15.258	61.368	10.010	QP
10			0.262	31.910	21.900	-19.458	51.368	10.010	AV
11			0.294	45.433	35.400	-14.977	60.411	10.033	QP
12			0.294	31.933	21.900	-18.477	50.411	10.033	AV

Note: Measure Level (dB μ V) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)



8. CONCLUSION

The data collected relate only the item(s) tested and show that the sengled element FCC ID :
2ABX8SH-000000010 is in compliance with Part 15C of the FCC Rules.

FCC ID: 2ABX8SH-000000010 Page Number: 54 of 54

The End

IC:12219A-00000000010