Page Number: 41 of 171



7.6.5. Test Result

| Test Mode | Data<br>Rate<br>(Mbps) | Channel<br>No. | Freq.<br>(MHz) | PSD<br>(dBm/<br>MHz) | Duty<br>Cycle<br>(%) | Total<br>PSD<br>(dBm/<br>MHz) | PSD<br>Limit<br>(dBm/<br>MHz) | EIRP<br>PSD<br>(dBm/<br>MHz) | EIRP PSD<br>Limit<br>(dBm/<br>MHz) | Result |
|-----------|------------------------|----------------|----------------|----------------------|----------------------|-------------------------------|-------------------------------|------------------------------|------------------------------------|--------|
| Ant 1     |                        |                |                |                      |                      |                               |                               |                              |                                    |        |
| 11a       | 6                      | 36             | 5180           | -2.78                | 96.5                 | -2.63                         | ≤ 11.00                       | 1.37                         | ≤ 10.00                            | Pass   |
| 11a       | 6                      | 44             | 5220           | 0.88                 | 96.5                 | 1.03                          | ≤ 11.00                       | 5.03                         | ≤ 10.00                            | Pass   |
| 11a       | 6                      | 48             | 5240           | 1.01                 | 96.5                 | 1.16                          | ≤ 11.00                       | 5.16                         | ≤ 10.00                            | Pass   |
| 11n-HT20  | 6.5                    | 36             | 5180           | -2.07                | 96.3                 | -1.91                         | ≤ 11.00                       | 2.09                         | ≤ 10.00                            | Pass   |
| 11n-HT20  | 6.5                    | 44             | 5220           | -1.80                | 96.3                 | -1.64                         | ≤ 11.00                       | 2.36                         | ≤ 10.00                            | Pass   |
| 11n-HT20  | 6.5                    | 48             | 5240           | -1.67                | 96.3                 | -1.51                         | ≤ 11.00                       | 2.49                         | ≤ 10.00                            | Pass   |
| 11n-HT40  | 13.5                   | 38             | 5190           | -5.98                | 96.3                 | -5.82                         | ≤ 11.00                       | -1.82                        | ≤ 10.00                            | Pass   |
| 11n-HT40  | 13.5                   | 46             | 5230           | 0.11                 | 96.3                 | 0.27                          | ≤ 11.00                       | 4.27                         | ≤ 10.00                            | Pass   |
| Ant 2     |                        |                |                |                      |                      |                               |                               |                              |                                    |        |
| 11a       | 6                      | 36             | 5180           | -1.21                | 96.5                 | -1.06                         | ≤ 11.00                       | 2.28                         | ≤ 10.00                            | Pass   |
| 11a       | 6                      | 44             | 5220           | 1.70                 | 96.5                 | 1.85                          | ≤ 11.00                       | 5.19                         | ≤ 10.00                            | Pass   |
| 11a       | 6                      | 48             | 5240           | 2.12                 | 96.5                 | 2.27                          | ≤ 11.00                       | 5.61                         | ≤ 10.00                            | Pass   |
| 11n-HT20  | 6.5                    | 36             | 5180           | -0.69                | 96.3                 | -0.53                         | ≤ 11.00                       | 2.81                         | ≤ 10.00                            | Pass   |
| 11n-HT20  | 6.5                    | 44             | 5220           | -0.65                | 96.3                 | -0.49                         | ≤ 11.00                       | 2.85                         | ≤ 10.00                            | Pass   |
| 11n-HT20  | 6.5                    | 48             | 5240           | -0.66                | 96.3                 | -0.50                         | ≤ 11.00                       | 2.84                         | ≤ 10.00                            | Pass   |
| 11n-HT40  | 13.5                   | 38             | 5190           | -4.93                | 96.3                 | -4.77                         | ≤ 11.00                       | -1.43                        | ≤ 10.00                            | Pass   |
| 11n-HT40  | 13.5                   | 46             | 5230           | -4.93                | 96.3                 | -4.77                         | ≤ 11.00                       | -1.43                        | ≤ 10.00                            | Pass   |

Note 1: When EUT duty cycle < 98%, the Total PSD = PSD + 10\*log(1/duty cycle).

Note 2: EIRP PSD (dBm/MHz) = Total PSD (dBm/MHz) + Antenna Gain (dBi).

Page Number: 42 of 171




| Test Mode | Data Rate | Channel | Freq. | PSD     | Duty  | Constant | Total PSD | Limit    | Result |
|-----------|-----------|---------|-------|---------|-------|----------|-----------|----------|--------|
| Tool Mode | (Mbps)    | No.     | (MHz) | (dBm/   | Cycle | Factor   | (dBm/     | (dBm/    |        |
|           | (11.250)  | 1101    | (     | 100kHz) | (%)   |          | ,         | 500kHz)  |        |
| Ant 1     | <u> </u>  |         |       | ,       | , ,   |          | ,         | <u> </u> |        |
| 11a       | 6         | 149     | 5745  | -12.30  | 96.5  | 7.00     | -5.15     | ≤ 30.00  | Pass   |
| 11a       | 6         | 157     | 5785  | -12.79  | 96.5  | 7.00     | -5.64     | ≤ 30.00  | Pass   |
| 11a       | 6         | 165     | 5825  | -12.12  | 96.5  | 7.00     | -4.97     | ≤ 30.00  | Pass   |
| 11n-HT20  | 6.5       | 149     | 5745  | -13.06  | 96.3  | 7.00     | -5.90     | ≤ 30.00  | Pass   |
| 11n-HT20  | 6.5       | 157     | 5785  | -13.60  | 96.3  | 7.00     | -6.44     | ≤ 30.00  | Pass   |
| 11n-HT20  | 6.5       | 165     | 5825  | -13.01  | 96.3  | 7.00     | -5.85     | ≤ 30.00  | Pass   |
| 11n-HT40  | 13.5      | 151     | 5755  | -8.37   | 96.3  | 7.00     | -1.21     | ≤ 30.00  | Pass   |
| 11n-HT40  | 13.5      | 159     | 5795  | -8.93   | 96.3  | 7.00     | -1.77     | ≤ 30.00  | Pass   |
| Ant 2     |           |         |       |         |       |          |           |          |        |
| 11a       | 6         | 149     | 5745  | -10.56  | 96.5  | 7.00     | -3.41     | ≤ 30.00  | Pass   |
| 11a       | 6         | 157     | 5785  | -11.66  | 96.5  | 7.00     | -4.51     | ≤ 30.00  | Pass   |
| 11a       | 6         | 165     | 5825  | -11.30  | 96.5  | 7.00     | -4.15     | ≤ 30.00  | Pass   |
| 11n-HT20  | 6.5       | 149     | 5745  | -11.83  | 96.3  | 7.00     | -4.67     | ≤ 30.00  | Pass   |
| 11n-HT20  | 6.5       | 157     | 5785  | -12.55  | 96.3  | 7.00     | -5.39     | ≤ 30.00  | Pass   |
| 11n-HT20  | 6.5       | 165     | 5825  | -12.74  | 96.3  | 7.00     | -5.58     | ≤ 30.00  | Pass   |
| 11n-HT40  | 13.5      | 151     | 5755  | -15.21  | 96.3  | 7.00     | -8.05     | ≤ 30.00  | Pass   |
| 11n-HT40  | 13.5      | 159     | 5795  | -15.98  | 96.3  | 7.00     | -8.82     | ≤ 30.00  | Pass   |

Note: When EUT duty cycle < 98%, Total PSD (dBm/500kHz) = PSD (dBm/100kHz) + 10\*log(1/duty cycle) + Constant Factor.


















Page Number: 45 of 171





















Page Number: 48 of 171







# 7.7. Frequency Stability Measurement

#### 7.7.1. Test Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

#### 7.7.2. Test Procedure Used

### **Frequency Stability Under Temperature Variations:**


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

### **Frequency Stability Under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation (±15%) and endpoint, record the maximum frequency change.

#### 7.7.3. Test Setup





Page Number: 50 of 171



# 7.7.4. Test Result

| Test Engineer | Milo Li    | Temperature       | 0 ~ 35°C |
|---------------|------------|-------------------|----------|
| Test Time     | 10-05-2015 | Relative Humidity | 52%RH    |

| Voltage | Power | Temp       | Frequency Tolerance (ppm) |           |           |            |  |
|---------|-------|------------|---------------------------|-----------|-----------|------------|--|
| (%)     | (VAC) | (°C)       | 0 minutes                 | 2 minutes | 5 minutes | 10 minutes |  |
|         |       | - 20       | 4.01                      | 3.82      | 3.91      | 3.80       |  |
|         |       | - 10       | 3.93                      | 3.76      | 3.78      | 3.77       |  |
|         |       | 0          | 3.81                      | 3.81      | 3.96      | 3.95       |  |
| 4000/   | 400   | + 10       | 4.06                      | 4.09      | 4.13      | 4.10       |  |
| 100%    | 120   | + 20 (Ref) | 3.90                      | 4.30      | 4.22      | 4.11       |  |
|         |       | + 30       | 3.99                      | 4.25      | 4.11      | 4.25       |  |
|         |       | + 40       | 4.06                      | 4.28      | 3.87      | 4.01       |  |
|         |       | + 50       | 3.99                      | 3.93      | 3.95      | 3.88       |  |
| 115%    | 138   | + 20       | 4.30                      | 3.89      | 4.29      | 3.90       |  |
| 85%     | 102   | + 20       | 4.35                      | 4.01      | 4.04      | 3.87       |  |

Note: Frequency Tolerance (ppm) =  $\{[Measured Frequency (Hz) - Declared Frequency (Hz)] / Declared Frequency (Hz)\} *10<sup>6</sup>.$ 

Page Number: 51 of 171



# 7.8. Radiated Spurious Emission Measurement

#### 7.8.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

| The first flact for exceed the limite enemial flactor per decident release. |                               |     |  |  |  |  |  |  |
|---|-------------------------------|-----|--|--|--|--|--|--|
| FCC Part 15 Subpart C Paragraph 15.209                                      |                               |     |  |  |  |  |  |  |
| Frequency<br>[MHz]  | Measured Distance<br>[Meters] |     |  |  |  |  |  |  |
| 0.009 - 0.490   | 2400/F (kHz)                  | 300 |  |  |  |  |  |  |
| 0.490 – 1.705   | 24000/F (kHz)                 | 30  |  |  |  |  |  |  |
| 1.705 - 30  | 30                            | 30  |  |  |  |  |  |  |
| 30 - 88   | 100                           | 3   |  |  |  |  |  |  |
| 88 - 216  | 150                           | 3   |  |  |  |  |  |  |
| 216 - 960   | 200                           | 3   |  |  |  |  |  |  |
| Above 960   | 500                           | 3   |  |  |  |  |  |  |


### 7.8.2. Test Procedure Used

KDB 789033 D02v01 - Section G

# 7.8.3. Test Setting

### Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize





### **Quasi-Peak Measurements below 1GHz**


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = 120 kHz
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

# Average Measurements above 1GHz (Method AD)

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = power average (RMS)
- 5. Number of measurement points = 1001 (Number of points must be  $> 2 \times \text{span/RBW}$ )
- 6. Sweep time = auto
- 7. Trace was averaged over at 100 sweeps

#### 7.8.4. Test Setup


### 9kHz ~ 30MHz Test Setup:









# 30MHz ~ 1GHz Test Setup:



# 1GHz ~18GHz Test Setup:



# 18GHz ~40GHz Test Setup:







#### 7.8.5. Test Result

| Test Mode:    | 802.11a - Ant 1                             | Test Site:   | AC1                       |  |  |  |  |
|---------------|---|--|---------------------------|--|--|--|--|
| Test Channel: | 36  | Test Engineer:   | Roy Cheng                 |  |  |  |  |
| Remark:       | Average measurement was no limit.           | Average measurement was not performed if peak level lower than average limit |                           |  |  |  |  |
|               | Other frequency was 20dB bel in the report. | ow limit line within 1   | -18GHz, there is not show |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9738.0    | 34.1    | 11.2   | 45.3     | 68.2     | -22.9  | Peak     | Horizontal   |
| *    | 10494.5   | 35.4    | 12.4   | 47.8     | 68.2     | -20.4  | Peak     | Horizontal   |
|      | 11111.0   | 33.0    | 12.7   | 45.7     | 74.0     | -28.3  | Peak     | Horizontal   |
|      | 13302.0   | 32.7    | 13.1   | 45.8     | 74.0     | -28.2  | Peak     | Horizontal   |
| *    | 9255.0    | 32.7    | 10.2   | 42.9     | 68.2     | -25.3  | Peak     | Vertical     |
| *    | 9738.0    | 33.1    | 11.2   | 44.3     | 68.2     | -23.9  | Peak     | Vertical     |
|      | 10843.0   | 34.5    | 12.7   | 47.2     | 74.0     | -26.8  | Peak     | Vertical     |
|      | 12052.0   | 33.3    | 12.0   | 45.3     | 74.0     | -28.7  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level ( $dB\mu V/m$ ) = Reading Level ( $dB\mu V$ ) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

FCC ID: 2ABX8SH-000000009 IC:12219A-00000000009



Page Number: 55 of 171



| Test Mode:    | 802.11a - Ant 1  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 44   | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9246.0    | 32.7    | 10.2   | 42.9     | 68.2     | -25.3  | Peak     | Horizontal   |
| *    | 9535.0    | 32.7    | 10.8   | 43.5     | 68.2     | -24.7  | Peak     | Horizontal   |
|      | 10782.0   | 33.0    | 12.6   | 45.6     | 74.0     | -28.4  | Peak     | Horizontal   |
|      | 11608.0   | 35.3    | 12.5   | 47.8     | 74.0     | -26.2  | Peak     | Horizontal   |
| *    | 9536.0    | 33.0    | 10.8   | 43.8     | 68.2     | -24.4  | Peak     | Vertical     |
| *    | 10341.5   | 34.4    | 12.2   | 46.6     | 68.2     | -21.6  | Peak     | Vertical     |
|      | 11505.0   | 32.5    | 12.8   | 45.3     | 74.0     | -28.7  | Peak     | Vertical     |
|      | 13302.0   | 32.6    | 13.1   | 45.7     | 74.0     | -28.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 56 of 171



| Test Mode:    | 802.11a - Ant 1  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 48   | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   | limit.         |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9569.0    | 32.7    | 10.9   | 43.6     | 68.2     | -24.6  | Peak     | Horizontal   |
| *    | 10299.0   | 34.3    | 12.0   | 46.3     | 68.2     | -21.9  | Peak     | Horizontal   |
|      | 11215.0   | 33.1    | 12.4   | 45.5     | 74.0     | -28.5  | Peak     | Horizontal   |
|      | 13308.0   | 31.9    | 13.2   | 45.1     | 74.0     | -28.9  | Peak     | Horizontal   |
| *    | 9247.0    | 32.9    | 10.2   | 43.1     | 68.2     | -25.1  | Peak     | Vertical     |
| *    | 9602.0    | 32.7    | 10.9   | 43.6     | 68.2     | -24.6  | Peak     | Vertical     |
|      | 11693.0   | 35.3    | 12.0   | 47.3     | 74.0     | -26.7  | Peak     | Vertical     |
|      | 12505.0   | 32.7    | 11.4   | 44.1     | 74.0     | -29.9  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 57 of 171



| Test Mode:    | 802.11a - Ant 1  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 149  | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9255.0    | 32.3    | 10.2   | 42.5     | 68.2     | -25.7  | Peak     | Horizontal   |
| *    | 9677.0    | 32.6    | 10.9   | 43.5     | 68.2     | -24.7  | Peak     | Horizontal   |
|      | 11106.5   | 34.5    | 12.8   | 47.3     | 74.0     | -26.7  | Peak     | Horizontal   |
|      | 12052.0   | 32.8    | 12.0   | 44.8     | 74.0     | -29.2  | Peak     | Horizontal   |
| *    | 9236.0    | 32.4    | 10.1   | 42.5     | 68.2     | -25.7  | Peak     | Vertical     |
| *    | 9629.0    | 32.7    | 11.0   | 43.7     | 68.2     | -24.5  | Peak     | Vertical     |
|      | 11395.5   | 34.5    | 12.6   | 47.1     | 74.0     | -26.9  | Peak     | Vertical     |
|      | 12415.0   | 32.6    | 11.5   | 44.1     | 74.0     | -29.9  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 58 of 171



| Test Mode:    | 802.11a - Ant 1  | Test Site:     | AC1       |  |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|--|
| Test Channel: | 157  | Test Engineer: | Roy Cheng |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |  |
|               | limit.   | limit.         |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9236.0    | 32.3    | 10.1   | 42.4     | 68.2     | -25.8  | Peak     | Horizontal   |
| *    | 9522.0    | 32.6    | 10.7   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
|      | 10741.0   | 34.7    | 12.5   | 47.2     | 74.0     | -26.8  | Peak     | Horizontal   |
|      | 13315.0   | 32.4    | 13.3   | 45.7     | 74.0     | -28.3  | Peak     | Horizontal   |
| *    | 9266.0    | 32.4    | 10.3   | 42.7     | 68.2     | -25.5  | Peak     | Vertical     |
| *    | 9818.0    | 32.9    | 11.6   | 44.5     | 68.2     | -23.7  | Peak     | Vertical     |
|      | 10928.0   | 34.1    | 13.0   | 47.1     | 74.0     | -26.9  | Peak     | Vertical     |
|      | 11282.0   | 33.3    | 12.4   | 45.7     | 74.0     | -28.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 59 of 171




| Test Mode:    | 802.11a - Ant 1  | Test Site:     | AC1       |  |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|--|
| Test Channel: | 165  | Test Engineer: | Roy Cheng |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |  |
|               | limit.   | limit.         |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9277.0    | 32.4    | 10.3   | 42.7     | 68.2     | -25.5  | Peak     | Horizontal   |
| *    | 9516.0    | 31.7    | 10.6   | 42.3     | 68.2     | -25.9  | Peak     | Horizontal   |
|      | 10945.0   | 33.7    | 13.1   | 46.8     | 74.0     | -27.2  | Peak     | Horizontal   |
|      | 11529.0   | 32.7    | 12.7   | 45.4     | 74.0     | -28.6  | Peak     | Horizontal   |
| *    | 9255.0    | 33.2    | 10.2   | 43.4     | 68.2     | -24.8  | Peak     | Vertical     |
| *    | 9569.0    | 32.8    | 10.9   | 43.7     | 68.2     | -24.5  | Peak     | Vertical     |
|      | 10843.0   | 34.2    | 12.7   | 46.9     | 74.0     | -27.1  | Peak     | Vertical     |
|      | 11245.0   | 32.3    | 12.4   | 44.7     | 74.0     | -29.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 60 of 171



| Test Mode:    | 802.11n-HT20 - Ant 1            | Test Site:   | AC1       |  |  |  |  |  |
|---------------|---------------------------------|--|-----------|--|--|--|--|--|
| Test Channel: | 36                              | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no   | . Average measurement was not performed if peak level lower than average       |           |  |  |  |  |  |
|               | limit.                          | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB bel | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |           |  |  |  |  |  |
|               | in the report.                  |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9244.0    | 33.2    | 10.2   | 43.4     | 68.2     | -24.8  | Peak     | Horizontal   |
| *    | 9848.0    | 32.5    | 11.6   | 44.1     | 68.2     | -24.1  | Peak     | Horizontal   |
|      | 11191.5   | 34.2    | 12.5   | 46.7     | 74.0     | -27.3  | Peak     | Horizontal   |
|      | 13329.0   | 32.7    | 13.4   | 46.1     | 74.0     | -27.9  | Peak     | Horizontal   |
| *    | 9236.0    | 32.4    | 10.1   | 42.5     | 68.2     | -25.7  | Peak     | Vertical     |
| *    | 9526.0    | 34.5    | 10.7   | 45.2     | 68.2     | -23.0  | Peak     | Vertical     |
|      | 10945.0   | 33.9    | 13.1   | 47.0     | 74.0     | -27.0  | Peak     | Vertical     |
|      | 11252.0   | 32.3    | 12.4   | 44.7     | 74.0     | -29.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 61 of 171




| Test Mode:    | 802.11n-HT20 - Ant 1   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 44   | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9263.0    | 33.4    | 10.3   | 43.7     | 68.2     | -24.5  | Peak     | Horizontal   |
| *    | 9515.0    | 32.4    | 10.6   | 43.0     | 68.2     | -25.2  | Peak     | Horizontal   |
|      | 10851.5   | 34.7    | 12.8   | 47.5     | 74.0     | -26.5  | Peak     | Horizontal   |
|      | 11262.0   | 32.7    | 12.4   | 45.1     | 74.0     | -28.9  | Peak     | Horizontal   |
| *    | 9268.0    | 32.9    | 10.3   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
| *    | 9549.0    | 31.9    | 10.8   | 42.7     | 68.2     | -25.5  | Peak     | Vertical     |
|      | 11302.0   | 34.3    | 12.5   | 46.8     | 74.0     | -27.2  | Peak     | Vertical     |
|      | 12525.0   | 33.7    | 11.4   | 45.1     | 74.0     | -28.9  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 62 of 171




| Test Mode:    | 802.11n-HT20 - Ant 1   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 48   | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9269.0    | 32.1    | 10.3   | 42.4     | 68.2     | -25.8  | Peak     | Horizontal   |
| *    | 9574.0    | 33.1    | 10.9   | 44.0     | 68.2     | -24.2  | Peak     | Horizontal   |
|      | 10919.5   | 33.8    | 13.0   | 46.8     | 74.0     | -27.2  | Peak     | Horizontal   |
|      | 11282.0   | 32.4    | 12.4   | 44.8     | 74.0     | -29.2  | Peak     | Horizontal   |
| *    | 9258.0    | 32.5    | 10.3   | 42.8     | 68.2     | -25.4  | Peak     | Vertical     |
| *    | 9516.0    | 32.6    | 10.6   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
|      | 10715.5   | 34.3    | 12.4   | 46.7     | 74.0     | -27.3  | Peak     | Vertical     |
|      | 11250.0   | 32.3    | 12.4   | 44.7     | 74.0     | -29.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 63 of 171



| Test Mode:    | 802.11n-HT20 - Ant 1   | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 149  | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   | limit.         |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9246.0    | 33.1    | 10.2   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
| *    | 9529.0    | 32.7    | 10.7   | 43.4     | 68.2     | -24.8  | Peak     | Horizontal   |
|      | 10911.0   | 33.8    | 13.0   | 46.8     | 74.0     | -27.2  | Peak     | Horizontal   |
|      | 11629.0   | 33.0    | 12.4   | 45.4     | 74.0     | -28.6  | Peak     | Horizontal   |
| *    | 9249.0    | 32.5    | 10.2   | 42.7     | 68.2     | -25.5  | Peak     | Vertical     |
| *    | 9567.0    | 33.5    | 10.9   | 44.4     | 68.2     | -23.8  | Peak     | Vertical     |
|      | 11412.5   | 34.0    | 12.6   | 46.6     | 74.0     | -27.4  | Peak     | Vertical     |
|      | 13308.0   | 31.7    | 13.2   | 44.9     | 74.0     | -29.1  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 64 of 171



| Test Mode:    | 802.11n-HT20 - Ant 1   | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 157  | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9238.0    | 32.5    | 10.2   | 42.7     | 68.2     | -25.5  | Peak     | Horizontal   |
| *    | 9518.0    | 32.9    | 10.6   | 43.5     | 68.2     | -24.7  | Peak     | Horizontal   |
|      | 11378.5   | 33.8    | 12.6   | 46.4     | 74.0     | -27.6  | Peak     | Horizontal   |
|      | 13304.0   | 32.8    | 13.1   | 45.9     | 74.0     | -28.1  | Peak     | Horizontal   |
| *    | 9271.0    | 33.2    | 10.3   | 43.5     | 68.2     | -24.7  | Peak     | Vertical     |
| *    | 9528.0    | 32.4    | 10.7   | 43.1     | 68.2     | -25.1  | Peak     | Vertical     |
|      | 11310.5   | 34.1    | 12.5   | 46.6     | 74.0     | -27.4  | Peak     | Vertical     |
|      | 13308.0   | 32.2    | 13.2   | 45.4     | 74.0     | -28.6  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 65 of 171



| Test Mode:    | 802.11n-HT20 - Ant 1   | Test Site:     | AC1       |  |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|--|
| Test Channel: | 165  | Test Engineer: | Roy Cheng |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9248.0    | 32.6    | 10.2   | 42.8     | 68.2     | -25.4  | Peak     | Horizontal   |
| *    | 9518.0    | 33.2    | 10.6   | 43.8     | 68.2     | -24.4  | Peak     | Horizontal   |
|      | 11370.0   | 34.4    | 12.6   | 47.0     | 74.0     | -27.0  | Peak     | Horizontal   |
|      | 13304.0   | 32.6    | 13.1   | 45.7     | 74.0     | -28.3  | Peak     | Horizontal   |
| *    | 9271.0    | 32.5    | 10.3   | 42.8     | 68.2     | -25.4  | Peak     | Vertical     |
| *    | 9538.0    | 32.9    | 10.8   | 43.7     | 68.2     | -24.5  | Peak     | Vertical     |
|      | 10953.5   | 34.3    | 13.1   | 47.4     | 74.0     | -26.6  | Peak     | Vertical     |
|      | 12005.0   | 32.9    | 11.9   | 44.8     | 74.0     | -29.2  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 66 of 171



| Test Mode:    | 802.11n-HT40 - Ant 1   | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 38   | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9248.0    | 33.4    | 10.2   | 43.6     | 68.2     | -24.6  | Peak     | Horizontal   |
| *    | 9536.0    | 33.2    | 10.8   | 44.0     | 68.2     | -24.2  | Peak     | Horizontal   |
|      | 11030.0   | 34.1    | 13.0   | 47.1     | 74.0     | -26.9  | Peak     | Horizontal   |
|      | 12020.0   | 32.9    | 11.9   | 44.8     | 74.0     | -29.2  | Peak     | Horizontal   |
| *    | 9236.0    | 32.7    | 10.1   | 42.8     | 68.2     | -25.4  | Peak     | Vertical     |
| *    | 9518.0    | 32.9    | 10.6   | 43.5     | 68.2     | -24.7  | Peak     | Vertical     |
|      | 11395.5   | 33.5    | 12.6   | 46.1     | 74.0     | -27.9  | Peak     | Vertical     |
|      | 12051.0   | 32.6    | 12.0   | 44.6     | 74.0     | -29.4  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 67 of 171



| Test Mode:    | 802.11n-HT40 - Ant 1   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 46   | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average |  |           |  |  |  |  |  |
|               | limit.   |  |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB bel  | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9248.0    | 33.1    | 10.2   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
| *    | 9518.0    | 32.1    | 10.6   | 42.7     | 68.2     | -25.5  | Peak     | Horizontal   |
|      | 10851.5   | 34.2    | 12.8   | 47.0     | 74.0     | -27.0  | Peak     | Horizontal   |
|      | 13325.0   | 32.6    | 13.4   | 46.0     | 74.0     | -28.0  | Peak     | Horizontal   |
| *    | 9218.0    | 32.8    | 10.1   | 42.9     | 68.2     | -25.3  | Peak     | Vertical     |
| *    | 9517.0    | 32.6    | 10.6   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
|      | 10877.0   | 33.5    | 12.9   | 46.4     | 74.0     | -27.6  | Peak     | Vertical     |
|      | 11252.0   | 32.3    | 12.4   | 44.7     | 74.0     | -29.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 68 of 171



| Test Mode:    | 802.11n-HT40 - Ant 1   | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 151  | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9248.0    | 33.1    | 10.2   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
| *    | 9568.0    | 32.7    | 10.9   | 43.6     | 68.2     | -24.6  | Peak     | Horizontal   |
|      | 10996.0   | 35.0    | 13.0   | 48.0     | 74.0     | -26.0  | Peak     | Horizontal   |
|      | 11250.0   | 33.4    | 12.4   | 45.8     | 74.0     | -28.2  | Peak     | Horizontal   |
| *    | 9248.0    | 32.9    | 10.2   | 43.1     | 68.2     | -25.1  | Peak     | Vertical     |
| *    | 9547.0    | 33.2    | 10.8   | 44.0     | 68.2     | -24.2  | Peak     | Vertical     |
|      | 10919.5   | 34.1    | 13.0   | 47.1     | 74.0     | -26.9  | Peak     | Vertical     |
|      | 12250.0   | 33.3    | 11.7   | 45.0     | 74.0     | -29.0  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 69 of 171



| Test Mode:    | 802.11n-HT40 - Ant 1   | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 159  | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9236.0    | 32.8    | 10.1   | 42.9     | 68.2     | -25.3  | Peak     | Horizontal   |
| *    | 9526.0    | 33.8    | 10.7   | 44.5     | 68.2     | -23.7  | Peak     | Horizontal   |
|      | 10894.0   | 33.8    | 12.9   | 46.7     | 74.0     | -27.3  | Peak     | Horizontal   |
|      | 11252.0   | 32.1    | 12.4   | 44.5     | 74.0     | -29.5  | Peak     | Horizontal   |
| *    | 9248.0    | 32.8    | 10.2   | 43.0     | 68.2     | -25.2  | Peak     | Vertical     |
| *    | 9538.0    | 32.4    | 10.8   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
|      | 10928.0   | 34.6    | 13.0   | 47.6     | 74.0     | -26.4  | Peak     | Vertical     |
|      | 11250.0   | 32.3    | 12.4   | 44.7     | 74.0     | -29.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 70 of 171



| Test Mode:    | 802.11a - Ant 2  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 36   | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9235.0    | 34.0    | 10.1   | 44.1     | 68.2     | -24.1  | Peak     | Horizontal   |
| *    | 9518.0    | 32.8    | 10.6   | 43.4     | 68.2     | -24.8  | Peak     | Horizontal   |
|      | 10877.0   | 34.0    | 12.9   | 46.9     | 74.0     | -27.1  | Peak     | Horizontal   |
|      | 11252.0   | 33.9    | 12.4   | 46.3     | 74.0     | -27.7  | Peak     | Horizontal   |
| *    | 9241.0    | 33.1    | 10.2   | 43.3     | 68.2     | -24.9  | Peak     | Vertical     |
| *    | 9518.0    | 32.7    | 10.6   | 43.3     | 68.2     | -24.9  | Peak     | Vertical     |
|      | 10860.0   | 35.4    | 12.8   | 48.2     | 74.0     | -25.8  | Peak     | Vertical     |
|      | 11252.0   | 32.6    | 12.4   | 45.0     | 74.0     | -29.0  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 71 of 171



| Test Mode:    | 802.11a - Ant 2  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 44   | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   | limit.         |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9232.0    | 33.2    | 10.1   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
| *    | 9516.0    | 32.7    | 10.6   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
|      | 10868.5   | 34.3    | 12.8   | 47.1     | 74.0     | -26.9  | Peak     | Horizontal   |
|      | 11252.0   | 32.5    | 12.4   | 44.9     | 74.0     | -29.1  | Peak     | Horizontal   |
| *    | 9236.0    | 31.9    | 10.1   | 42.0     | 68.2     | -26.2  | Peak     | Vertical     |
| *    | 9518.0    | 31.5    | 10.6   | 42.1     | 68.2     | -26.1  | Peak     | Vertical     |
|      | 11081.0   | 33.9    | 12.9   | 46.8     | 74.0     | -27.2  | Peak     | Vertical     |
|      | 11258.0   | 32.5    | 12.4   | 44.9     | 74.0     | -29.1  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 72 of 171



| Test Mode:    | 802.11a - Ant 2  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 48   | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9238.0    | 32.8    | 10.2   | 43.0     | 68.2     | -25.2  | Peak     | Horizontal   |
| *    | 9528.0    | 31.9    | 10.7   | 42.6     | 68.2     | -25.6  | Peak     | Horizontal   |
|      | 10732.5   | 33.1    | 12.5   | 45.6     | 74.0     | -28.4  | Peak     | Horizontal   |
|      | 11285.0   | 32.8    | 12.4   | 45.2     | 74.0     | -28.8  | Peak     | Horizontal   |
| *    | 9268.0    | 32.6    | 10.3   | 42.9     | 68.2     | -25.3  | Peak     | Vertical     |
| *    | 9569.0    | 32.6    | 10.9   | 43.5     | 68.2     | -24.7  | Peak     | Vertical     |
|      | 10877.0   | 33.6    | 12.9   | 46.5     | 74.0     | -27.5  | Peak     | Vertical     |
|      | 11286.0   | 33.3    | 12.4   | 45.7     | 74.0     | -28.3  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 73 of 171



| Test Mode:    | 802.11a - Ant 2  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 149  | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9269.0    | 32.6    | 10.3   | 42.9     | 68.2     | -25.3  | Peak     | Horizontal   |
| *    | 9518.0    | 33.1    | 10.6   | 43.7     | 68.2     | -24.5  | Peak     | Horizontal   |
|      | 10860.0   | 34.0    | 12.8   | 46.8     | 74.0     | -27.2  | Peak     | Horizontal   |
|      | 11252.0   | 33.1    | 12.4   | 45.5     | 74.0     | -28.5  | Peak     | Horizontal   |
| *    | 9236.0    | 32.7    | 10.1   | 42.8     | 68.2     | -25.4  | Peak     | Vertical     |
| *    | 9548.0    | 32.4    | 10.8   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
|      | 10945.0   | 33.6    | 13.1   | 46.7     | 74.0     | -27.3  | Peak     | Vertical     |
|      | 12150.0   | 33.3    | 11.8   | 45.1     | 74.0     | -28.9  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 74 of 171



| Test Mode:    | 802.11a - Ant 2  | Test Site:     | AC1       |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|
| Test Channel: | 157  | Test Engineer: | Roy Cheng |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9251.0    | 33.3    | 10.2   | 43.5     | 68.2     | -24.7  | Peak     | Horizontal   |
| *    | 9569.0    | 33.3    | 10.9   | 44.2     | 68.2     | -24.0  | Peak     | Horizontal   |
|      | 10758.0   | 34.9    | 12.5   | 47.4     | 74.0     | -26.6  | Peak     | Horizontal   |
|      | 11258.0   | 33.0    | 12.4   | 45.4     | 74.0     | -28.6  | Peak     | Horizontal   |
| *    | 9258.0    | 33.5    | 10.3   | 43.8     | 68.2     | -24.4  | Peak     | Vertical     |
| *    | 9549.0    | 32.3    | 10.8   | 43.1     | 68.2     | -25.1  | Peak     | Vertical     |
|      | 10758.0   | 34.9    | 12.5   | 47.4     | 74.0     | -26.6  | Peak     | Vertical     |
|      | 11252.0   | 32.8    | 12.4   | 45.2     | 74.0     | -28.8  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 75 of 171



| Test Mode:    | 802.11a - Ant 2  | Test Site:     | AC1       |  |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|--|
| Test Channel: | 165  | Test Engineer: | Roy Cheng |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |  |
|               | limit.   | limit.         |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9268.0    | 32.6    | 10.3   | 42.9     | 68.2     | -25.3  | Peak     | Horizontal   |
| *    | 9548.0    | 32.5    | 10.8   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
|      | 11250.0   | 32.7    | 12.4   | 45.1     | 74.0     | -28.9  | Peak     | Horizontal   |
|      | 11506.0   | 34.4    | 12.8   | 47.2     | 74.0     | -26.8  | Peak     | Horizontal   |
| *    | 9235.0    | 32.4    | 10.1   | 42.5     | 68.2     | -25.7  | Peak     | Vertical     |
| *    | 9524.0    | 32.3    | 10.7   | 43.0     | 68.2     | -25.2  | Peak     | Vertical     |
|      | 11412.5   | 34.5    | 12.6   | 47.1     | 74.0     | -26.9  | Peak     | Vertical     |
|      | 12052.0   | 32.3    | 12.0   | 44.3     | 74.0     | -29.7  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 76 of 171



| Test Mode:    | 802.11n-HT20 - Ant 2   | Test Site:     | AC1       |  |  |  |
|---------------|--|----------------|-----------|--|--|--|
| Test Channel: | 36   | Test Engineer: | Roy Cheng |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |
|               | limit.   |                |           |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |
|               | in the report.   |                |           |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9218.0    | 34.5    | 10.1   | 44.6     | 68.2     | -23.6  | Peak     | Horizontal   |
| *    | 9535.0    | 33.2    | 10.8   | 44.0     | 68.2     | -24.2  | Peak     | Horizontal   |
|      | 11591.0   | 35.7    | 12.6   | 48.3     | 74.0     | -25.7  | Peak     | Horizontal   |
|      | 12065.0   | 33.7    | 12.0   | 45.7     | 74.0     | -28.3  | Peak     | Horizontal   |
| *    | 9261.0    | 32.3    | 10.3   | 42.6     | 68.2     | -25.6  | Peak     | Vertical     |
| *    | 9516.0    | 32.0    | 10.6   | 42.6     | 68.2     | -25.6  | Peak     | Vertical     |
|      | 11591.0   | 33.5    | 12.6   | 46.1     | 74.0     | -27.9  | Peak     | Vertical     |
|      | 12082.0   | 34.2    | 12.0   | 46.2     | 74.0     | -27.8  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 77 of 171



| Test Mode:    | 802.11n-HT20 - Ant 2   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 44   | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   |  |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9264.0    | 32.5    | 10.3   | 42.8     | 68.2     | -25.4  | Peak     | Horizontal   |
| *    | 9518.0    | 32.9    | 10.6   | 43.5     | 68.2     | -24.7  | Peak     | Horizontal   |
|      | 11565.5   | 34.8    | 12.7   | 47.5     | 74.0     | -26.5  | Peak     | Horizontal   |
|      | 15424.5   | 33.8    | 12.6   | 46.4     | 74.0     | -27.6  | Peak     | Horizontal   |
| *    | 9218.0    | 33.0    | 10.1   | 43.1     | 68.2     | -25.1  | Peak     | Vertical     |
| *    | 9523.0    | 32.8    | 10.7   | 43.5     | 68.2     | -24.7  | Peak     | Vertical     |
|      | 11081.0   | 34.6    | 12.9   | 47.5     | 74.0     | -26.5  | Peak     | Vertical     |
|      | 12053.0   | 33.8    | 12.0   | 45.8     | 74.0     | -28.2  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 78 of 171



| Test Mode:    | 802.11n-HT20 - Ant 2   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 48   | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9215.0    | 33.1    | 10.1   | 43.2     | 68.2     | -25.0  | Peak     | Horizontal   |
| *    | 9526.0    | 32.2    | 10.7   | 42.9     | 68.2     | -25.3  | Peak     | Horizontal   |
|      | 11021.5   | 33.9    | 13.0   | 46.9     | 74.0     | -27.1  | Peak     | Horizontal   |
|      | 11786.5   | 33.7    | 11.9   | 45.6     | 74.0     | -28.4  | Peak     | Horizontal   |
| *    | 9236.0    | 33.0    | 10.1   | 43.1     | 68.2     | -25.1  | Peak     | Vertical     |
| *    | 9517.0    | 31.7    | 10.6   | 42.3     | 68.2     | -25.9  | Peak     | Vertical     |
|      | 10996.0   | 33.9    | 13.0   | 46.9     | 74.0     | -27.1  | Peak     | Vertical     |
|      | 11251.0   | 32.7    | 12.4   | 45.1     | 74.0     | -28.9  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 79 of 171



| Test Mode:    | 802.11n-HT20 - Ant 2   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 149  | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9236.0    | 32.6    | 10.1   | 42.7     | 68.2     | -25.5  | Peak     | Horizontal   |
| *    | 9562.0    | 32.0    | 10.9   | 42.9     | 68.2     | -25.3  | Peak     | Horizontal   |
|      | 11548.5   | 34.8    | 12.7   | 47.5     | 74.0     | -26.5  | Peak     | Horizontal   |
|      | 12020.0   | 32.6    | 11.9   | 44.5     | 74.0     | -29.5  | Peak     | Horizontal   |
| *    | 9236.0    | 32.5    | 10.1   | 42.6     | 68.2     | -25.6  | Peak     | Vertical     |
| *    | 9518.0    | 32.0    | 10.6   | 42.6     | 68.2     | -25.6  | Peak     | Vertical     |
|      | 10979.0   | 33.8    | 13.0   | 46.8     | 74.0     | -27.2  | Peak     | Vertical     |
|      | 11252.0   | 31.5    | 12.4   | 43.9     | 74.0     | -30.1  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 80 of 171



| Test Mode:    | 802.11n-HT20 - Ant 2   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 157  | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9236.0    | 32.6    | 10.1   | 42.7     | 68.2     | -25.5  | Peak     | Horizontal   |
| *    | 9517.0    | 32.2    | 10.6   | 42.8     | 68.2     | -25.4  | Peak     | Horizontal   |
|      | 10825.0   | 33.0    | 12.7   | 45.7     | 74.0     | -28.3  | Peak     | Horizontal   |
|      | 10979.0   | 33.8    | 13.0   | 46.8     | 74.0     | -27.2  | Peak     | Horizontal   |
| *    | 9236.0    | 32.7    | 10.1   | 42.8     | 68.2     | -25.4  | Peak     | Vertical     |
| *    | 9518.0    | 32.6    | 10.6   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
|      | 10681.5   | 34.6    | 12.4   | 47.0     | 74.0     | -27.0  | Peak     | Vertical     |
|      | 11252.0   | 32.5    | 12.4   | 44.9     | 74.0     | -29.1  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 81 of 171



| Test Mode:    | 802.11n-HT20 - Ant 2   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 165  | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9236.0    | 32.4    | 10.1   | 42.5     | 68.2     | -25.7  | Peak     | Horizontal   |
| *    | 9518.0    | 32.5    | 10.6   | 43.1     | 68.2     | -25.1  | Peak     | Horizontal   |
|      | 11574.0   | 34.8    | 12.6   | 47.4     | 74.0     | -26.6  | Peak     | Horizontal   |
|      | 12053.0   | 33.0    | 12.0   | 45.0     | 74.0     | -29.0  | Peak     | Horizontal   |
| *    | 9236.0    | 32.9    | 10.1   | 43.0     | 68.2     | -25.2  | Peak     | Vertical     |
| *    | 9547.0    | 32.8    | 10.8   | 43.6     | 68.2     | -24.6  | Peak     | Vertical     |
|      | 10877.0   | 36.3    | 12.9   | 49.2     | 74.0     | -24.8  | Peak     | Vertical     |
|      | 12325.0   | 32.6    | 11.6   | 44.2     | 74.0     | -29.8  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 82 of 171



| Test Mode:    | 802.11n-HT40 - Ant 2   | Test Site:   | AC1       |  |  |  |  |  |
|---------------|--|--|-----------|--|--|--|--|--|
| Test Channel: | 38   | Test Engineer:   | Roy Cheng |  |  |  |  |  |
| Remark:       | 1. Average measurement was no  | . Average measurement was not performed if peak level lower than average |           |  |  |  |  |  |
|               | limit.   | limit.   |           |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |  |           |  |  |  |  |  |
|               | in the report.   |  |           |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9236.0    | 33.1    | 10.1   | 43.2     | 68.2     | -25.0  | Peak     | Horizontal   |
| *    | 9517.0    | 32.1    | 10.6   | 42.7     | 68.2     | -25.5  | Peak     | Horizontal   |
|      | 10936.5   | 33.6    | 13.0   | 46.6     | 74.0     | -27.4  | Peak     | Horizontal   |
|      | 12052.0   | 33.6    | 12.0   | 45.6     | 74.0     | -28.4  | Peak     | Horizontal   |
| *    | 9236.0    | 33.3    | 10.1   | 43.4     | 68.2     | -24.8  | Peak     | Vertical     |
| *    | 9517.0    | 32.6    | 10.6   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
|      | 10651.0   | 33.0    | 11.9   | 44.9     | 74.0     | -29.1  | Peak     | Vertical     |
|      | 10936.5   | 33.6    | 13.0   | 46.6     | 74.0     | -27.4  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 83 of 171




| Test Mode:    | 802.11n-HT40 - Ant 2   | Test Site:     | AC1       |  |  |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|--|--|
| Test Channel: | 46   | Test Engineer: | Roy Cheng |  |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9215.0    | 32.2    | 10.1   | 42.3     | 68.2     | -25.9  | Peak     | Horizontal   |
| *    | 9517.0    | 31.9    | 10.6   | 42.5     | 68.2     | -25.7  | Peak     | Horizontal   |
|      | 11344.5   | 33.2    | 12.5   | 45.7     | 74.0     | -28.3  | Peak     | Horizontal   |
|      | 12305.0   | 32.2    | 11.6   | 43.8     | 74.0     | -30.2  | Peak     | Horizontal   |
| *    | 9235.0    | 32.9    | 10.1   | 43.0     | 68.2     | -25.2  | Peak     | Vertical     |
| *    | 9518.0    | 32.6    | 10.6   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
|      | 11599.5   | 34.9    | 12.6   | 47.5     | 74.0     | -26.5  | Peak     | Vertical     |
|      | 12050.0   | 32.9    | 12.0   | 44.9     | 74.0     | -29.1  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 84 of 171




| Test Mode:    | 802.11n-HT40 - Ant 2   | Test Site:     | AC1       |  |  |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|--|--|
| Test Channel: | 151  | Test Engineer: | Roy Cheng |  |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9249.0    | 33.2    | 10.2   | 43.4     | 68.2     | -24.8  | Peak     | Horizontal   |
| *    | 9526.0    | 33.1    | 10.7   | 43.8     | 68.2     | -24.4  | Peak     | Horizontal   |
|      | 11404.0   | 33.9    | 12.6   | 46.5     | 74.0     | -27.5  | Peak     | Horizontal   |
|      | 15577.5   | 35.5    | 12.1   | 47.6     | 74.0     | -26.4  | Peak     | Horizontal   |
| *    | 9236.0    | 33.0    | 10.1   | 43.1     | 68.2     | -25.1  | Peak     | Vertical     |
| *    | 9548.0    | 32.5    | 10.8   | 43.3     | 68.2     | -24.9  | Peak     | Vertical     |
|      | 10800.5   | 33.5    | 12.6   | 46.1     | 74.0     | -27.9  | Peak     | Vertical     |
|      | 11268.0   | 35.0    | 12.4   | 47.4     | 74.0     | -26.6  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)



Page Number: 85 of 171



| Test Mode:    | 802.11n-HT40 - Ant 2   | Test Site:     | AC1       |  |  |  |  |  |  |
|---------------|--|----------------|-----------|--|--|--|--|--|--|
| Test Channel: | 159  | Test Engineer: | Roy Cheng |  |  |  |  |  |  |
| Remark:       | Average measurement was not performed if peak level lower than average         |                |           |  |  |  |  |  |  |
|               | limit.   |                |           |  |  |  |  |  |  |
|               | 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show |                |           |  |  |  |  |  |  |
|               | in the report.   |                |           |  |  |  |  |  |  |

| Mark | Frequency | Reading | Factor | Measure  | Limit    | Margin | Detector | Polarization |
|------|-----------|---------|--------|----------|----------|--------|----------|--------------|
|      | (MHz)     | Level   | (dB)   | Level    | (dBµV/m) | (dB)   |          |              |
|      |           | (dBµV)  |        | (dBµV/m) |          |        |          |              |
| *    | 9248.0    | 32.7    | 10.2   | 42.9     | 68.2     | -25.3  | Peak     | Horizontal   |
| *    | 9531.0    | 32.6    | 10.7   | 43.3     | 68.2     | -24.9  | Peak     | Horizontal   |
|      | 10928.0   | 34.1    | 13.0   | 47.1     | 74.0     | -26.9  | Peak     | Horizontal   |
|      | 12052.0   | 32.6    | 12.0   | 44.6     | 74.0     | -29.4  | Peak     | Horizontal   |
| *    | 9235.0    | 33.1    | 10.1   | 43.2     | 68.2     | -25.0  | Peak     | Vertical     |
| *    | 9518.0    | 32.8    | 10.6   | 43.4     | 68.2     | -24.8  | Peak     | Vertical     |
|      | 10945.0   | 34.1    | 13.1   | 47.2     | 74.0     | -26.8  | Peak     | Vertical     |
|      | 11353.0   | 35.1    | 12.5   | 47.6     | 74.0     | -26.4  | Peak     | Vertical     |

Note 1: "\*" is not in restricted band, its limit is -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)




Page Number: 86 of 171



### The worst case of Radiated Emission below 1GHz:

| Site: AC1                               | Time: 2015/10/08 - 18:56 |
|---|--------------------------|
| Limit: FCC_Part15.209_RE(3m)            | Engineer: Lewis Huang    |
| Probe: VULB9162_0.03-8GHz               | Polarity: Horizontal     |
| EUT: sengled pulse flex                 | Power: AC 120V/60Hz      |
| Worst Mode: Transmit at channel 5180MHz |                          |




| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 36.305    | 16.307   | 3.154   | -23.693    | 40.000   | 13.153 | QP   |
| 2  |      |      | 50.370    | 15.510   | 0.610   | -24.490    | 40.000   | 14.900 | QP   |
| 3  |      |      | 201.690   | 15.496   | 3.240   | -28.004    | 43.500   | 12.256 | QP   |
| 4  |      |      | 228.365   | 17.279   | 4.325   | -28.721    | 46.000   | 12.955 | QP   |
| 5  |      | *    | 317.120   | 24.527   | 9.587   | -21.473    | 46.000   | 14.940 | QP   |
| 6  |      |      | 626.065   | 21.314   | 1.042   | -24.686    | 46.000   | 20.272 | QP   |

Note: Measure Level ( $dB\mu V/m$ ) = Reading Level ( $dB\mu V$ ) + Factor (dB)





| Site: AC1                               | Time: 2015/10/08 - 18:56 |
|---|--------------------------|
| Limit: FCC_Part15.209_RE(3m)            | Engineer: Lewis Huang    |
| Probe: VULB9162_0.03-8GHz               | Polarity: Vertical       |
| EUT: sengled pulse flex                 | Power: AC 120V/60Hz      |
| Worst Mode: Transmit at channel 5180MHz |                          |



| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 39.701    | 20.103   | 6.315   | -19.897    | 40.000   | 13.788 | QP   |
| 2  |      |      | 49.402    | 20.290   | 5.374   | -19.710    | 40.000   | 14.916 | QP   |
| 3  |      |      | 117.785   | 22.228   | 10.646  | -21.272    | 43.500   | 11.582 | QP   |
| 4  |      |      | 234.185   | 19.593   | 6.424   | -26.407    | 46.000   | 13.169 | QP   |
| 5  |      | *    | 317.605   | 26.379   | 11.425  | -19.621    | 46.000   | 14.954 | QP   |
| 6  |      |      | 549.920   | 23.292   | 4.254   | -22.708    | 46.000   | 19.038 | QP   |


Note: Measure Level ( $dB\mu V/m$ ) = Reading Level ( $dB\mu V$ ) + Factor (dB)



Page Number: 88 of 171



| Probe: FMZB1519_0.009-30MHz                          | Polarity: Face on                     |  |  |
|--|---------------------------------------|--|--|
| Probe: FMZB1519_0.009-30MHz  EUT: sengled pulse flex | Polarity: Face on Power: AC 120V/60Hz |  |  |
| Limit: FCC_Part15.209_RE(3m)                         | Engineer: Roy Cheng                   |  |  |
| Site: AC1  | Time: 2015/10/06 - 19:18              |  |  |



| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 0.029     | 56.610   | 35.660  | -61.732    | 118.342  | 21.049 | QP   |
| 2  |      | *    | 0.061     | 51.899   | 31.588  | -59.988    | 111.887  | 20.311 | QP   |


Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)



Page Number: 89 of 171



| Site: AC1  | Time: 2015/10/06 - 19:19 |  |  |  |
|--|--------------------------|--|--|--|
| Limit: FCC_Part15.209_RE(3m)                                       | Engineer: Roy Cheng      |  |  |  |
| Probe: FMZB1519_0.009-30MHz  | Polarity: Face on        |  |  |  |
| EUT: sengled pulse flex  | Power: AC 120V/60Hz      |  |  |  |
| Note: There is the ambient noise within frequency range 9kHz~30MHz |                          |  |  |  |




| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 0.482     | 36.584   | 16.183  | -57.359    | 93.943   | 20.401 | QP   |
| 2  |      | *    | 1.338     | 31.001   | 10.512  | -34.098    | 65.099   | 20.489 | QP   |

Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Page Number: 90 of 171



| Site: AC1   | Time: 2015/10/06 - 21:25 |  |  |  |
|---|--------------------------|--|--|--|
| Limit: FCC_Part15.209_RE(1m)  | Engineer: Roy Cheng      |  |  |  |
| Probe: BBHA9170_18-40GHz  | Polarity: Horizontal     |  |  |  |
| EUT: sengled pulse flex   | Power: AC 120V/60Hz      |  |  |  |
| Note: There is the ambient noise within frequency range 18GHz~40GHz |                          |  |  |  |



| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 24864.000 | 51.836   | 37.061  | -31.664    | 83.500   | 14.775 | PK   |
| 2  |      |      | 24864.088 | 39.225   | 24.450  | -24.275    | 63.500   | 14.775 | AV   |
| 3  |      |      | 26260.988 | 39.469   | 24.050  | -24.031    | 63.500   | 15.419 | AV   |
| 4  |      |      | 26261.000 | 51.956   | 36.537  | -31.544    | 83.500   | 15.419 | PK   |
| 5  |      |      | 33180.000 | 61.461   | 39.940  | -22.039    | 83.500   | 21.521 | PK   |
| 6  |      |      | 33180.361 | 49.061   | 27.540  | -14.439    | 63.500   | 21.521 | AV   |
| 7  |      | *    | 38437.980 | 58.523   | 31.190  | -4.977     | 63.500   | 27.333 | AV   |
| 8  |      |      | 38438.000 | 72.021   | 44.688  | -11.479    | 83.500   | 27.333 | PK   |

Note: Measure Level  $(dB\mu V/m)$  = Reading Level  $(dB\mu V)$  + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) – Pre\_Amplifier Gain (dB)

 $Limit@1m = 20*Log(500uV/m) + 20*Log(3m/1m) = 63.5dB\mu\nu/m \ (Average \ detector), \ and \ 83.5dB\mu\nu/m \ (Peak \ detector).$ 

Page Number: 91 of 171



| Site: AC1   | Time: 2015/10/06 - 21:28 |  |  |  |
|---|--------------------------|--|--|--|
| Limit: FCC_Part15.209_RE(1m)  | Engineer: Roy Cheng      |  |  |  |
| Probe: BBHA9170_18-40GHz  | Polarity: Vertical       |  |  |  |
| EUT: sengled pulse flex   | Power: AC 120V/60Hz      |  |  |  |
| Note: There is the ambient noise within frequency range 18GHz~40GHz |                          |  |  |  |



| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 24886.000 | 52.313   | 37.528  | -31.187    | 83.500   | 14.785 | PK   |
| 2  |      |      | 24886.970 | 39.234   | 24.449  | -24.266    | 63.500   | 14.785 | AV   |
| 3  |      |      | 26503.000 | 53.227   | 37.207  | -30.273    | 83.500   | 16.020 | PK   |
| 4  |      |      | 26503.872 | 39.572   | 23.550  | -23.928    | 63.500   | 16.022 | AV   |
| 5  |      |      | 33213.000 | 62.110   | 40.572  | -21.390    | 83.500   | 21.538 | PK   |
| 6  |      |      | 33213.984 | 49.098   | 27.560  | -14.402    | 63.500   | 21.538 | AV   |
| 7  |      |      | 38900.000 | 72.096   | 44.211  | -11.404    | 83.500   | 27.885 | PK   |
| 8  |      | *    | 38900.755 | 58.705   | 30.820  | -4.795     | 63.500   | 27.885 | AV   |

Note: Measure Level  $(dB\mu V/m)$  = Reading Level  $(dB\mu V)$  + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) – Pre\_Amplifier Gain (dB)

 $Limit@1m = 20*Log(500uV/m) + 20*Log(3m/1m) = 63.5dB\mu\nu/m \ (Average \ detector), \ and \ 83.5dB\mu\nu/m \ (Peak \ detector).$ 



## 7.9. Radiated Restricted Band Edge Measurement

#### 7.9.1. Test Limit

#### For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

| Frequency<br>(MHz)                         | Frequency<br>(MHz)   | Frequency<br>(MHz)           | Frequency<br>(GHz)               |
|--|--|------------------------------|----------------------------------|
|  | (MHz)  16.42 - 16.423  16.69475 - 16.69525  16.80425 - 16.80475  25.5 - 25.67  37.5 - 38.25  73 - 74.6  74.8 - 75.2  108 - 121.94  123 - 138  149.9 - 150.05  156.52475 - 156.525225  156.7 - 156.9  162.0125 - 167.17 |                              |                                  |
| 12.51975 - 12.52025<br>12.57675 - 12.57725 | 167.72 - 173.2<br>240 - 285<br>322 - 335.4   | 3345.8 - 3358<br>3600 - 4400 | 35.43 - 36.5<br>( <sup>2</sup> ) |

### For RSS-Gen Section 8.10 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 8.10 of RSS-Gen, must also comply with the radiated emission limits specified in Section 8.9.

| Frequency<br>(MHz) | Frequency<br>(MHz) | Frequency<br>(GHz) |
|--------------------|--------------------|--------------------|
| 0.009 - 0.110      | 240 - 285          | 9.0 - 9.2          |
| 2.1735 - 2.1905    | 322 - 335.4        | 9.3 - 9.5          |
| 3.020 - 3.026      | 399.9 - 410        | 10.6 - 12.7        |
| 4.125 - 4.128      | 608 - 614          | 13.25 - 13.4       |
| 4.17725 - 4.17775  | 960 - 1427         | 14.47 - 14.5       |
| 4.20725 - 4.20775  | 1435 - 1626.5      | 15.35 - 16.2       |
| 5.677 - 5.683      | 1645.5 - 1646.5    | 17.7 - 21.4        |
| 6.215 - 6.218      | 1660 - 1710        | 22.01 - 23.12      |

FCC ID: 2ABX8SH-000000009 IC:12219A-00000000009

Page Number: 93 of 171



| 6.26775 - 6.26825      | 1718.8 -1722.2 | 23.6 - 24.0  |
|------------------------|----------------|--------------|
| 6.31175 - 6.31225      | 2200 - 2300    | 31.2 - 31.8  |
| 8.291 - 8.294          | 2310 -2390     | 36.43 - 36.5 |
| 8.362 - 8.366          | 2655 - 2900    | Above 38.6   |
| 8.37625 - 8.38675      | 3260 - 3267    |              |
| 8.41425 - 8.41475      | 3332 -3339     |              |
| 12.29 - 12.293         | 334.5 - 3358   |              |
| 12.51975 - 12.52025    | 3500 - 4400    |              |
| 12.57675 - 12.57725    | 4500 - 5150    |              |
| 13.36 -13.41           | 5350 - 5460    |              |
| 16.42 - 16.423         | 7250 - 7750    |              |
| 16.69475 - 16.69525    | 8025 - 8500    |              |
| 16.80425 - 16.80475    |                |              |
| 25.5 - 25.67           |                |              |
| 37.5 - 38.25           |                |              |
| 73 - 74.6              |                |              |
| 74.8 - 75.2            |                |              |
| 108 - 138              |                |              |
| 156.52475 - 156.525225 |                |              |
| 156.7 - 156.9          |                |              |

#### For 15.407(b) requirement:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

Note: Refer to KDB 789033 D02v01 G)2)c), as specified in § 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a maximum emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in § 15.407(b)(4)). However, an out-of-band emission that complies with both the peak and average limits of § 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz maximum emission limit.



Page Number: 94 of 171



All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

| FCC Part 15 Subpart C Paragraph 15.209 |                         |                               |  |  |  |  |  |
|--|-------------------------|-------------------------------|--|--|--|--|--|
| Frequency<br>[MHz]                     | Field Strength<br>[V/m] | Measured Distance<br>[Meters] |  |  |  |  |  |
| 0.009 - 0.490                          | 2400/F (kHz)            | 300                           |  |  |  |  |  |
| 0.490 – 1.705                          | 24000/F (kHz)           | 30                            |  |  |  |  |  |
| 1.705 - 30                             | 30                      | 30                            |  |  |  |  |  |
| 30 - 88                                | 100                     | 3                             |  |  |  |  |  |
| 88 - 216                               | 150                     | 3                             |  |  |  |  |  |
| 216 - 960                              | 200                     | 3                             |  |  |  |  |  |
| Above 960                              | 500                     | 3                             |  |  |  |  |  |





# 7.9.2. Test Result of Radiated Restricted Band Edge

| Site: AC 1  | Time: 2015/09/26 - 15:11 |  |  |
|---|--------------------------|--|--|
| Limit: FCC_Part15.209_RE(3m)                            | Engineer: Lewis Huang    |  |  |
| Probe: BBHA9120D_1-18GHz                                | Polarity: Horizontal     |  |  |
| EUT: sengled pulse flex                                 | Power: AC 120V/60Hz      |  |  |
| Test Mode: Transmit by 802.11a at channel 5180MHz Ant 1 |                          |  |  |

| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 5138.845  | 60.582   | 57.272  | -13.418    | 74.000   | 3.311  | PK   |
| 2  |      |      | 5150.000  | 55.603   | 52.294  | -18.397    | 74.000   | 3.309  | PK   |
| 3  |      | *    | 5179.750  | 101.605  | 98.332  | N/A        | N/A      | 3.273  | PK   |


5110 5115 5120 5125 5130 5135 5140 5145 5150 5155 5160 5165 5170 5175 5180 5185 5190 5195 5200 Frequency(MHz)

Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)






| Site: AC 1  | Time: 2015/09/26 - 15:15 |  |  |  |
|---|--------------------------|--|--|--|
| Limit: FCC_Part15.209_RE(3m)                            | Engineer: Lewis Huang    |  |  |  |
| Probe: BBHA9120D_1-18GHz                                | Polarity: Horizontal     |  |  |  |
| EUT: sengled pulse flex                                 | Power: AC 120V/60Hz      |  |  |  |
| Test Mode: Transmit by 802.11a at channel 5180MHz Ant 1 |                          |  |  |  |




| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 5143.390  | 47.381   | 44.072  | -6.619     | 54.000   | 3.309  | AV   |
| 2  |      |      | 5150.000  | 43.123   | 39.814  | -10.877    | 54.000   | 3.309  | AV   |
| 3  |      | *    | 5179.075  | 88.798   | 85.524  | N/A        | N/A      | 3.274  | AV   |

Note: Measure Level ( $dB\mu V/m$ ) = Reading Level ( $dB\mu V$ ) + Factor (dB)





| Site: AC 1  | Time: 2015/09/26 - 15:16 |  |  |  |
|---|--------------------------|--|--|--|
| Limit: FCC_Part15.209_RE(3m)                            | Engineer: Lewis Huang    |  |  |  |
| Probe: BBHA9120D_1-18GHz                                | Polarity: Vertical       |  |  |  |
| EUT: sengled pulse flex                                 | Power: AC 120V/60Hz      |  |  |  |
| Test Mode: Transmit by 802.11a at channel 5180MHz Ant 1 |                          |  |  |  |



| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 5146.810  | 59.397   | 56.088  | -14.603    | 74.000   | 3.308  | PK   |
| 2  |      |      | 5150.000  | 54.566   | 51.257  | -19.434    | 74.000   | 3.309  | PK   |
| 3  |      | *    | 5179.930  | 99.493   | 96.220  | N/A        | N/A      | 3.273  | PK   |

Note: Measure Level ( $dB\mu V/m$ ) = Reading Level ( $dB\mu V$ ) + Factor (dB)





| Site: AC 1  | Time: 2015/09/26 - 15:18 |  |  |  |  |
|---|--------------------------|--|--|--|--|
| Limit: FCC_Part15.209_RE(3m)                            | Engineer: Lewis Huang    |  |  |  |  |
| Probe: BBHA9120D_1-18GHz                                | Polarity: Vertical       |  |  |  |  |
| EUT: sengled pulse flex                                 | Power: AC 120V/60Hz      |  |  |  |  |
| Test Mode: Transmit by 802.11a at channel 5180MHz Ant 1 |                          |  |  |  |  |

120 (W,Nng) 70 50 40 30

| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 5146.630  | 45.781   | 42.472  | -8.219     | 54.000   | 3.309  | AV   |
| 2  |      |      | 5150.000  | 41.968   | 38.659  | -12.032    | 54.000   | 3.309  | AV   |
| 3  |      | *    | 5181.145  | 86.326   | 83.054  | N/A        | N/A      | 3.272  | AV   |

Frequency(MHz)

5150 5155 5160 5165 5170 5175 5180 5185 5190

Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m).

5110 5115 5120 5125 5130 5135 5140 5145





| Site: AC 1  | Time: 2015/09/26 - 15:18 |  |  |  |  |
|---|--------------------------|--|--|--|--|
| Limit: FCC_Part15.209_RE(3m)                            | Engineer: Lewis Huang    |  |  |  |  |
| Probe: BBHA9120D_1-18GHz                                | Polarity: Horizontal     |  |  |  |  |
| EUT: sengled pulse flex                                 | Power: AC 120V/60Hz      |  |  |  |  |
| Test Mode: Transmit by 802.11a at channel 5745MHz Ant 1 |                          |  |  |  |  |

Level(dBuV/m) MANUAL PROPERTY 5760 5765

| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 5709.053  | 59.948   | 56.205  | -14.052    | 74.000   | 3.743  | PK   |
| 2  |      |      | 5715.000  | 55.459   | 51.698  | -18.541    | 74.000   | 3.761  | PK   |
| 3  |      |      | 5724.635  | 62.018   | 58.228  | -16.182    | 78.200   | 3.790  | PK   |
| 4  |      |      | 5725.000  | 59.666   | 55.875  | -18.534    | 78.200   | 3.791  | PK   |
| 5  |      | *    | 5744.875  | 98.131   | 94.279  | N/A        | N/A      | 3.853  | PK   |

Frequency(MHz)

Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)





| Site: AC 1  | Time: 2015/09/26 - 15:20 |  |  |  |  |
|---|--------------------------|--|--|--|--|
| Limit: FCC_Part15.209_RE(3m)                            | Engineer: Lewis Huang    |  |  |  |  |
| Probe: BBHA9120D_1-18GHz                                | Polarity: Horizontal     |  |  |  |  |
| EUT: sengled pulse flex                                 | Power: AC 120V/60Hz      |  |  |  |  |
| Test Mode: Transmit by 802.11a at channel 5745MHz Ant 1 |                          |  |  |  |  |



| No | Flag | Mark | Frequency | Measure  | Reading | Over Limit | Limit    | Factor | Туре |
|----|------|------|-----------|----------|---------|------------|----------|--------|------|
|    |      |      | (MHz)     | Level    | Level   | (dB)       | (dBuV/m) | (dB)   |      |
|    |      |      |           | (dBuV/m) | (dBuV)  |            |          |        |      |
| 1  |      |      | 5667.135  | 46.267   | 42.610  | -7.733     | 54.000   | 3.656  | AV   |
| 2  |      |      | 5715.000  | 41.638   | 37.877  | -12.362    | 54.000   | 3.761  | AV   |
| 3  |      | *    | 5746.715  | 85.694   | 81.835  | N/A        | N/A      | 3.859  | AV   |

Note: Measure Level ( $dB\mu V/m$ ) = Reading Level ( $dB\mu V$ ) + Factor (dB)