

MRT Technology (Suzhou) Co., Ltd

Phone: +86-512-66308358 Fax: +86-512-66308368 www.mrt-cert.com

Report No.: 1509RSU02903 Report Version: Issue Date: 10-15-2015

RF Exposure Evaluation Declaration

FCC ID: 2ABX8SH-000000012

Zhejiang shenghui lighting Co., Ltd. Shanghai Branch APPLICANT:

Application Type: Certification

Product: sengled pulse flex

C02-BR30NAE26 Model No.:

Brand Name: sengled

FCC Classification: Digital Transmission System (DTS)

Unlicensed National Information Infrastructure (UNII)

Reviewed By : Robin Wu)

Approved By : Marlinchen (Marlin Chen)





The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

FCC ID: 2ABX8SH-000000012 Page Number: 1 of 5





Revision History

Report No.	Version	Description	Issue Date
1509RSU02903	Rev. 01	Initial report	10-15-2015



1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	sengled pulse flex
Model No.	C02-BR30NAE26
Brand Name	sengled
Wi-Fi Specification	802.11a/b/g/n
Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462 MHz
	802.11n-HT40: 2422 ~ 2452 MHz
	802.11a/n-HT20: 5180~5240MHz, 5745~5825MHz
	802.11n-HT40: 5190~5230MHz, 5755~5795MHz

1.2. Description of Available Antennas

Antenna No.	Antenna Type	Frequency Band	Manufacturer	Max
		(GHz)		Peak Gain (dBi)
		2412~2462		4.04
Ant 1	PCB Antenna	5180~5240	Zhejiang	4.00
		5745~5825	shenghui lighting	4.53
		2412~2462	Co., Ltd.	4.43
Ant 2	PCB Antenna	5180~5240	Shanghai Branch	3.34
		5745~5825		5.87



2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm ²)	(Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500			f/1500	6
1500-100,000			1	30

f= Frequency in MHz

Calculation Formula: Pd = (Pout*G)/(4*p

8G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

FCC ID: 2ABX8SH-000000012 Page Number: 4 of 5





2.2. Test Result of RF Exposure Evaluation

Product	sengled pulse flex
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to Section 1.2.

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density at $R = 20 \text{ cm}$ (mW/cm^2)	Limit (mW/cm²)
802.11b/g/n	2412 ~ 2462	15.10	0.0179	1
802.11an	5180 ~ 5240	11.39	0.0069	1
	5745 ~ 5825	9.26	0.0065	1

CONCULISON:

The Max Power Density at R $(20 \text{ cm}) = 0.0179 \text{mW/cm}^2 < 1 \text{mW/cm}^2$. So the EUT complies with the requirement.

The End