



MRT Technology (Suzhou) Co., Ltd
Phone: +86-512-66308358
Fax: +86-512-66308368
Web: www.mrt-cert.com

Report No.: 1601RSU00304
Report Version: V01
Issue Date: 01-14-2016

RF Exposure Evaluation Declaration

FCC ID: 2ABX8SH-000000013

APPLICANT: Zhejiang shenghui lighting Co., Ltd. Shanghai Branch

Application Type: Certification

Product: Pulse Link

Model No.: C01-BR30NA LINK

Brand Name: sengled

FCC Classification: FCC Part 15 Spread Spectrum Transmitter(DSS)

Unlicensed National Information Infrastructure (UNII)

Reviewed By : Robin Wu
(Robin Wu)



Approved By : Marlinchen
(Marlin Chen)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date
1601RSU00304	Rev. 01	Initial report	01-14-2016

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	Pulse Link
Model No.	C01-BR30NA LINK
Frequency Range	Buletooth: 2402~2480MHz Wireless: 5150~5250MHz, 5725~5850MHz
Type of Modulation	Buletooth: 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK) Wireless: QPSK

1.2. Antenna Description

Antenna No.	Antenna Type	Frequency Band (MHz)	Manufacturer	Tx Paths	Max Peak Gain (dBi)
Bluetooth Antenna					
Antenna	PCB Antenna	2402 ~ 2480	Zhejiang shenghui lighting Co., Ltd. Shanghai Branch	1	3.1
Wireless Antenna					
Antenna A	PCB Antenna	5180 ~ 5240	SMSC Inc.	1	3.0
		5736 ~ 5814		1	3.2
Antenna B	PCB Antenna	5180 ~ 5240	SMSC Inc.	1	3.0
		5736 ~ 5814		1	3.2

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	Pulse Link
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to Clause 1.2 of antenna description.

Test Mode	Frequency Band (MHz)	Maximum Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
Bluetooth	2402 ~ 2480	0.44	0.0004	1
Wireless	5180 ~ 5240	9.46	0.0035	1
	5736 ~ 5814	13.18	0.0086	1

CONCLUSION:

Both of the Bluetooth 2.4GHz and Wireless 5GHz can transmit simultaneously. Therefore, the Max Power Density at R (20 cm) = 0.0004mW/cm² + 0.0086mW/cm² = 0.0090mW/cm² < 1mW/cm². So the EUT complies with the requirement.

The End