

#01_Bluetooth_LE_Front_0mm_Ch39

Communication System: Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:3.195

Medium: HSL_2450_210903 Medium parameters used: $f = 2480$ MHz; $\sigma = 1.886$ S/m; $\epsilon_r = 38.92$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3728; ConvF(7.36, 7.36, 7.36) @ 2480 MHz; Calibrated: 2021/2/23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2021/5/21
- Phantom: SAM_Left; Type: QD000P40CD; Serial: TP:1682
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (61x71x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.289 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.318 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.281 W/kg

SAR(1 g) = 0.119 W/kg; SAR(10 g) = 0.046 W/kg

Maximum value of SAR (measured) = 0.208 W/kg

