



# TEST REPORT

**APPLICANT** : Adam Elements International Co., LTD.

**PRODUCT NAME** : Magnetic Tripod Selfie Stick

**MODEL NAME** : SELFIE III

**BRAND NAME** : ADAM elements

**FCC ID** : 2ABY9SELFIE-III

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**RECEIPT DATE** : 2025-08-21

**TEST DATE** : 2025-08-22 to 2025-08-29

**ISSUE DATE** : 2025-09-22

Edited by:

Zeng Xiaoying  
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng  
Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





## DIRECTORY

<b>1. Summary of Test Result</b>	<b>4</b>
<b>1.1. Testing Applied Standards</b>	<b>5</b>
<b>1.2. Test Equipment List</b>	<b>6</b>
<b>1.3. Measurement Uncertainty</b>	<b>8</b>
<b>1.4. Testing Laboratory</b>	<b>8</b>
<b>2. General Description</b>	<b>9</b>
<b>2.1. Information of Applicant and Manufacturer</b>	<b>9</b>
<b>2.2. Information of EUT</b>	<b>9</b>
<b>2.3. Channel List of EUT</b>	<b>10</b>
<b>2.4. Test Configuration of EUT</b>	<b>11</b>
<b>2.5. Test Conditions</b>	<b>11</b>
<b>2.6. Test Setup Layout Diagram</b>	<b>11</b>
<b>3. Test Results</b>	<b>14</b>
<b>3.1. Antenna Requirement</b>	<b>14</b>
<b>3.2. Duty Cycle of Test Signal</b>	<b>15</b>
<b>3.3. Maximum Peak Conducted Output Power</b>	<b>16</b>
<b>3.4. Maximum Average Conducted Output Power</b>	<b>17</b>
<b>3.5. 6 dB Bandwidth</b>	<b>18</b>
<b>3.6. Conducted Spurious Emissions and Band Edge</b>	<b>19</b>
<b>3.7. Power Spectral Density</b>	<b>20</b>
<b>3.8. Conducted Emission</b>	<b>21</b>
<b>3.9. Restricted Frequency Bands</b>	<b>22</b>
<b>3.10. Radiated Emission</b>	<b>23</b>
<b>Annex A Test Data and Result</b>	<b>25</b>



Change History		
Version	Date	Reason for change
1.0	2025-09-22	First edition



# 1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Aug. 22, 2025	Li Xinpeng	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Aug. 22, 2025	Li Xinpeng	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Aug. 22, 2025	Li Xinpeng	PASS	/
5	15.247(a)	Bandwidth	Aug. 22, 2025	Li Xinpeng	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Aug. 22, 2025	Li Xinpeng	PASS	/
7	15.247(e)	Power Spectral Density	Aug. 22, 2025	Li Xinpeng	PASS	/
8	15.207	Conducted Emission	Aug. 25, 2025	Wang Yapeng	PASS	/
9	15.247(d)	Restricted Frequency Bands	Aug. 25, 2025	Wang Deyong	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Aug. 23, 2025	Wang Deyong	PASS	/

**Note 1:** Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

**Note 2:** The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

**Note 3:** Any additions, deviation, or exclusions from the method shall be noted in the "Remark".



REPORT No.: SZ25080332W01

## 1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



## 1.2. Test Equipment List

### 1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

### 1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2025.05.15	2026.05.14
LISN	103131	ENV 216	R&S	2025.03.20	2026.03.19
RF Coaxial Cable (DC-100MHz)	EMC-CE-00514	N/A	N/A	2025.05.06	2026.05.05

### 1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-274	VULB 9163	Schwarzbeck	2025.06.28	2026.06.27
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna - Horn	01774	BBHA 9120D	Schwarzbeck	2025.06.20	2026.06.19
Test Antenna - Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2025.06.20	2026.06.19
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.09.11	2025.09.10
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.06.21	2028.06.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29



## 1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	±2.22dB	Confidence levels of 95%
Power Spectral Density	±2.22dB	Confidence levels of 95%
Bandwidth	±5%	Confidence levels of 95%
Conducted Spurious Emission	±2.77dB	Confidence levels of 95%
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

## 1.4. Testing Laboratory

<b>Laboratory Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Laboratory Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525
<b>FCC Designation Number:</b>	CN1192
<b>FCC Test Firm Registration Number:</b>	226174



## 2. General Description

### 2.1. Information of Applicant and Manufacturer

<b>Applicant:</b>	Adam Elements International Co., LTD.
<b>Applicant Address:</b>	8F.-5, No. 148, Sec. 4, Zhongxiao E. Rd., Da'an Dist., Taipei City 106, Taiwan
<b>Manufacturer:</b>	Adam Elements International Co., LTD.
<b>Manufacturer Address:</b>	8F.-5, No. 148, Sec. 4, Zhongxiao E. Rd., Da'an Dist., Taipei City 106, Taiwan

### 2.2. Information of EUT

<b>Product Name:</b>	Magnetic Tripod Selfie Stick
<b>Sample No.:</b>	2#, 3#
<b>Hardware Version:</b>	V1.0
<b>Software Version:</b>	V1.0
<b>Equipment Type:</b>	Bluetooth LE
<b>Bluetooth Version:</b>	5.0
<b>Modulation Type:</b>	GFSK
<b>Data Rate:</b>	1Mbps
<b>Operating Frequency Range:</b>	2402MHz-2480MHz
<b>Antenna Type:</b>	PCB Antenna
<b>Antenna Gain:</b>	2.30dBi

**Note 1:** The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



## 2.3. Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	<b>2402</b>	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	<b>19</b>	<b>2440</b>	29	2460	<b>39</b>	<b>2480</b>

**Note 1:** The black bold channels were selected for test.

## 2.4. Test Configuration of EUT


The EUT is controlled by dedicated software to transmit at the default maximum power level.

## 2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

## 2.6. Test Setup Layout Diagram

### 2.6.1. Conducted Measurement




### 2.6.2. Conducted Emission Measurement




### 2.6.3.Radiation Measurement


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to1GHz



## 3) For radiated emissions above 1GHz





## 3. Test Results

### 3.1. Antenna Requirement

#### 3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
<input checked="" type="checkbox"/> Internal <input type="checkbox"/> External	<input type="checkbox"/> FPC Antenna <input type="checkbox"/> Spring Antenna <input type="checkbox"/> Ceramic Antenna <input type="checkbox"/> Integrated Antenna <input type="checkbox"/> Dipole Antenna <input checked="" type="checkbox"/> PCB Antenna <input type="checkbox"/> PIFA Antenna <input type="checkbox"/> Monopole Antenna	<input type="checkbox"/> I-PEX Connector <input type="checkbox"/> SMA Connector <input type="checkbox"/> RP-SMA Connector <input type="checkbox"/> Metal Shrapnel <input checked="" type="checkbox"/> Layout



## 3.2. Duty Cycle of Test Signal

### 3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration( $T$ ) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed  $T$  at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle ( $D$ ). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be non constant.

### 3.2.2. Test Result

Refer to Annex A.1 in this report.



### 3.3. Maximum Peak Conducted Output Power

#### 3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

#### 3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

#### 3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

#### 3.3.4. Test Result

Refer to Annex A.2 in this report.



## 3.4. Maximum Average Conducted Output Power

### 3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

### 3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

### 3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.4.4. Test Result

Refer to Annex A.3 in this report.



## 3.5.6 dB Bandwidth

### 3.5.1. Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.5.1. Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.

### 3.5.2. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.5.3. Test Result

Refer to Annex A.4 in this report.



## 3.6. Conducted Spurious Emissions and Band Edge

### 3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

### 3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



## 3.7. Power Spectral Density

### 3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

### 3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.7.4. Test Result

Refer to Annex A.7 in this report.



## 3.8. Conducted Emission

### 3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

### 3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

### 3.8.4. Test Result

Refer to Annex A.8 in this report.



## 3.9. Restricted Frequency Bands

### 3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 kHz for  $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

### 3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

### 3.9.4. Test Result

Refer to Annex A.9 in this report.



## 3.10. Radiated Emission

### 3.10.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

**Note1:** For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

**Note2:** For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



### 3.10.2. Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

### 3.10.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

### 3.10.4. Test Result


Refer to Annex A.10 in this report.



## Annex A Test Data and Result


### A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	61.12	2.14	2.62
NVNT	BLE 1M	2440	Ant1	61.12	2.14	2.62
NVNT	BLE 1M	2480	Ant1	61.07	2.14	2.62





REPORT No.: SZ25080332W01




MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn


**A.2. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-2.62	0	-2.62	0.00055	30	Pass
NVNT	BLE 1M	2440	Ant1	-2.27	0	-2.27	0.00059	30	Pass
NVNT	BLE 1M	2480	Ant1	-1.86	0	-1.86	0.00065	30	Pass





REPORT No.: SZ25080332W01




MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn


**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-5.29	2.14	-3.15	0.00048	30	Pass
NVNT	BLE 1M	2440	Ant1	-4.8	2.14	-2.66	0.00054	30	Pass
NVNT	BLE 1M	2480	Ant1	-4.56	2.14	-2.42	0.00057	30	Pass





REPORT No.: SZ25080332W01




MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555      Fax: 86-755-36698525  
Http://www.morlab.cn      E-mail: service@morlab.cn


**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.697	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.6757	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.6885	0.5	Pass





REPORT No.: SZ25080332W01



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Fax: 86-755-36698525


[Http://www.morlab.cn](http://www.morlab.cn)


E-mail: [service@morlab.cn](mailto:service@morlab.cn)



### A.5. Conducted Spurious Emissions


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-35.65	-20	Pass
NVNT	BLE 1M	2440	Ant1	-36.84	-20	Pass
NVNT	BLE 1M	2480	Ant1	-33.97	-20	Pass







REPORT No.: SZ25080332W01



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn



REPORT No.: SZ25080332W01


#### A.6. Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-27.84	-20	Pass
NVNT	BLE 1M	2480	Ant1	-40.81	-20	Pass

**MORLAB**

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555      Fax: 86-755-36698525  
Http://www.morlab.cn      E-mail: service@morlab.cn









### A.7. Power Spectral Density

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-18.07	0	-18.07	8	Pass
NVNT	BLE 1M	2440	Ant1	-17.74	0	-17.74	8	Pass
NVNT	BLE 1M	2480	Ant1	-17.29	0	-17.29	8	Pass





REPORT No.: SZ25080332W01



MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn



## A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

### A. Test Setup:

Test Mode: EUT+PC+PC Adapter+Serial port board+BLE TX


Test voltage: AC 120V/60Hz

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}] = U_R + L_{\text{Cable loss}} [\text{dB}] + A_{\text{Factor}}$$


$U_R$ : Receiver Reading

$A_{\text{Factor}}$ : Voltage division factor of LISN

**B. Test Plot:**


(L Phase)

No.	Fre. (MHz)	Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1590	51.23	36.59	65.52	55.52	Line	PASS
2	0.1680	48.22	33.26	65.06	55.06		PASS
3	0.4650	34.54	27.63	56.60	46.60		PASS
4	1.2930	32.43	24.83	56.00	46.00		PASS
5	2.5438	33.24	25.47	56.00	46.00		PASS
6	3.9301	29.97	21.21	56.00	46.00		PASS



(N Phase)


No.	Fre. (MHz)	Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1545	52.97	36.29	65.75	36.29	Neutral	PASS
2	0.2625	37.91	26.71	61.35	26.71		PASS
3	0.6361	32.32	23.67	56.00	23.67		PASS
4	2.1797	36.58	27.66	56.00	27.66		PASS
5	3.8085	32.75	23.47	56.00	23.47		PASS
6	16.7051	26.34	20.17	60.00	20.17		PASS

### A.9. Restricted Frequency Bands

**Note:** Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Vertical) was recorded in this test report.

#### 1Mbps

Plot for Channel 0




Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Verdict
2334.79	9.0	46.32	37.320	54.00	7.68	151	AV	PASS
2346.81	21.2	58.62	37.420	74.00	15.38	346	PK	PASS
2356.76	8.7	46.16	37.460	54.00	7.84	351	AV	PASS
2376.72	21.3	58.76	37.480	74.00	15.24	198	PK	PASS
2377.75	9.7	47.20	37.480	54.00	6.80	136	AV	PASS
2386.30	21.2	58.71	37.490	74.00	15.29	312	PK	PASS



REPORT No.: SZ25080332W01

Plot for Channel 39



Frequency [MHz]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Factor [dB/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Angle [°]	Detector	Verdict
2486.51	8.4	46.69	38.270	54.00	7.31	256	AV	PASS
2489.12	21.3	59.56	38.260	74.00	14.44	146	PK	PASS
2491.74	8.4	46.65	38.260	54.00	7.35	80	AV	PASS
2494.31	21.1	59.32	38.260	74.00	14.68	246	PK	PASS
2495.65	8.5	46.75	38.260	54.00	7.25	5	AV	PASS
2497.77	20.7	58.96	38.250	74.00	15.04	265	PK	PASS

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn



## A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [dB\mu V/m] = U_R + A_T + A_{Factor} [dB]; A_T = L_{Cable\ loss} [dB] - G_{preamp} [dB]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{preamp}$ : Preamplifier Gain

$A_{Factor}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{Factor}$  were built in test software.

**Note1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


**Note2:** For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note3:** For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note 4:** All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.


**1Mbps**

Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
35.8258	31.15	-36.91	40.00	8.85	150	204	Horizontal	PASS
62.0420	25.52	-29.99	40.00	14.48	150	269	Horizontal	PASS
129.0390	31.22	-32.25	43.50	12.28	150	277	Horizontal	PASS
185.3554	37.61	-32.56	43.50	5.89	150	182	Horizontal	PASS
260.1201	34.27	-29.95	46.00	11.73	150	262	Horizontal	PASS
532.9630	35.33	-23.86	46.00	10.67	150	262	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1105.4211	40.14	-24.48	74.00	33.86	150	287	Horizontal	PASS
1391.0782	38.47	-24.78	74.00	35.53	150	345	Horizontal	PASS
2503.1006	38.31	-19.54	74.00	35.69	150	270	Horizontal	PASS
5730.3461	47.59	-7.05	74.00	26.41	150	169	Horizontal	PASS
8597.1194	41.62	-1.39	74.00	32.38	150	35	Horizontal	PASS
13613.1226	47.17	6.93	74.00	26.83	150	278	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)


Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
35.8258	33.58	-36.91	40.00	6.42	150	91	Vertical	PASS
87.2873	28.86	-33.84	40.00	11.14	150	32	Vertical	PASS
128.0681	29.22	-32.12	43.50	14.28	150	98	Vertical	PASS
220.3103	29.70	-31.39	46.00	16.30	150	193	Vertical	PASS
312.5526	31.44	-29.20	46.00	14.56	150	280	Vertical	PASS
531.0210	32.53	-23.71	46.00	13.47	150	294	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)


Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1941.9884	40.11	-22.38	74.00	33.89	150	267	Vertical	PASS
3196.8394	41.33	-17.21	74.00	32.67	150	217	Vertical	PASS
4801.9604	48.15	-10.56	74.00	25.85	150	133	Vertical	PASS
5958.1916	46.93	-6.48	74.00	27.07	150	133	Vertical	PASS
11025.2050	43.43	2.80	74.00	30.57	150	301	Vertical	PASS
13045.2090	45.36	6.44	74.00	28.64	150	107	Vertical	PASS

## Plot for Channel 19




(Antenna Horizontal, 30MHz to 1GHz)

Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
35.8258	31.09	-36.91	40.00	8.91	150	39	Horizontal	PASS
128.0681	34.35	-32.12	43.50	9.15	150	105	Horizontal	PASS
187.2973	37.10	-32.85	43.50	6.40	150	309	Horizontal	PASS
260.1201	34.24	-29.95	46.00	11.76	150	265	Horizontal	PASS
531.9920	34.27	-23.79	46.00	11.73	150	258	Horizontal	PASS
982.5225	36.15	-18.09	54.00	17.85	150	345	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1061.2122	40.25	-24.57	74.00	33.75	150	236	Horizontal	PASS
1965.7932	39.74	-22.23	74.00	34.26	150	286	Horizontal	PASS
3190.0380	40.91	-17.27	74.00	33.09	150	144	Horizontal	PASS
5771.1542	47.57	-7.41	74.00	26.43	150	94	Horizontal	PASS
10413.0826	42.21	2.45	74.00	31.79	150	177	Horizontal	PASS
13749.1498	46.42	7.22	74.00	27.58	150	303	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)


Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
35.8258	33.18	-36.91	40.00	6.82	150	81	Vertical	PASS
55.2452	26.52	-28.97	40.00	13.48	150	226	Vertical	PASS
103.7938	29.78	-30.69	43.50	13.72	150	197	Vertical	PASS
126.1261	29.97	-32.70	43.50	13.53	150	103	Vertical	PASS
312.5526	32.72	-29.20	46.00	13.28	150	299	Vertical	PASS
531.0210	31.64	-23.71	46.00	14.36	150	103	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)


Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1268.6537	38.35	-24.69	74.00	35.65	150	18	Vertical	PASS
2125.6251	41.51	-20.27	74.00	32.49	150	161	Vertical	PASS
3067.6135	42.20	-17.14	74.00	31.80	150	345	Vertical	PASS
5873.1746	46.86	-6.97	74.00	27.14	150	253	Vertical	PASS
9301.0602	41.76	1.40	74.00	32.24	150	77	Vertical	PASS
13630.1260	46.14	5.99	74.00	27.86	150	26	Vertical	PASS

## Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
35.8258	31.19	-36.91	40.00	8.81	150	2	Horizontal	PASS
64.9550	25.90	-30.25	40.00	14.10	150	277	Horizontal	PASS
187.2973	37.43	-32.85	43.50	6.07	150	2	Horizontal	PASS
312.5526	35.43	-29.20	46.00	10.57	150	132	Horizontal	PASS
531.9920	32.65	-23.79	46.00	13.35	150	270	Horizontal	PASS
981.5516	34.99	-18.11	54.00	19.01	150	335	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1105.4211	41.08	-24.48	74.00	32.92	150	345	Horizontal	PASS
1965.7932	39.86	-22.23	74.00	34.14	150	283	Horizontal	PASS
2503.1006	42.98	-19.54	74.00	31.02	150	266	Horizontal	PASS
4958.3917	46.99	-9.61	74.00	27.01	150	325	Horizontal	PASS
9297.6595	42.44	1.38	74.00	31.56	150	232	Horizontal	PASS
13749.1498	46.02	7.22	74.00	27.98	150	56	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)

Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
35.8258	33.53	-36.91	40.00	6.47	150	133	Vertical	PASS
87.2873	31.69	-33.84	40.00	8.31	150	351	Vertical	PASS
132.9229	29.09	-32.93	43.50	14.41	150	18	Vertical	PASS
312.5526	30.70	-29.20	46.00	15.30	150	293	Vertical	PASS
531.0210	30.92	-23.71	46.00	15.08	150	293	Vertical	PASS
979.6096	36.94	-18.10	54.00	17.06	150	300	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)

Freq. [MHz]	Level [dB $\mu$ V/m]	Factor [dB]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1122.4245	39.62	-24.44	74.00	34.38	150	284	Vertical	PASS
2125.6251	42.21	-20.27	74.00	31.79	150	250	Vertical	PASS
4954.9910	47.02	-9.56	74.00	26.98	150	141	Vertical	PASS
5747.3495	47.46	-6.77	74.00	26.54	150	90	Vertical	PASS
9607.1214	41.96	0.98	74.00	32.04	150	342	Vertical	PASS
13052.0104	45.59	6.46	74.00	28.41	150	225	Vertical	PASS

————— END OF REPORT —————