



FCC RADIO TEST REPORT

FCC ID : 2ABZ2-EE149
Equipment : Smart Phone
Brand Name : ONEPLUS
Model Name : IN2019
Applicant : OnePlus Technology (Shenzhen) Co., Ltd
18C02, 18C03, 18C04 and 18C05, Shum Yip
Terra Building, Binhe Avenue North, Futian
District, Shenzhen
Manufacturer : OnePlus Technology (Shenzhen) Co., Ltd
18C02, 18C03, 18C04 and 18C05, Shum Yip
Terra Building, Binhe Avenue North, Futian
District, Shenzhen
Standard : 47 CFR Part 2, 22(H), 24(E), 27(L)

The product was received on Jan. 03, 2020 and testing was started from Jan. 12, 2020 and completed on Feb. 14, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	6
1.1 Product Feature of Equipment Under Test	6
1.2 Modification of EUT	6
1.3 Testing Location	7
1.4 Applicable Standards	8
2 Test Configuration of Equipment Under Test	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration	10
2.4 Measurement Results Explanation Example	10
2.5 Frequency List of Low/Middle/High Channels	11
3 Conducted Test Result	12
3.1 Measuring Instruments.....	12
3.2 Conducted Output Power and ERP/EIRP	13
3.3 Peak-to-Average Ratio	14
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	15
3.5 Conducted Band Edge	16
3.6 Conducted Spurious Emission	17
3.7 Frequency Stability	18
4 Radiated Test Items	19
4.1 Measuring Instruments.....	19
4.2 Test Setup	19
4.3 Test Result of Radiated Test.....	20
4.4 Field Strength of Spurious Radiation Measurement	21
5 List of Measuring Equipment.....	22
6 Uncertainty of Evaluation	24
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of ERP/EIRP and Radiated Test	
Appendix C. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FG9D0701A	01	Initial issue of report	Mar. 09, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Pass	-
	§22.913 (a)(2)	Effective Radiated Power (GSM850) (WCDMA Band V)		
	§24.232 (c)	Equivalent Isotropic Radiated Power (GSM1900) (WCDMA Band II)		
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power (WCDMA Band IV)		
3.3	§24.232 (d)	Peak-to-Average Ratio	Pass	
3.4	§2.1049 §22.917 (b) §24.238 (b) §27.53 (g)	Occupied Bandwidth (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	-
3.5	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Band Edge Measurement (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	-
3.6	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Conducted Emission (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	-
3.7	§2.1055 §22.355 §24.235 §27.54	Frequency Stability Temperature & Voltage	Pass	-
4.4	§2.1053 §22.917 (a) §24.238 (a) §27.53 (h)	Field Strength of Spurious Radiation (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	Under limit 25.17 dB at 2472.000 MHz for Lower Antenna Under limit 20.30 dB at 2472.000 MHz for Upper Antenna



Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Vivian Hsu

1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE/5G NR, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC, and GNSS.

Product Specification subjective to this standard	
Antenna Type	WWAN: Loop / IFA Antenna WLAN 2.4GHz: <Ant. 1> Couple Loop Antenna <Ant. 2> Monopole Antenna WLAN 5GHz: <Ant. 1> Couple Loop Antenna <Ant. 2> Loop Antenna Bluetooth: Couple Loop Antenna GPS / Glonass / BDS / Galileo / SBAS: Couple Loop Antenna NFC: Coil Antenna

<WWAN Antenna Information>

Antenna	GSM	WCDMA	LTE	5GNR
Ant. 0	850	V	5,8,12,13,17,26,71	n5
Ant. 1	850	V	5,8,12,13,17,26,66,71	n5
Ant. 2	1900	II, IV	2,4,25,66,7,30,41	n2,n66
Ant. 3	1900	II, IV	2,4,25,66,7,30,41,48	n2,n66
Ant. 6	-	-	48	-

Remark: In this test report, Upper Antenna means Ant. 0, Ant. 3, and Ant. 6 and Lower Antenna means Ant. 1, and Ant. 2. The detailed antenna information please reference declaration of antenna report by manufacturer.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.



1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY
Test Engineer	Louis Chung
Temperature	21~24℃
Relative Humidity	51-55%

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH13-HY
Test Engineer	Jimmy Chung 、Karl Hou 、Wilson Wu
Temperature	21.5~23.5℃
Relative Humidity	49.5~55.5%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Lower Antenna: X Plane with Adapter for Cellular Band, X Plane with Earphone for PCS Band, Y Plane for AWS Band; Upper Antenna: Y Plane for Cellular Band and AWS Band, Z Plane for PCS Band) were recorded in this report.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V
2. 30 MHz to 18000 MHz for WCDMA Band IV
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II


All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM850	■ GPRS Class 8 Link ■ EDGE Class 8 Link	■ GPRS Class 8 Link ■ EDGE Class 8 Link
GSM1900	■ GPRS Class 8 Link ■ EDGE Class 8 Link	■ GPRS Class 8 Link ■ EDGE Class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Remark: All the radiated test cases were performed with Adapter 3 and USB Cable 1.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example:

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. Set EUT to transmit at maximum output power.
3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
5. Record the maximum PAPR level associated with a probability of 0.1%.

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.7 Frequency Stability

3.7.1 Description of Frequency Stability Measurement

22.355

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

24.235 & 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated emissions below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 06, 2019	Jan. 12, 2020~ Jan. 13, 2020	Mar. 05, 2020	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 04, 2019	Jan. 12, 2020~ Jan. 13, 2020	Sep. 03, 2020	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Nov. 26, 2019	Jan. 12, 2020~ Jan. 13, 2020	Nov. 25, 2020	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~4A	Oct. 09, 2019	Jan. 12, 2020~ Jan. 13, 2020	Oct. 08, 2020	Conducted (TH03-HY)
Base Station(Measur e)	Rohde & Schwarz	CMU200	117995	GSM / GPRS / WCDMA / CDMA	Aug. 23, 2019	Jan. 12, 2020~ Jan. 13, 2020	Aug. 22, 2020	Conducted (TH03-HY)
Power Divider	Warison	WCOU-0.4-26.5S-20	#A	N/A	Nov. 06, 2019	Jan. 12, 2020~ Jan. 13, 2020	Nov. 05, 2020	Conducted (TH03-HY)
Amplifier	Sonoma-Instru ment	310 N	187282	9KHz~1GHz	Dec. 17, 2019	Jan. 13, 2020~ Feb. 14, 2020	Dec. 16, 2020	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	40103&07	30MHz to 1GHz	Apr. 30, 2019	Jan. 13, 2020~ Feb. 14, 2020	Apr. 29, 2020	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	41912 & 05	30MHz to 1GHz	Feb. 09, 2020	Jan. 13, 2020~ Feb. 14, 2020	Feb. 08, 2021	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jul. 02, 2019	Jan. 13, 2020~ Feb. 14, 2020	Jul. 01, 2020	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1212	1GHz ~ 18GHz	May 14, 2019	Jan. 13, 2020~ Feb. 14, 2020	May 13, 2020	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 20, 2019	Jan. 13, 2020~ Feb. 14, 2020	May 19, 2020	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Mar. 15, 2019	Jan. 13, 2020~ Feb. 14, 2020	Mar. 14, 2020	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 19, 2019	Jan. 13, 2020~ Feb. 14, 2020	Mar. 18, 2020	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jan. 13, 2020~ Feb. 14, 2020	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jan. 13, 2020~ Feb. 14, 2020	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jan. 13, 2020~ Feb. 14, 2020	N/A	Radiation (03CH13-HY)
Software	Audix	E3 6.2009-8-24	RK-000992	N/A	N/A	Jan. 13, 2020~ Feb. 14, 2020	N/A	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Jan. 13, 2020~ Feb. 14, 2020	Dec. 12, 2020	Radiation (03CH13-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
RF Cable	HUBER + SUHNER	SF102/2*11SK 252	MY4278/2	9kHz~40GHz	May. 16, 2019	Jan. 13, 2020~ Feb. 14, 2020	May. 15, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30M-18G	Feb. 26, 2019	Jan. 13, 2020~ Feb. 14, 2020	Feb. 25, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30M~40GHz	Feb. 26, 2019	Jan. 13, 2020~ Feb. 14, 2020	Feb. 25, 2020	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917058 4	18GHz- 40GHz	Dec. 10, 2019	Jan. 13, 2020~ Feb. 14, 2020	Dec. 09, 2020	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917057 6	18GHz~40GHz	May 14, 2019	Jan. 13, 2020~ Feb. 14, 2020	May 13, 2020	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-2700 -3000-18000-6 OSS	SN2	3GHz High Pass Filter	Jul. 14, 2019	Jan. 13, 2020~ Feb. 14, 2020	Jul. 13, 2020	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-1080 -1200-15000-6 OSS	SN3	1.2GHz High Pass Filter	Jul. 03, 2019	Jan. 13, 2020~ Feb. 14, 2020	Jul. 02, 2020	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303B	TP157151	N/A	Jun. 17, 2019	Jan. 13, 2020~ Feb. 14, 2020	Jun. 16, 2020	Radiation (03CH13-HY)

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.21
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.24
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.99
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

<For Lower Antenna>

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	32.76	33.04	33.26	26.76	27.32	27.85
GPRS class 8	32.80	33.11	33.28	26.78	27.35	27.88
GPRS class 10	30.65	30.84	30.95	25.28	25.19	25.52
GPRS class 11	28.97	29.54	29.58	22.67	23.78	24.29
GPRS class 12	27.67	28.20	28.34	23.53	22.77	23.36
EGPRS class 8	26.36	26.96	26.95	22.89	23.14	23.58
EGPRS class 10	26.02	26.46	26.38	22.18	22.24	22.30
EGPRS class 11	24.67	25.16	25.13	20.87	20.82	20.77
EGPRS class 12	23.87	24.22	24.14	19.97	20.07	20.42

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	23.37	23.39	23.31	20.89	20.97	20.94
HSDPA Subtest-1	22.37	22.40	22.34	20.86	20.89	20.93
HSDPA Subtest-2	22.42	22.40	22.35	20.84	20.87	20.94
HSDPA Subtest-3	21.89	21.94	21.84	20.37	20.43	20.44
HSDPA Subtest-4	21.88	21.94	21.84	20.38	20.40	20.46
HSUPA Subtest-1	22.38	22.38	22.36	20.36	19.93	19.95
HSUPA Subtest-2	20.42	20.40	20.35	19.56	19.69	19.68
HSUPA Subtest-3	21.41	21.32	21.33	20.18	20.27	20.25
HSUPA Subtest-4	20.34	20.39	20.34	20.36	20.43	20.47
HSUPA Subtest-5	22.41	22.43	22.33	20.86	20.91	20.95



Conducted Power (*Unit: dBm)			
Band	WCDMA Band IV		
Channel	1312	1413	1513
Frequency	1712.4	1732.6	1752.6
RMC 12.2K	21.00	21.06	21.04
HSDPA Subtest-1	20.99	20.99	20.99
HSDPA Subtest-2	20.99	20.98	20.99
HSDPA Subtest-3	20.43	20.17	20.48
HSDPA Subtest-4	20.42	20.18	20.50
HSUPA Subtest-1	19.98	20.02	20.00
HSUPA Subtest-2	19.67	19.43	19.52
HSUPA Subtest-3	20.49	20.50	20.43
HSUPA Subtest-4	20.50	20.49	20.48
HSUPA Subtest-5	20.99	20.89	20.99



<For Upper Antenna>

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	32.57	32.95	32.58	29.18	29.75	30.04
GPRS class 8	32.59	33.01	32.98	29.19	29.77	30.06
GPRS class 10	30.70	30.92	30.78	27.46	27.67	28.03
GPRS class 11	29.37	29.49	29.52	25.13	26.03	26.62
GPRS class 12	27.85	28.14	27.58	24.11	25.03	25.55
EGPRS class 8	26.64	26.89	26.89	26.08	25.82	26.72
EGPRS class 10	25.87	26.73	26.71	24.37	24.85	25.21
EGPRS class 11	24.22	25.63	25.70	23.10	23.43	23.77
EGPRS class 12	23.82	24.79	24.71	22.32	22.89	23.29

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	23.14	23.23	23.17	23.14	23.17	23.19
HSDPA Subtest-1	22.16	22.21	22.15	23.12	23.17	23.15
HSDPA Subtest-2	22.14	22.19	22.12	22.86	23.18	23.13
HSDPA Subtest-3	21.62	21.65	21.66	22.63	22.68	22.64
HSDPA Subtest-4	21.60	21.60	21.63	22.67	22.67	22.65
HSUPA Subtest-1	22.17	22.22	22.17	22.26	22.20	22.19
HSUPA Subtest-2	20.15	20.23	20.18	21.91	21.87	21.86
HSUPA Subtest-3	21.15	21.22	21.18	22.46	22.44	22.49
HSUPA Subtest-4	20.17	20.23	20.19	22.48	22.42	22.45
HSUPA Subtest-5	22.20	22.30	22.20	23.15	23.15	23.15









Conducted Power (*Unit: dBm)			
Band	WCDMA Band IV		
Channel	1312	1413	1513
Frequency	1712.4	1732.6	1752.6
RMC 12.2K	23.18	23.22	23.19
HSDPA Subtest-1	22.97	22.99	23.00
HSDPA Subtest-2	22.95	22.97	22.98
HSDPA Subtest-3	22.50	22.49	22.48
HSDPA Subtest-4	22.47	22.47	22.46
HSUPA Subtest-1	22.03	22.02	22.01
HSUPA Subtest-2	21.68	21.76	21.74
HSUPA Subtest-3	22.27	22.32	22.49
HSUPA Subtest-4	22.45	22.43	22.48
HSUPA Subtest-5	22.92	22.94	22.93









A2. GSM

Peak-to-Average Ratio


Mode	GSM850		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.36	3.52	PASS
Middle CH	0.36	3.52	
Highest CH	0.32	3.28	
Mode	GSM1900		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.4	3.56	PASS
Middle CH	0.36	3.52	
Highest CH	0.36	3.44	


GSM850 (GPRS class 8)	GSM850 (EDGE class 8)
Lowest Channel	Lowest Channel
 Center 824.2 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 33.41 dBm Peak 33.77 dBm Crest 0.36 dB 10 % 0.24 dB 1 % 0.32 dB .1 % 0.36 dB .01 % 0.36 dB Date: 12.JAN.2020 12:56:30	 Center 824.2 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 26.65 dBm Peak 30.24 dBm Crest 3.60 dB 10 % 2.68 dB 1 % 3.40 dB .1 % 3.52 dB .01 % 3.56 dB Date: 12.JAN.2020 12:31:59
Middle Channel	Middle Channel
 Center 836.4 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 33.39 dBm Peak 33.77 dBm Crest 0.38 dB 10 % 0.24 dB 1 % 0.32 dB .1 % 0.36 dB .01 % 0.40 dB Date: 12.JAN.2020 12:56:46	 Center 836.4 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 26.50 dBm Peak 30.10 dBm Crest 3.60 dB 10 % 2.68 dB 1 % 3.36 dB .1 % 3.52 dB .01 % 3.56 dB Date: 12.JAN.2020 12:32:15
Highest Channel	Highest Channel
 Center 848.8 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 33.74 dBm Peak 34.05 dBm Crest 0.31 dB 10 % 0.20 dB 1 % 0.28 dB .1 % 0.32 dB .01 % 0.32 dB Date: 12.JAN.2020 12:57:08	 Center 848.8 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 26.87 dBm Peak 30.24 dBm Crest 3.38 dB 10 % 2.68 dB 1 % 3.16 dB .1 % 3.28 dB .01 % 3.32 dB Date: 12.JAN.2020 12:32:26

GSM1900 (GPRS class 8)	GSM1900 (EDGE class 8)
Lowest Channel	Lowest Channel
 Center 1.8502 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.54 dBm Peak 29.96 dBm Crest 0.42 dB 10 % 0.24 dB 1 % 0.36 dB .1 % 0.40 dB .01 % 0.44 dB Date: 12.JAN.2020 13:43:31	 Center 1.8502 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 24.96 dBm Peak 28.62 dBm Crest 3.66 dB 10 % 2.72 dB 1 % 3.44 dB .1 % 3.56 dB .01 % 3.64 dB Date: 12.JAN.2020 13:29:13
Middle Channel	Middle Channel
 Center 1.88 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.69 dBm Peak 30.03 dBm Crest 0.34 dB 10 % 0.24 dB 1 % 0.32 dB .1 % 0.36 dB .01 % 0.36 dB Date: 12.JAN.2020 13:43:48	 Center 1.88 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.09 dBm Peak 28.69 dBm Crest 3.60 dB 10 % 2.76 dB 1 % 3.36 dB .1 % 3.52 dB .01 % 3.60 dB Date: 12.JAN.2020 13:29:33
Highest Channel	Highest Channel
 Center 1.9098 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.69 dBm Peak 30.03 dBm Crest 0.34 dB 10 % 0.20 dB 1 % 0.28 dB .1 % 0.36 dB .01 % 0.36 dB Date: 12.JAN.2020 13:44:00	 Center 1.9098 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.22 dBm Peak 28.76 dBm Crest 3.54 dB 10 % 2.60 dB 1 % 3.24 dB .1 % 3.44 dB .01 % 3.48 dB Date: 12.JAN.2020 13:29:45

**26dB Bandwidth**


Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.313	0.305
Middle CH	0.313	0.301
Highest CH	0.315	0.306
Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.297	0.293
Middle CH	0.297	0.308
Highest CH	0.311	0.294







**Occupied Bandwidth**


Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.243	0.242
Middle CH	0.248	0.246
Highest CH	0.247	0.242
Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.241	0.244
Middle CH	0.241	0.246
Highest CH	0.240	0.241






**Conducted Band Edge****GSM850 (GPRS class 8)****Lowest Band Edge**


Date: 12.JAN.2020 12:51:57

Highest Band Edge

Date: 12.JAN.2020 12:53:31

GSM850 (EDGE class 8)**Lowest Band Edge**

Date: 12.JAN.2020 12:35:54


Highest Band Edge

Date: 12.JAN.2020 12:37:27




GSM1900 (GPRS class 8)

Lowest Band Edge



Date: 12.JAN.2020 13:38:52


Highest Band Edge



Date: 12.JAN.2020 13:40:21


GSM1900 (EDGE class 8)

Lowest Band Edge









Date: 12.JAN.2020 13:24:48

Highest Band Edge



Date: 12.JAN.2020 13:26:21


**Conducted Spurious Emission**

GSM850 (GPRS class 8)		GSM850 (EDGE class 8)																																																																																					
Lowest Channel		Lowest Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAve</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>636.127500 M</td><td>-42.54</td><td>-29.54</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>996.665010 M</td><td>-42.04</td><td>-29.04</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.648500 G</td><td>-26.02</td><td>-23.02</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.098000 G</td><td>-37.52</td><td>-24.52</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.363500 G</td><td>-34.87</td><td>-21.87</td></tr></table> Date: 12.JAN.2020 12:54:26		Start	Stop	RBW	Freq	PerAve	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	636.127500 M	-42.54	-29.54	850.000 M	1.000 G	1.00 M	996.665010 M	-42.04	-29.04	1.000 G	3.000 G	1.00 M	1.648500 G	-26.02	-23.02	3.000 G	7.000 G	1.00 M	3.098000 G	-37.52	-24.52	7.000 G	9.000 G	1.00 M	8.363500 G	-34.87	-21.87	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAve</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>819.802500 M</td><td>-30.85</td><td>-17.85</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>873.378751 M</td><td>-41.89</td><td>-28.89</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.648500 G</td><td>-34.30</td><td>-21.30</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.093500 G</td><td>-37.57</td><td>-24.57</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>7.592500 G</td><td>-35.23</td><td>-22.23</td></tr></table> Date: 12.JAN.2020 12:29:54		Start	Stop	RBW	Freq	PerAve	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	819.802500 M	-30.85	-17.85	850.000 M	1.000 G	1.00 M	873.378751 M	-41.89	-28.89	1.000 G	3.000 G	1.00 M	1.648500 G	-34.30	-21.30	3.000 G	7.000 G	1.00 M	3.093500 G	-37.57	-24.57	7.000 G	9.000 G	1.00 M	7.592500 G	-35.23	-22.23
Start	Stop	RBW	Freq	PerAve	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	636.127500 M	-42.54	-29.54																																																																																		
850.000 M	1.000 G	1.00 M	996.665010 M	-42.04	-29.04																																																																																		
1.000 G	3.000 G	1.00 M	1.648500 G	-26.02	-23.02																																																																																		
3.000 G	7.000 G	1.00 M	3.098000 G	-37.52	-24.52																																																																																		
7.000 G	9.000 G	1.00 M	8.363500 G	-34.87	-21.87																																																																																		
Start	Stop	RBW	Freq	PerAve	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	819.802500 M	-30.85	-17.85																																																																																		
850.000 M	1.000 G	1.00 M	873.378751 M	-41.89	-28.89																																																																																		
1.000 G	3.000 G	1.00 M	1.648500 G	-34.30	-21.30																																																																																		
3.000 G	7.000 G	1.00 M	3.093500 G	-37.57	-24.57																																																																																		
7.000 G	9.000 G	1.00 M	7.592500 G	-35.23	-22.23																																																																																		
Middle Channel		Middle Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAve</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>817.432500 M</td><td>-42.68</td><td>-29.68</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>946.208708 M</td><td>-40.79</td><td>-27.79</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.673000 G</td><td>-26.48</td><td>-23.48</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.610000 G</td><td>-37.80</td><td>-24.80</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.063500 G</td><td>-35.49</td><td>-22.49</td></tr></table> Date: 12.JAN.2020 12:55:17		Start	Stop	RBW	Freq	PerAve	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	817.432500 M	-42.68	-29.68	850.000 M	1.000 G	1.00 M	946.208708 M	-40.79	-27.79	1.000 G	3.000 G	1.00 M	1.673000 G	-26.48	-23.48	3.000 G	7.000 G	1.00 M	3.610000 G	-37.80	-24.80	7.000 G	9.000 G	1.00 M	8.063500 G	-35.49	-22.49	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAve</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>643.237500 M</td><td>-42.29</td><td>-29.29</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>827.862500 M</td><td>-41.32</td><td>-28.32</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.673000 G</td><td>-38.13</td><td>-25.13</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.129000 G</td><td>-37.51</td><td>-24.51</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.384500 G</td><td>-35.25</td><td>-22.25</td></tr></table> Date: 12.JAN.2020 12:30:48		Start	Stop	RBW	Freq	PerAve	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	643.237500 M	-42.29	-29.29	850.000 M	1.000 G	1.00 M	827.862500 M	-41.32	-28.32	1.000 G	3.000 G	1.00 M	1.673000 G	-38.13	-25.13	3.000 G	7.000 G	1.00 M	3.129000 G	-37.51	-24.51	7.000 G	9.000 G	1.00 M	8.384500 G	-35.25	-22.25
Start	Stop	RBW	Freq	PerAve	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	817.432500 M	-42.68	-29.68																																																																																		
850.000 M	1.000 G	1.00 M	946.208708 M	-40.79	-27.79																																																																																		
1.000 G	3.000 G	1.00 M	1.673000 G	-26.48	-23.48																																																																																		
3.000 G	7.000 G	1.00 M	3.610000 G	-37.80	-24.80																																																																																		
7.000 G	9.000 G	1.00 M	8.063500 G	-35.49	-22.49																																																																																		
Start	Stop	RBW	Freq	PerAve	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	643.237500 M	-42.29	-29.29																																																																																		
850.000 M	1.000 G	1.00 M	827.862500 M	-41.32	-28.32																																																																																		
1.000 G	3.000 G	1.00 M	1.673000 G	-38.13	-25.13																																																																																		
3.000 G	7.000 G	1.00 M	3.129000 G	-37.51	-24.51																																																																																		
7.000 G	9.000 G	1.00 M	8.384500 G	-35.25	-22.25																																																																																		
Highest Channel		Highest Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAve</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>747.517500 M</td><td>-42.64</td><td>-29.64</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>855.036250 M</td><td>-33.29</td><td>-20.29</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.697000 G</td><td>-31.80</td><td>-18.80</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>5.216000 G</td><td>-37.24</td><td>-24.24</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.369500 G</td><td>-34.48</td><td>-21.48</td></tr></table> Date: 12.JAN.2020 12:56:11		Start	Stop	RBW	Freq	PerAve	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	747.517500 M	-42.64	-29.64	850.000 M	1.000 G	1.00 M	855.036250 M	-33.29	-20.29	1.000 G	3.000 G	1.00 M	1.697000 G	-31.80	-18.80	3.000 G	7.000 G	1.00 M	5.216000 G	-37.24	-24.24	7.000 G	9.000 G	1.00 M	8.369500 G	-34.48	-21.48	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAve</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>659.235000 M</td><td>-42.50</td><td>-29.50</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>855.145000 M</td><td>-39.87</td><td>-26.87</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.698000 G</td><td>-35.28</td><td>-22.28</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.000000 G</td><td>-37.19</td><td>-24.19</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.351500 G</td><td>-35.50</td><td>-22.50</td></tr></table> Date: 12.JAN.2020 12:31:40		Start	Stop	RBW	Freq	PerAve	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	659.235000 M	-42.50	-29.50	850.000 M	1.000 G	1.00 M	855.145000 M	-39.87	-26.87	1.000 G	3.000 G	1.00 M	1.698000 G	-35.28	-22.28	3.000 G	7.000 G	1.00 M	3.000000 G	-37.19	-24.19	7.000 G	9.000 G	1.00 M	8.351500 G	-35.50	-22.50
Start	Stop	RBW	Freq	PerAve	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	747.517500 M	-42.64	-29.64																																																																																		
850.000 M	1.000 G	1.00 M	855.036250 M	-33.29	-20.29																																																																																		
1.000 G	3.000 G	1.00 M	1.697000 G	-31.80	-18.80																																																																																		
3.000 G	7.000 G	1.00 M	5.216000 G	-37.24	-24.24																																																																																		
7.000 G	9.000 G	1.00 M	8.369500 G	-34.48	-21.48																																																																																		
Start	Stop	RBW	Freq	PerAve	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	659.235000 M	-42.50	-29.50																																																																																		
850.000 M	1.000 G	1.00 M	855.145000 M	-39.87	-26.87																																																																																		
1.000 G	3.000 G	1.00 M	1.698000 G	-35.28	-22.28																																																																																		
3.000 G	7.000 G	1.00 M	3.000000 G	-37.19	-24.19																																																																																		
7.000 G	9.000 G	1.00 M	8.351500 G	-35.50	-22.50																																																																																		



GSM1900 (GPRS class 8)


Lowest Channel



Date: 12.JAN.2020 13:41:13


GSM1900 (EDGE class 8)

Lowest Channel




Date: 12.JAN.2020 13:27:11

Middle Channel




Date: 12.JAN.2020 13:42:00

Middle Channel




Date: 12.JAN.2020 13:28:01

Highest Channel



Date: 12.JAN.2020 13:42:51

Highest Channel



Date: 12.JAN.2020 13:28:51

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GPRS class 8)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0024	0.0060	PASS
40	Normal Voltage	0.0012	0.0012	
30	Normal Voltage	0.0024	0.0036	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0012	0.0024	
0	Normal Voltage	0.0072	0.0036	
-10	Normal Voltage	0.0108	0.0060	
-20	Normal Voltage	0.0120	0.0048	
-30	Normal Voltage	0.0036	0.0072	
20	Maximum Voltage	0.0048	0.0024	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0000	0.0060	

Test Conditions	Middle Channel	GSM1900 (GPRS class 8)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0016	0.0266	PASS
40	Normal Voltage	0.0011	0.0021	
30	Normal Voltage	0.0011	0.0016	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0016	0.0234	
0	Normal Voltage	0.0053	0.0069	
-10	Normal Voltage	0.0048	0.0032	
-20	Normal Voltage	0.0011	0.0053	
-30	Normal Voltage	0.0027	0.0074	
20	Maximum Voltage	0.0005	0.0032	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0005	0.0064	

Note:

1. Normal Voltage = 3.87V. ; Battery End Point (BEP) = 3.6 V. ; Maximum Voltage =4.45 V
2. The frequency fundamental emissions stay within the authorized frequency block.









A3. WCDMA

Peak-to-Average Ratio


Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.24	3.32	3.32	PASS
Middle CH	3.20	3.32	3.48	
Highest CH	3.40	3.24	3.08	



WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)																
Lowest Channel	Lowest Channel																
 Ref: 30 dBm, Att: 30 dB, AQT: 3.125 ms, RSW: 10 MHz Center: 826.4 MHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 23.02 dBm Peak: 26.51 dBm Crest: 3.49 dB <table><tr><td>10 %</td><td>1.84 dB</td></tr><tr><td>1 %</td><td>2.84 dB</td></tr><tr><td>.1 %</td><td>3.24 dB</td></tr><tr><td>.01 %</td><td>3.40 dB</td></tr></table> Date: 12.JAN.2020 13:15:18	10 %	1.84 dB	1 %	2.84 dB	.1 %	3.24 dB	.01 %	3.40 dB	 Ref: 30 dBm, Att: 30 dB, AQT: 3.125 ms, RSW: 10 MHz Center: 1.8524 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 21.92 dBm Peak: 25.53 dBm Crest: 3.60 dB <table><tr><td>10 %</td><td>1.80 dB</td></tr><tr><td>1 %</td><td>2.84 dB</td></tr><tr><td>.1 %</td><td>3.32 dB</td></tr><tr><td>.01 %</td><td>3.48 dB</td></tr></table> Date: 12.JAN.2020 14:03:44	10 %	1.80 dB	1 %	2.84 dB	.1 %	3.32 dB	.01 %	3.48 dB
10 %	1.84 dB																
1 %	2.84 dB																
.1 %	3.24 dB																
.01 %	3.40 dB																
10 %	1.80 dB																
1 %	2.84 dB																
.1 %	3.32 dB																
.01 %	3.48 dB																
Middle Channel	Middle Channel																
 Ref: 30 dBm, Att: 30 dB, AQT: 3.125 ms, RSW: 10 MHz Center: 836.4 MHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 22.96 dBm Peak: 26.37 dBm Crest: 3.42 dB <table><tr><td>10 %</td><td>1.80 dB</td></tr><tr><td>1 %</td><td>2.80 dB</td></tr><tr><td>.1 %</td><td>3.20 dB</td></tr><tr><td>.01 %</td><td>3.36 dB</td></tr></table> Date: 12.JAN.2020 13:15:33	10 %	1.80 dB	1 %	2.80 dB	.1 %	3.20 dB	.01 %	3.36 dB	 Ref: 30 dBm, Att: 30 dB, AQT: 3.125 ms, RSW: 10 MHz Center: 1.85 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 22.03 dBm Peak: 25.53 dBm Crest: 3.49 dB <table><tr><td>10 %</td><td>1.80 dB</td></tr><tr><td>1 %</td><td>2.84 dB</td></tr><tr><td>.1 %</td><td>3.32 dB</td></tr><tr><td>.01 %</td><td>3.44 dB</td></tr></table> Date: 12.JAN.2020 14:03:55	10 %	1.80 dB	1 %	2.84 dB	.1 %	3.32 dB	.01 %	3.44 dB
10 %	1.80 dB																
1 %	2.80 dB																
.1 %	3.20 dB																
.01 %	3.36 dB																
10 %	1.80 dB																
1 %	2.84 dB																
.1 %	3.32 dB																
.01 %	3.44 dB																
Highest Channel	Highest Channel																
 Ref: 30 dBm, Att: 30 dB, AQT: 3.125 ms, RSW: 10 MHz Center: 846.6 MHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 22.83 dBm Peak: 26.58 dBm Crest: 3.75 dB <table><tr><td>10 %</td><td>1.84 dB</td></tr><tr><td>1 %</td><td>2.92 dB</td></tr><tr><td>.1 %</td><td>3.40 dB</td></tr><tr><td>.01 %</td><td>3.60 dB</td></tr></table> Date: 12.JAN.2020 13:15:48	10 %	1.84 dB	1 %	2.92 dB	.1 %	3.40 dB	.01 %	3.60 dB	 Ref: 30 dBm, Att: 30 dB, AQT: 3.125 ms, RSW: 10 MHz Center: 1.9076 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 21.83 dBm Peak: 25.31 dBm Crest: 3.48 dB <table><tr><td>10 %</td><td>1.76 dB</td></tr><tr><td>1 %</td><td>2.76 dB</td></tr><tr><td>.1 %</td><td>3.24 dB</td></tr><tr><td>.01 %</td><td>3.40 dB</td></tr></table> Date: 12.JAN.2020 14:04:05	10 %	1.76 dB	1 %	2.76 dB	.1 %	3.24 dB	.01 %	3.40 dB
10 %	1.84 dB																
1 %	2.92 dB																
.1 %	3.40 dB																
.01 %	3.60 dB																
10 %	1.76 dB																
1 %	2.76 dB																
.1 %	3.24 dB																
.01 %	3.40 dB																


WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 12.JAN.2020 14:17:39

Middle Channel



Date: 12.JAN.2020 14:17:52

Highest Channel



Date: 12.JAN.2020 14:18:06




26dB Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.72	4.71	4.71
Middle CH	4.75	4.71	4.72
Highest CH	4.71	4.74	4.73



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 12.JAN.2020 13:01:26


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 12.JAN.2020 13:47:21

Middle Channel




Date: 12.JAN.2020 13:02:08

Middle Channel




Date: 12.JAN.2020 13:47:57

Highest Channel



Date: 12.JAN.2020 13:02:41


Highest Channel



Date: 12.JAN.2020 13:48:30


WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 12.JAN.2020 14:06:01

Middle Channel



Date: 12.JAN.2020 14:06:36

Highest Channel



Date: 12.JAN.2020 14:07:09


**Occupied Bandwidth**

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.14	4.15	4.15
Middle CH	4.16	4.15	4.16
Highest CH	4.16	4.16	4.16




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 12.JAN.2020 14:07:46

Middle Channel




Date: 12.JAN.2020 14:08:19


Highest Channel




Date: 12.JAN.2020 14:08:51

**Conducted Band Edge****WCDMA Band V (RMC 12.2Kbps)****Lowest Band Edge**


Date: 12.JAN.2020 13:07:22

Highest Band Edge

Date: 12.JAN.2020 13:12:09

WCDMA Band II (RMC 12.2Kbps)**Lowest Band Edge**

Date: 12.JAN.2020 13:53:00


Highest Band Edge

Date: 12.JAN.2020 13:55:46




WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge









Date: 12.JAN.2020 14:11:40

Highest Band Edge




Date: 12.JAN.2020 14:14:31

**Conducted Spurious Emission**

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)																																																																																										
Lowest Channel	Lowest Channel																																																																																										
<table><thead><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr></thead><tbody><tr><td>30,000 M</td><td>820,000 M</td><td>1,000 M</td><td>819,407500 M</td><td>-30.68</td><td>-17.68</td></tr><tr><td>850,000 M</td><td>1,000 G</td><td>1,000 M</td><td>856,703750 M</td><td>-42.14</td><td>-29.14</td></tr><tr><td>1,000 G</td><td>3,000 G</td><td>1,000 M</td><td>2,886000 G</td><td>-41.08</td><td>-28.08</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,028000 G</td><td>-38.14</td><td>-25.14</td></tr><tr><td>7,000 G</td><td>9,000 G</td><td>1,000 M</td><td>8,176000 G</td><td>-35.48</td><td>-22.48</td></tr></tbody></table> Date: 12.JAN.2020 13:13:01	Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	820,000 M	1,000 M	819,407500 M	-30.68	-17.68	850,000 M	1,000 G	1,000 M	856,703750 M	-42.14	-29.14	1,000 G	3,000 G	1,000 M	2,886000 G	-41.08	-28.08	3,000 G	7,000 G	1,000 M	3,028000 G	-38.14	-25.14	7,000 G	9,000 G	1,000 M	8,176000 G	-35.48	-22.48	<table><thead><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr></thead><tbody><tr><td>30,000 M</td><td>1,000 G</td><td>1,000 M</td><td>886,905000 M</td><td>-41.25</td><td>-28.25</td></tr><tr><td>1,000 G</td><td>1,845 G</td><td>1,000 M</td><td>1,841400 G</td><td>-30.04</td><td>-17.04</td></tr><tr><td>1,915 G</td><td>3,000 G</td><td>1,000 M</td><td>2,890000 G</td><td>-39.55</td><td>-26.55</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,017000 G</td><td>-36.01</td><td>-23.01</td></tr><tr><td>7,000 G</td><td>13,600 G</td><td>1,000 M</td><td>12,595975 G</td><td>-33.91</td><td>-20.91</td></tr><tr><td>13,600 G</td><td>19,100 G</td><td>1,000 M</td><td>15,329062 G</td><td>-24.57</td><td>-11.57</td></tr></tbody></table> Date: 12.JAN.2020 14:01:41	Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	1,000 G	1,000 M	886,905000 M	-41.25	-28.25	1,000 G	1,845 G	1,000 M	1,841400 G	-30.04	-17.04	1,915 G	3,000 G	1,000 M	2,890000 G	-39.55	-26.55	3,000 G	7,000 G	1,000 M	3,017000 G	-36.01	-23.01	7,000 G	13,600 G	1,000 M	12,595975 G	-33.91	-20.91	13,600 G	19,100 G	1,000 M	15,329062 G	-24.57	-11.57
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	820,000 M	1,000 M	819,407500 M	-30.68	-17.68																																																																																						
850,000 M	1,000 G	1,000 M	856,703750 M	-42.14	-29.14																																																																																						
1,000 G	3,000 G	1,000 M	2,886000 G	-41.08	-28.08																																																																																						
3,000 G	7,000 G	1,000 M	3,028000 G	-38.14	-25.14																																																																																						
7,000 G	9,000 G	1,000 M	8,176000 G	-35.48	-22.48																																																																																						
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	1,000 G	1,000 M	886,905000 M	-41.25	-28.25																																																																																						
1,000 G	1,845 G	1,000 M	1,841400 G	-30.04	-17.04																																																																																						
1,915 G	3,000 G	1,000 M	2,890000 G	-39.55	-26.55																																																																																						
3,000 G	7,000 G	1,000 M	3,017000 G	-36.01	-23.01																																																																																						
7,000 G	13,600 G	1,000 M	12,595975 G	-33.91	-20.91																																																																																						
13,600 G	19,100 G	1,000 M	15,329062 G	-24.57	-11.57																																																																																						
Middle Channel	Middle Channel																																																																																										
<table><thead><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr></thead><tbody><tr><td>30,000 M</td><td>820,000 M</td><td>1,000 M</td><td>780,890000 M</td><td>-43.23</td><td>-30.23</td></tr><tr><td>850,000 M</td><td>1,000 G</td><td>1,000 M</td><td>993,293760 M</td><td>-42.04</td><td>-29.04</td></tr><tr><td>1,000 G</td><td>3,000 G</td><td>1,000 M</td><td>2,987000 G</td><td>-40.81</td><td>-27.81</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,020000 G</td><td>-38.18</td><td>-25.18</td></tr><tr><td>7,000 G</td><td>9,000 G</td><td>1,000 M</td><td>7,688000 G</td><td>-35.51</td><td>-22.51</td></tr></tbody></table> Date: 12.JAN.2020 13:13:53	Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	820,000 M	1,000 M	780,890000 M	-43.23	-30.23	850,000 M	1,000 G	1,000 M	993,293760 M	-42.04	-29.04	1,000 G	3,000 G	1,000 M	2,987000 G	-40.81	-27.81	3,000 G	7,000 G	1,000 M	3,020000 G	-38.18	-25.18	7,000 G	9,000 G	1,000 M	7,688000 G	-35.51	-22.51	<table><thead><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr></thead><tbody><tr><td>30,000 M</td><td>1,000 G</td><td>1,000 M</td><td>890,875000 M</td><td>-41.40</td><td>-28.40</td></tr><tr><td>1,000 G</td><td>1,845 G</td><td>1,000 M</td><td>1,293849 G</td><td>-40.69</td><td>-27.69</td></tr><tr><td>1,915 G</td><td>3,000 G</td><td>1,000 M</td><td>2,990000 G</td><td>-39.17</td><td>-26.17</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,078000 G</td><td>-36.18</td><td>-23.18</td></tr><tr><td>7,000 G</td><td>13,600 G</td><td>1,000 M</td><td>11,635675 G</td><td>-33.87</td><td>-20.87</td></tr><tr><td>13,600 G</td><td>19,100 G</td><td>1,000 M</td><td>15,302250 G</td><td>-24.37</td><td>-11.37</td></tr></tbody></table> Date: 12.JAN.2020 14:02:35	Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	1,000 G	1,000 M	890,875000 M	-41.40	-28.40	1,000 G	1,845 G	1,000 M	1,293849 G	-40.69	-27.69	1,915 G	3,000 G	1,000 M	2,990000 G	-39.17	-26.17	3,000 G	7,000 G	1,000 M	3,078000 G	-36.18	-23.18	7,000 G	13,600 G	1,000 M	11,635675 G	-33.87	-20.87	13,600 G	19,100 G	1,000 M	15,302250 G	-24.37	-11.37
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	820,000 M	1,000 M	780,890000 M	-43.23	-30.23																																																																																						
850,000 M	1,000 G	1,000 M	993,293760 M	-42.04	-29.04																																																																																						
1,000 G	3,000 G	1,000 M	2,987000 G	-40.81	-27.81																																																																																						
3,000 G	7,000 G	1,000 M	3,020000 G	-38.18	-25.18																																																																																						
7,000 G	9,000 G	1,000 M	7,688000 G	-35.51	-22.51																																																																																						
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	1,000 G	1,000 M	890,875000 M	-41.40	-28.40																																																																																						
1,000 G	1,845 G	1,000 M	1,293849 G	-40.69	-27.69																																																																																						
1,915 G	3,000 G	1,000 M	2,990000 G	-39.17	-26.17																																																																																						
3,000 G	7,000 G	1,000 M	3,078000 G	-36.18	-23.18																																																																																						
7,000 G	13,600 G	1,000 M	11,635675 G	-33.87	-20.87																																																																																						
13,600 G	19,100 G	1,000 M	15,302250 G	-24.37	-11.37																																																																																						
Highest Channel	Highest Channel																																																																																										
<table><thead><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr></thead><tbody><tr><td>30,000 M</td><td>820,000 M</td><td>1,000 M</td><td>602,135000 M</td><td>-43.97</td><td>-30.97</td></tr><tr><td>850,000 M</td><td>1,000 G</td><td>1,000 M</td><td>872,617501 M</td><td>-41.98</td><td>-28.98</td></tr><tr><td>1,000 G</td><td>3,000 G</td><td>1,000 M</td><td>2,977500 G</td><td>-40.64</td><td>-27.64</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,033000 G</td><td>-37.76</td><td>-24.76</td></tr><tr><td>7,000 G</td><td>9,000 G</td><td>1,000 M</td><td>7,543000 G</td><td>-35.59</td><td>-22.59</td></tr></tbody></table> Date: 12.JAN.2020 13:14:44	Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	820,000 M	1,000 M	602,135000 M	-43.97	-30.97	850,000 M	1,000 G	1,000 M	872,617501 M	-41.98	-28.98	1,000 G	3,000 G	1,000 M	2,977500 G	-40.64	-27.64	3,000 G	7,000 G	1,000 M	3,033000 G	-37.76	-24.76	7,000 G	9,000 G	1,000 M	7,543000 G	-35.59	-22.59	<table><thead><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr></thead><tbody><tr><td>30,000 M</td><td>1,000 G</td><td>1,000 M</td><td>884,722500 M</td><td>-41.73</td><td>-28.73</td></tr><tr><td>1,000 G</td><td>1,845 G</td><td>1,000 M</td><td>1,160339 G</td><td>-40.84</td><td>-27.84</td></tr><tr><td>1,915 G</td><td>3,000 G</td><td>1,000 M</td><td>1,953271 G</td><td>-33.79</td><td>-18.79</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,013000 G</td><td>-36.32</td><td>-23.32</td></tr><tr><td>7,000 G</td><td>13,600 G</td><td>1,000 M</td><td>10,592000 G</td><td>-33.93</td><td>-20.93</td></tr><tr><td>13,600 G</td><td>19,100 G</td><td>1,000 M</td><td>15,289388 G</td><td>-24.76</td><td>-11.76</td></tr></tbody></table> Date: 12.JAN.2020 14:03:29	Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	1,000 G	1,000 M	884,722500 M	-41.73	-28.73	1,000 G	1,845 G	1,000 M	1,160339 G	-40.84	-27.84	1,915 G	3,000 G	1,000 M	1,953271 G	-33.79	-18.79	3,000 G	7,000 G	1,000 M	3,013000 G	-36.32	-23.32	7,000 G	13,600 G	1,000 M	10,592000 G	-33.93	-20.93	13,600 G	19,100 G	1,000 M	15,289388 G	-24.76	-11.76
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	820,000 M	1,000 M	602,135000 M	-43.97	-30.97																																																																																						
850,000 M	1,000 G	1,000 M	872,617501 M	-41.98	-28.98																																																																																						
1,000 G	3,000 G	1,000 M	2,977500 G	-40.64	-27.64																																																																																						
3,000 G	7,000 G	1,000 M	3,033000 G	-37.76	-24.76																																																																																						
7,000 G	9,000 G	1,000 M	7,543000 G	-35.59	-22.59																																																																																						
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	1,000 G	1,000 M	884,722500 M	-41.73	-28.73																																																																																						
1,000 G	1,845 G	1,000 M	1,160339 G	-40.84	-27.84																																																																																						
1,915 G	3,000 G	1,000 M	1,953271 G	-33.79	-18.79																																																																																						
3,000 G	7,000 G	1,000 M	3,013000 G	-36.32	-23.32																																																																																						
7,000 G	13,600 G	1,000 M	10,592000 G	-33.93	-20.93																																																																																						
13,600 G	19,100 G	1,000 M	15,289388 G	-24.76	-11.76																																																																																						


WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 12.JAN.2020 14:15:33

Middle Channel



Date: 12.JAN.2020 14:16:24

Highest Channel



Date: 12.JAN.2020 14:17:16

**Frequency Stability**

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0000	PASS
40	Normal Voltage	0.0012	
30	Normal Voltage	0.0012	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0179	
0	Normal Voltage	0.0179	
-10	Normal Voltage	0.0167	
-20	Normal Voltage	0.0179	
-30	Normal Voltage	0.0155	
20	Maximum Voltage	0.0155	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0167	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0021	PASS
40	Normal Voltage	0.0032	
30	Normal Voltage	0.0016	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0016	
0	Normal Voltage	0.0021	
-10	Normal Voltage	0.0016	
-20	Normal Voltage	0.0016	
-30	Normal Voltage	0.0005	
20	Maximum Voltage	0.0000	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0005	

Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0046	PASS
40	Normal Voltage	0.0040	
30	Normal Voltage	0.0035	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0202	
0	Normal Voltage	0.0225	
-10	Normal Voltage	0.0214	
-20	Normal Voltage	0.0190	
-30	Normal Voltage	0.0046	
20	Maximum Voltage	0.0035	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0029	

Note:

1. Normal Voltage = 3.87V. ; Battery End Point (BEP) =3.6V. ; Maximum Voltage =4.45 V
2. The frequency fundamental emissions stay within the authorized frequency block.

**Appendix B. Test Results of ERP/EIRP and Radiated Test****ERP/EIRP****<For Lower Antenna>**

Channel	Mode	Conducted		ERP	
		Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	GSM850	32.80	1.9055	26.15	0.4121
Middle	GPRS class 8	33.11	2.0464	26.46	0.4426
Highest	(GT - LC = -4.5 dB)	33.28	2.1281	26.63	0.4603
Lowest	GSM850	26.36	0.4325	19.71	0.0935
Middle	EDGE class 8	26.96	0.4966	20.31	0.1074
Highest	(GT - LC = -4.5 dB)	26.95	0.4955	20.30	0.1072
Lowest	WCDMA Band V	23.37	0.2173	16.72	0.0470
Middle	RMC 12.2Kbps	23.39	0.2183	16.74	0.0472
Highest	(GT - LC = -4.5 dB)	23.31	0.2143	16.66	0.0463
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Conducted		EIRP	
		Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900	26.78	0.4764	25.28	0.3373
Middle	GPRS class 8	27.35	0.5433	25.85	0.3846
Highest	(GT - LC = -1.5 dB)	27.88	0.6138	26.38	0.4345
Lowest	GSM1900	22.89	0.1945	21.39	0.1377
Middle	EDGE class 8	23.14	0.2061	21.64	0.1459
Highest	(GT - LC = -1.5 dB)	23.58	0.2280	22.08	0.1614
Lowest	WCDMA Band II	20.89	0.1227	19.39	0.0869
Middle	RMC 12.2Kbps	20.97	0.1250	19.47	0.0885
Highest	(GT - LC = -1.5 dB)	20.94	0.1242	19.44	0.0879
Limit	EIRP < 2W	Result		PASS	

Channel	Mode	Conducted		EIRP	
		Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)
Lowest	WCDMA Band IV	21.00	0.1259	20.00	0.1000
Middle	RMC 12.2Kbps	21.06	0.1276	20.06	0.1014
Highest	(GT - LC = -1 dB)	21.04	0.1271	20.04	0.1009
Limit	EIRP < 1W	Result		PASS	

**<For Upper Antenna>**

Channel	Mode	Conducted		ERP	
		Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	GSM850	32.59	1.8155	21.94	0.1563
Middle	GPRS class 8	33.01	1.9999	22.36	0.1722
Highest	(GT - LC = -8.5 dB)	32.98	1.9861	22.33	0.1710
Lowest	GSM850	26.64	0.4613	15.99	0.0397
Middle	EDGE class 8	26.89	0.4887	16.24	0.0421
Highest	(GT - LC = -8.5 dB)	26.89	0.4887	16.24	0.0421
Lowest	WCDMA Band V	23.14	0.2061	12.49	0.0177
Middle	RMC 12.2Kbps	23.23	0.2104	12.58	0.0181
Highest	(GT - LC = -8.5 dB)	23.17	0.2075	12.52	0.0179
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Conducted		EIRP	
		Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900	29.19	0.8299	28.19	0.6592
Middle	GPRS class 8	29.77	0.9484	28.77	0.7534
Highest	(GT - LC = -1 dB)	30.06	1.0139	29.06	0.8054
Lowest	GSM1900	26.08	0.4055	25.08	0.3221
Middle	EDGE class 8	25.82	0.3819	24.82	0.3034
Highest	(GT - LC = -1 dB)	26.72	0.4699	25.72	0.3733
Lowest	WCDMA Band II	23.14	0.2061	22.14	0.1637
Middle	RMC 12.2Kbps	23.17	0.2075	22.17	0.1648
Highest	(GT - LC = -1 dB)	23.19	0.2084	22.19	0.1656
Limit	EIRP < 2W	Result		PASS	

Channel	Mode	Conducted		EIRP	
		Power (dBm)	Power (Watts)	EIRP(dBm)	EIRP(W)
Lowest	WCDMA Band IV	23.18	0.2080	22.18	0.1652
Middle	RMC 12.2Kbps	23.22	0.2099	22.22	0.1667
Highest	(GT - LC = -1 dB)	23.19	0.2084	22.19	0.1656
Limit	EIRP < 1W	Result		PASS	

Radiated Spurious Emission

<For Lower Antenna>

GPRS 850

GPRS 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-55.70	-13	-42.70	-68.67	-61.09	1.23	8.76	H
	2472	-38.17	-13	-25.17	-55	-45.06	1.44	10.48	H
	3297	-57.28	-13	-44.28	-75.88	-65.22	1.70	11.79	H
	1648	-54.67	-13	-41.67	-67.52	-60.06	1.23	8.76	V
	2472	-39.42	-13	-26.42	-56.54	-46.31	1.44	10.48	V
	3297	-57.00	-13	-44.00	-75.99	-64.94	1.70	11.79	V
Middle	1672	-60.57	-13	-47.57	-73.59	-66.04	1.24	8.85	H
	2512	-41.40	-13	-28.40	-58.17	-48.32	1.44	10.51	H
	3344	-57.26	-13	-44.26	-75.56	-65.30	1.74	11.93	H
	1672	-57.63	-13	-44.63	-70.54	-63.10	1.24	8.85	V
	2512	-41.38	-13	-28.38	-58.34	-48.30	1.44	10.51	V
	3344	-56.69	-13	-43.69	-75.52	-64.73	1.74	11.93	V
Highest	1696	-61.21	-13	-48.21	-74.27	-66.76	1.24	8.94	H
	2544	-43.04	-13	-30.04	-59.87	-49.98	1.44	10.54	H
	3392	-57.75	-13	-44.75	-75.77	-65.89	1.78	12.08	H
	1696	-57.31	-13	-44.31	-70.28	-62.86	1.24	8.94	V
	2544	-40.02	-13	-27.02	-57.06	-46.96	1.44	10.54	V
	3392	-57.26	-13	-44.26	-75.93	-65.40	1.78	12.08	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**EDGE 850**

EDGE 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-59.54	-13	-46.54	-72.51	-64.93	1.23	8.76	H
	2472	-51.57	-13	-38.57	-68.4	-58.46	1.44	10.48	H
	3297	-56.96	-13	-43.96	-75.56	-64.90	1.70	11.79	H
	1648	-62.30	-13	-49.30	-75.15	-67.69	1.23	8.76	V
	2472	-46.98	-13	-33.98	-64.1	-53.87	1.44	10.48	V
	3297	-56.25	-13	-43.25	-75.24	-64.19	1.70	11.79	V
Middle	1680	-62.19	-13	-49.19	-75.23	-67.69	1.24	8.88	H
	2512	-46.36	-13	-33.36	-63.13	-53.28	1.44	10.51	H
	3344	-57.63	-13	-44.63	-75.93	-65.67	1.74	11.93	H
	1680	-62.17	-13	-49.17	-75.11	-67.67	1.24	8.88	V
	2512	-42.17	-13	-29.17	-59.13	-49.09	1.44	10.51	V
	3344	-57.02	-13	-44.02	-75.85	-65.06	1.74	11.93	V
Highest	1704	-62.23	-13	-49.23	-75.31	-67.81	1.25	8.98	H
	2544	-51.88	-13	-38.88	-68.71	-58.82	1.44	10.54	H
	3400	-58.06	-13	-45.06	-76.02	-66.22	1.79	12.10	H
	1704	-62.37	-13	-49.37	-75.37	-67.95	1.25	8.98	V
	2544	-55.86	-13	-42.86	-72.9	-62.80	1.44	10.54	V
	3400	-57.37	-13	-44.37	-76.01	-65.53	1.79	12.10	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**WCDMA 850**

WCDMA 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1656	-53.65	-13	-40.65	-66.64	-59.06	1.23	8.79	H
	2480	-45.56	-13	-32.56	-62.37	-52.46	1.44	10.48	H
	3304	-57.62	-13	-44.62	-76.17	-65.57	1.71	11.81	H
	1656	-57.69	-13	-44.69	-70.55	-63.10	1.23	8.79	V
	2480	-52.14	-13	-39.14	-69.21	-59.04	1.44	10.48	V
	3304	-56.91	-13	-43.91	-75.87	-64.86	1.71	11.81	V
Middle	1672	-57.62	-13	-44.62	-70.64	-63.09	1.24	8.85	H
	2509	-48.31	-13	-35.31	-65.08	-55.23	1.44	10.51	H
	3344	-57.57	-13	-44.57	-75.87	-65.61	1.74	11.93	H
	1672	-61.85	-13	-48.85	-74.76	-67.32	1.24	8.85	V
	2509	-55.20	-13	-42.20	-72.16	-62.12	1.44	10.51	V
	3344	-56.93	-13	-43.93	-75.76	-64.97	1.74	11.93	V
Highest	1696	-61.85	-13	-48.85	-74.91	-67.40	1.24	8.94	H
	2536	-48.69	-13	-35.69	-65.49	-55.63	1.44	10.53	H
	3384	-57.93	-13	-44.93	-75.98	-66.06	1.77	12.05	H
	1696	-62.32	-13	-49.32	-75.29	-67.87	1.24	8.94	V
	2536	-57.92	-13	-44.92	-74.93	-64.86	1.44	10.53	V
	3384	-57.12	-13	-44.12	-75.81	-65.25	1.77	12.05	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GPRS 1900

GPRS 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-53.88	-13	-40.88	-74.42	-64.19	1.97	12.28	H
	5548	-51.44	-13	-38.44	-75.02	-61.56	2.14	12.27	H
	7403	-47.81	-13	-34.81	-75.92	-55.81	2.17	10.17	H
	3700	-55.05	-13	-42.05	-76.11	-65.36	1.97	12.28	V
	5548	-48.81	-13	-35.81	-73.01	-58.93	2.14	12.27	V
	7403	-47.61	-13	-34.61	-75.68	-55.61	2.17	10.17	V
Middle	3763	-53.39	-13	-40.39	-74.08	-63.63	2.01	12.24	H
	5639	-49.65	-13	-36.65	-73.31	-59.92	2.12	12.39	H
	7520	-48.33	-13	-35.33	-76.13	-56.29	2.11	10.07	H
	3763	-55.03	-13	-42.03	-76.22	-65.27	2.01	12.24	V
	5639	-49.98	-13	-36.98	-74.26	-60.25	2.12	12.39	V
	7520	-48.37	-13	-35.37	-76.06	-56.33	2.11	10.07	V
Highest	3820	-54.73	-13	-41.73	-75.53	-64.90	2.04	12.21	H
	5730	-49.11	-13	-36.11	-73.2	-59.53	2.10	12.52	H
	7639	-48.57	-13	-35.57	-75.89	-56.96	2.11	10.50	H
	3820	-54.11	-13	-41.11	-75.38	-64.28	2.04	12.21	V
	5730	-46.17	-13	-33.17	-70.81	-56.59	2.10	12.52	V
	7639	-48.55	-13	-35.55	-75.91	-56.94	2.11	10.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**EDGE 1900**

EDGE 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-55.86	-13	-42.86	-76.4	-66.17	1.97	12.28	H
	5548	-53.53	-13	-40.53	-77.11	-63.65	2.14	12.27	H
	7400	-47.40	-13	-34.40	-75.51	-55.40	2.18	10.18	H
	3700	-55.43	-13	-42.43	-76.49	-65.74	1.97	12.28	V
	5548	-52.84	-13	-39.84	-77.04	-62.96	2.14	12.27	V
	7400	-47.90	-13	-34.90	-75.98	-55.90	2.18	10.18	V
Middle	3756	-55.02	-13	-42.02	-75.69	-65.26	2.00	12.25	H
	5646	-52.85	-13	-39.85	-76.53	-63.13	2.12	12.40	H
	7520	-47.48	-13	-34.48	-75.28	-55.44	2.11	10.07	H
	3756	-54.61	-13	-41.61	-75.78	-64.85	2.00	12.25	V
	5646	-52.46	-13	-39.46	-76.76	-62.74	2.12	12.40	V
	7520	-47.88	-13	-34.88	-75.57	-55.84	2.11	10.07	V
Highest	3820	-55.42	-13	-42.42	-76.22	-65.59	2.04	12.21	H
	5729	-52.18	-13	-39.18	-76.26	-62.60	2.10	12.52	H
	7639	-48.73	-13	-35.73	-76.05	-57.12	2.11	10.50	H
	3820	-54.86	-13	-41.86	-76.13	-65.03	2.04	12.21	V
	5729	-51.76	-13	-38.76	-76.39	-62.18	2.10	12.52	V
	7639	-48.47	-13	-35.47	-75.83	-56.86	2.11	10.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**WCDMA 1900**

WCDMA 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-56.02	-13	-43.02	-76.56	-66.33	1.97	12.28	H
	5555	-53.33	-13	-40.33	-76.9	-63.46	2.14	12.28	H
	7410	-48.02	-13	-35.02	-76.1	-56.01	2.17	10.16	H
	3700	-55.58	-13	-42.58	-76.64	-65.89	1.97	12.28	V
	5555	-52.80	-13	-39.80	-76.99	-62.93	2.14	12.28	V
	7410	-47.91	-13	-34.91	-75.95	-55.90	2.17	10.16	V
Middle	3756	-55.56	-13	-42.56	-76.23	-65.80	2.00	12.25	H
	5646	-53.00	-13	-40.00	-76.68	-63.28	2.12	12.40	H
	7520	-48.49	-13	-35.49	-76.29	-56.45	2.11	10.07	H
	3756	-55.36	-13	-42.36	-76.53	-65.60	2.00	12.25	V
	5646	-52.88	-13	-39.88	-77.18	-63.16	2.12	12.40	V
	7520	-48.40	-13	-35.40	-76.09	-56.36	2.11	10.07	V
Highest	3819	-55.42	-13	-42.42	-76.22	-65.59	2.04	12.21	H
	5722	-52.72	-13	-39.72	-76.77	-63.13	2.10	12.51	H
	7630	-48.60	-13	-35.60	-75.9	-56.95	2.11	10.47	H
	3819	-54.86	-13	-41.86	-76.13	-65.03	2.04	12.21	V
	5722	-51.97	-13	-38.97	-76.57	-62.38	2.10	12.51	V
	7630	-48.39	-13	-35.39	-75.73	-56.74	2.11	10.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**WCDMA 1700**

WCDMA 1700									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3425	-56.99	-13	-43.99	-76.07	-67.36	1.81	12.18	H
	5137	-52.93	-13	-39.93	-76.34	-62.75	2.30	12.13	H
	6850	-49.52	-13	-36.52	-75.72	-58.20	2.37	11.05	H
	3425	-56.31	-13	-43.31	-76.02	-66.68	1.81	12.18	V
	5137	-52.40	-13	-39.40	-76.38	-62.22	2.30	12.13	V
	6850	-49.08	-13	-36.08	-75.84	-57.76	2.37	11.05	V
Middle	3465	-56.37	-13	-43.37	-75.82	-66.82	1.84	12.30	H
	5198	-52.76	-13	-39.76	-76.22	-62.62	2.28	12.14	H
	6930	-49.48	-13	-36.48	-75.93	-58.05	2.40	10.97	H
	3465	-55.60	-13	-42.60	-75.58	-66.05	1.84	12.30	V
	5198	-52.73	-13	-39.73	-76.74	-62.59	2.28	12.14	V
	6930	-48.92	-13	-35.92	-75.99	-57.49	2.40	10.97	V
Highest	3505	-56.32	-13	-43.32	-76.13	-66.84	1.87	12.40	H
	5258	-53.38	-13	-40.38	-76.89	-63.28	2.25	12.15	H
	7010	-48.75	-13	-35.75	-75.48	-57.22	2.41	10.88	H
	3505	-55.91	-13	-42.91	-76.17	-66.43	1.87	12.40	V
	5258	-52.67	-13	-39.67	-76.71	-62.57	2.25	12.15	V
	7010	-48.31	-13	-35.31	-75.7	-56.78	2.41	10.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Radiated Spurious Emission

<For Upper Antenna>

Part 22H GPRS 850

GPRS 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-54.07	-13	-41.07	-67.04	-59.46	1.23	8.76	H
	2472	-33.30	-13	-20.30	-50.13	-40.19	1.44	10.48	H
	4120	-50.66	-13	-37.66	-71.04	-58.52	2.09	12.10	H
	1648	-53.08	-13	-40.08	-65.93	-58.47	1.23	8.76	V
	2472	-37.82	-13	-24.82	-54.94	-44.71	1.44	10.48	V
	4120	-53.14	-13	-40.14	-74.09	-61.00	2.09	12.10	V
Middle	1672	-58.56	-13	-45.56	-71.58	-64.03	1.24	8.85	H
	2512	-42.41	-13	-29.41	-59.18	-49.33	1.44	10.51	H
	3344	-57.90	-13	-44.90	-76.2	-65.94	1.74	11.93	H
	1672	-58.70	-13	-45.70	-71.61	-64.17	1.24	8.85	V
	2512	-46.29	-13	-33.29	-63.25	-53.21	1.44	10.51	V
	3344	-57.15	-13	-44.15	-75.98	-65.19	1.74	11.93	V
Highest	1696	-56.09	-13	-43.09	-69.15	-61.64	1.24	8.94	H
	2544	-35.33	-13	-22.33	-52.16	-42.27	1.44	10.54	H
	3392	-58.16	-13	-45.16	-76.18	-66.30	1.78	12.08	H
	1696	-56.23	-13	-43.23	-69.2	-61.78	1.24	8.94	V
	2544	-42.23	-13	-29.23	-59.27	-49.17	1.44	10.54	V
	3392	-57.01	-13	-44.01	-75.68	-65.15	1.78	12.08	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**Part 22H EDGE 850**

EDGE 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-61.22	-13	-48.22	-74.19	-66.61	1.23	8.76	H
	2472	-46.55	-13	-33.55	-63.38	-53.44	1.44	10.48	H
	3297	-57.36	-13	-44.36	-75.96	-65.30	1.70	11.79	H
	1648	-59.76	-13	-46.76	-72.61	-65.15	1.23	8.76	V
	2472	-47.92	-13	-34.92	-65.04	-54.81	1.44	10.48	V
	3297	-56.89	-13	-43.89	-75.88	-64.83	1.70	11.79	V
Middle	1673	-61.64	-13	-48.64	-74.66	-67.11	1.24	8.86	H
	2512	-51.42	-13	-38.42	-68.19	-58.34	1.44	10.51	H
	3346	-57.53	-13	-44.53	-75.82	-65.57	1.74	11.94	H
	1673	-61.99	-13	-48.99	-74.9	-67.46	1.24	8.86	V
	2512	-57.75	-13	-44.75	-74.71	-64.67	1.44	10.51	V
	3346	-57.12	-13	-44.12	-75.94	-65.16	1.74	11.94	V
Highest	1698	-61.92	-13	-48.92	-74.99	-67.48	1.25	8.95	H
	2544	-49.86	-13	-36.86	-66.69	-56.80	1.44	10.54	H
	3395	-57.90	-13	-44.90	-75.89	-66.05	1.78	12.09	H
	1698	-62.01	-13	-49.01	-75	-67.57	1.25	8.95	V
	2544	-54.35	-13	-41.35	-71.39	-61.29	1.44	10.54	V
	3395	-57.46	-13	-44.46	-76.12	-65.61	1.78	12.09	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**Part 22H WCDMA 850**

WCDMA 850									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1656	-61.78	-13	-48.78	-74.77	-67.19	1.23	8.79	H
	2480	-57.26	-13	-44.26	-74.07	-64.16	1.44	10.48	H
	3304	-57.33	-13	-44.33	-75.88	-65.28	1.71	11.81	H
	1656	-61.88	-13	-48.88	-74.74	-67.29	1.23	8.79	V
	2480	-57.92	-13	-44.92	-74.99	-64.82	1.44	10.48	V
	3304	-56.77	-13	-43.77	-75.73	-64.72	1.71	11.81	V
Middle	1672	-61.78	-13	-48.78	-74.8	-67.25	1.24	8.85	H
	2509	-57.93	-13	-44.93	-74.7	-64.85	1.44	10.51	H
	3344	-57.61	-13	-44.61	-75.91	-65.65	1.74	11.93	H
	1672	-62.09	-13	-49.09	-75	-67.56	1.24	8.85	V
	2509	-58.64	-13	-45.64	-75.6	-65.56	1.44	10.51	V
	3344	-57.00	-13	-44.00	-75.83	-65.04	1.74	11.93	V
Highest	1696	-62.16	-13	-49.16	-75.22	-67.71	1.24	8.94	H
	2536	-58.67	-13	-45.67	-75.47	-65.61	1.44	10.53	H
	3384	-57.83	-13	-44.83	-75.88	-65.96	1.77	12.05	H
	1696	-62.06	-13	-49.06	-75.03	-67.61	1.24	8.94	V
	2536	-58.85	-13	-45.85	-75.86	-65.79	1.44	10.53	V
	3384	-57.22	-13	-44.22	-75.91	-65.35	1.77	12.05	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**Part 24E GPRS 1900**

GPRS 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-44.38	-13	-31.38	-64.92	-54.69	1.97	12.28	H
	5548	-41.44	-13	-28.44	-65.02	-51.56	2.14	12.27	H
	7403	-47.72	-13	-34.72	-75.83	-55.72	2.17	10.17	H
	3700	-42.21	-13	-29.21	-63.27	-52.52	1.97	12.28	V
	5548	-41.88	-13	-28.88	-66.08	-52.00	2.14	12.27	V
	7403	-47.71	-13	-34.71	-75.78	-55.71	2.17	10.17	V
Middle	3763	-42.47	-13	-29.47	-63.16	-52.71	2.01	12.24	H
	5639	-38.75	-13	-25.75	-62.41	-49.02	2.12	12.39	H
	7520	-47.86	-13	-34.86	-75.66	-55.82	2.11	10.07	H
	3763	-43.59	-13	-30.59	-64.78	-53.83	2.01	12.24	V
	5639	-40.15	-13	-27.15	-64.43	-50.42	2.12	12.39	V
	7520	-48.03	-13	-35.03	-75.72	-55.99	2.11	10.07	V
Highest	3819	-41.03	-13	-28.03	-61.83	-51.20	2.04	12.21	H
	5730	-40.37	-13	-27.37	-64.46	-50.79	2.10	12.52	H
	7641	-48.37	-13	-35.37	-75.69	-56.76	2.11	10.51	H
	3819	-42.27	-13	-29.27	-63.54	-52.44	2.04	12.21	V
	5730	-36.76	-13	-23.76	-61.4	-47.18	2.10	12.52	V
	7641	-48.18	-13	-35.18	-75.55	-56.57	2.11	10.51	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**Part 24E EDGE 1900**

EDGE 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-50.59	-13	-37.59	-71.13	-60.90	1.97	12.28	H
	5548	-45.54	-13	-32.54	-69.12	-55.66	2.14	12.27	H
	7400	-47.57	-13	-34.57	-75.68	-55.57	2.18	10.18	H
	3700	-45.78	-13	-32.78	-66.84	-56.09	1.97	12.28	V
	5548	-46.69	-13	-33.69	-70.89	-56.81	2.14	12.27	V
	7400	-47.45	-13	-34.45	-75.53	-55.45	2.18	10.18	V
Middle	3763	-49.53	-13	-36.53	-70.22	-59.77	2.01	12.24	H
	5639	-43.56	-13	-30.56	-67.22	-53.83	2.12	12.39	H
	7522	-47.87	-13	-34.87	-75.65	-55.83	2.11	10.08	H
	3763	-46.91	-13	-33.91	-68.1	-57.15	2.01	12.24	V
	5639	-42.83	-13	-29.83	-67.11	-53.10	2.12	12.39	V
	7522	-47.86	-13	-34.86	-75.54	-55.82	2.11	10.08	V
Highest	3819	-48.37	-13	-35.37	-69.17	-58.54	2.04	12.21	H
	5730	-43.92	-13	-30.92	-68.01	-54.34	2.10	12.52	H
	7641	-48.23	-13	-35.23	-75.55	-56.62	2.11	10.51	H
	3819	-47.66	-13	-34.66	-68.93	-57.83	2.04	12.21	V
	5730	-39.60	-13	-26.60	-64.24	-50.02	2.10	12.52	V
	7641	-47.69	-13	-34.69	-75.06	-56.08	2.11	10.51	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**Part 24E WCDMA 1900**

WCDMA 1900									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-54.74	-13	-41.74	-75.28	-65.05	1.97	12.28	H
	5555	-51.78	-13	-38.78	-75.35	-61.91	2.14	12.28	H
	7410	-47.69	-13	-34.69	-75.77	-55.68	2.17	10.16	H
	3700	-53.88	-13	-40.88	-74.94	-64.19	1.97	12.28	V
	5555	-49.33	-13	-36.33	-73.52	-59.46	2.14	12.28	V
	7410	-47.54	-13	-34.54	-75.58	-55.53	2.17	10.16	V
Middle	3756	-54.31	-13	-41.31	-74.98	-64.55	2.00	12.25	H
	5646	-50.06	-13	-37.06	-73.74	-60.34	2.12	12.40	H
	7520	-48.16	-13	-35.16	-75.96	-56.12	2.11	10.07	H
	3756	-53.33	-13	-40.33	-74.5	-63.57	2.00	12.25	V
	5646	-49.93	-13	-36.93	-74.23	-60.21	2.12	12.40	V
	7520	-47.84	-13	-34.84	-75.53	-55.80	2.11	10.07	V
Highest	3819	-53.80	-13	-40.80	-74.6	-63.97	2.04	12.21	H
	5722	-51.22	-13	-38.22	-75.27	-61.63	2.10	12.51	H
	7630	-48.17	-13	-35.17	-75.47	-56.52	2.11	10.47	H
	3819	-53.39	-13	-40.39	-74.66	-63.56	2.04	12.21	V
	5722	-50.72	-13	-37.72	-75.32	-61.13	2.10	12.51	V
	7630	-48.20	-13	-35.20	-75.54	-56.55	2.11	10.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**Part 27L WCDMA 1700**

WCDMA 1700									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3425	-56.45	-13	-43.45	-75.53	-66.82	1.81	12.18	H
	5135	-44.44	-13	-31.44	-67.85	-54.26	2.30	12.13	H
	6850	-49.62	-13	-36.62	-75.82	-58.30	2.37	11.05	H
	3425	-56.10	-13	-43.10	-75.81	-66.47	1.81	12.18	V
	5135	-48.88	-13	-35.88	-72.86	-58.70	2.30	12.13	V
	6850	-48.39	-13	-35.39	-75.15	-57.07	2.37	11.05	V
Middle	3462	-56.76	-13	-43.76	-76.19	-67.21	1.84	12.29	H
	5198	-45.33	-13	-32.33	-68.79	-55.19	2.28	12.14	H
	6930	-49.88	-13	-36.88	-76.33	-58.45	2.40	10.97	H
	3462	-56.23	-13	-43.23	-76.19	-66.68	1.84	12.29	V
	5198	-48.78	-13	-35.78	-72.79	-58.64	2.28	12.14	V
	6930	-49.13	-13	-36.13	-76.2	-57.70	2.40	10.97	V
Highest	3505	-56.16	-13	-43.16	-75.97	-66.68	1.87	12.40	H
	5258	-46.04	-13	-33.04	-69.55	-55.94	2.25	12.15	H
	7011	-49.02	-13	-36.02	-75.75	-57.49	2.41	10.88	H
	3505	-55.57	-13	-42.57	-75.83	-66.09	1.87	12.40	V
	5258	-49.43	-13	-36.43	-73.47	-59.33	2.25	12.15	V
	7011	-48.40	-13	-35.40	-75.78	-56.87	2.41	10.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.