



FCC Test Report

APPLICANT : OnePlus Technology (Shenzhen) Co., Ltd.
EQUIPMENT : OnePlus Magnetic Power Bank Air 5000mAh
BRAND NAME : ONEPLUS
MODEL NAME : MPBV02
FCC ID : 2ABZ2-MPBV02
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : Apr. 11, 2025 ~ Apr. 14, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang



Approved by: Fly Liang

Sportun International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

| | |
|--|-----------|
| REVISION HISTORY..... | 3 |
| SUMMARY OF TEST RESULT | 4 |
| 1. GENERAL DESCRIPTION..... | 5 |
| 1.1. Applicant..... | 5 |
| 1.2. Manufacturer | 5 |
| 1.3. Product Feature of Equipment Under Test | 5 |
| 1.4. Product Specification of Equipment Under Test | 5 |
| 1.5. Modification of EUT | 5 |
| 1.6. Test Location..... | 6 |
| 1.7. Test Software | 6 |
| 1.8. Applicable Standards | 6 |
| 2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... | 7 |
| 2.1. Test Mode | 7 |
| 2.2. Connection Diagram of Test System | 8 |
| 2.3. Support Unit used in test configuration and system..... | 8 |
| 2.4. EUT Operation Test Setup | 8 |
| 3. TEST RESULT..... | 9 |
| 3.1. Test of AC Conducted Emission Measurement | 9 |
| 3.2. Test of Radiated Emission Measurement | 13 |
| 4. LIST OF MEASURING EQUIPMENT | 18 |
| 5. MEASUREMENT UNCERTAINTY | 19 |

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|----------|-----------------------|-----------------|--------|--|
| 3.1 | 15.107 | AC Conducted Emission | < 15.107 limits | PASS | Under limit 17.95 dB at 0.92 MHz |
| 3.2 | 15.109 | Radiated Emission | < 15.109 limits | PASS | Under limit 6.73 dB at 48.43 MHz for Quasi-Peak |

Conformity Assessment Condition:

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. Please refer to each test results in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1. General Description

1.1. Applicant

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04, and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen, Guangdong, P.R. China.

1.2. Manufacturer

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04, and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen, Guangdong, P.R. China.

1.3. Product Feature of Equipment Under Test

| Product Feature | |
|--|--|
| Equipment | OnePlus Magnetic Power Bank Air 5000mAh |
| Brand Name | ONEPLUS |
| Model Name | MPBV02 |
| FCC ID | 2ABZ2-MPBV02 |
| EUT supports Radios application | WPT |
| SN Code | Conduction: O631446000018F3L002105 Radiation: O63146000018F3L005528 |
| HW Version | V0.1 |
| SW Version | V0.1 |
| EUT Stage | Production Unit |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

| Standards-related Product Specification | |
|---|------------------------|
| Tx Frequency | WPT: 111kHz~ 148.5 kHz |
| Rx Frequency | WPT: 111kHz~ 148.5 kHz |
| Antenna Type | WPT: Loop Antenna |
| Type of Modulation | WPT: ASK |

1.5. Modification of EUT

No modifications are made to the EUT during all test items.



1.6. Test Location

Sportun International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

| | | | |
|---------------------------|---|----------------------------|---------------------------------------|
| Test Firm | Sportun International Inc. (Shenzhen) | | |
| Test Site Location | 101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985 | | |
| Test Site No. | Sportun Site No. | FCC Designation No. | FCC Test Firm Registration No. |
| | CO02-SZ 03CH05-SZ | CN1256 | 421272 |

1.7. Test Software

| Item | Site | Manufacturer | Name | Version |
|------|-----------|--------------|------|-------------|
| 1. | 03CH05-SZ | AUDIX | E3 | 6.2009-8-24 |
| 2. | CO02-SZ | AUDIX | E3 | 6.120613b |

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

| Test Items | Function Type |
|-----------------------|---|
| AC Conducted Emission | Mode 1: EUT wireless charging to Phone + USB Cable (Charging from Adapter) Mode 2: EUT + USB Cable (Charging from Adapter) |
| Radiated Emissions | Mode 1: EUT charging to Phone with USB Cable Mode 2: EUT wireless charging to Phone + USB Cable (Charging from Adapter) Mode 3: EUT + USB Cable (Charging from Adapter) |

Remark:

1. The worst case of AC is mode 1; only the test data of this mode is reported.
2. The worst case of RE is mode 2; only the test data of this mode is reported.

2.2. Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model Name | FCC ID | Data Cable | Power Cord |
|------|-----------|------------|------------|--------|------------|------------|
| 1. | Phone | OPPO | CPH2653 | N/A | N/A | N/A |
| 2. | Adapter | Apple | A2244 | N/A | N/A | N/A |
| 3. | Adapter | Huawei | N/A | N/A | N/A | N/A |

2.4. EUT Operation Test Setup

The following program installed in the EUT was programmed during the test.

1. Turn on WPT function.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

| Frequency of emission (MHz) | Conducted limit (dBuV) | |
|--------------------------------|------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission





| Test Engineer : | Nathon | Temperature : | 22 ~ 24°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|----------------------------|------------|------------|------------|-------------|------------|------------|------------|-------------|------------|--------|--|-----|------|----|------|------|----|----|--|---|------|-------|--------|-------|------|------|-------|---------|---|------|-------|--------|-------|-------|------|-------|----|---|------|-------|--------|-------|------|------|-------|---------|---|------|-------|--------|-------|-------|------|-------|----|---|------|-------|--------|-------|------|------|-------|---------|---|------|-------|--------|-------|-------|------|-------|----|---|------|-------|--------|-------|------|------|-------|---------|---|------|-------|--------|-------|-------|------|-------|----|---|------|-------|--------|-------|------|------|-------|---------|----|------|-------|--------|-------|-------|------|-------|----|----|------|-------|--------|-------|------|------|-------|---------|------|------|-------|--------|-------|-------|------|-------|----|
| | | Relative Humidity : | 44 ~ 50% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Voltage : | 120Vac / 60Hz | Phase : | Neutral | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark : | All emissions not reported here are more than 10 dB below the prescribed limit. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Site | : CO02-SZ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Condition | : FCC 15B_QP LISN_2025-N NEUTRAL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th></th> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>Read Level</th> <th>LISN Factor</th> <th>Cable Loss</th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB</th> <th>dBuV</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0.17</td> <td>29.26</td> <td>-25.46</td> <td>54.72</td> <td>9.31</td> <td>9.77</td> <td>10.18</td> <td>Average</td> </tr> <tr> <td>2</td> <td>0.17</td> <td>37.36</td> <td>-27.36</td> <td>64.72</td> <td>17.41</td> <td>9.77</td> <td>10.18</td> <td>QP</td> </tr> <tr> <td>3</td> <td>0.21</td> <td>26.08</td> <td>-27.24</td> <td>53.32</td> <td>6.10</td> <td>9.80</td> <td>10.18</td> <td>Average</td> </tr> <tr> <td>4</td> <td>0.21</td> <td>40.18</td> <td>-23.14</td> <td>63.32</td> <td>20.20</td> <td>9.80</td> <td>10.18</td> <td>QP</td> </tr> <tr> <td>5</td> <td>0.25</td> <td>29.13</td> <td>-22.69</td> <td>51.82</td> <td>9.41</td> <td>9.53</td> <td>10.19</td> <td>Average</td> </tr> <tr> <td>6</td> <td>0.25</td> <td>37.73</td> <td>-24.09</td> <td>61.82</td> <td>18.01</td> <td>9.53</td> <td>10.19</td> <td>QP</td> </tr> <tr> <td>7</td> <td>0.31</td> <td>26.64</td> <td>-23.33</td> <td>49.97</td> <td>6.60</td> <td>9.83</td> <td>10.21</td> <td>Average</td> </tr> <tr> <td>8</td> <td>0.31</td> <td>34.54</td> <td>-25.43</td> <td>59.97</td> <td>14.50</td> <td>9.83</td> <td>10.21</td> <td>QP</td> </tr> <tr> <td>9</td> <td>0.58</td> <td>26.07</td> <td>-19.93</td> <td>46.00</td> <td>6.20</td> <td>9.63</td> <td>10.24</td> <td>Average</td> </tr> <tr> <td>10</td> <td>0.58</td> <td>36.17</td> <td>-19.83</td> <td>56.00</td> <td>16.30</td> <td>9.63</td> <td>10.24</td> <td>QP</td> </tr> <tr> <td>11</td> <td>0.92</td> <td>28.05</td> <td>-17.95</td> <td>46.00</td> <td>8.10</td> <td>9.72</td> <td>10.23</td> <td>Average</td> </tr> <tr> <td>12 *</td> <td>0.92</td> <td>37.85</td> <td>-18.15</td> <td>56.00</td> <td>17.90</td> <td>9.72</td> <td>10.23</td> <td>QP</td> </tr> </tbody> </table> | | | | | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark | | MHz | dBuV | dB | dBuV | dBuV | dB | dB | | 1 | 0.17 | 29.26 | -25.46 | 54.72 | 9.31 | 9.77 | 10.18 | Average | 2 | 0.17 | 37.36 | -27.36 | 64.72 | 17.41 | 9.77 | 10.18 | QP | 3 | 0.21 | 26.08 | -27.24 | 53.32 | 6.10 | 9.80 | 10.18 | Average | 4 | 0.21 | 40.18 | -23.14 | 63.32 | 20.20 | 9.80 | 10.18 | QP | 5 | 0.25 | 29.13 | -22.69 | 51.82 | 9.41 | 9.53 | 10.19 | Average | 6 | 0.25 | 37.73 | -24.09 | 61.82 | 18.01 | 9.53 | 10.19 | QP | 7 | 0.31 | 26.64 | -23.33 | 49.97 | 6.60 | 9.83 | 10.21 | Average | 8 | 0.31 | 34.54 | -25.43 | 59.97 | 14.50 | 9.83 | 10.21 | QP | 9 | 0.58 | 26.07 | -19.93 | 46.00 | 6.20 | 9.63 | 10.24 | Average | 10 | 0.58 | 36.17 | -19.83 | 56.00 | 16.30 | 9.63 | 10.24 | QP | 11 | 0.92 | 28.05 | -17.95 | 46.00 | 8.10 | 9.72 | 10.23 | Average | 12 * | 0.92 | 37.85 | -18.15 | 56.00 | 17.90 | 9.72 | 10.23 | QP |
| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0.17 | 29.26 | -25.46 | 54.72 | 9.31 | 9.77 | 10.18 | Average | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | 0.17 | 37.36 | -27.36 | 64.72 | 17.41 | 9.77 | 10.18 | QP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | 0.21 | 26.08 | -27.24 | 53.32 | 6.10 | 9.80 | 10.18 | Average | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | 0.21 | 40.18 | -23.14 | 63.32 | 20.20 | 9.80 | 10.18 | QP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | 0.25 | 29.13 | -22.69 | 51.82 | 9.41 | 9.53 | 10.19 | Average | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | 0.25 | 37.73 | -24.09 | 61.82 | 18.01 | 9.53 | 10.19 | QP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | 0.31 | 26.64 | -23.33 | 49.97 | 6.60 | 9.83 | 10.21 | Average | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | 0.31 | 34.54 | -25.43 | 59.97 | 14.50 | 9.83 | 10.21 | QP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 | 0.58 | 26.07 | -19.93 | 46.00 | 6.20 | 9.63 | 10.24 | Average | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 0.58 | 36.17 | -19.83 | 56.00 | 16.30 | 9.63 | 10.24 | QP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 11 | 0.92 | 28.05 | -17.95 | 46.00 | 8.10 | 9.72 | 10.23 | Average | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 * | 0.92 | 37.85 | -18.15 | 56.00 | 17.90 | 9.72 | 10.23 | QP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Note:

1. Level(dB μ V) = Read Level(dB μ V) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dB μ V) – Limit Line(dB μ V)



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|--------------------|--------------------------------------|----------------------------------|
| 30 – 88 | 100 | 3 |
| 88 – 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz






3.2.5. Test Result of Radiated Emission





| Test Engineer : | ZhanSheng Liu | Temperature : | 24 ~ 25°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------|----------------------------|--------------|-------------|-------|------------|-------|-------------|--------------|--------|-------|-------|--------|-----|--------------|----|--------------|------------|------|----|----|----|---|-------|-------|-------|-------|-------|-------|------|-------|------------|---|--------|-------|--------|-------|-------|-------|------|-------|--------------|-----|--------|-------|--------|-------|-------|-------|------|-------|--------------|---|--------|-------|--------|-------|-------|-------|------|-------|--------------|---|--------|-------|--------|-------|-------|-------|------|-------|--------------|---|--------|-------|--------|-------|-------|-------|------|-------|--------------|---|---------|-------|--------|-------|-------|-------|------|-------|--------------|---|---------|-------|--------|-------|-------|-------|-------|-------|--------------|---|---------|-------|--------|-------|-------|-------|-------|-------|--------------|----|----------|-------|--------|-------|-------|-------|-------|-------|--------------|----|----------|-------|--------|-------|-------|-------|-------|-------|--------------|----|----------|-------|--------|-------|-------|-------|-------|-------|--------------|
| | | Relative Humidity : | 48 ~ 49% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Distance : | 3m | Polarization : | Vertical | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Site : 03CH05-SZ Condition : FCC CLASS-B 3m VULB9168-01001 VERTICAL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Freq</th> <th style="text-align: center;">Level</th> <th style="text-align: center;">Over Limit</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">ReadAntenna</th> <th style="text-align: center;">Cable</th> <th style="text-align: center;">Preamp</th> <th style="text-align: center;">A/Pos</th> <th style="text-align: center;">T/Pos</th> <th rowspan="2" style="text-align: center;">Remark</th> </tr> <tr> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBμV/m</th> <th style="text-align: center;">dB</th> <th style="text-align: center;">dBμV/m</th> <th style="text-align: center;">dBμV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dB</th> <th style="text-align: center;">dB</th> <th style="text-align: center;">cm</th> </tr> </thead> <tbody> <tr> <td>1</td><td>48.43</td><td>33.27</td><td>-6.73</td><td>40.00</td><td>46.60</td><td>19.68</td><td>1.63</td><td>34.64</td><td>100 244 QP</td></tr> <tr> <td>2</td><td>139.61</td><td>24.46</td><td>-19.04</td><td>43.50</td><td>38.89</td><td>18.38</td><td>2.27</td><td>35.08</td><td>--- --- Peak</td></tr> <tr> <td>3 *</td><td>205.57</td><td>28.60</td><td>-14.90</td><td>43.50</td><td>44.60</td><td>16.09</td><td>2.78</td><td>34.87</td><td>--- --- Peak</td></tr> <tr> <td>4</td><td>315.18</td><td>21.53</td><td>-24.47</td><td>46.00</td><td>33.59</td><td>19.76</td><td>3.28</td><td>35.10</td><td>--- --- Peak</td></tr> <tr> <td>5</td><td>448.07</td><td>25.00</td><td>-21.00</td><td>46.00</td><td>32.99</td><td>22.96</td><td>3.46</td><td>34.41</td><td>--- --- Peak</td></tr> <tr> <td>6</td><td>581.93</td><td>27.49</td><td>-18.51</td><td>46.00</td><td>32.87</td><td>25.50</td><td>3.56</td><td>34.44</td><td>--- --- Peak</td></tr> <tr> <td>7</td><td>2544.00</td><td>42.76</td><td>-31.24</td><td>74.00</td><td>55.82</td><td>32.98</td><td>7.36</td><td>53.40</td><td>--- --- Peak</td></tr> <tr> <td>8</td><td>5792.00</td><td>45.29</td><td>-28.71</td><td>74.00</td><td>51.78</td><td>35.97</td><td>10.12</td><td>52.58</td><td>--- --- Peak</td></tr> <tr> <td>9</td><td>8928.00</td><td>46.71</td><td>-27.29</td><td>74.00</td><td>48.87</td><td>37.06</td><td>12.28</td><td>51.50</td><td>--- --- Peak</td></tr> <tr> <td>10</td><td>11196.00</td><td>47.33</td><td>-26.67</td><td>74.00</td><td>46.63</td><td>38.50</td><td>13.40</td><td>51.20</td><td>--- --- Peak</td></tr> <tr> <td>11</td><td>14877.00</td><td>46.09</td><td>-27.91</td><td>74.00</td><td>42.27</td><td>40.28</td><td>15.40</td><td>51.86</td><td>--- --- Peak</td></tr> <tr> <td>12</td><td>16902.00</td><td>46.44</td><td>-27.56</td><td>74.00</td><td>42.30</td><td>42.00</td><td>15.26</td><td>53.12</td><td>--- --- Peak</td></tr> </tbody> </table> | | | | Freq | Level | Over Limit | Limit | ReadAntenna | Cable | Preamp | A/Pos | T/Pos | Remark | MHz | dB μ V/m | dB | dB μ V/m | dB μ V | dB/m | dB | dB | cm | 1 | 48.43 | 33.27 | -6.73 | 40.00 | 46.60 | 19.68 | 1.63 | 34.64 | 100 244 QP | 2 | 139.61 | 24.46 | -19.04 | 43.50 | 38.89 | 18.38 | 2.27 | 35.08 | --- --- Peak | 3 * | 205.57 | 28.60 | -14.90 | 43.50 | 44.60 | 16.09 | 2.78 | 34.87 | --- --- Peak | 4 | 315.18 | 21.53 | -24.47 | 46.00 | 33.59 | 19.76 | 3.28 | 35.10 | --- --- Peak | 5 | 448.07 | 25.00 | -21.00 | 46.00 | 32.99 | 22.96 | 3.46 | 34.41 | --- --- Peak | 6 | 581.93 | 27.49 | -18.51 | 46.00 | 32.87 | 25.50 | 3.56 | 34.44 | --- --- Peak | 7 | 2544.00 | 42.76 | -31.24 | 74.00 | 55.82 | 32.98 | 7.36 | 53.40 | --- --- Peak | 8 | 5792.00 | 45.29 | -28.71 | 74.00 | 51.78 | 35.97 | 10.12 | 52.58 | --- --- Peak | 9 | 8928.00 | 46.71 | -27.29 | 74.00 | 48.87 | 37.06 | 12.28 | 51.50 | --- --- Peak | 10 | 11196.00 | 47.33 | -26.67 | 74.00 | 46.63 | 38.50 | 13.40 | 51.20 | --- --- Peak | 11 | 14877.00 | 46.09 | -27.91 | 74.00 | 42.27 | 40.28 | 15.40 | 51.86 | --- --- Peak | 12 | 16902.00 | 46.44 | -27.56 | 74.00 | 42.30 | 42.00 | 15.26 | 53.12 | --- --- Peak |
| Freq | Level | Over Limit | Limit | ReadAntenna | Cable | Preamp | A/Pos | T/Pos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dB μ V/m | dB | dB μ V/m | dB μ V | dB/m | dB | dB | cm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 48.43 | 33.27 | -6.73 | 40.00 | 46.60 | 19.68 | 1.63 | 34.64 | 100 244 QP | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | 139.61 | 24.46 | -19.04 | 43.50 | 38.89 | 18.38 | 2.27 | 35.08 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 * | 205.57 | 28.60 | -14.90 | 43.50 | 44.60 | 16.09 | 2.78 | 34.87 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | 315.18 | 21.53 | -24.47 | 46.00 | 33.59 | 19.76 | 3.28 | 35.10 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | 448.07 | 25.00 | -21.00 | 46.00 | 32.99 | 22.96 | 3.46 | 34.41 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | 581.93 | 27.49 | -18.51 | 46.00 | 32.87 | 25.50 | 3.56 | 34.44 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | 2544.00 | 42.76 | -31.24 | 74.00 | 55.82 | 32.98 | 7.36 | 53.40 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | 5792.00 | 45.29 | -28.71 | 74.00 | 51.78 | 35.97 | 10.12 | 52.58 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 | 8928.00 | 46.71 | -27.29 | 74.00 | 48.87 | 37.06 | 12.28 | 51.50 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 11196.00 | 47.33 | -26.67 | 74.00 | 46.63 | 38.50 | 13.40 | 51.20 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 11 | 14877.00 | 46.09 | -27.91 | 74.00 | 42.27 | 40.28 | 15.40 | 51.86 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 16902.00 | 46.44 | -27.56 | 74.00 | 42.30 | 42.00 | 15.26 | 53.12 | --- --- Peak | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Note:

1. Level(dB μ V/m) = Read Level(dB μ V) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
2. Over Limit(dB) = Level(dB μ V/m) - Limit Line(dB μ V/m)



4. List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|---------------------------|----------------|-----------|--------------|-----------------|------------------|---------------|---------------|-----------------------|
| EMI Test Receiver | R&S | ESR7 | 102261 | 9kHz~7GHz | Apr. 08, 2025 | Apr. 14, 2025 | Apr. 07, 2026 | Radiation (03CH05-SZ) |
| EXA Spectrum Analyzer | KEYSIGHT | N9010B | MY59071191 | 10Hz~44GHz | Apr. 08, 2025 | Apr. 14, 2025 | Apr. 07, 2026 | Radiation (03CH05-SZ) |
| Log-periodic Antenna | SCHWARZBECK | VULB 9168 | 01001 | 20MHz~1.5GHz | Jul. 08, 2024 | Apr. 14, 2025 | Jul. 07, 2025 | Radiation (03CH05-SZ) |
| Amplifier | EM Electronics | EM330 | 060756 | 0.01Hz ~3000MHz | Apr. 08, 2025 | Apr. 14, 2025 | Apr. 07, 2026 | Radiation (03CH05-SZ) |
| Double Ridge Horn Antenna | SCHWARZBECK | BBHA9120D | 9120D-2206 | 1GHz~18GHz | Apr. 08, 2025 | Apr. 14, 2025 | Apr. 07, 2026 | Radiation (03CH05-SZ) |
| HF Amplifier | EM Electronics | EM01G18GA | 060781 | 1GHz~18GHz | Apr. 08, 2025 | Apr. 14, 2025 | Apr. 07, 2026 | Radiation (03CH05-SZ) |
| HF Amplifier | EM Electronics | EM18G40G | 060778 | 18GHz~40GHz | Apr. 08, 2025 | Apr. 14, 2025 | Apr. 07, 2026 | Radiation (03CH05SZ) |
| Horn Antenna | SCHWARZBECK | BBHA9170 | 00983 | 15GHz~40GHz | Apr. 08, 2025 | Apr. 14, 2025 | Apr. 07, 2026 | Radiation (03CH05-SZ) |
| AC Power Source | APC | AFV-S-600 | F119050013 | N/A | Oct. 14, 2024 | Apr. 14, 2025 | Oct. 13, 2025 | Radiation (03CH05-SZ) |
| Turn Table | EMEC | T-200-S-1 | 060925-T | 0~360 degree | NCR | Apr. 14, 2025 | NCR | Radiation (03CH05-SZ) |
| Antenna Mast | EMEC | MBS-400-1 | 060927 | 1 m~4 m | NCR | Apr. 14, 2025 | NCR | Radiation (03CH05-SZ) |
| EMI Receiver | R&S | ESR7 | 102297 | 9kHz~7GHz; | Jul. 03, 2024 | Apr. 11, 2025 | Jul. 02, 2025 | Conduction (CO02-SZ) |
| AC LISN | R&S | ENV216 | 101499 | 9kHz~30MHz | Jul. 03, 2024 | Apr. 11, 2025 | Jul. 02, 2025 | Conduction (CO02-SZ) |
| AC Power Source | CHROMA | 61601 | 616010002470 | 100Vac~250Vac | Dec.25, 2024 | Apr. 11, 2025 | Dec. 24, 2025 | Conduction (CO02-SZ) |

NCR: No Calibration Required



5. Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

| | |
|--|--------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 2.5 dB |
|--|--------|

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|--|--------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 4.2 dB |
|--|--------|

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

| | |
|--|--------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 5.1 dB |
|--|--------|

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

| | |
|--|--------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 4.1 dB |
|--|--------|

----- THE END -----