

**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 Issue 3**

TEST REPORT

For

WIFI+BT Module

MODEL NUMBER: DCT5BM1601

REPORT NUMBER: 4791809672-1-RF-3

ISSUE DATE: June 24, 2025

**FCC ID:2AC23-DCT5B
IC:12290A-DCT5B**

Prepared for

**Hui Zhou Gaoshengda Technology Co.,LTD
No.6,Qiaoguang Road,Chenjiang Street,Zhongkai High-tech
Zone,Huizhou,Guangdong,China**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

**Tel: +86 769 22038881
Fax: +86 769 33244054
Website: www.ul.com**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	June 24, 2025	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.2.3.1	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.5	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C, ISED RSS-247 Issue 3> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS	7
2. TEST METHODOLOGY	8
3. FACILITIES AND ACCREDITATION	8
4. CALIBRATION AND UNCERTAINTY	9
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>9</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>9</i>
5. EQUIPMENT UNDER TEST	10
5.1. <i>DESCRIPTION OF EUT</i>	<i>10</i>
5.2. <i>CHANNEL LIST</i>	<i>10</i>
5.3. <i>MAXIMUM POWER</i>	<i>11</i>
5.4. <i>TEST CHANNEL CONFIGURATION</i>	<i>11</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	<i>12</i>
5.6. <i>WORST-CASE CONFIGURATIONS</i>	<i>12</i>
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>13</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST</i>	<i>14</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED	15
7. ANTENNA PORT TEST RESULTS	18
7.1. <i>CONDUCTED OUTPUT POWER</i>	<i>18</i>
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i>	<i>19</i>
7.3. <i>POWER SPECTRAL DENSITY</i>	<i>21</i>
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION</i>	<i>23</i>
7.5. <i>DUTY CYCLE</i>	<i>25</i>
8. RADIATED TEST RESULTS	26
8.1. <i>RESTRICTED BANDEDGE FOR ANT0</i>	<i>34</i>
8.2. <i>RESTRICTED BANDEDGE FOR ANT1</i>	<i>52</i>
8.3. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ) FOR ANT0</i>	<i>70</i>
8.4. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ) FOR ANT1</i>	<i>76</i>
8.5. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ) FOR ANT0</i>	<i>82</i>
8.6. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ) FOR ANT1</i>	<i>106</i>
8.7. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i>	<i>130</i>
8.8. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i>	<i>133</i>
8.9. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i>	<i>135</i>

9. ANTENNA REQUIREMENT	137
10. AC POWER LINE CONDUCTED EMISSION	138
11. TEST DATA for ANT0	142
11.1. APPENDIX A1 DTS BANDWIDTH	142
11.1.1. Test Result	142
11.1.2. Test Graphs	143
11.2. APPENDIX B1: OCCUPIED CHANNEL BANDWIDTH	147
11.2.1. Test Result	147
11.2.2. Test Graphs	148
11.3. APPENDIX C1: MAXIMUM CONDUCTED OUTPUT POWER	152
11.3.1. Test Result	152
11.4. APPENDIX D1: MAXIMUM POWER SPECTRAL DENSITY	153
11.4.1. Test Result	153
11.4.2. Test Graphs	154
11.5. APPENDIX E1: BAND EDGE MEASUREMENTS	158
11.5.1. Test Result	158
11.5.2. Test Graphs	159
11.6. APPENDIX F1: CONDUCTED SPURIOUS EMISSION	162
11.6.1. Test Result	162
11.6.2. Test Graphs	163
11.7. APPENDIX G1: DUTY CYCLE	175
11.7.1. Test Result	175
11.7.2. Test Graphs	176
12. TEST DATA for ANT1	178
12.1. APPENDIX A2: DTS BANDWIDTH	178
12.1.1. Test Result	178
12.1.2. Test Graphs	179
12.2. APPENDIX B2: OCCUPIED CHANNEL BANDWIDTH	183
12.2.1. Test Result	183
12.2.2. Test Graphs	184
12.3. APPENDIX C2: MAXIMUM CONDUCTED OUTPUT POWER	188
12.3.1. Test Result	188
12.4. APPENDIX D2: MAXIMUM POWER SPECTRAL DENSITY	189
12.4.1. Test Result	189
12.4.2. Test Graphs	190
12.5. APPENDIX E2: BAND EDGE MEASUREMENTS	194
12.5.1. Test Result	194
12.5.2. Test Graphs	195
12.6. APPENDIX F2: CONDUCTED SPURIOUS EMISSION	198
12.6.1. Test Result	198
12.6.2. Test Graphs	199
12.7. APPENDIX G2: DUTY CYCLE	211

12.7.1.	Test Result.....	211
12.7.2.	Test Graphs	212

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
 Address: No.6,Qiaoguang Road,Chenjiang Street,Zhongkai High-tech Zone,Huizhou,Guangdong,China

Manufacturer Information


Company Name: Hui Zhou Gaoshengda Technology Co.,LTD
 Address: No.6,Qiaoguang Road,Chenjiang Street,Zhongkai High-tech Zone,Huizhou,Guangdong,China

EUT Information

EUT Name: WIFI+BT Module
 Model: DCT5BM1601
 Brand: GSD
 Sample Received Date: May 28, 2025
 Sample Status: Normal
 Sample ID: 8521591
 Date of Tested: May 28, 2025 to June 24, 2025

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 3	Pass

Prepared By:



Fanny Huang

Engineer Project Associate

Checked By:



Kebo Zhang

Senior Project Engineer

Approved By:



Stephen Guo

Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 Issue 3, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01
Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2013 and ISED RSS-GEN Issue 5

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p>
---------------------------	--

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101,
Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd.
Song Shan Lake Branch had been calibrated and compared to the open field sites and the test
anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to
measurements obtained on an open field site. And these measurements below 30 MHz had
been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz) 5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz) ±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	WIFI+BT Module
Model	DCT5BM1601

Frequency Range:	2412 MHz to 2462 MHz
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Radio Technology:	IEEE 802.11b/g/n HT20/11n HT40
Normal Test Voltage:	DC 3.3 V

5.2. CHANNEL LIST

Channel List For Bandwidth=20 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List For Bandwidth=40 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.3. MAXIMUM POWER

ANT0

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)	Maximum AVG EIRP (dBm)
b	2412 ~ 2462	1-11[11]	16.23	17.95
g	2412 ~ 2462	1-11[11]	15.68	17.40
n HT20	2412 ~ 2462	1-11[11]	14.39	16.11
n HT40	2422 ~ 2452	3-9[7]	14.58	16.30

ANT1

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)	Maximum AVG EIRP (dBm)
b	2412 ~ 2462	1-11[11]	16.66	19.64
g	2412 ~ 2462	1-11[11]	15.75	18.73
n HT20	2412 ~ 2462	1-11[11]	14.66	17.64
n HT40	2422 ~ 2452	3-9[7]	14.63	17.61

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band						
Test Software		QA Tool				
Modulation Mode	Transmit Antenna Number	Test Channel				
		NCB: 20MHz			NCB: 40MHz	
		CH 1	CH 6	CH 11	CH 3	CH 6
802.11b	0	20	20	20	/	
	1	20	20	20		
802.11g	0	1E	1E	1E		
	1	1E	1E	1E		
802.11n HT20	0	1E	1E	1E	/	
	1	1E	1E	1E		
802.11n HT40	0	/			1E	1E
	1	/			1E	1E

5.6. WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
 802.11g mode: 6 Mbps
 802.11n HT20 mode: MCS0
 802.11n HT40 mode: MCS0

All modes only support SISO mode..

The EUT has 2 separate antennas which correspond to 2 separate antenna ports. Core 0 and Core 1 correspond to antenna 0 and antenna 1 respectively.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
0(external)	2412-2462	PIFA antenna	1.72
1(on board)	2412-2462	PIFA antenna	2.98

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 0 or ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 0 or ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 0 or ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 0 or ANT 1 can be used as transmitting/receiving antenna.
Note: 1.BT&WLAN 2.4G, BT & WLAN 5G, WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client)		

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E42-80	/
2	AC Adaptor	Lenovo	ADLX65YCC3D	Input: AC 100-240V, 1.8A, 50-60Hz Output: DC 20V, 3.25A, 65.0W Max

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



Note: AC Adaptor only use for AC POWER LINE CONDUCTED EMISSION test.

6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.27,2024	Dec.26,2025
Vector Signal Generator	R&S	SMBV100A	261637	Sep.28, 2024	Sep.27, 2025
Signal Generator	R&S	SMB100A	178553	Sep.28, 2024	Sep.27, 2025
Signal Analyzer	R&S	FSV40	101118	Sep.28, 2024	Sep.27, 2025
Software					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.13, 2024	Sep.12, 2025
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.28, 2024	Sep.27, 2025
DC power supply	Keysight	E3642A	MY55159130	Sep.28, 2024	Sep.27, 2025
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.28, 2024	Sep.27, 2025
Attenuator	Aglient	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025
RF Control Unit	Tonsend	JS0806-2	23B80620666	Dec.27,2024	Dec.26,2025
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.28, 2024	Sep.27, 2025
Two-Line V-Network	R&S	ENV216	101983	Sep.28, 2024	Sep.27, 2025
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.28, 2024	Sep.27, 2025
Software					
Description		Manufacturer		Name	Version
Test Software for Conducted Emissions		Farad		EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.28, 2024	Sep.27, 2025
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.28, 2024	Sep.27, 2025
EMI Measurement Receiver	R&S	ESR26	101377	Sep.28, 2024	Sep.27, 2025
Horn Antenna	TDK	HRN-0118	130940	Dec.10, 2024	Dec.11, 2027
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.28, 2024	Sep.27, 2025
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.28, 2024	Sep.27, 2025
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.28, 2024	Sep.27, 2025
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Sep.28, 2024	Sep.27, 2025
Software					
Description		Manufacturer		Name	Version
Test Software for Radiated Emissions		Farad		EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.8, 2024	Oct.7, 2025
Barometer	Yiyi	Baro	N/A	Oct.10, 2024	Oct.9, 2025
Attenuator	Agilent	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	49.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.3V

TEST DATE / ENGINEER

Test Date	June 12, 2025	Test By	Walker Yuan
-----------	---------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix C1&C2

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5


TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

- a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP**TEST ENVIRONMENT**

Temperature	22.6°C	Relative Humidity	49.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.3V

TEST DATE / ENGINEER

Test Date	June 12, 2025	Test By	Walker Yuan
-----------	---------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A1&A2&B1&B2

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x OBW bandwidth
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	49.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.3V

TEST DATE / ENGINEER

Test Date	June 12, 2025	Test By	Walker Yuan
-----------	---------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix D1&D2

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
measurement points	\geq span/RBW
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

Temperature	22.6°C	Relative Humidity	49.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.3V

TEST DATE / ENGINEER

Test Date	June 12, 2025	Test By	Walker Yuan
-----------	---------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E1&E2&F1&F2

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	49.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.3V

TEST DATE / ENGINEER

Test Date	June 12, 2025	Test By	Walker Yuan
-----------	---------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix G1&G2

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands ^{Note 1}		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.8 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.877 - 5.883	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2855 - 2900	
13.36 - 13.41	3260 - 3287	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dB_V/m, which is equivalent to $Y-51.5 = Z$ dB_A/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes and antennas have been tested, but only the worst data was recorded in the report.
5. $dBuA/m = dBuV/m - 20\log_{10}[120\pi] = dBuV/m - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes and antennas have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $V_{BW} = 1/T_{on}$, where: T_{on} is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.
9. *-indicates frequency is out of the restricted bands and the limit is referring to 15.247 (d) and RSS-247 clause 5.5. We had already performed the conducted non-restricted bands test, please refer to clause 7.5.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes and antennas have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	21.6°C	Relative Humidity	58.4%
Atmosphere Pressure	101kPa	Test Voltage	


TEST DATE / ENGINEER

Test Date	June 19, 2025	Test By	Mason Wang
-----------	---------------	---------	------------

TEST RESULTS


8.1. RESTRICTED BANDEdge FOR ANTO

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.785	21.33	31.71	53.04	74.00	-20.96	peak
2	2390.000	19.97	31.73	51.70	74.00	-22.30	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.785	6.56	31.71	38.27	54.00	-15.73	AVG
2	2390.000	6.62	31.73	38.35	54.00	-15.65	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dB _{UV})	Correct (dB/m)	Result (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Remark
1	2376.355	21.12	32.51	53.63	74.00	-20.37	peak
2	2390.000	19.93	32.55	52.48	74.00	-21.52	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2376.355	5.82	32.51	38.33	54.00	-15.67	AVG
2	2390.000	6.19	32.55	38.74	54.00	-15.26	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.15	32.00	52.15	74.00	-21.85	peak
2	2486.150	22.20	32.00	54.20	74.00	-19.80	peak

Test Mode:	802.11b AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	6.81	32.00	38.81	54.00	-15.19	AVG
2	2486.150	7.07	32.00	39.07	54.00	-14.93	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dB _{UV})	Correct (dB/m)	Result (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)	Remark
1	2389.810	32.15	31.73	63.88	74.00	-10.12	peak
2	2390.000	31.04	31.73	62.77	74.00	-11.23	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.810	15.14	31.73	46.87	54.00	-7.13	AVG
2	2390.000	15.37	31.73	47.10	54.00	-6.90	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	23.79	32.00	55.79	74.00	-18.21	peak
2	2485.800	24.93	32.00	56.93	74.00	-17.07	peak

Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	10.21	32.00	42.21	54.00	-11.79	AVG
2	2485.800	9.58	32.00	41.58	54.00	-12.42	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.235	31.66	31.73	63.39	74.00	-10.61	peak
2	2390.000	29.73	31.73	61.46	74.00	-12.54	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.235	12.93	31.73	44.66	54.00	-9.34	AVG
2	2390.000	13.57	31.73	45.30	54.00	-8.70	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	23.26	32.00	55.26	74.00	-18.74	peak
2	2485.200	23.74	32.00	55.74	74.00	-18.26	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.46	32.00	41.46	54.00	-12.54	AVG
2	2485.200	9.15	32.00	41.15	54.00	-12.85	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.245	34.88	31.73	66.61	74.00	-7.39	peak
2	2390.000	32.82	31.73	64.55	74.00	-9.45	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.245	17.54	31.73	49.27	54.00	-4.73	AVG
2	2390.000	17.75	31.73	49.48	54.00	-4.52	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.08	32.00	58.08	74.00	-15.92	peak
2	2488.940	28.54	32.01	60.55	74.00	-13.45	peak


Test Mode:	802.11n HT40 AV	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	11.10	32.00	43.10	54.00	-10.90	AVG
2	2488.940	10.19	32.01	42.20	54.00	-11.80	AVG


8.2. RESTRICTED BANDEDGE FOR ANT1

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.985	21.55	31.66	53.21	74.00	-20.79	peak
2	2390.000	19.79	31.73	51.52	74.00	-22.48	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.985	6.76	31.66	38.42	54.00	-15.58	AVG
2	2390.000	7.14	31.73	38.87	54.00	-15.13	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2374.170	21.88	32.49	54.37	74.00	-19.63	peak
2	2390.000	20.71	32.55	53.26	74.00	-20.74	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2374.170	7.53	32.49	40.02	54.00	-13.98	AVG
2	2390.000	8.22	32.55	40.77	54.00	-13.23	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.00	32.80	54.80	74.00	-19.20	peak
2	2486.700	23.28	32.81	56.09	74.00	-17.91	peak

Test Mode:	802.11b AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.19	32.80	41.99	54.00	-12.01	AVG
2	2486.700	9.59	32.81	42.40	54.00	-11.60	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.235	27.17	32.55	59.72	74.00	-14.28	peak
2	2390.000	26.06	32.55	58.61	74.00	-15.39	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.235	13.14	32.55	45.69	54.00	-8.31	AVG
2	2390.000	13.14	32.55	45.69	54.00	-8.31	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	29.72	32.80	62.52	74.00	-11.48	peak
2	2486.350	30.93	32.81	63.74	74.00	-10.26	peak

Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.49	32.80	47.29	54.00	-6.71	AVG
2	2486.350	13.55	32.81	46.36	54.00	-7.64	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.325	26.00	32.53	58.53	74.00	-15.47	peak
2	2390.000	25.07	32.55	57.62	74.00	-16.38	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.325	11.59	32.53	44.12	54.00	-9.88	AVG
2	2390.000	12.46	32.55	45.01	54.00	-8.99	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	27.31	32.80	60.11	74.00	-13.89	peak
2	2488.100	30.39	32.81	63.20	74.00	-10.80	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.97	32.80	47.77	54.00	-6.23	AVG
2	2488.100	14.20	32.81	47.01	54.00	-6.99	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.30	32.55	60.85	74.00	-13.15	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	14.34	32.55	46.89	54.00	-7.11	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	29.85	32.80	62.65	74.00	-11.35	peak
2	2486.070	30.68	32.80	63.48	74.00	-10.52	peak


Test Mode:	802.11n HT40 AV	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	16.48	32.80	49.28	54.00	-4.72	AVG
2	2486.070	15.30	32.80	48.10	54.00	-5.90	AVG


8.3. SPURIOUS EMISSIONS(1 GHZ~3 GHZ) FOR ANT0

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1234.000	46.92	-13.30	33.62	74.00	-40.38	peak
2	1438.000	47.47	-12.24	35.23	74.00	-38.77	peak
3*	1848.000	46.21	-9.99	36.22	/	/	peak
4	2234.000	47.86	-9.21	38.65	74.00	-35.35	peak
5	2412.000	65.37	-8.53	56.84	/	/	fundamental
6*	2576.000	53.84	-7.86	45.98	/	/	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1438.000	48.38	-12.06	36.32	74.00	-37.68	peak
2	1584.000	47.12	-11.22	35.90	74.00	-38.10	peak
3*	2030.000	46.74	-9.09	37.65	/	/	peak
4	2412.000	66.72	-7.71	59.01	/	/	fundamental
5*	2576.000	53.40	-6.99	46.41	/	/	peak
6	2802.000	44.59	-5.81	38.78	74.00	-35.22	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1438.000	47.87	-12.24	35.63	74.00	-38.37	peak
2	1722.000	46.28	-10.52	35.76	74.00	-38.24	peak
3*	2032.000	46.33	-9.98	36.35	/	/	peak
4	2437.000	73.17	-8.46	64.71	/	/	fundamental
5*	2600.000	51.03	-7.76	43.27	/	/	peak
6	2858.000	43.62	-6.66	36.96	74.00	-37.04	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1078.000	47.47	-13.45	34.02	74.00	-39.98	peak
2	1500.000	47.64	-11.78	35.86	74.00	-38.14	peak
3*	1962.000	45.49	-9.23	36.26	/	/	peak
4	2274.000	49.35	-8.22	41.13	74.00	-32.87	peak
5	2437.000	71.50	-7.65	63.85	/	/	fundamental
6*	2600.000	55.40	-6.86	48.54	/	/	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1440.000	46.91	-12.23	34.68	74.00	-39.32	peak
2	1606.000	46.31	-11.34	34.97	74.00	-39.03	peak
3*	1786.000	46.38	-10.06	36.32	/	/	peak
4	2260.000	47.24	-9.11	38.13	74.00	-35.87	peak
5	2462.000	48.87	-8.36	40.51	/	/	fundamental
6*	2628.000	55.54	-7.64	47.90	/	/	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	1292.000	48.07	-12.65	35.42	/	/	peak
2	1440.000	49.64	-12.06	37.58	74.00	-36.42	peak
3*	1784.000	46.77	-9.52	37.25	/	/	peak
4	2462.000	50.10	-7.53	42.57	/	/	fundamental
5*	2624.000	50.27	-6.74	43.53	/	/	peak
6	2798.000	44.72	-5.83	38.89	74.00	-35.11	peak


8.4. SPURIOUS EMISSIONS(1 GHZ~3 GHZ) FOR ANT1

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1440.000	47.70	-12.23	35.47	74.00	-38.53	peak
2*	1786.000	46.08	-10.06	36.02	/	/	peak
3*	2190.000	46.71	-9.38	37.33	/	/	peak
4	2412.000	45.96	-8.55	37.41	/	/	fundamental
5*	2648.000	45.13	-7.56	37.57	/	/	peak
6	2844.000	44.36	-6.72	37.64	74.00	-36.36	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1108.000	46.75	-13.35	33.40	74.00	-40.60	peak
2	1584.000	46.53	-11.22	35.31	74.00	-38.69	peak
3*	1844.000	46.04	-9.34	36.70	/	/	peak
4	2412.000	51.80	-7.75	44.05	/	/	fundamental
5*	2576.000	55.17	-6.99	48.18	/	/	peak
6	2858.000	44.97	-5.50	39.47	74.00	-34.53	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1442.000	46.62	-12.21	34.41	74.00	-39.59	peak
2*	1734.000	45.29	-10.43	34.86	/	/	peak
3*	1940.000	48.97	-10.05	38.92	/	/	peak
4	2437.000	47.06	-8.44	38.62	/	/	fundamental
5*	2598.000	46.42	-7.77	38.65	/	/	peak
6*	2918.000	43.59	-6.38	37.21	/	/	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1566.000	46.39	-11.35	35.04	74.00	-38.96	peak
2*	1902.000	46.66	-9.29	37.37	/	/	peak
3	2276.000	54.26	-8.20	46.06	74.00	-27.94	peak
4	2437.000	56.98	-7.63	49.35	/	/	fundamental
5*	2600.000	58.31	-6.86	51.45	/	/	peak
6	2800.000	44.75	-5.82	38.93	74.00	-35.07	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1236.000	46.65	-13.28	33.37	74.00	-40.63	peak
2	1436.000	47.14	-12.25	34.89	74.00	-39.11	peak
3*	1834.000	46.08	-9.99	36.09	/	/	peak
4*	2078.000	46.02	-9.80	36.22	/	/	peak
5	2462.000	46.97	-8.36	38.61	/	/	fundamental
6	2790.000	44.77	-6.97	37.80	74.00	-36.20	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	1640.000	46.68	-10.77	35.91	/	/	peak
2*	1912.000	47.13	-9.28	37.85	/	/	peak
3	2300.000	53.53	-8.13	45.40	74.00	-28.60	peak
4	2462.000	52.82	-7.57	45.25	/	/	fundamental
5*	2626.000	56.93	-6.72	50.21	/	/	peak
6	2838.000	44.56	-5.61	38.95	74.00	-35.05	peak


8.5. SPURIOUS EMISSIONS(3 GHZ~18 GHZ) FOR ANT0

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.90	0.50	44.40	74.00	-29.60	peak
2	7275.000	38.36	6.99	45.35	74.00	-28.65	peak
3*	8850.000	38.36	9.72	48.08	/	/	peak
4	11430.000	30.55	17.72	48.27	74.00	-25.73	peak
5*	13995.000	27.94	23.78	51.72	/	/	peak
6	18000.000	21.11	29.64	50.75	74.00	-23.25	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	42.28	1.59	43.87	74.00	-30.13	peak
2*	6675.000	37.91	6.20	44.11	/	/	peak
3*	9945.000	36.87	12.70	49.57	/	/	peak
4	12645.000	28.86	18.11	46.97	74.00	-27.03	peak
5*	14415.000	27.32	21.71	49.03	/	/	peak
6*	17025.000	24.69	25.19	49.88	/	/	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.96	0.65	43.61	74.00	-30.39	peak
2	7305.000	40.99	7.03	48.02	74.00	-25.98	peak
3*	8700.000	38.43	9.43	47.86	/	/	peak
4	11805.000	28.98	18.50	47.48	74.00	-26.52	peak
5*	14460.000	28.28	22.05	50.33	/	/	peak
6	17985.000	19.28	29.49	48.77	74.00	-25.23	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5970.000	39.27	4.08	43.35	/	/	peak
2	7305.000	39.11	7.68	46.79	74.00	-27.21	peak
3*	8670.000	38.85	9.94	48.79	/	/	peak
4	11895.000	30.91	17.43	48.34	74.00	-25.66	peak
5*	14175.000	28.98	22.26	51.24	/	/	peak
6*	16830.000	25.51	24.97	50.48	/	/	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	48.60	0.76	49.36	74.00	-24.64	peak
2*	5865.000	39.72	2.86	42.58	/	/	peak
3*	9210.000	37.29	11.13	48.42	/	/	peak
4	11850.000	28.64	18.55	47.19	74.00	-26.81	peak
5*	13995.000	26.91	23.78	50.69	/	/	peak
6	17985.000	19.63	29.49	49.12	74.00	-24.88	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.85	1.91	44.76	74.00	-29.24	peak
2	7275.000	38.15	7.67	45.82	74.00	-28.18	peak
3*	8640.000	38.15	9.90	48.05	/	/	peak
4	12195.000	28.27	17.71	45.98	74.00	-28.02	peak
5*	13560.000	28.61	20.86	49.47	/	/	peak
6	17775.000	22.76	26.21	48.97	74.00	-25.03	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	41.52	0.50	42.02	74.00	-31.98	peak
2*	5685.000	39.77	2.51	42.28	/	/	peak
3*	8955.000	38.09	10.04	48.13	/	/	peak
4	12345.000	28.47	18.90	47.37	74.00	-26.63	peak
5*	13980.000	26.41	23.71	50.12	/	/	peak
6	17985.000	19.74	29.49	49.23	74.00	-24.77	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5340.000	40.45	2.74	43.19	/	/	peak
2*	6015.000	39.02	4.19	43.21	/	/	peak
3	8340.000	39.00	9.35	48.35	74.00	-25.65	peak
4	12660.000	28.45	18.13	46.58	74.00	-27.42	peak
5*	13530.000	28.53	20.80	49.33	/	/	peak
6*	16830.000	23.85	24.97	48.82	/	/	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5940.000	39.12	3.01	42.13	/	/	peak
2	7305.000	39.73	7.03	46.76	74.00	-27.24	peak
3*	8865.000	38.16	9.76	47.92	/	/	peak
4	11670.000	27.60	18.27	45.87	74.00	-28.13	peak
5*	13530.000	27.19	22.49	49.68	/	/	peak
6	17985.000	19.63	29.49	49.12	74.00	-24.88	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5685.000	39.25	3.63	42.88	/	/	peak
2	7350.000	38.27	7.71	45.98	74.00	-28.02	peak
3*	9270.000	36.57	11.57	48.14	/	/	peak
4	11865.000	30.12	17.37	47.49	74.00	-26.51	peak
5*	13590.000	28.48	20.92	49.40	/	/	peak
6*	16770.000	24.02	24.84	48.86	/	/	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	44.94	0.76	45.70	74.00	-28.30	peak
2*	5880.000	39.20	2.90	42.10	/	/	peak
3*	9210.000	36.77	11.13	47.90	/	/	peak
4	11805.000	29.43	18.50	47.93	74.00	-26.07	peak
5*	13635.000	26.86	22.68	49.54	/	/	peak
6	17970.000	19.54	29.33	48.87	74.00	-25.13	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5850.000	39.38	3.90	43.28	/	/	peak
2	8265.000	38.85	9.21	48.06	74.00	-25.94	peak
3	9315.000	36.97	11.73	48.70	74.00	-25.30	peak
4*	12750.000	29.55	18.32	47.87	/	/	peak
5*	14430.000	28.70	21.68	50.38	/	/	peak
6*	16800.000	22.71	24.93	47.64	/	/	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4320.000	43.76	-1.08	42.68	74.00	-31.32	peak
2*	6015.000	39.36	3.20	42.56	/	/	peak
3*	8550.000	38.61	9.17	47.78	/	/	peak
4	11850.000	28.08	18.55	46.63	74.00	-27.37	peak
5*	13950.000	26.63	23.58	50.21	/	/	peak
6	17940.000	19.78	29.03	48.81	74.00	-25.19	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5685.000	39.22	3.63	42.85	/	/	peak
2	7290.000	37.36	7.68	45.04	74.00	-28.96	peak
3	9165.000	38.08	11.19	49.27	74.00	-24.73	peak
4	11850.000	29.62	17.33	46.95	74.00	-27.05	peak
5*	14400.000	27.24	21.73	48.97	/	/	peak
6	17790.000	22.65	26.25	48.90	74.00	-25.10	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5175.000	40.52	1.12	41.64	/	/	peak
2*	6675.000	37.64	5.37	43.01	/	/	peak
3*	9210.000	37.06	11.13	48.19	/	/	peak
4	11295.000	28.40	17.36	45.76	74.00	-28.24	peak
5*	13590.000	26.78	22.60	49.38	/	/	peak
6	17985.000	18.80	29.49	48.29	74.00	-25.71	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	40.90	1.59	42.49	74.00	-31.51	peak
2*	5925.000	40.25	4.02	44.27	/	/	peak
3*	9210.000	36.92	11.36	48.28	/	/	peak
4	11415.000	30.41	16.28	46.69	74.00	-27.31	peak
5*	14415.000	27.82	21.71	49.53	/	/	peak
6*	16905.000	24.95	25.06	50.01	/	/	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.39	0.76	43.15	74.00	-30.85	peak
2*	5865.000	39.70	2.86	42.56	/	/	peak
3*	8730.000	38.20	9.47	47.67	/	/	peak
4	12660.000	27.51	19.12	46.63	74.00	-27.37	peak
5*	13965.000	25.48	23.65	49.13	/	/	peak
6	17985.000	19.64	29.49	49.13	74.00	-24.87	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5940.000	38.83	4.04	42.87	/	/	peak
2	7275.000	37.39	7.67	45.06	74.00	-28.94	peak
3*	8565.000	39.36	9.78	49.14	/	/	peak
4	11820.000	30.46	17.27	47.73	74.00	-26.27	peak
5*	14415.000	28.44	21.71	50.15	/	/	peak
6*	17655.000	23.19	25.87	49.06	/	/	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4320.000	43.01	-1.08	41.93	74.00	-32.07	peak
2	7290.000	38.12	7.02	45.14	74.00	-28.86	peak
3*	9210.000	37.02	11.13	48.15	/	/	peak
4	11430.000	29.80	17.72	47.52	74.00	-26.48	peak
5*	13770.000	27.36	22.88	50.24	/	/	peak
6	17925.000	20.52	28.87	49.39	74.00	-24.61	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5925.000	39.46	4.02	43.48	/	/	peak
2	7320.000	37.46	7.69	45.15	74.00	-28.85	peak
3	9330.000	36.63	11.78	48.41	74.00	-25.59	peak
4	11430.000	31.03	16.31	47.34	74.00	-26.66	peak
5*	14205.000	27.58	22.26	49.84	/	/	peak
6*	16875.000	24.12	25.02	49.14	/	/	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5880.000	40.20	2.90	43.10	/	/	peak
2*	8595.000	38.44	9.29	47.73	/	/	peak
3	11430.000	29.73	17.72	47.45	74.00	-26.55	peak
4	12690.000	28.66	19.21	47.87	74.00	-26.13	peak
5*	14400.000	28.09	22.29	50.38	/	/	peak
6	17985.000	20.64	29.49	50.13	74.00	-23.87	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4650.000	41.80	1.01	42.81	74.00	-31.19	peak
2*	5865.000	39.54	3.92	43.46	/	/	peak
3*	9210.000	36.83	11.36	48.19	/	/	peak
4	11865.000	30.11	17.37	47.48	74.00	-26.52	peak
5*	14295.000	27.94	22.01	49.95	/	/	peak
6	17790.000	23.71	26.25	49.96	74.00	-24.04	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	43.76	0.72	44.48	74.00	-29.52	peak
2	7350.000	38.51	7.09	45.60	74.00	-28.40	peak
3	8370.000	38.24	8.84	47.08	74.00	-26.92	peak
4	11835.000	28.62	18.54	47.16	74.00	-26.84	peak
5*	13545.000	27.99	22.52	50.51	/	/	peak
6	17985.000	19.06	29.49	48.55	74.00	-25.45	peak


Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	40.81	1.59	42.40	74.00	-31.60	peak
2*	5700.000	39.65	3.65	43.30	/	/	peak
3	9165.000	38.30	11.19	49.49	74.00	-24.51	peak
4	11685.000	30.36	16.96	47.32	74.00	-26.68	peak
5*	13785.000	29.17	21.26	50.43	/	/	peak
6*	16890.000	24.99	25.05	50.04	/	/	peak


8.6. SPURIOUS EMISSIONS(3 GHZ~18 GHZ) FOR ANT1

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	46.90	0.50	47.40	74.00	-26.60	peak
2*	7230.000	40.46	6.93	47.39	/	/	peak
3*	8835.000	38.02	9.67	47.69	/	/	peak
4	11850.000	29.05	18.55	47.60	74.00	-26.40	peak
5*	14250.000	26.15	23.08	49.23	/	/	peak
6	18000.000	19.15	29.64	48.79	74.00	-25.21	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	44.85	1.59	46.44	74.00	-27.56	peak
2*	7230.000	40.24	7.65	47.89	/	/	peak
3*	8820.000	38.51	10.10	48.61	/	/	peak
4	11655.000	30.75	16.88	47.63	74.00	-26.37	peak
5*	13995.000	27.81	22.18	49.99	/	/	peak
6*	17280.000	24.75	25.35	50.10	/	/	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	49.19	0.65	49.84	74.00	-24.16	peak
2	7305.000	43.18	7.03	50.21	74.00	-23.79	peak
3	9195.000	37.98	11.06	49.04	74.00	-24.96	peak
4	11055.000	31.87	16.28	48.15	74.00	-25.85	peak
5*	13995.000	26.42	23.78	50.20	/	/	peak
6	17985.000	20.68	29.49	50.17	74.00	-23.83	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	45.99	1.78	47.77	74.00	-26.23	peak
2	7305.000	41.81	7.68	49.49	74.00	-24.51	peak
3	9150.000	37.71	11.15	48.86	74.00	-25.14	peak
4	12555.000	30.33	18.00	48.33	74.00	-25.67	peak
5*	14145.000	27.76	22.24	50.00	/	/	peak
6*	17010.000	25.03	25.19	50.22	/	/	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	50.49	0.76	51.25	74.00	-22.75	peak
2	7710.000	40.68	7.62	48.30	74.00	-25.70	peak
3*	8895.000	37.83	9.84	47.67	/	/	peak
4	11670.000	28.35	18.27	46.62	74.00	-27.38	peak
5*	13935.000	25.80	23.52	49.32	/	/	peak
6	17970.000	20.17	29.33	49.50	74.00	-24.50	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3270.000	48.89	-3.02	45.87	/	/	peak
2	4920.000	47.03	1.91	48.94	74.00	-25.06	peak
3*	8760.000	39.00	10.01	49.01	/	/	peak
4	11910.000	29.71	17.44	47.15	74.00	-26.85	peak
5*	14460.000	29.02	21.64	50.66	/	/	peak
6*	16845.000	25.74	24.99	50.73	/	/	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	45.83	0.50	46.33	74.00	-27.67	peak
2*	7230.000	40.99	6.93	47.92	/	/	peak
3*	9270.000	38.37	11.38	49.75	/	/	peak
4	11505.000	29.63	17.99	47.62	74.00	-26.38	peak
5*	13965.000	26.50	23.65	50.15	/	/	peak
6	17925.000	20.92	28.87	49.79	74.00	-24.21	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	42.93	1.59	44.52	74.00	-29.48	peak
2*	7230.000	40.18	7.65	47.83	/	/	peak
3*	8760.000	38.86	10.01	48.87	/	/	peak
4	11805.000	30.80	17.24	48.04	74.00	-25.96	peak
5*	14265.000	27.91	22.10	50.01	/	/	peak
6*	16830.000	25.79	24.97	50.76	/	/	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.23	0.65	42.88	74.00	-31.12	peak
2	7305.000	41.60	7.03	48.63	74.00	-25.37	peak
3	8430.000	39.09	8.93	48.02	74.00	-25.98	peak
4	11820.000	28.28	18.51	46.79	74.00	-27.21	peak
5*	13995.000	25.84	23.78	49.62	/	/	peak
6	17985.000	20.54	29.49	50.03	74.00	-23.97	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3240.000	49.71	-3.05	46.66	/	/	peak
2	7305.000	40.33	7.68	48.01	74.00	-25.99	peak
3*	8820.000	38.89	10.10	48.99	/	/	peak
4	11850.000	30.20	17.33	47.53	74.00	-26.47	peak
5*	14400.000	28.59	21.73	50.32	/	/	peak
6*	17340.000	24.33	25.37	49.70	/	/	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	45.36	0.76	46.12	74.00	-27.88	peak
2*	6555.000	38.44	4.91	43.35	/	/	peak
3	9120.000	37.29	10.72	48.01	74.00	-25.99	peak
4	11850.000	29.30	18.55	47.85	74.00	-26.15	peak
5*	13950.000	26.69	23.58	50.27	/	/	peak
6	18000.000	20.43	29.64	50.07	74.00	-23.93	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3270.000	48.00	-3.02	44.98	/	/	peak
2	4920.000	41.13	1.91	43.04	74.00	-30.96	peak
3*	8790.000	37.68	10.03	47.71	/	/	peak
4	11835.000	28.95	17.31	46.26	74.00	-27.74	peak
5	14490.000	27.53	21.60	49.13	74.00	-24.87	peak
6*	17670.000	22.35	25.91	48.26	/	/	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	44.55	0.50	45.05	74.00	-28.95	peak
2*	7245.000	41.84	6.95	48.79	/	/	peak
3	9105.000	37.99	10.66	48.65	74.00	-25.35	peak
4	11505.000	28.53	17.99	46.52	74.00	-27.48	peak
5*	13965.000	26.05	23.65	49.70	/	/	peak
6	17970.000	19.42	29.33	48.75	74.00	-25.25	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.09	1.59	44.68	74.00	-29.32	peak
2*	7230.000	42.26	7.65	49.91	/	/	peak
3*	9255.000	37.73	11.51	49.24	/	/	peak
4	11835.000	30.35	17.31	47.66	74.00	-26.34	peak
5*	14235.000	28.04	22.17	50.21	/	/	peak
6*	17235.000	24.68	25.33	50.01	/	/	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.03	0.65	44.68	74.00	-29.32	peak
2	7305.000	41.45	7.03	48.48	74.00	-25.52	peak
3*	9270.000	38.33	11.38	49.71	/	/	peak
4	11835.000	28.25	18.54	46.79	74.00	-27.21	peak
5*	13680.000	28.11	22.74	50.85	/	/	peak
6	17745.000	22.09	27.20	49.29	74.00	-24.71	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3240.000	47.66	-3.05	44.61	/	/	peak
2	7305.000	39.79	7.68	47.47	74.00	-26.53	peak
3*	9210.000	37.35	11.36	48.71	/	/	peak
4	12240.000	29.35	17.78	47.13	74.00	-26.87	peak
5*	14040.000	27.52	22.21	49.73	/	/	peak
6*	17250.000	24.54	25.34	49.88	/	/	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	46.85	0.76	47.61	74.00	-26.39	peak
2*	6555.000	40.11	4.91	45.02	/	/	peak
3	9165.000	37.24	10.92	48.16	74.00	-25.84	peak
4	11805.000	29.12	18.50	47.62	74.00	-26.38	peak
5*	13590.000	27.77	22.60	50.37	/	/	peak
6	17985.000	20.83	29.49	50.32	74.00	-23.68	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3270.000	46.68	-3.02	43.66	/	/	peak
2	4935.000	41.89	1.96	43.85	74.00	-30.15	peak
3*	7965.000	40.18	8.48	48.66	/	/	peak
4	11040.000	30.77	15.33	46.10	74.00	-27.90	peak
5*	14460.000	27.12	21.64	48.76	/	/	peak
6*	16890.000	24.95	25.05	50.00	/	/	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.000	41.79	0.58	42.37	74.00	-31.63	peak
2	7275.000	38.67	6.99	45.66	74.00	-28.34	peak
3*	9225.000	37.13	11.19	48.32	/	/	peak
4	11820.000	29.43	18.51	47.94	74.00	-26.06	peak
5*	13680.000	27.76	22.74	50.50	/	/	peak
6	17970.000	21.24	29.33	50.57	74.00	-23.43	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3225.000	46.66	-3.06	43.60	/	/	peak
2*	5670.000	39.89	3.59	43.48	/	/	peak
3	9300.000	37.46	11.68	49.14	74.00	-24.86	peak
4	11535.000	31.14	16.57	47.71	74.00	-26.29	peak
5*	14415.000	28.47	21.71	50.18	/	/	peak
6*	16875.000	24.46	25.02	49.48	/	/	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4890.000	42.83	0.68	43.51	74.00	-30.49	peak
2*	6495.000	39.00	4.73	43.73	/	/	peak
3*	8550.000	38.64	9.17	47.81	/	/	peak
4	11850.000	28.36	18.55	46.91	74.00	-27.09	peak
5*	14010.000	25.93	23.78	49.71	/	/	peak
6	17985.000	20.14	29.49	49.63	74.00	-24.37	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	DC 3.3V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3240.000	47.54	-3.05	44.49	/	/	peak
2	7305.000	39.67	7.68	47.35	74.00	-26.65	peak
3*	8655.000	38.09	9.91	48.00	/	/	peak
4	11460.000	31.03	16.39	47.42	74.00	-26.58	peak
5*	14415.000	27.98	21.71	49.69	/	/	peak
6*	17235.000	24.88	25.33	50.21	/	/	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	44.44	0.72	45.16	74.00	-28.84	peak
2*	5955.000	39.07	3.04	42.11	/	/	peak
3*	8520.000	39.00	9.07	48.07	/	/	peak
4	11730.000	29.68	18.38	48.06	74.00	-25.94	peak
5*	13545.000	27.84	22.52	50.36	/	/	peak
6	17985.000	20.33	29.49	49.82	74.00	-24.18	peak


Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	3255.000	46.35	-3.03	43.32	/	/	peak
2	7350.000	39.58	7.71	47.29	74.00	-26.71	peak
3*	8760.000	38.51	10.01	48.52	/	/	peak
4*	12705.000	29.03	18.22	47.25	/	/	peak
5*	14265.000	28.40	22.10	50.50	/	/	peak
6*	17055.000	24.53	25.21	49.74	/	/	peak


8.7. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V




No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.0100	76.72	-101.40	-24.68	47.60	-76.18	-3.90	-72.28	peak
2	0.0128	73.37	-101.38	-28.01	45.46	-79.51	-6.04	-73.47	peak
3	0.0212	70.54	-101.35	-30.81	41.07	-82.31	-10.43	-71.88	peak
4	0.0371	64.89	-101.42	-36.53	36.21	-88.03	-15.29	-72.74	peak
5	0.0656	60.36	-101.55	-41.19	31.26	-92.69	-20.24	-72.45	peak
6	0.0994	57.70	-101.80	-44.10	27.65	-95.60	-23.85	-71.75	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1567	73.95	-101.65	-27.70	23.70	-79.20	-27.80	-51.40	peak
2	0.1945	71.69	-101.70	-30.01	21.82	-81.51	-29.68	-51.83	peak
3	0.2273	68.29	-101.76	-33.47	20.47	-84.97	-31.03	-53.94	peak
4	0.2746	64.96	-101.83	-36.87	18.83	-88.37	-32.67	-55.70	peak
5	0.3180	63.68	-101.88	-38.20	17.55	-89.70	-33.95	-55.75	peak
6	0.3986	61.25	-101.96	-40.71	15.59	-92.21	-35.91	-56.30	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.6169	63.05	-62.08	0.97	31.80	-50.53	-19.70	-30.83	peak
2	1.5443	58.35	-62.03	-3.68	23.83	-55.18	-27.67	-27.51	peak
3	2.4672	56.66	-61.71	-5.05	29.54	-56.55	-21.96	-34.59	peak
4	5.2705	55.04	-61.45	-6.41	29.54	-57.91	-21.96	-35.95	peak
5	7.6314	55.01	-61.12	-6.11	29.54	-57.61	-21.96	-35.65	peak
6	16.4542	53.25	-60.96	-7.71	29.54	-59.21	-21.96	-37.25	


8.8. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18416.000	49.73	-5.35	44.38	74.00	-29.62	peak
2	19392.000	50.62	-5.57	45.05	74.00	-28.95	peak
3	21032.000	48.65	-4.87	43.78	74.00	-30.22	peak
4	22040.000	48.57	-4.44	44.13	74.00	-29.87	peak
5	23208.000	48.44	-3.38	45.06	74.00	-28.94	peak
6	25968.000	44.63	-1.00	43.63	74.00	-30.37	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18616.000	48.89	-5.34	43.55	74.00	-30.45	peak
2	20096.000	50.10	-5.51	44.59	74.00	-29.41	peak
3	21272.000	48.25	-4.76	43.49	74.00	-30.51	peak
4	22752.000	47.72	-3.69	44.03	74.00	-29.97	peak
5	24464.000	45.89	-2.40	43.49	74.00	-30.51	peak
6	25752.000	43.04	-0.62	42.42	74.00	-31.58	peak


8.9. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	44.5500	25.48	-14.91	10.57	40.00	-29.43	QP
2	192.9600	32.76	-12.05	20.71	43.50	-22.79	QP
3	423.8200	33.29	-8.91	24.38	46.00	-21.62	QP
4	553.8000	31.40	-6.93	24.47	46.00	-21.53	QP
5	691.5400	28.08	-4.45	23.63	46.00	-22.37	QP
6	887.4800	29.03	-0.65	28.38	46.00	-17.62	QP

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	DC 3.3V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	44.5500	46.93	-14.91	32.02	40.00	-7.98	QP
2	120.2100	35.40	-14.70	20.70	43.50	-22.80	QP
3	207.5100	33.50	-12.60	20.90	43.50	-22.60	QP
4	418.9700	28.82	-9.05	19.77	46.00	-26.23	QP
5	563.5000	31.42	-6.69	24.73	46.00	-21.27	QP
6	927.2500	28.64	-0.65	27.99	46.00	-18.01	QP

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	24.5°C	Relative Humidity	55.2%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.3V

TEST DATE / ENGINEER

Test Date	June 23, 2025	Test By	Deacon Tan
-----------	---------------	---------	------------

TEST RESULTS

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1632	40.05	9.71	49.76	65.30	-15.54	QP
2	0.1632	25.21	9.71	34.92	55.30	-20.38	AVG
3	0.2218	32.57	9.64	42.21	62.75	-20.54	QP
4	0.2218	19.34	9.64	28.98	52.75	-23.77	AVG
5	0.4913	27.16	9.64	36.80	56.15	-19.35	QP
6	0.4913	13.98	9.64	23.62	46.15	-22.53	AVG
7	4.4041	23.77	9.73	33.50	56.00	-22.50	QP
8	4.4041	17.25	9.73	26.98	46.00	-19.02	AVG
9	12.5700	28.89	9.73	38.62	60.00	-21.38	QP
10	12.5700	21.60	9.73	31.33	50.00	-18.67	AVG
11	19.0661	22.74	9.74	32.48	60.00	-27.52	QP
12	19.0661	17.11	9.74	26.85	50.00	-23.15	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes and antennas have been tested, only the worst data was recorded in the report.

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1625	39.40	9.64	49.04	65.34	-16.30	QP
2	0.1625	23.40	9.64	33.04	55.34	-22.30	AVG
3	0.4890	31.06	9.64	40.70	56.18	-15.48	QP
4	0.4890	17.63	9.64	27.27	46.18	-18.91	AVG
5	0.6147	26.86	9.64	36.50	56.00	-19.50	QP
6	0.6147	17.49	9.64	27.13	46.00	-18.87	AVG
7	3.3052	24.92	9.63	34.55	56.00	-21.45	QP
8	3.3052	16.73	9.63	26.36	46.00	-19.64	AVG
9	6.3208	22.97	9.71	32.68	60.00	-27.32	QP
10	6.3208	17.37	9.71	27.08	50.00	-22.92	AVG
11	18.9067	21.26	9.74	31.00	60.00	-29.00	QP
12	18.9067	15.93	9.74	25.67	50.00	-24.33	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes and antennas have been tested, only the worst data was recorded in the report.


11. TEST DATA for ANTO


11.1. APPENDIX A1 DTS BANDWIDTH


11.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant0	2412	8.08	2407.48	2415.56	≥ 0.5	PASS
		2437	9.04	2432.48	2441.52	≥ 0.5	PASS
		2462	9.04	2457.48	2466.52	≥ 0.5	PASS
11G	Ant0	2412	14.96	2404.56	2419.52	≥ 0.5	PASS
		2437	15.08	2429.48	2444.56	≥ 0.5	PASS
		2462	15.00	2454.52	2469.52	≥ 0.5	PASS
11N20SISO	Ant0	2412	16.28	2403.84	2420.12	≥ 0.5	PASS
		2437	15.12	2429.44	2444.56	≥ 0.5	PASS
		2462	17.56	2453.20	2470.76	≥ 0.5	PASS
11N40SISO	Ant0	2422	35.12	2404.48	2439.60	≥ 0.5	PASS
		2437	35.12	2419.48	2454.60	≥ 0.5	PASS
		2452	35.12	2434.48	2469.60	≥ 0.5	PASS

11.1.2. Test Graphs











11.2. APPENDIX B1: OCCUPIED CHANNEL BANDWIDTH


11.2.1. Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B	Ant0	2412	13.666	2405.1668	2418.8332	PASS
		2437	13.626	2430.2068	2443.8332	PASS
		2462	13.626	2455.2068	2468.8332	PASS
11G	Ant0	2412	17.223	2403.4086	2420.6314	PASS
		2437	17.183	2428.4086	2445.5914	PASS
		2462	17.183	2453.4086	2470.5914	PASS
11N20SISO	Ant0	2412	18.062	2403.0090	2421.0709	PASS
		2437	18.062	2427.9690	2446.0310	PASS
		2462	18.062	2453.0090	2471.0709	PASS
11N40SISO	Ant0	2422	36.523	2403.7782	2440.3017	PASS
		2437	36.364	2418.8581	2455.2218	PASS
		2452	36.444	2433.7782	2470.2218	PASS

11.2.2. Test Graphs









11.3. APPENDIX C1: MAXIMUM CONDUCTED OUTPUT POWER

11.3.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant0	2412	16.08	≤30.00	PASS
		2437	16.23	≤30.00	PASS
		2462	16.06	≤30.00	PASS
11G	Ant0	2412	15.49	≤30.00	PASS
		2437	15.50	≤30.00	PASS
		2462	15.68	≤30.00	PASS
11N20SISO	Ant0	2412	14.33	≤30.00	PASS
		2437	14.30	≤30.00	PASS
		2462	14.39	≤30.00	PASS
11N40SISO	Ant0	2422	14.35	≤30.00	PASS
		2437	14.58	≤30.00	PASS
		2452	14.45	≤30.00	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor

2. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.


11.4. APPENDIX D1: MAXIMUM POWER SPECTRAL DENSITY


11.4.1. Test Result


Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant0	2412	-15.23	≤8.00	PASS
		2437	-14.89	≤8.00	PASS
		2462	-14.98	≤8.00	PASS
11G	Ant0	2412	-17.07	≤8.00	PASS
		2437	-17.22	≤8.00	PASS
		2462	-17.22	≤8.00	PASS
11N20SISO	Ant0	2412	-18.29	≤8.00	PASS
		2437	-18.25	≤8.00	PASS
		2462	-18.44	≤8.00	PASS
11N40SISO	Ant0	2422	-19.69	≤8.00	PASS
		2437	-19.18	≤8.00	PASS
		2452	-19.66	≤8.00	PASS


Note: 1. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.

11.4.2. Test Graphs











11.5. APPENDIX E1: BAND EDGE MEASUREMENTS


11.5.1. Test Result

Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant0	Low	2412	6.66	-39.71	≤-23.34	PASS
		High	2462	7.13	-45.1	≤-22.87	PASS
11G	Ant0	Low	2412	5.37	-39.12	≤-24.63	PASS
		High	2462	3.46	-45.14	≤-26.54	PASS
11N20SISO	Ant0	Low	2412	3.99	-39.25	≤-26.01	PASS
		High	2462	3.01	-46.13	≤-26.99	PASS
11N40SISO	Ant0	Low	2422	1.27	-37.97	≤-28.73	PASS
		High	2452	2.08	-44.6	≤-27.92	PASS

11.5.2. Test Graphs







11.6. APPENDIX F1: CONDUCTED SPURIOUS EMISSION

11.6.1. Test Result

Test Mode	Antenna	Frequency[MHz]	FreqRange [Mhz]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant0	2412	Reference	8.32	---	PASS
			30~1000	-45.03	≤-21.68	PASS
			1000~26500	-40.4	≤-21.68	PASS
		2437	Reference	8.25	---	PASS
			30~1000	-45.64	≤-21.75	PASS
			1000~26500	-40.33	≤-21.75	PASS
		2462	Reference	7.97	---	PASS
			30~1000	-44.25	≤-22.03	PASS
			1000~26500	-40.22	≤-22.03	PASS
11G	Ant0	2412	Reference	5.78	---	PASS
			30~1000	-44.62	≤-24.22	PASS
			1000~26500	-40.49	≤-24.22	PASS
		2437	Reference	5.65	---	PASS
			30~1000	-45.55	≤-24.35	PASS
			1000~26500	-40.14	≤-24.35	PASS
		2462	Reference	5.91	---	PASS
			30~1000	-45.03	≤-24.09	PASS
			1000~26500	-40.19	≤-24.09	PASS
11N20SISO	Ant0	2412	Reference	4.51	---	PASS
			30~1000	-43.64	≤-25.49	PASS
			1000~26500	-39.32	≤-25.49	PASS
		2437	Reference	4.62	---	PASS
			30~1000	-40.01	≤-25.38	PASS
			1000~26500	-39.96	≤-25.38	PASS
		2462	Reference	4.75	---	PASS
			30~1000	-45.72	≤-25.25	PASS
			1000~26500	-39.56	≤-25.25	PASS
11N40SISO	Ant0	2422	Reference	1.96	---	PASS
			30~1000	-44.78	≤-28.04	PASS
			1000~26500	-39.99	≤-28.04	PASS
		2437	Reference	2.36	---	PASS
			30~1000	-45.08	≤-27.64	PASS
			1000~26500	-40.41	≤-27.64	PASS
		2452	Reference	1.74	---	PASS
			30~1000	-44.76	≤-28.26	PASS
			1000~26500	-40.49	≤-28.26	PASS

11.6.2. Test Graphs

