

SPECIFICATION

SHEET FOR APPROVAL

	CUSTOMER(客户名称)	高盛达	
	CS P/N(客户机种)		
	PART NAME(品名)	WIFI Antenna	
	FREQUENCY(频率)	2400-2500MHz 5150-5850 MHz	
	GSD NO.(物料编号)	WC0D	
	DATE(日期)	2016-06-25	

CUSTOMER	
CHECKE	APPROVAL

Remark(备注):

Sign(客户确认签字盖章): _____

DESIGN	CHECK	APPROVAL
	邹一麟	赵烽

惠州高盛达科技有限公司

HUIZHOU GAOSHENGDA TECHNOLOGY CO.,LTD

ANTENNA SPECIFICATION

Index

1.			General Description	1
2.			Electrical Specifications	2
	2-1		Set-up	2
		2-1-1	Frequency Band	2
		2-1-2	Impedance	2
		2-1-3	Matching Requirements	2
		2-1-4	VSWR	2
	2-2		Test Data	3
		2-2-1	VSWR	3
		2-2-2	Smith Chart	4
		2-2-3	GAIN Efficiency	4
		2-2-4	The direction of figure	5~6
		2-2-5	Testing equipment	6~7
3.			Mechanical Specification	8
	3-1		Mechanical Configuration	8
		3-1-1	Mechanical Configuration(WIFI 2.4G)	8
		3-1-2	Mechanical Configuration(天线组件)	9

ANTENNA SPECIFICATION

1. General Description

Dbi	Decibel relative isotropic antenna
Tx	Transmit frequency
Rx	Receive frequency
VSWR	Voltage Standing Wave Ratio
GSM	Global Service for Mobile communication
DCS	Digital Communication System
PCS	Personal Communication System
PHS	Personal Handy-phone System
SAR	Specific Absorption Rate
PCB	Printed Circuit Board

2. Electrical Specifications


2-1 Set-up

2-1-1 Frequency Band

Frequency Band	Frequency
WIFI 2.4G	2400-2500MHZ
WIFI 5G	5150-5850MHZ

2-1-2 Impedance

Nominal Impedance(including matching circuit) : **50 ohms**



2-1-3 Matching Requirements

The matching circuit on the PCB of the handset is according to Figure 1

Optimum matching circuit is highly dependent on the handset and thus.

Final matching circuit layout and values will be defined when handset is available.

ANTENNA SPECIFICATION

GSD P/N : WC0D

Version 1.0 Page 3 of 10

2-1-4 VSWR And GAIN


VSWR		GAIN	
Freq. Band	OPEN SPEC	Band Freq.	OPEN SPEC
2400MHz	≤ 2.0	2400MHz	$\geq -1.0\text{dBi}$
2500MHz	≤ 2.0	2500MHz	$\geq -1.0\text{dBi}$
5150MHz	≤ 2.0	5150MHz	$\geq -1.0\text{dBi}$
5850MHz	≤ 2.0	5850MHz	$\geq -1.0\text{dBi}$

※Measuring a 50 Ω test jig is connected to a network analyzer to measure the VSWR.

※※All test value is done in customer approval fixture.

2-2 Test Data

2-2-1 VSWR




Model No:WC0D	File:
GSD NO:WC0D Antenna	Note: WIFI2.4G/5G
Sample No:yes	
Test Condition: Free Space	

ANTENNA SPECIFICATION

GSD P/N : WC0D

Version 1.0 Page 4 of 10

2-2-2 Smith Chart



2-2-3 GAIN Efficiency


WIFI Gain:

	WIFI				
Frequency (MHz)	2400	2450	2500	5150	5850
Gain	1.42	1.72	1.65	2.34	2.57
Efficiency (dBi)	(44%)	(48%)	(45%)	(61%)	(66%)


ANTENNA SPECIFICATION

2-2-4 The direction of figure

H



E1




ANTENNA SPECIFICATION


GSD P/N : WC0D

Version 1.0 Page 6 of 10


E2



2-2-5 Testing equipment



ANTENNA SPECIFICATION



ANTENNA SPECIFICATION

3. Mechanical Specification

3-1 Mechanical Configuration

3-1-1 Mechanical Configuration(WIFI2.4G/5G)

ANTENNA SPECIFICATION

GSD P/N : WC0D



Version 1.0

Page 9 of 10


版本	说明	审核	日期	批准	日期

展开图

粉红色线为折弯线



立体图



环保要求:

MATTER	Roh's (PPM)	未注明公差 5 UND ±0.08	範圍	材料圖	項目	規格	單位	尺寸	比例	零件號碼
Cd	≤ 100	5-10 ±0.10	射頻	龍秋霖	日期:	2016-06-01	mm	A1	1:1	
Pb	≤ 1000	5-10 ±0.10	射頻		日期:		件組	S3304 P40.30mm (橡製)	1/1	
Hg	≤ 1000	10-35 ±0.12	審核	/	日期:	/	LZ	產品名錄		
Cr+6	≤ 1000	35-50 ±0.15	審核	/	日期:	/		WCOD (WiFi)		
PBB	≤ 1000	50-100 ±0.18	批准		日期:		板金	圖紙編號		ZTX-QR-RD-029
PBDE	≤ 1000	100 OVE ±0.20			日期:		A4			

备注:


1. 角度尺寸模具设计时依图纸尺寸作参照, 样品及量产实配即可;
2. 打“*”为严格控制尺寸 (TQC 必测等级 A);
3. 字母说明 (采用宋体, 要求字迹清晰, 弹片无变形);
4. 产品不能有油污、毛刺、利边、缺料、变形、压印过深等不良;
5. 需通过 48 小时盐雾测试;
6. 包装时需用吸塑盒摆放整齐, 运输过程中产品不能挤压碰撞等;
7. 未经过 ZTX 公司确认, 材料不能随意更改;

3-1-2 Mechanical Configuration(天线组件)

ANTENNA SPECIFICATION

GSD P/N : WC0D

版本	说明	审核	日期	批准	日期



材质说明:

序号	结构说明	材质	工艺
①	RF同轴线	FEF (F46) 一代高仿端子	
②	WiFi弹片	SUS304 T=0.30mm	镀镍
③	支撑泡棉	防火EVA 3M 9495	通过UL-94
④	固定泡棉胶	泡棉胶 3M RP45	通过UL-746C
⑤	护套	黑色热缩套管	

注: 带*号尺寸为CPK检测尺寸

环保要求:

MATTER	RoHs (PPM)
Cd	≤100
Pb	≤1000
Hg	≤1000
Cr6+	≤1000
PBB	≤1000
PBDE	≤1000

中天迅通技术有限公司

未注明公差	单位	版本	A1	比例	1:1	物料编号	2.000000030
5 UNL	±0.08	2016.06.24	日期:	材料	SUS304 T=0.30mm (镀镍)	比例	1/1
5-10	±0.10	射频	日期:	工艺	WC0D-60 (MFR组件)	物料编号	ZTXQR-RD-018
10-35	±0.12	审核	日期:	版本	WC0D-60 (MFR组件)	物料编号	ZTXQR-RD-018
35-50	±0.15	批准	日期:	版本	WC0D-60 (MFR组件)	物料编号	ZTXQR-RD-018
50-100	±0.18		日期:	版本	WC0D-60 (MFR组件)	物料编号	ZTXQR-RD-018
100 OVE	±0.20		日期:	版本	WC0D-60 (MFR组件)	物料编号	ZTXQR-RD-018