










Test Channel:		Highest Channel		Ant. Polar. :		Horizontal	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2483.50	44.497	74	37.519	54	Pass		
2489.20	46.546	74	N/A	54	Pass		



Test Channel:		Highest Channel		Ant. Polar. :		Vertical	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2483.5	43.526	74	37.048	54	Pass		
2486.68	47.577	74	N/A	54	Pass		

IEEE 802.11n-20



Test Channel:		Lowest Channel		Ant. Polar. :		Horizontal	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2400.00	64.452	74	44.609	54	Pass		



Test Channel:		Lowest Channel		Ant. Polar. :		Vertical	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2387.98	58.585	74	N/A	54	Pass		
2390.00	57.375	74	46.421	54	Pass		



Test Channel:		Highest Channel		Ant. Polar. :		Horizontal	
Peak			Avg.				
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2483.50	43.981	74	37.201	54	Pass		
2488.66	46.670	74	N/A	54	Pass		

Test Channel:		Highest Channel		Ant. Polar. :		Vertical	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)		AV level (dBuv/m)	AV Limit (dBuv/m)		Conclusion
2483.50	45.920	74		37.012	54		Pass

IEEE 802.11n-40



Test Channel:		Lowest Channel		Ant. Polar. :		Horizontal	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2390.00	60.467	74	48.452	54	Pass		



Test Channel:		Lowest Channel		Ant. Polar. :		Vertical	
Peak			Avg.				
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2386.72	63.913	74	50.721	54	Pass		
2390.00	62.289	74	51.729	54	Pass		





Model No.: W7LM1110A

IEEE 802.11b

Test Channel:		Lowest Channel		Ant. Polar. :		Horizontal	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)		AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion	
2390.00	54.604	74		40.615	54	Pass	



Test Channel:		Lowest Channel		Ant. Polar. :		Vertical	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)		AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion	
2390.00	49.740	74		38.401	54	Pass	





IEEE 802.11g


Test Channel:		Lowest Channel		Ant. Polar. :		Horizontal	
Peak				Avg.			
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)		AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion	
2389.76	64.891	74		47.828	54	Pass	
2390.00	61.339	74		48.321	54	Pass	



Test Channel:		Lowest Channel		Ant. Polar. :		Vertical	
Peak				Avg.			
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)		AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion	
2390.00	59.773	74		45.610	54	Pass	





IEEE 802.11n-20



Test Channel:		Highest Channel		Ant. Polar. :		Horizontal	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2483.50	55.327	74	43.955	54	Pass		

Test Channel:		Highest Channel		Ant. Polar. :		Vertical	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2483.50	54.499	74	42.809	54	Pass		
2484.64	57.511	74	41.532	54	Pass		

IEEE 802.11n-40



Test Channel:		Highest Channel		Ant. Polar. :		Horizontal	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2483.50	56.810	74	48.525	54	Pass		
2484.58	60.658	74	47.854	54	Pass		

Test Channel:		Highest Channel		Ant. Polar. :		Vertical	
Peak				Avg.			
							
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion		
2483.50	58.490	74	46.878	54	Pass		
2484.34	59.893	74	47.143	54	Pass		

5.5 CONDUCTED EMISSION

Test Requirement: 47 CFR Part 15C Section 15.207
RSS-Gen Issue 4, Section 8.8

Test Method: ANSI C63.10-2013 Section 6.2

Limits:

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.4.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.

Test Result: Pass


The measurement data as follows:

Quasi Peak and Average:

Model No.: W7LM1110


Mode: WIFI Link

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.166	23.60	10.20	33.80	55.20	-21.40	Average
2	0.166	42.40	10.20	52.60	65.20	-12.60	QP
3	0.230	17.20	10.20	27.40	52.40	-25.00	Average
4	0.230	35.80	10.20	46.00	62.40	-16.40	QP
5*	0.282	12.30	10.20	22.50	50.80	-28.30	Average
6	0.282	31.00	10.20	41.20	60.80	-19.60	QP

Neutral Line




No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	0.170	24.80	10.20	35.00	55.00	-20.00	Average
2	0.170	40.80	10.20	51.00	65.00	-14.00	QP
3	0.226	20.30	10.30	30.60	52.60	-22.00	Average
4	0.226	35.30	10.30	45.60	62.60	-17.00	QP
5*	0.286	16.80	10.30	27.10	50.60	-23.50	Average
6	0.286	30.50	10.30	40.80	60.60	-19.80	QP

Model No.: W7LM1110A


Mode: WIFI Link

Live Line



No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	0.158	23.90	10.20	34.10	55.60	-21.50	Average
2	0.158	43.90	10.20	54.10	65.60	-11.50	QP
3	0.214	18.60	10.20	28.80	53.00	-24.20	Average
4	0.214	38.60	10.20	48.80	63.00	-14.20	QP
5*	0.266	15.30	10.20	25.50	51.20	-25.70	Average
6	0.266	34.30	10.20	44.50	61.20	-16.70	QP

Neutral Line



No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	0.170	24.80	10.20	35.00	55.00	-20.00	Average
2	0.170	40.80	10.20	51.00	65.00	-14.00	QP
3	0.226	20.30	10.30	30.60	52.60	-22.00	Average
4	0.226	35.30	10.30	45.60	62.60	-17.00	QP
5*	0.286	16.80	10.30	27.10	50.60	-23.50	Average
6	0.286	30.50	10.30	40.80	60.60	-19.80	QP

Remark:

1. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
