

TEST REPORT


Product Name: WIFI+BT Module
Trade Mark: GSD
Model No.: WCT6PA2201
HVIN: WCT6PA2201
Report Number: 171227005RFC-4
FCC 47 CFR Part 15 Subpart E
Test Standards: RSS-247 Issue 2
RSS-Gen Issue 4
FCC ID: 2AC23-WCT6LA2701
IC: 12290A-WCT6LA2701
Test Result: PASS
Date of Issue: February 5, 2018

Prepared for:


Hui Zhou Gaoshengda Technology Co.,LTD
NO.75 Zhongkai Development Area, Huizhou, Guangdong, China

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Tested by: 
Henry Lu
Engineer

Reviewed by: 
Kevin Liang
Team Leader

Approved by: 
Jim Long
Assistant Manager

Date: February 5, 2018



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Version

Version No.	Date	Description
V1.0	February 5, 2018	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	6
1.5 DESCRIPTION OF SUPPORT UNITS	6
1.6 TEST LOCATION	6
1.7 TEST FACILITY	7
1.8 DEVIATION FROM STANDARDS	7
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	7
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
1.11 MEASUREMENT UNCERTAINTY	7
2. TEST SUMMARY	8
3. EQUIPMENT LIST	10
4. TEST CONFIGURATION	11
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	11
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	11
4.2 TEST CHANNELS	11
4.3 EUT TEST STATUS	12
4.4 PRE-SCAN	12
4.4.1 PRE-SCAN UNDER ALL RATES	12
4.4.2 WORST-CASE DATA RATES	12
4.5 TEST SETUP	13
4.5.1 FOR RADIATED EMISSIONS TEST SETUP	13
4.5.2 FOR CONDUCTED RF TEST SETUP	15
4.6 SYSTEM TEST CONFIGURATION	16
4.7 DUTY CYCLE	17
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	20
5.1 REFERENCE DOCUMENTS FOR TESTING	20
5.2 ANTENNA REQUIREMENT	20
5.3 26 dB BANDWIDTH & OCCUPIED BANDWIDTH	21
5.4 6 dB BANDWIDTH & OCCUPIED BANDWIDTH	29
5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P	32
5.6 PEAK POWER SPECTRAL DENSITY	38
5.7 FREQUENCY STABILITY	57
5.8 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT	60
5.9 DYNAMIC FREQUENCY SELECTION	109
APPENDIX 1 PHOTOS OF TEST SETUP	118
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	118

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Hui Zhou Gaoshengda Technology Co.,LTD
Address of Applicant:	NO.75 Zhongkai Development Area, Huizhou, Guangdong, China
Manufacturer:	Hui Zhou Gaoshengda Technology Co.,LTD
Address of Manufacturer:	NO.75 Zhongkai Development Area, Huizhou, Guangdong, China

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	WIFI+BT Module		
Model No.:	WCT6PA2201		
HVIN:	WCT6PA2201		
Add. Model No.:	N/A		
Trade Mark:	GSD		
DUT Stage:	Identical Prototype		
EUT Supports Function:	2.4 GHz ISM Band:	IEEE 802.11b/g/n Bluetooth: V3.0+EDR & V4.1 LE	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
Sample Received Date:	December 27, 2017		
Sample Tested Date:	December 28, 2017 to February 3, 2018		

1.2.2 Description of Accessories

None.

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Range:	5150 MHz to 5250 MHz
	5250 MHz to 5350 MHz
	5470 MHz to 5725 MHz
	5 725 MHz to 5 850 MHz
Support Standards:	IEEE 802.11a/n/ac
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20: 20 MHz
	IEEE 802.11n-HT40/ac-VHT40: 40 MHz
	IEEE 802.11ac-VHT80: 80 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps
	IEEE 802.11n-HT20: Up to MCS15
	IEEE 802.11n-HT40: Up to MCS15
	IEEE 802.11ac-VHT20: Up to MCS8
	IEEE 802.11ac-VHT40: Up to MCS9
	IEEE 802.11ac-VHT80: Up to MCS9

Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80				
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80				
	5470 MHz to 5725 MHz: 11 for IEEE 802.11a/n-HT20/ac-VHT20 5 for IEEE 802.11n-HT40/ac-VHT40 2 for IEEE 802.11ac-VHT80				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11ac-VHT80				
Antenna Type:	Chain 0	PIFA Antenna			
	Chain 1	PIFA Antenna			
Antenna Gain:	Chain 0	5150 MHz to 5250 MHz: 2.95 dBi			
		5250 MHz to 5350 MHz: 3.26 dBi			
		5470 MHz to 5725 MHz: 4.52 dBi			
		5725 MHz to 5850 MHz: 4.56 dBi			
	Chain 1	5150 MHz to 5250 MHz: 4.06 dBi			
		5250 MHz to 5350 MHz: 4.06 dBi			
		5470 MHz to 5725 MHz: 4.60 dBi			
		5725 MHz to 5850 MHz: 4.32 dBi			
Directional gain:	5150 MHz to 5250 MHz:	6.53 dBi			
	5250 MHz to 5350 MHz:	6.68 dBi			
	5470 MHz to 5725 MHz:	7.57 dBi			
	5725 MHz to 5850 MHz:	7.45 dBi			
Maximum conducted output power (dBm):	SISO_Chain 0	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	14.70	15.80	16.08	14.78
	IEEE 802.11n-HT20:	11.20	11.66	11.94	11.37
	IEEE 802.11n-HT40:	11.06	11.56	12.00	10.84
	IEEE 802.11ac-VHT80:	9.82	10.38	10.31	8.95
	SISO_Chain 1	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	14.29	14.17	13.69	14.05
	IEEE 802.11n-HT20:	10.37	11.29	10.81	9.34
	IEEE 802.11n-HT40:	10.12	11.32	9.29	9.01
	IEEE 802.11ac-VHT80:	8.15	10.40	10.51	7.24
	MIMO_Chain 0+1	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11n-HT20:	13.82	14.44	14.42	13.48
	IEEE 802.11n-HT40:	13.63	14.45	13.86	13.03
	IEEE 802.11ac-VHT80:	12.08	13.40	13.42	11.19
Maximum EIRP (dBm):	U-NII-1				
		SISO_Chain 0	SISO_Chain 1	MIMO_Chain 0+1	
	IEEE 802.11a:	17.65	18.35	N/A	
	IEEE 802.11n-HT20:	14.15	14.43	17.30	
	IEEE 802.11n-HT40:	14.01	14.18	17.11	

	IEEE 802.11ac-VHT80:	12.77	12.21	15.51
Normal Test Voltage:	3.3 Vdc			
Extreme Test Voltage:	2.8 to 3.8 Vdc			
Extreme Test Temperature:	-20 °C to +50 °C			

1.4 OTHER INFORMATION

Operation Frequency Each of Channel				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11ac-VHT20	$f = 5000 + 5k, k = 32 + 4n$			$f = 5000 + 5k,$ $k = 145 + 4n$
	$n = 1, \dots, 4$	$n = 5, \dots, 8$	$n = 17, \dots, 27$	$n = 1, \dots, 5$
IEEE 802.11n-HT40, IEEE 802.11ac-VHT40	$f = 5000 + 5k, k = 30 + 8n$			$f = 5000 + 5k,$ $k = 143 + 8n$
	$n = 1, 2$	$n = 1, \dots, 5$	$n = 9, \dots, 13$	$n = 1, 2$
IEEE 802.11ac-VHT80	$f = 5000 + 5k, k = 26 + 16n$			$f = 5000 + 5k,$ $k = 155$
	$n = 1$	$n = 1, 2$	$n = 5, 6$	
Note: f is the operating frequency (MHz); k is the operating channel.				

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	FCC ID	Supplied by
Notebook	Lenovo	E450	SL10G10780	N/A	UnionTrust
Wireless AP	Alcatel-Lucent	G-240W-B	N/A	2ADZRG240WB	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable * 2	SMA	0.30 Meter	UnionTrust
2	USB Cable	USB	0.80 Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

IC-Registration No.: 21600-1

The 3m Semi-anechoic chamber of Shenzhen UnionTrust Quality and Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 21600-1.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.8 dB
2	Conducted emission 150KHz-30MHz	±3.4 dB
3	Radiated emission 9KHz-30MHz	±4.9 dB
4	Radiated emission 30MHz-1GHz	±4.7 dB
5	Radiated emission 1GHz-18GHz	±5.1 dB
6	Radiated emission 18GHz-26GHz	±5.2 dB
7	Radiated emission 26GHz-40GHz	±5.2 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart E Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203 FCC 47 CFR Part 15 Subpart C Section 15.407(a)(1) (2) RSS-Gen Issue 4, Section 8.3	ANSI C63.10-2013	PASS
26 dB emission bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5) RSS-247 Issue 2 Section 6.2.1.2	KDB 789033 D02 v02r01 Section C.1	PASS ^{NOTE 3}
6 dB bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (e) RSS-247 Issue 2 Section 6.2.4.1	KDB 789033 D02 v02r01 Section C.2	PASS ^{NOTE 3}
Occupied Bandwidth	RSS-Gen section 6.6	KDB 789033 D02 v02r01 Section D	PASS ^{NOTE 3}
Maximum conducted output power	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section E.3.a(Method PM)	PASS ^{NOTE 3}
Peak Power Spectral Density	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section F	PASS ^{NOTE 3}
Frequency stability	FCC 47 CFR Part 15 Subpart E Section 15.407 (g) RSS-Gen Issue 4, Section 6.11	ANSI C63.10-2013	PASS ^{NOTE 3}
Radiated Emissions and Band Edge Measurement	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6) FCC 47 CFR Part 15 Subpart C Section 15.209/205 RSS-247 Issue 2 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	PASS ^{NOTE 3}
Dynamic Frequency Selection	FCC 47 CFR Part 15 Subpart E Section 15.407 (h) RSS-247 Issue 2 Section 6.3	KDB 905462 D03 Client Without DFS New Rules v01r02	PASS ^{NOTE 3}
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6) FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 4, Section 8.8	ANSI C63.10-2013	N/A ^{NOTE 1, 2}
Note: 1) N/A: In this whole report not application. 2) This EUT is powered by DC. 3) The EUT (WCT6PA2201) this time and original model (WCT6LA2701) both WIFI+BT Module are identical in chipset, about the difference between the both WIFI+BT Module, please refer to the difference statement. After assessment, all technical data is referred to previous report no. 170615002RFC-4 dated July 11, 2017 except Radiated Emissions, Band edge (Radiated), Dynamic Frequency Selection, e.i.r.p. and all other items that increase the channels.			

For Dynamic Frequency Selection

Test Case	Result
Channel Availability Check Time	N/A ¹
U-NII Detection Bandwidth	N/A ¹
Channel Closing Transmission Time	PASS
Channel Move Time	PASS
DFS Detection Threshold	N/A ¹
Non- Occupancy Period	N/A ¹
Note: 1) The EUT is slave, NA In this whole report not application.	

3. EQUIPMENT LIST

Radiated Emission Test Equipment List (3M Chamber)						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 20, 2015	Dec. 19, 2018
☒	Receiver	R&S	ESIB26	100114	Dec. 10, 2017	Dec. 10, 2018
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec.10, 2017	Dec. 10, 2018
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	Dec. 17, 2017	Dec. 17, 2018
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Dec. 17, 2017	Dec. 17, 2018
☒	Preamplifier	HP	8447F	2805A02960	Dec. 10, 2017	Dec. 10, 2018
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	Dec. 17, 2017	Dec. 17, 2018
☒	Horn Antenna	ETS-LINDGREN	3116C	00200180	Jul. 28, 2015	Jul. 27, 2018
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Dec. 17, 2017	Dec. 17, 2018
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec. 10, 2017	Dec. 10, 2018
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Dec. 10, 2017	Dec. 10, 2018
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	Dec. 10, 2017	Dec. 10, 2018
☐	EXG-B RF Analog Signal Generator	KEYSIGHT	N5171B	MY53051777	Dec. 10, 2017	Dec. 10, 2018
☒	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	Dec. 14, 2017	Dec. 14, 2018
☒	DC Source	KIKUSUI	PWR400L	LK003024	Sep. 14, 2017	Sep. 13, 2018
☒	Temp & Humidity chamber	Espec	GL(U)04KA(W)	16921H201P3	Sep. 14, 2017	Sep. 13, 2018
☒	Temp & Humidity chamber	Votisch	VT4002	58566133290020	Jun. 19, 2017	Jun. 18, 2018

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Test Environment	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
TN/VN	+15 to +35	3.3	20 to 75
TL/VL	-20	2.8	20 to 75
TH/VL	+50	2.8	20 to 75
TL/VH	-20	3.8	20 to 75
TH/VH	+50	3.8	20 to 75

Remark:

- The EUT just work in such extreme temperature of -20 °C to +50 °C and the extreme voltage of 2.8 V to 3.8 V, so here the EUT is tested in the temperature of -20 °C to +50 °C and the voltage of 2.8 V to 3.8 V.
- VN: Normal Voltage; TN: Normal Temperature;
TL: Low Extreme Test Temperature; TH: High Extreme Test Temperature;
VL: Low Extreme Test Voltage; VH: High Extreme Test Voltage.

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48
		5180 MHz	5220 MHz	5240 MHz
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64
		5260 MHz	5300 MHz	5320 MHz
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140
		5500 MHz	5580 MHz	5700 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165
		5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134
		5510 MHz	5550 MHz	5670 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159
		5755 MHz	--	5795 MHz
IEEE 802.11ac-VHT80	5150 MHz to 5250 MHz	--	Channel 42	--
		--	5210 MHz	--
	5250 MHz to 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 MHz to 5725 MHz	Channel 106	--	--
		5530 MHz	--	--
	5725 MHz to 5850 MHz	--	Channel 155	--
		--	5775 MHz	--

4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11a/n/ac	1Tx/1Rx or 2Tx/2Rx	1. Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

4.4 PRE-SCAN

4.4.1 Pre-scan under all rates

Mode and Frequency	Maximum Conducted Average Power (dBm) for Data Rates (Mbps)							
IEEE 802.11a 5180 MHz	6	9	12	18	24	36	48	54
	14.52	14.36	14.31	14.29	11.93	11.71	11.7	10.38
IEEE 802.11n-HT20 5180 MHz	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	10.25	10.01	9.67	7.53	7.29	7.05	5.87	4.98
	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
	10.26	9.97	9.75	7.45	7.26	7.25	6.18	5.14
IEEE 802.11n-HT40 5190 MHz	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	10.11	9.49	9.37	7.71	7.55	7.26	6.26	4.51
	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
	10.13	9.31	9.09	7.56	7.21	7.05	5.57	4.13
IEEE 802.11ac-VHT20 5180 MHz	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	9.47	9.16	8.94	6.64	6.45	6.44	5.37	4.33
	MCS8							
	4.27							
IEEE 802.11ac-VHT40 5190 MHz	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	9.13	8.60	8.48	7.82	7.66	7.37	6.37	5.62
	MCS8	MCS9						
	4.70	4.00						
IEEE 802.11ac-VHT80 5210 MHz	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	9.03	7.96	7.72	7.33	6.06	5.86	4.51	4.10
	MCS8	MCS9						
	3.19	3.26						

4.4.2 Worst-case data rates

Mode	Worst-case data rates
IEEE 802.11a	6 Mbps
IEEE 802.11n-HT20	MCS8
IEEE 802.11n-HT40	MCS8
IEEE 802.11ac-VHT20	MCS0
IEEE 802.11ac-VHT40	MCS0
IEEE 802.11ac-VHT80	MCS0

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz



4.5.2 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION



For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.3Vdc. Only the worst case data were recorded in this test report.


The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Y axis
	1TX	Chain 1	Y axis
	2TX	Chain 0+1	Y axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.





5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 2	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 4	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
6	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	Guidelines for compliance testing of unlicensed national information infrastructure (U-NII) device part 15 subpart E
7	905462 D06 802.11 Channel Plans New Rules v02	Operation in U-NII bands -802.11 channel PLAN(\$15.407)
8	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for Unlicensed –National Information Infrastructure devices operates in the frequency bands 5250 MHz to 5350 MHz and 5470 MHz to 5725 MHz bands incorporating dynamic frequency selection
9	KDB 905462 D03 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability
10	KDB 662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.407(a)(1) (2) requirement: The conducted output power limit specified in paragraph (a) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (a) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-Gen Issue 4, Section 8.3 requirement: According to RSS-Gen Issue 4, section 8.3, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. EUT Antenna: Both antenna in the interior of the equipment and no consideration of replacement. The Tx chains are correlated and the antenna gain is unequal among the chains and the best case directional gain of the antenna is 6.53dBi@5150MHz~5250MHz, 6.68dBi@5150MHz~5250MHz, 7.57dBi@5150MHz~5250MHz and 7.45dBi@5725MHz~5850MHz (See section 5.5).

5.326 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a) (2)(5)
RSS-247 Issue 2 Section 6.2.1.2

Test Method: KDB 789033 D02 v02r01 Section C.1

Limit: None; for reporting purposes only.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.

Spectrum analyzer according to the following Settings:

a) Set RBW = approximately 1 % of the emission bandwidth.

b) Set the VBW > RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details


Test Mode: Transmitter mode


Test Results: Pass


Test Data:

Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
The worst case test data: Chain 0			
IEEE 802.11a	36 (5180)	19.49	16.395
	44 (5220)	19.34	16.337
	48 (5240)	20.84	16.422
	52 (5260)	19.58	16.373
	60 (5300)	19.11	16.350
	64 (5320)	19.22	16.354
	100 (5500)	19.02	16.306
	116 (5580)	19.28	16.307
	140 (5700)	19.11	16.311
IEEE 802.11n-HT20	36 (5180)	19.74	17.454
	44 (5220)	20.28	17.426
	48 (5240)	19.87	17.462
	52 (5260)	20.53	17.448
	60 (5300)	20.39	17.457
	64 (5320)	20.33	17.437
	100 (5500)	20.30	17.445
	116 (5580)	20.38	17.464
	140 (5700)	20.31	17.426
IEEE 802.11n-HT40	38 (5190)	40.25	35.865
	46 (5230)	40.74	35.867
	54 (5270)	40.42	35.850
	62 (5310)	40.42	35.796
	102 (5510)	40.01	35.824
	110 (5550)	39.26	35.821
	134 (5670)	39.53	35.744
IEEE 802.11ac-VHT80	42 (5230)	83.89	75.201
	58 (5290)	81.51	75.360
	106 (5530)	82.85	75.232


The test plot as follows:















5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.407 (e)
RSS-247 Issue 2 Section 6.2.4.1

Test Method: KDB 789033 D02 v01r04Section C.2

Limit: Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Mode	Channel/ Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limit	Pass / Fail
The worst case test data: Chain 0					
IEEE 802.11a	149 (5745)	15.27	16.453	> 500 kHz	Pass
	157 (5785)	15.32	16.405	> 500 kHz	Pass
	165 (5825)	15.10	16.292	> 500 kHz	Pass
IEEE 802.11n-HT20	149 (5745)	15.11	17.425	> 500 kHz	Pass
	157 (5785)	15.45	17.448	> 500 kHz	Pass
	165 (5825)	15.47	17.434	> 500 kHz	Pass
IEEE 802.11n-HT40	151 (5755)	33.94	35.759	> 500 kHz	Pass
	159 (5795)	35.19	35.726	> 500 kHz	Pass
IEEE 802.11ac-VHT80	155 (5775)	75.21	75.057	> 500 kHz	Pass