



FCC RF EXPOSURE REPORT

For

WIFI Module

MODEL NUMBER: WKC21M2511

REPORT NUMBER: 4791856253-RF-3

ISSUE DATE: July 21, 2025

FCC ID: 2AC23-WKC21

Prepared for

Hui Zhou Gaoshengda Technology Co.,LTD No.6,Qiaoguang Road,Chenjiang Street,Zhongkai High-tech Zone,Huizhou,Guangdong,China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China

Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4791856253-RF-3 Page 2 of 7

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	July 21, 2025	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	5
1	REQUIREMENT	6



REPORT NO.: 4791856253-RF-3

Page 4 of 7

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD

Address: No.6, Qiaoguang Road, Chenjiang Street, Zhongkai High-tech

Zone, Huizhou, Guangdong, China

Manufacturer Information

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD

Address: No.6, Qiaoguang Road, Chenjiang Street, Zhongkai High-tech

Zone, Huizhou, Guangdong, China

EUT Information

EUT Name: WIFI Module Model: WKC21M2511

Brand: GSD

Sample Received Date: June 23, 2025

Sample Status: Normal Sample ID: 8674947

Date of Tested: June 24, 2025 to July 21, 2025

APPLICABLE STANDARDS					
STANDARD	TEST RESULTS				
447498 D04 Interim General RF Exposure Guidance v01	PASS				

Prepared By:

Checked By:

Kebo . Thurs

Kebo Zhang

Kebo Zhang

Senior Project Engineer

Stephen Guo

Approved By:

Project Engineer

Operations Manager

REPORT NO.: 4791856253-RF-3 Page 5 of 7

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 1 Subpart I, section 1.1307 and KDB 447498 D04 Interim General RF Exposure Guidance v01.

3. FACILITIES AND ACCREDITATION

A2LA (Certificate No.: 4102.01)

UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.

FCC (FCC Designation No.: CN1187)

UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.

Accreditation Certificate

ISED (Company No.: 21320)

UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.

VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202)

UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.

Facility Name:

Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



4. REQUIREMENT

LIMIT AND CALCULATION METHOD

According to 447498 D04 Interim General RF Exposure Guidance v01,

2.1.4 MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.10 For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

MPE-based Exemption

$$P_{\text{th}} (\text{mW}) = ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B.1)

$$P_{\text{th (mW)}} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$
(B.2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\,\mathrm{cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1).



REPORT NO.: 4791856253-RF-3

Page 7 of 7

CALCULATED RESULTS

For Single RF Source

Operating Mode	Max. Tune up Power	Max. Antenna Gain	EIRP	ERP	ERP	Distance	Limit Threshold
	(dBm)	(dBi)	(dBm)	(dBm)	(mW)	(cm)	(mW)
WIFI2.4G	18.50	2.61	21.11	18.96	78.70	20	3060
WIFI5G	18.00	2.56	20.56	18.41	69.34	20	3060

Note:

- 1. The calculated distance is 20 cm.
- 2. The power comes from operation description.
- 3. The EUT does not support simultaneous operation.

END OF REPORT