

RF EXPOSURE REPORT

FCC ID: 2AC23-WL71

IC: 12290A-WL71

Applicant's name : Hui Zhou Gaoshengda Technology Co., LTD

Address : NO.75 Zhongkai Development Area, Huizhou,
Guangdong,China

Manufacturer : Hui Zhou Gaoshengda Technology Co., LTD

Equipment : WIFI+ BT Module

Trade Mark : GSD

Model : WL71T1500

Ratings : I/P: DC 3.3V

Testing Laboratory : DongGuan ShuoXin Electronic Technology Co., Ltd.

Address : Zone A, 1F, No. 6, XinGang Road YuanGang Street,
XinAn District, ChangAn Town, DongGuan City,
GuangDong, China

According : FCC Guidelines for Human Exposure IEEE C95.1 &
FCC Part 2.1091

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note
1	N/A	N/A	PIFA	N/A	3	
2	N/A	N/A	PIFA	N/A	3	

TEST RESULTS

EUT :	WIFI+ BT Module	Model Name :	WL71T1500
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	DC 3.3V		

For FCC

2.4G WIFI

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.995	24.29	268.5344	0.10665	1	Complies

BLE

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.995	3.952	2.4843	0.00099	1	Complies

Note: the calculated distance is 20 cm.