



198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555

Fax: +86 (0) 20 82075059

Email: ee.guangzhou@sgs.com

Report No.: GZEM140800417804

Page: 1 of 23

FCC ID: 2AC3GVSMSV5L

TEST REPORT

Application No.:	GZEM1408004178RF
Applicant:	Guangzhou Waytronic Electronics Co., Ltd.
Manufacturer:	Same as Applicant
Factory:	Same as Applicant
FCC ID:	2AC3GVSMSV5L
Product Name:	Vehicle Warning System V5.10
Product Description:	Radio transmitter with 2.4GHz as carrier
Model No.:	Log Uploader
Standards:	CFR 47 PART 15 Subpart C: 2013 section 15.249
Date of Receipt:	2014-08-12
Date of Test:	2014-09-03 to 2014-10-14
Date of Issue:	2015-01-12
Test Result :	Pass*

* In the configuration tested, the EUT complied with the standards specified above.

Jerry Chan
Manager



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-01-12		Original

Authorized for issue by:			
Tested By	 (Jack Liang) /Project Engineer		2014-09-03 to 2014-10-14
Prepared By	 (Millie Li) /Clerk		2014-11-20
Checked By	 (Jerry Chan)/Reviewer		2014-11-24

3 Test Summary

Test	Test Requirement	Test method	Result
Field Strength of Fundamental	FCC PART 15 C section 15.249 (a)	ANSI C63.10: Clause 6.6	PASS
Field Strength of Unwanted Emissions	FCC PART 15 C section 15.249 (a) section 15.249 (d)	ANSI C63.10: Clause 6.4, 6.6 and 6.7	PASS
Band Edges	FCC PART 15 C section 15.249 (d)	ANSI C63.10: Clause 6.9.2	PASS
Occupied Bandwidth	FCC PART 15 C section 15.215(c)	ANSI C63.10: Clause 6.9.1	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS

Remark:

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.

4 Contents

1	Cover Page	1
2	Version	2
3	Test Summary	3
4	Contents	4
5	General Information	5
5.1	Client Information	5
5.2	General Description of E.U.T.	5
5.3	Details of E.U.T.	5
5.4	Description of Support Units	5
5.5	Other Information Requested by the Customer	6
5.6	Deviation from Standards	6
5.7	Test Location	6
6	Equipment Used during Test	8
7	Test Results	9
7.1	E.U.T. Operation	9
7.2	Antenna Requirement	11
7.3	Field Strength of Fundamental & Field Strength of Unwanted Emissions & Band Edge	12
7.4	Occupied Bandwidth	19
7.1	Conducted Emissions at Mains Terminals 150 kHz to 30 MHz	20

5 General Information

5.1 Client Information

Applicant:	Guangzhou Waytronic Electronics Co., Ltd.
Address of Applicant:	502 Room, West 2nd Building, Tangli Mansion, Tangxia, Tianhe District, Guangzhou Guangdong China
Manufacturer:	Same as Applicant
Address of Manufacturer:	Same as Applicant
Factory:	Same as Applicant
Address of Factory:	Same as Applicant

5.2 General Description of E.U.T.

Product Name:	Vehicle Warning System V5.10
Model No.:	Log Uploader

5.3 Details of E.U.T.

Operating Frequency	2432.498MHz
Type of Modulation:	MSK
Number of Channels	1
Channel Separation:	/
Antenna Type	External Antenna
Antenna Gain:	3.0 dBi
Function:	2.4GHz is used for common channel for data transfer. Transmitter will be hopped at 2432.498MHz for searching the Receiver. When the receiver is found, this frequency will be fixed and not be changed any more.
Power Supply:	DC 5.0V by micro USB port DC 3.3V 500mAh for internal rechargeable battery operated
Test Voltage	AC 120V, DC 3.7-4.2V
Adapter:	Model: MX12X8-0501000UU Input: AC 100-240V 50/60Hz 0.35A Output: DC 5V 1A
Power Cord:	1.5 m unscreened USB cable

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Other Information Requested by the Customer

None.

5.6 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.7 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,
198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.

6 Equipment Used during Test

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2013-12-5	2014-12-5
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-04-19	2015-04-19
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2014-03-03	2015-03-03
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2014-05-09	2015-05-09
EMC2025	Trilog Broadband Antenna 30-1000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9160	9160-3372	2014-07-14	2017-07-14
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2013-08-31	2016-08-31
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-05-04	2017-05-04
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2013-08-31	2016-08-31
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2012-07-01	2015-07-01
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2014-03-03	2015-03-03
EMC2065	Amplifier	HP	8447F	N/A	2014-08-25	2015-08-25
EMC0075	310N Amplifier	Sonama	310N	272683	2014-03-03	2015-03-03
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-03-03	2016-03-03
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2014-05-26	2017-05-26
EMC2069	2.4GHz filter	Micro-Tronics	BRM 50702	149	2014-04-19	2015-04-19
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2014-05-03	2016-05-03

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0006	DMM	Fluke	73	70681569	2014-09-15	2015-09-15
EMC0007	DMM	Fluke	73	70671122	2014-09-15	2015-09-15

7 Test Results

7.1 E.U.T. Operation

Test Voltage: AC 120V, DC 4.0V

Temperature: 20.0 -25.0 °C

Humidity: 38-50 % RH

Atmospheric Pressure: 1000 -1010 mbar

Test Frequencies and Frequency Range: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

EUT channels and frequencies list: 2432.498MHz

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0		27		54	
1		28		55	
2		29		56	
3		30	2432.498MHz	57	
4		31		58	
5		32		59	
6		33		60	
7		34		61	
8		35		62	
9		36		63	
10		37		64	
11		38		65	
12		39		66	
13		40		67	
14		41		68	
15		42		69	
16		43		70	
17		44		71	
18		45		72	
19		46		73	
20		47		74	
21		48		75	
22		49		76	
23		50		77	
24		51		78	
25		52			
26		53			

7.2 Antenna Requirement

Standard requirement


15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT Antenna

The antenna is a special male head external antenna and no consideration of replacement. When the external antenna is used, the integral antenna cannot work.

The best case gain of the antenna is 3.0 dBi.



Test result: The unit does meet the FCC requirements.

7.3 Field Strength of Fundamental & Field Strength of Unwanted Emissions & Band Edge

Test Requirement: FCC Part15 C section 15.249

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dB μ V/m @ 3m)	Field Strength of Harmonics (dB μ V/m @ 3m)
902 to 928	94.0	54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0
24000 to 24250	108.0	68.0

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Limits: The fundamental frequency of the EUT is 2432.498MHz.

The limit for Average field strength dB μ V/m for the fundamental frequency = 94.0 dB μ V/m.

The limit for Peak field strength dB μ V/m for the fundamental frequency = 114.0 dB μ V/m.

No fundamental is allowed in the restricted bands.

The limit for average field strength dB μ V/m for the harmonics = 54.0 dB μ V/m.

The limit for peak field strength dB μ V/m for the harmonics = 74.0 dB μ V/m.

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or 54.0 dB μ V/m in 15.209. Here the limit for the other emission is 54.0 dB μ V/m.

Test Method: ANSI C63.10: Clause 6.4, 6.6 and 6.7 for Field Strength of Fundamental & Field Strength of Unwanted Emissions

ANSI C63.10: Clause 6.9.2 for Band Edge

Status Pre-test the EUT in continuous transmitting mode with setup as stand-alone in X, Y, Z threes axes with supply by adapter and internal battery, found the worst case is X axes with supply by adapter and report the data.

Measurement Distance: 3m (Semi-Anechoic Chamber)

Frequency range 9 kHz – 25 GHz for transmitting mode.

Test instrumentation resolution bandwidth

9 kHz (9 kHz - 30 MHz), 120 kHz (30 MHz - 1000 MHz), 1 MHz (1000 MHz – 25 GHz)

Test Procedure:

1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.10. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2) 30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.


3) 1 GHz to 25 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.


For testing performed with the horn antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scan between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

Test Configuration:


1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 25 GHz emissions:



The field strength is calculated by adding the Antenna Factor, Cable Loss & Per-amplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss – Preamplifier Factor

Test at 2432.498MHz in transmitting status


9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

Vertical:

Peak scan


Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	Read Antenna Level		Cable Preamp Loss Factor		Level dB	Limit Line dB μ V/m	Over Limit dB	Over Limit Remark
	Antenna Level dB μ V	Factor	Loss Factor	Preamp Level dB				
31.510	49.72	12.32	0.84	31.02	31.86	40.00	-8.14	QP
51.843	52.38	13.16	1.10	31.00	35.64	40.00	-4.36	QP
66.733	52.25	10.02	1.17	31.00	32.44	40.00	-7.56	QP
104.170	48.51	12.78	1.41	31.00	31.70	43.50	-11.80	QP
331.355	46.45	13.79	2.48	30.97	31.75	46.00	-14.25	QP
798.980	39.42	20.06	3.80	30.90	32.38	46.00	-13.62	QP

Horizontal:

Peak scan

Level (dB μ V/m)

Quasi-peak measurement

Freq MHz	Read Level dB μ V	Antenna Factor dB/m	Cable Loss dB		Preamp Factor dB	Level dB μ V/m	Limit Line dB μ V/m	Over Line dB	Over Limit Remark
32.406	40.82	12.32	0.84	31.02	22.96	40.00	-17.04		
66.733	48.36	10.02	1.17	31.00	28.55	40.00	-11.45		
104.170	45.72	12.78	1.41	31.00	28.91	43.50	-14.59		
133.151	47.29	8.67	1.51	31.03	26.44	43.50	-17.06		
331.355	42.03	13.79	2.48	30.97	27.33	46.00	-18.67		
798.980	40.76	20.06	3.80	30.90	33.72	46.00	-12.28		

1~25 GHz Field Strength of Fundamental & Field Strength of Unwanted Emissions.**Peak & Average Measurement**

Peak Measurement:							
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2431.248	27.57	6.73	38.25	66.64	62.69	114.00	V
4862.496	31.56	11.21	38.56	39.25	43.46	74.00	V
7293.744	36.49	13.15	38.87	43.20	53.97	74.00	V
9724.992	38.38	15.07	39.74	44.38	58.09	74.00	V
2431.248	27.57	6.73	38.25	66.19	62.24	114.00	H
4862.496	31.56	11.21	38.56	43.27	47.48	74.00	H
7293.744	36.49	13.15	38.87	42.36	53.13	74.00	H
9724.992	38.38	15.07	39.74	44.92	58.63	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2431.248	27.57	6.73	38.25	73.36	69.41	94.00	V
4862.496	31.56	11.21	38.56	37.76	41.97	54.00	V
7293.744	36.49	13.15	38.87	37.23	48.00	54.00	V
9724.992	38.38	15.07	39.74	35.53	49.24	54.00	V
2431.248	27.57	6.73	38.25	64.10	60.15	94.00	H
4862.496	31.56	11.21	38.56	38.70	42.91	54.00	H
7293.744	36.49	13.15	38.87	36.03	46.80	54.00	H
9724.992	38.38	15.07	39.74	36.09	49.80	54.00	H

Band Edge:

Peak Measurement:							
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.00	27.58	6.56	49.44	55.43	40.13	74.00	V
2483.50	27.55	6.99	49.42	56.47	41.59	74.00	V
2400.00	27.58	6.56	49.44	55.74	40.44	74.00	H
2483.50	27.55	6.99	49.42	55.02	40.14	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.00	27.58	6.56	49.44	47.93	32.63	54.00	V
2483.50	27.55	6.99	49.42	48.77	33.89	54.00	V
2400.00	27.58	6.56	49.44	45.84	30.54	54.00	H
2483.50	27.55	6.99	49.42	47.72	32.84	54.00	H

Remark:

- 1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Loss - Preamplifier Factor.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.
- 4). For Radiated Emissions fall in the restricted bands (2400MHz is worse case than 2390MHz and report it as above), which set out in Section 15.205 Restricted bands.

Also there is not any other emission which falls in restricted bands can be detected and reported.

Test result: The unit does meet the FCC requirements.

7.4 Occupied Bandwidth

Test Requirement: FCC Part 15 C section 15.249


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Test Method: ANSI C63.10: Clause 6.9.1

Operation within the band 2.400 to 2.4835 GHz

Method of measurement: A small sample of the transmitter output was fed into the Spectrum Analyzer and the attached plot was taken.

Test in the frequency 2.432498 GHz



The results: The unit does meet the FCC requirements.

7.1 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz

Test Requirement: FCC Part 15 C section 15.207
Test Method: ANSI C63.10: Clause 6.2
Frequency Range: 150 kHz to 30 MHz
Detector: Peak for pre-scan (9 kHz Resolution Bandwidth)


Test Limit

Limits for conducted disturbance at the mains ports of class B

Frequency Range (MHz)	Class B Limit dB(µV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.
Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Test Configuration:**Test procedure:**

1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

Measurement Data


An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

The following Quasi-Peak and Average measurements were performed on the EUT:


Live Line

Level(dB μ V)



Measure result:

Freq MHz	Read Level dB μ V	Cable Loss dB	LISN Factor dB	Level dB μ V	Limit Line dB μ V	Over Limit dB	Remark
	dB μ V	dB	dB	dB μ V	dB μ V	dB	
0.334	26.96	0.09	9.70	36.75	59.35	-22.61	QP
0.334	11.70	0.09	9.70	21.49	49.35	-27.87	AVERAGE
0.461	36.06	0.07	9.66	45.79	56.67	-10.88	QP
0.461	25.29	0.07	9.66	35.02	46.67	-11.65	AVERAGE
1.249	13.95	0.05	9.70	23.70	46.00	-22.30	AVERAGE
1.249	27.36	0.05	9.70	37.11	56.00	-18.89	QP
2.044	26.26	0.06	9.70	36.02	56.00	-19.98	QP
2.044	18.96	0.06	9.70	28.72	46.00	-17.28	AVERAGE
2.993	24.58	0.15	9.70	34.43	56.00	-21.57	QP
2.993	14.70	0.15	9.70	24.55	46.00	-21.45	AVERAGE
5.305	9.02	0.18	9.72	18.92	50.00	-31.08	AVERAGE
5.305	19.80	0.18	9.72	29.70	60.00	-30.30	QP

Neutral Line
Level(dB μ V)

Measure data:

Freq	Read	Cable	LISN	Limit	Over	Limit	Remark
	Level	Loss	Factor				
MHz	dB μ V	dB	dB	dB μ V	dB μ V	dB	
0.367	13.57	0.07	9.66	23.30	48.56	-25.26	AVERAGE
0.367	26.64	0.07	9.66	36.37	58.56	-22.19	QP
0.461	19.77	0.07	9.66	29.50	46.67	-17.17	AVERAGE
0.461	36.08	0.07	9.66	45.81	56.67	-10.86	QP
1.249	28.64	0.05	9.68	38.37	56.00	-17.63	QP
1.249	13.77	0.05	9.68	23.50	46.00	-22.50	AVERAGE
2.285	28.74	0.08	9.69	38.51	56.00	-17.49	QP
2.285	16.77	0.08	9.69	26.54	46.00	-19.46	AVERAGE
2.993	16.77	0.15	9.70	26.62	46.00	-19.38	AVERAGE
2.993	28.96	0.15	9.70	38.81	56.00	-17.19	QP
11.621	17.84	0.20	9.91	27.95	60.00	-32.05	QP
11.621	9.27	0.20	9.91	19.38	50.00	-30.62	AVERAGE

--End of the report--